

## Vehicle document wallet

You can find comprehensive printed information about operating your vehicle, the Service Booklet and your vehicle warranty here.



Order no. P167 0672 13 Part no. 167 584 40 25 Edition B 2023

2

rcedes-Benz



GLS


Operator's Manual

Mercedes-Benz



# Front passenger air bag warning







Risque de BLESSURE GRAVE ou MORTELLE: - Les enfants âgés de 12 ans et moins peuvent être tués par le coussin gentlable - Les enfants sont en plus grande SÉCURITÉ sur les IÉES ARRIÉTE. - NE JAMAS placer un port-bébé oriente ves l'arriére sur les sége avant à moins que le fonctionnement du coussin gentlable soit annulé - s'assori aussi loin que possible du coussin gentlable - 10/IUI/UIS BOURTE les CENTINES DE JIÉES EN 1950-1951 SE DE SÉCURITÉ POUR ENFANTS DE - 10/IUI/UIS BOURTE les CENTINES DE JIÉES EN 1950-1951 SE DE SÉCURITÉ POUR ENFANTS DE - 10/IUI/UIS BOURTE les CENTINES DE JIÉES EN 1950-1951 SE DE SÉCURITÉ POUR ENFANTS DE - 10/IUI/UIS BOURTE SE CENTINES DE JIÉES EN 1950-1951 SE DE SÉCURITÉ POUR ENFANTS DE - 10/IUI/UIS BOURTE SE CENTINES DE JIÉES DE L'AUTRE DE

Air bag warning sticker for USA and Canada

**WARNING** Risk of injury or fatal injuries if the front passenger air bag is enabled

If the front passenger air bag is enabled, a child on the front passenger seat may be struck by the front passenger air bag in the event of an accident.

NEVER use a rearward-facing child restraint system on a seat with an ENA-BLED FRONT AIR BAG. This can result in the DEATH of or SERIOUS INJURY to the CHILD.

Observe the chapter "Children in the vehicle".

#### Publication details

#### Internet

Further information about Mercedes-Benz vehicles and about Mercedes-Benz AG can be found on the following websites:

https://www.mbusa.com (USA only)

https://www.mercedes-benz.ca (Canada only)

#### Documentation team

<sup>©</sup>Mercedes-Benz AG: Not to be reprinted, translated or otherwise reproduced, in whole or in part, without written permission from Mercedes-Benz AG.

#### Vehicle manufacturer

Mercedes-Benz AG

Mercedesstraße 120

70372 Stuttgart

Germany

As at 11.07.22

## Welcome to the world of Mercedes-Benz

Before your first drive, please read this Operator's Manual carefully and familiarize yourself with your vehicle. For your own safety and a longer service life of the vehicle, follow the instructions and warning notices in this Operator's Manual. Disregarding them may lead to damage to the vehicle or injury to people.

Damage to the vehicle resulting from the disregard of the instructions is not covered by the Mercedes-Benz Limited warranty.

The standard equipment and product description of your vehicle may vary and depends on the following factors:

- Model
- Order
- National version
- Availability

Your vehicle may therefore differ from that shown in the descriptions and illustrations in individual cases.

Mercedes-Benz reserves the right to introduce changes in the following areas:

- Design
- Equipment
- · Technical features

The following documents are components of the vehicle:

- Digital operator's manual
- Printed Operator's Manual
- · Maintenance Booklet
- Supplementary manuals relating to specific equipment
- Supplementary documents

Keep these documents in the vehicle at all times. Ensure that all documents are in the vehicle or passed on in the event of sale or rental.

Mercedes-Benz USA, LLC

Mercedes-Benz Canada, Inc.

A Mercedes-Benz Group AG Company

1675844025



# 2 Contents

Symbols	. 5	National information for components relevant to radio regulation	28 28	Safely transporting children in the vehicle Brief overview of most important points	55
At a glance  Cockpit  Indicator and warning lamps  Overhead control panel  Door operating unit and seat adjustment  Control settings in the rear passenger		Qualified specialist workshop	29 30 30 31 31	Important safety notes	61 62
compartment Emergencies and breakdowns	16 18	Reporting safety defects Limited Warranty  OR code for rescue card  Data storage	32 33	Opening and closing	72 76
Digital Operator's Manual		Copyright	37	Running boards	80 87
General notes	<b>22</b> 22 22	Occupant safety	<b>39</b>	Roller sun blinds	95
Operator's Manual	25	the restraint system		Seats and stowing	99 99 100 119

Memory function	122 123 126 142 143 145 147
Light and visibility  Exterior lighting	151 151 156 158 163 166 166
Climate control	<b>167</b> 167 168

Driving and parking  Driving	175 175 190 194 199 200 201 203 211 279 283
Instrument display and on-board computer	284

Overview and operation	291 300 304 313 317 324 328 335
Maintenance and care ASSYST PLUS service interval display Maintenance Management Telediagnosis Engine compartment Cleaning and care	336 336 337 337 338 344
Breakdown assistance Emergency Flat tire Battery (vehicle) Tow starting or towing away Electrical fuses	<b>353</b> 353 354 360 366 371

MBUX multimedia system ...... 291

# 4 Contents

Wheels and tires  Notes on noise or unusual handling characteristics  Notes on regularly inspecting wheels and tires  Notes on snow chains  Tire pressure  Loading the vehicle  Tire labeling  Definition of terms for tires and loading  Changing a wheel  Emergency spare wheel  Collapsible spare wheel	375 375 376 376 382 386 391 393 404 406
Technical data	<b>409</b> 409 409 411
engine number overview	411 413 421 425

Display messages and warning/indicator         lamps       428         Display messages       428         Warning and indicator lamps       485	Index	502
	lamps Display messages	428

In this Operator's Manual, you will find the following symbols:

**WARNING** Danger due to failure to observe the warning notices

Warning notices draw your attention to hazards that may endanger your health or life, or the health or life of others.

Observe the warning notices.

ENVIRONMENTAL NOTE Environmental damage due to failure to observe environmental notes

Environmental notes include information on environmentally responsible behavior or environmentally responsible disposal.

Observe environmental notes.

NOTE Damage to property due to failure to observe notes on material damage

Notes on material damage inform you of risks which may lead to your vehicle being damaged.

Observe notes on material damage.

(i) These symbols indicate useful instructions or further information that could be helpful to you.

Instruction

(→ page) Further information on a topic

Display

Display field in the Instrument Display/media display




Highest menu level, which is to be selected in the multimedia system



Relevant submenus, which are to be selected in the multimedia system

Indicates a cause

# 6 At a glance - Cockpit



Left-hand-drive vehicles

Steering wheel paddle shifters	$\rightarrow$	196
Combination switch	$\rightarrow$	152
3 Instrument display	$\rightarrow$	285
DIRECT SELECT lever	$\rightarrow$	194
Media display	$\rightarrow$	291
Climate control systems	$\rightarrow$	168
Mazard warning light system	$\rightarrow$	153
PASSENGER AIR BAG indicator lamps	$\rightarrow$	43
Glove box	$\rightarrow$	129
Stowage space	$\rightarrow$	129
Controller for volume and switching sound on/off	$\rightarrow$	291
ර Switches the MBUX multimedia system on/off	$\rightarrow$	291
	$\rightarrow$	293
RADIO MEDIA Calls up radio or media	$\rightarrow$	293
TEL Calls up the telephone	$\rightarrow$	293

Switch panel for:		
Individual wheel control (vehicles without off-road package) or	$\rightarrow$	256
RANGE Transfer case (vehicles with off-road package)	$\rightarrow$	199
M Manual gearshifting	$\rightarrow$	196
ৰ্ক্টী AIRMATIC or	$\rightarrow$	247
ি E-ACTIVE BODY CONTROL	$\rightarrow$	252
🐉 Activates/deactivates ESP®	$\rightarrow$	214
Downhill Speed Regulation	$\rightarrow$	229
	$\rightarrow$	293
Calls up vehicle functions	$\rightarrow$	293
Active Parking Assist	$\rightarrow$	273
DYNAMIC SELECT switch	$\rightarrow$	192
Touchpad	$\rightarrow$	293
Start/stop button	$\rightarrow$	176
(A) ECO start/stop function	$\rightarrow$	187


# 8 At a glance - Cockpit

Control panel for the MBUX multimedia system	$\rightarrow$	286
Adjusts the steering wheel manually	$\rightarrow$	119
Adjusts the steering wheel electrically	$\rightarrow$	119
Switches the steering wheel heater on/off	$\rightarrow$	120
Control panel:		
On-board computer	$\rightarrow$	286

Cruise control	$\rightarrow$	221
Active Distance Assist DISTRONIC	$\rightarrow$	224
Diagnostics connection	$\rightarrow$	28
Opens the hood	$\rightarrow$	338
Electric parking brake	$\rightarrow$	207
29 Light switch	$\rightarrow$	151



# 10 At a glance – Indicator and warning lamps




Instrument display

● ◆ ▼ Turn signal lights	$\rightarrow$	152
Restraint system	$\rightarrow$	487
③ 【♣F ESP® OFF	$\rightarrow$	496
<b>₽</b> ESP®	$\rightarrow$	496
	$\rightarrow$	152
	$\rightarrow$	152
D Low beam	$\rightarrow$	151
⊋oo∈ Standing lights	$\rightarrow$	151
Coolant temperature		
Coolant temperature display	$\rightarrow$	285
Electric parking brake (yellow)	$\rightarrow$	493
Recuperative Brake System, USA only	$\rightarrow$	493
(III) Brakes (yellow), Canada only	$\rightarrow$	493
Electrical malfunction	$\rightarrow$	489
Distance warning	$\rightarrow$	496
(a) ABS	$\rightarrow$	496

Power steering     Power steering	$\rightarrow$	488
(1) Tire pressure monitoring system	$\rightarrow$	500
Reserve fuel with fuel filler flap location indicator	$\rightarrow$	489
Fuel level	$\rightarrow$	285
© Electric parking brake (red)	$\rightarrow$	493
PARK USA only		
(e) Canada only		
Brakes (red)	$\rightarrow$	493
BRAKE USA only		
(II) Canada only		
Seat belt	$\rightarrow$	487
© Check Engine	$\rightarrow$	489
Suspension (red)	$\rightarrow$	496
Suspension (yellow)	$\rightarrow$	496

# 12 At a glance - Overhead control panel




Δt	а	σlance	_	Overhead	control	nanel	
ΑL	а	gianice	_	Overneau	COLLLO	parier	

Sun visors		
② [Yang Switches the left-hand reading lamp on/off	$\rightarrow$	156
Switches automatic interior lighting control on/off	$\rightarrow$	156
Switches the front interior lighting on/off	$\rightarrow$	156
Switches the rear interior lighting on/off	$\rightarrow$	156
Switches the right-hand reading lamp on/off	$\rightarrow$	156

me button	$\rightarrow$	317
Sos SOS button	$\rightarrow$	317
Opens/closes the panorama roof with power tilt/sliding panel	$\rightarrow$	90
Opens/closes the roller sunblind	$\rightarrow$	90
Inside rearview mirror	$\rightarrow$	164

# 14 At a glance – Door operating unit and seat adjustment




# At a glance – Door operating unit and seat adjustment 15

Opens the door	$\rightarrow$	76	
② 🔁 🔂 Locks/unlocks the vehicle	$\rightarrow$	76	① Child sa
Sets the memory function	$\rightarrow$	122	dows
Adjusts the seats electrically	$\rightarrow$	100	② [日] Opens/
Switches the seat heating on/off	$\rightarrow$	116	
Switches the seat ventilation on/off	$\rightarrow$	118	
Adjusts the front passenger seat from	$\rightarrow$	102	6 Adjusts the 4-
the driver's seat			Seat adjustment
Opens/closes the tailgate	$\rightarrow$	80	Adjusts the he
Opens/closes the right side window	$\rightarrow$	87	

Opens/closes the rear right side window	$\rightarrow$	87
Child safety lock for the rear side windows	$\rightarrow$	71
Opens/closes the rear left side window	$\rightarrow$	87
Opens/closes the left side window	$\rightarrow$	87
Operates the outside mirrors	$\rightarrow$	163
Adjusts the 4-way lumbar support	$\rightarrow$	104
Seat adjustment using the multimedia system	$\rightarrow$	114
Adjusts the head restraints	$\rightarrow$	110

# 16 At a glance – Control settings in the rear passenger compartment




At a glance - Contro	I settings in the real	r passenger compartment

Rear climate control operating unit	$\rightarrow$	168
Stowage compartment in the center console		
115 V socket	$\rightarrow$	144
<ul><li>Adjusts the front passenger seat electrically</li></ul>	$\rightarrow$	103
Switches the rear seat ventilation on/off	$\rightarrow$	118
⑤ ₩ Switches the rear seat heating on/off	$\rightarrow$	116
Adjusts the rear seat electrically	$\rightarrow$	104
Mercedes-Maybach vehicles: adjusts a reclining rear seat electrically	<b>→</b>	105

7	Mercedes-Maybach vehicles: operates the memory function	$\rightarrow$	123
8	Mercedes-Maybach vehicles: sets the fully reclined position	$\rightarrow$	105
9	Mercedes-Maybach vehicles: access to the refrigerator box	$\rightarrow$	145
10	Stowage compartment in the rear armrest		
	MBUX rear tablet bracket		

# 18 At a glance – Emergencies and breakdowns



At a	alanco	Emorgon	cine and	breakdowns
AL a	glatice -	cillergen	cies and	breakdowns

B-pillar with:			Flat tire	$\rightarrow$	354
QR code for accessing the rescue card	$\rightarrow$	33	Tow-starting or towing away	$\rightarrow$	368
Safety vests	$\rightarrow$	353	Fuel filler flap with:		
3 🚾 me button	$\rightarrow$	317	information label on fuel type	$\rightarrow$	201
<b>ℚsos</b> ] SOS button	$\rightarrow$	317	Information label on tire pressure	$\rightarrow$	378
A Hazard warning light system	$\rightarrow$	153	QR code for accessing the rescue card	$\rightarrow$	33
To check and refill operating fluids	$\rightarrow$	413	Warning triangle	$\rightarrow$	354
Jump-starting	$\rightarrow$	365	1 TIREFIT kit	$\rightarrow$	356
Tow-starting or towing away	$\rightarrow$	368	First-aid kit (soft sided)	$\rightarrow$	354

# Calling up the Digital Operator's Manual

Multimedia system:






The Digital Operator's Manual describes the functions and operation of the vehicle and the multimedia system.

- Select one of the following menu items in the Digital Operator's Manual:
- Search: search for keywords in order to find quick answers to questions about the operation of the vehicle.

- Quick start: here is where you find the first steps towards setting up your vehicle.
- Tips: find information that prepares you for certain everyday situations with your vehicle.
- Animations: watch animations of the vehicle functions.
- Messages: receive additional information about the messages on the Instrument Display.
- Bookmarks: gain access to your personally saved bookmarks.
- Language: select the language for the Digital Operator's Manual.



- Back
- Adds bookmarks
- ② Picture
- Contents section
- Directions of movement of contents section
- 6 Menu

Some sections in the Digital Operator's Manual, suchas warning notes, can be expanded and collapsed.

Additional methods of calling up the Digital Operator's Manual:

**Direct access:** open the required content in the Digital Operator's Manual by pressing and holding an entry on the tab bar in the multimedia system:



**Instrument Display:** call up brief information as display messages in the instrument cluster

**Voice Control System:** call up via the voice control system

For safety reasons, the Digital Operator's Manual is deactivated while driving.

# Protecting the environment



**ENVIRONMENTAL NOTE** Environmental damage due to operating conditions and personal driving style

The pollutant emission of the vehicle is directly related to the way you operate the vehicle.

Operate your vehicle in an environmentally responsible manner to help protect the environment. Please observe the following recommendations on operating conditions and personal driving style.

## Operating conditions:

- Make sure that the tire pressure is correct.
- Do not carry any unnecessary weight (e.g. roof luggage racks once you no longer need them).
- Adhere to the service intervals. A regularly serviced vehicle will contribute to environmental protection.

Always have maintenance work carried out at a qualified specialist workshop.

# Personal driving style:

- Do not depress the accelerator pedal when starting the engine.
- Do not warm up the vehicle while stationary.
- Drive carefully and maintain a suitable distance from the vehicle in front.
- Avoid frequent, sudden acceleration and braking.
- Change gear in good time and use each gear only up to ⅔ of its maximum engine speed.
- Switch off the vehicle in stationary traffic, e.g. by using the ECO start/stop function.
- Drive in a fuel-efficient manner. Observe the ECO display for an economical driving style.

#### Environmental issues and recommendations:

It is recommended that you re-use or recycle materials instead of just disposing of them.

The relevant environmental guidelines and regulations serve to protect the environment and must be strictly observed.

# Mercedes-Benz GenuineParts



**ENVIRONMENTAL NOTE** Environmental damage due to not using recycled reconditioned components

Mercedes-Benz AG offers recycled reconditioned components and parts with the same quality as new parts. The same entitlement from the Limited Warranty is valid as for new parts.

Use recycled reconditioned components and parts from Mercedes-Benz AG.

NOTE Impairment of the operating efficiency of the restraint systems from installing accessory parts or from repairs or welding

Air bags and Emergency Tensioning Devices, as well as control units and sensors for the restraint systems, may be installed in the following areas of your vehicle:

- doors
- door pillars
- sill
- seats
- cockpit
- · instrument display
- · center console
- · lateral roof frame
- Do not install accessory parts such as audio systems in these areas.
- Do not carry out repairs or welding.
- Have accessories retrofitted at a qualified specialist workshop.

You could jeopardize the operating safety of your vehicle if you use parts, tires and wheels as well as accessories relevant to safety that have not been approved by Mercedes-Benz. Safety-critical systems (e.g. the brake system) may malfunction. Use only Mercedes-Benz GenuineParts or parts of equal quality. Use only tires, wheels and accessory parts that have been specifically approved for your vehicle model.

Mercedes-Benz GenuineParts are subject to strict quality inspections. Each part has been specially developed, manufactured or selected for Mercedes-Benz vehicles and adapted to them. Therefore, only Mercedes-Benz GenuineParts should be used.

More than 300,000 different Mercedes-Benz GenuineParts are available for Mercedes-Benz models.

All authorized Mercedes-Benz Service Centers maintain a supply of Mercedes-Benz GenuineParts for necessary service and repair work. In addition, strategically located parts delivery centers provide for quick and reliable parts service.

Always specify the vehicle identification number (VIN) (→ page 411) when ordering Mercedes-Benz GenuineParts.

### Operator's Manual

This Operator's Manual and the Digital Operator's Manual in the vehicle describe the following models and the standard and special equipment for your vehicle:

- The models and the standard and special equipment available at the time of this Operator's Manual going to press.
- The models and the standard and special equipment only available in certain countries.
- The models and the standard and special equipment, which will only be available at a later date.

Note that your vehicle may not have all features described. This is also the case for systems relevant to safety. Therefore, the equipment on your vehicle may differ from that in the descriptions and illustrations.

#### 24 General notes

The original purchase agreement for your vehicle contains a list of the equipment in your vehicle at the time of delivery.

Should you have any questions concerning equipment and operation, please consult an authorized Mercedes-Benz Center.

 Please bear in mind that all the speed values stated in this Operator's Manual are approximate and are subject to a certain tolerance.

The Operator's Manual, Supplement, further supplementary documents and Maintenance Booklet are important documents and should be kept in the vehicle.

# Mercedes me app

## Notes about the on-demand feature

You can also activate various functions (ondemand feature) subsequently via Mercedes me after purchasing your vehicle.

Information is available at any authorized Mercedes-Benz Service Center.

# Activating on-demand feature using Mercedes me

#### Requirements

- The vehicle has a wireless connection.
- The vehicle is linked to the Mercedes me user account.

## Ordering and activating on-demand feature

- Add the desired on-demand feature for the vehicle to the shopping basket in the Mercedes me Store.
- Complete the order.
   The on-demand feature is activated when operating the vehicle.

# Speeding up activation

- Switch the vehicle off and lock it.
- Unlock the vehicle after about two minutes and switch on the vehicle.

The on-demand feature has been activated. For some features, a notification also appears in the vehicle's multimedia system.

If the activation was not successful, repeat the process.

## Service and vehicle operation

# Vehicle operation outside the USA or Canada

When you are abroad with your vehicle, observe the following points:

- service points or replacement parts may not be available immediately.
- unleaded fuel may not be available for vehicles with a catalytic converter. Leaded fuel may cause damage to the catalytic converter.
- the fuel may have an extremely low octane number. Unsuitable fuel can cause engine damage.

Some Mercedes-Benz models are available in Europe through our European Delivery Program. For more information, please consult an authorized Mercedes-Benz Service Center, or write to one of the following addresses:

#### in the USA:

Mercedes-Benz USA, LLC European Delivery Department One Mercedes-Benz Drive Sandy Springs, GA 30328

#### in Canada:

Mercedes-Benz Canada, Inc. European Delivery Department 98 Vanderhoof Avenue Toronto. Ontario M4G 4C9

#### Maintenance

Your customer advisor confirms the service in the service report.

#### Roadside Assistance

The Mercedes-Benz Roadside Assistance Program offers technical help in the case of a breakdown. Your calls to the toll-free Roadside Assistance Hotline are answered by our agents 24 hours a day, 365 days a year.

1-800-FOR-MERCedes (1-800-367-6372) (USA) 1-800-387-0100 (Canada)

You can find further information in the Mercedes-Benz Roadside Assistance Program brochure (USA) or the "Roadside Assistance" section in the Service and Warranty booklet (Canada). You will find both in the vehicle document wallet.

# Change of address or change of ownership

In the event of a change of address, please send us the "Notification of address change" in the Service and Guarantee booklet or simply call the Mercedes-Benz Customer Assistance Center (USA) on the hotline number

1-800-FOR-MERCedes (1-800-367-6372) or Customer Service (Canada) on 1-800-387-0100. We can then reach you in a timely fashion, if necessary.

If you sell your Mercedes, please leave all literature in the vehicle so that it is available to the next owner. If you have purchased a used vehicle, please send us the "Notice of Purchase of Used Car" in the Service and Guarantee booklet or simply call the Mercedes-Benz Customer Assistance Center (USA) at the hotline number 1-800-FOR-MERCedes (1-800-367-6372) or Cus-

tomer Service (Canada) at 1-800-387-0100.

# Possible danger due to substances hazardous to health

In compliance with Proposition 65 ("Prop65"), the following detachable label has been added to each vehicle sold in California:



# WARNING



Operating, servicing and maintaining a passenger vehicle, pickup truck, van or off-road motor vehicle can expose you to chemicals including engine exhaust, carbon monoxide, phthalates, and lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. To minimize exposure, avoid breathing exhaust, do not idle the engine except as necessary, service your vehicle in a well-ventilated area and wear gloves or wash your hands frequently when servicing your vehicle. For more information go to www.P65Warmings.ca.gov/passenger-vehicle

# Operating safety



**WARNING** Risk of accident due to malfunctions or system failures

If you do not have the prescribed service/ maintenance work or any required repairs car-

#### 26 General notes

ried out, this could result in malfunctions or system failures.

Always have the prescribed service and maintenance work or any required repairs carried out in a qualified specialist workshop.

▲ WARNING Risk of accident or injury due to incorrect modifications on electronic component parts

Modification of electronic components, their software or wiring could impair their function and/or the function of other networked component parts or safety-relevant systems.

This can endanger the operating safety of the vehicle.

- Never tamper with the wiring and electronic component parts or their software.
- You should have all work on electrical and electronic components carried out at a qualified specialist workshop.

Observe the "On-board electronics" section in "Technical data".



**WARNING** Risk of fire caused by flammable material on hot exhaust system components

Flammable material such as leaves, grass or twigs may ignite if they come into contact with hot parts of the exhaust system.

- When driving on an unpaved road or offroad, check the vehicle underside regularly.
- In particular, remove trapped plant parts or other flammable material.
- If there is damage, consult a qualified specialist workshop immediately.

NOTE Damage to the vehicle due to driving too fast and due to impacts to the vehicle underbody or suspension components

In the following situations, in particular, there is a risk of damage to the vehicle:

- The vehicle becomes grounded, e.g. on a high curb or an unpaved road
- The vehicle is driven too fast over an obstacle, e.g. a curb, speed bump or pothole
- A heavy object strikes the underbody or suspension components

In situations such as these, damage to the body, underbody, suspension components, wheels or tires may not be visible. Components damaged in this way can unexpectedly fail or, in the case of an accident, may no longer absorb the resulting force as intended.

If the underbody paneling is damaged, flammable materials such as leaves, grass or twigs can collect between the underbody and the underbody paneling. These materials may ignite if they come into contact with hot parts of the exhaust system.

Have the vehicle checked and repaired immediately at a qualified specialist workshop.

or

If driving safety is impaired while continuing your journey, pull over and stop the vehicle immediately, while paying attention to road and traffic conditions, and contact a qualified specialist workshop.

## Vehicles with a 48 V on-board electrical system

**DANGER** Risk of fatal injury by touching damaged high-voltage components

Vehicles with a 48 V on-board electrical system contain individual high-voltage components. These high-voltage components are under high voltage.

If you modify component parts of these highvoltage components or touch damaged component parts, you may be electrocuted.

High voltage components may be damaged in an accident, although the damage may not be visible.

- Never perform modifications to component parts of high-voltage components.
- Never touch damaged component parts of high-voltage components.
- Never touch component parts of highvoltage components after an accident.

Vehicles with a 48 V on-board electrical system contain high-voltage components. These components are marked with a high-voltage label:



All work on high-voltage components must be carried out at a qualified specialist workshop.

Notes on assembling the license plate on the front license plate holder

NOTE Malfunctions and system failures due to incorrect mounting of the license plate on the front license plate holder

If the license plate is incorrectly mounted on the front license plate holder, sensors, cameras or driving and safety systems may malfunction or fail.

#### 28 General notes

Observe the following points when mounting the license plate on the front license plate holder:

- Mount the license plate directly on the license plate holder without advertising media or other holders.
- Mount the license plate so that it does not protrude above or to the side of the license plate adapter.

# National information for components relevant to radio regulation

# Information on crossing national borders

You must observe the radio regulations for the country in which you are currently operating your vehicle.



USA: "Radio based devices of this vehicle comply with Part 15 of the FCC Rules. Operation is subject to the following two conditions: 1) These devi-

ces may not cause harmful interference, and 2) These devices must accept any interference received, including interference that may cause undesired operation. Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment."

Canada: "This vehicle contains licence-exempt transmitter(s)/receiver(s) that comply with Innovation, Science and Economic Development Canada's licence-exempt RSS(s). Operation is subject to the following two conditions: (1) These devices may not cause interference. (2) These devices must accept any interference, including interference that may cause undesired operation of the devices." "Les émetteurs/récepteurs dans cette véhicule sont conforme aux CNR d'Innovation. Sciences et Développement économique Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes: 1) Ces appareils ne doivent pas produire de brouillage; 2) Ces appareils doivent accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement."

# Diagnostics connection

The diagnostics connection is a technical interface in the vehicle. It is used, for example, during repair and maintenance work or for reading out vehicle data in a specialist workshop. Diagnostic devices should therefore only be connected in a qualified specialist workshop.



WARNING Risk of accident due to connecting devices to the diagnostics connection

If you connect devices to the diagnostics connection of the vehicle, the function of vehicle systems and operating safety may be impaired.

For safety reasons, we recommend that you use and connect only products approved by an authorized Mercedes-Benz Service Center. **WARNING** Risk of accident due to objects in the driver's footwell

Objects in the driver's footwell may impede pedal travel or block a depressed pedal.

This jeopardizes the operating and road safety of the vehicle.

- Stow all objects in the vehicle securely so that they cannot get into the driver's footwell.
- Always install the floor mats securely and as prescribed in order to ensure that there is always sufficient room for the pedals.
- Do not use loose floor mats and do not place floor mats on top of one another.


NOTE Battery discharging from using devices connected to the diagnostics connection

Using devices at the diagnostics connection drains the battery.

Check the charge level of the battery.

If the charge level is low, charge the battery, e.g. by driving a considerable distance.

Please also note the information about the 12 V battery and short-distance trips in the "Driving and Parking" chapter ( $\rightarrow$  page 180).



Connecting and using another device with the diagnostics connection can have the following effects:

- · Malfunctions in the vehicle system
- Permanent damage to vehicle components

Please refer to the warranty terms and conditions for this matter.

Moreover, connecting equipment to the diagnostics connection can lead to emissions monitoring information being reset, for example. This may lead to the vehicle failing to meet the requirements of the next emissions inspection during the main inspection.

# Qualified specialist workshop

An authorized Mercedes-Benz Service Center is a qualified specialist workshop. It has the necessary special skills, tools and qualifications to correctly carry out the work required on your vehicle. This particularly applies to safety-relevant work.

#### 30 General notes

For the following, always have your vehicle checked at an authorized Mercedes-Benz Service Center:

- · Safety-relevant work
- Service and maintenance work
- Repair work
- Modifications as well as installations and conversions
- · Work on electronic components
- Vehicles with 48 V on-board electrical system: work on the high-voltage component of the 48 V on-board electrical system

Mercedes-Benz recommends a Mercedes-Benz Service Center.

#### Correct use of the vehicle

If you remove any warning stickers, you or others could fail to recognize certain dangers. Leave warning stickers in position.

Observe the following information in particular when driving your vehicle:

- the safety notes in this Operator's Manual, vehicle-specific supplements and further supplementary documents
- technical data for the vehicle
- traffic laws and regulations of the country you are currently driving in
- laws pertaining to motor vehicles and safety standards of the country you are currently driving in
- radio regulatory requirements of the country you are currently driving in

# Sport Utility Vehicle

A

**WARNING** Risk of accident when the center of gravity is too high

The vehicle may start to skid and rollover in the event of sudden steering maneuvers and/or when the vehicle's speed is not adapted to the road conditions. Always adapt your speed and driving style to the vehicle's driving characteristics and to the prevailing road and weather conditions.



USA



#### Canada

Utility vehicles have a significantly higher rollover rate than other types of vehicles.

If this type of vehicle is not driven safely, an accident can occur, the vehicle can roll over and occupants can suffer serious or even fatal injuries.

In a rollover crash, an unbelted person is significantly more likely to die than a person wearing a seat belt.

You and all vehicle occupants should always wear your seat belts.

## Notes for persons with electronic medical aids

Mercedes-Benz AG cannot, despite carefully developing vehicle systems, completely rule out the interaction of vehicle systems with electronic medical aids such as cardiac pacemakers.

In addition, there are components installed in the vehicle that, regardless of the operating status of the vehicle, can generate magnetic fields on a par with permanent magnets. These fields can be found, for example, in the area around the multimedia and sound system or also in the area of the seats, depending on the vehicle equipment.

For this reason, the following can occur in isolated cases, depending on the aids used:

- Medical aids malfunctioning
- · Adverse health effects

Observe the notes and warnings of the manufacturer of the medical aids; if in doubt, contact the device manufacturer and/or your doctor. If there is continuing uncertainty concerning the possibility of medical aids malfunctioning, Mercedes-Benz AG recommends using only few electrical

vehicle systems and/or maintaining a distance from the components.

Only have repairs and maintenance work in the area of the following components carried out at a qualified specialist workshop:

- · Vehicle components carrying live voltage
- Transmission antenna
- Multimedia system and sound system

If you have any queries or suggestions, consult a qualified specialist workshop.

# Problems with your vehicle

If you should experience a problem with your vehicle, particularly one that you believe may affect its safe operation, we urge you to contact an authorized Mercedes-Benz Center immediately to have the problem diagnosed and rectified. If the problem is not resolved to your satisfaction, please discuss the problem again with an authorized Mercedes-Benz Center or, if necessary, contact us at one of the following addresses:

In the USA:

#### 32 General notes

Mercedes-Benz USA, LLC Customer Assistance Center One Mercedes-Benz Drive Sandy Springs, GA 30328

#### In Canada:

Mercedes-Benz Canada, Inc. Customer Relations Department 98 Vanderhoof Avenue Toronto, Ontario M4G 4C9

## Reporting safety defects

# USA only:

The following text is published as required of manufacturers under Title 49, Code of U.S. Federal Regulations, Part 575 pursuant to the "National Traffic and Motor Vehicle Safety Act of 1966".

If you believe that your vehicle has a defect which could cause a crash or could cause injury or death, you should immediately inform the National Highway Traffic Safety Administration (NHTSA) in addition to notifying Mercedes-Benz USA, LLC.

If NHTSA receives similar complaints, it may open an investigation, and if it finds that a safety defect exists in a group of vehicles, it may order a recall and remedy campaign. However, NHTSA cannot become involved in individual problems between you, your dealer, or Mercedes-Benz USA, LLC.

To contact NHTSA, you may call the Vehicle Safety Hotline toll-free at 1-888-327-4236 (TTY: 1-800-424-9153); go to https://www.safercar.gov; or write to: Administrator, NHTSA, 400 Seventh Street, SW., Washington, DC 20590, USA.

You can also obtain other information about motor vehicle safety from https://www.safercar.gov.

# Canada only:

The following text is published as required of manufacturers under subsection 18.4 (4) of the Motor Vehicle Safety Regulations.

If you believe that your vehicle has a defect which could cause a crash or could cause injury or death, you should immediately inform Transport Canada in addition to notifying Mercedes-Benz Canada Inc.

If Transport Canada received similar complaints, it may open an investigation, and if it finds that a safety defect exists in a group of vehicles, it may order a recall and remedy campaign. However, Transport Canada cannot become involved in individual problems between you, your dealer, or Mercedes-Benz Canada Inc.

To contact Transport Canada, you may call the Defect Investigations and Recalls Division toll-free in Canada at 1-800-333-0510 or 819-994-3328 in the Gatineau-Ottawa area or internationally; may also go to the following websites for more information:

- English: https://www.tc.gc.ca/recalls
- French: https://www.tc.gc.ca/rappels

# **Limited Warranty**

! NOTE Damage to the vehicle arising from violation of these operating instructions.

Damage to the vehicle can arise from violation of these operating instructions.

This damage is not covered either by the Mercedes-Benz implied warranty or by the New- or Used-Vehicle Warranty.

Follow the instructions in these operating instructions on proper operation of your vehicle as well as on possible vehicle damage.

#### QR code for rescue card

QR codes are attached in the fuel filler flap and on the opposite side on the B-pillar. In the event of an accident, rescue services can use the QR code to quickly find the appropriate rescue card for your vehicle. The current rescue card contains the most important information about your vehicle (e.g. the routing of the electric lines) in compact form.

Further information can be obtained at https://www.mercedes-benz.de/gr-code

## Data storage

Data processing in the vehicle

#### Electronic control units

Your vehicle is installed with electronic control units. Control units process data that they e.g. receive from vehicle sensors, generate themselves or exchange among themselves. Some control units are required for the safe operation of your vehicle, some assist you when driving (e.g. driver assistance systems), while others enable convenience or infotainment functions.

In the following, you will find general information about data processing in the vehicle. Additional information on what specific data is collected, stored and transmitted to third parties for what purpose in your vehicle can be found in the notes on the functional features in question in the respective operating instructions. These are also available online and, depending on the equipment, digitally in the vehicle.

#### Personal data

Each vehicle is marked with a unique vehicle identification number. Depending on the country, this

vehicle identification number can be used by, for example, government authorities to determine the identity of the owner. There are other possibilities for using data collected from the vehicle to identify the owner or driver (e.g. the license plate number).

The data generated or processed by control units may therefore be personal or, under certain conditions, become personal. Depending on what vehicle data is available, it may be possible to make inferences about e.g. your driving behavior, location, route or use patterns.

# Legal requirements for the disclosure of data

If legal regulations exist, manufacturers are generally obligated to release data stored by the manufacturer to the necessary extent in individual cases at the request of state authorities. This may be the case during the investigation of a criminal offense, for example.

Within the framework of applicable law, state authorities are also authorized to read out data from vehicles themselves in specific cases. In the event of an accident, for example, information can

be read from the air bag control unit that can help to establish what happened.

#### Operating data in the vehicle

Control units process data to operate the vehicle.

This includes the following data:

- Vehicle status information such as the speed, longitudinal acceleration, lateral acceleration, number of wheel revolutions or the fastened seat belts display
- Ambient conditions such as temperature, rain sensor or distance sensor

As a rule, this data is volatile, is not stored beyond the operating time and is processed only in the vehicle itself. Control units (e.g. the vehicle key) often contain data memories. These are used to temporarily or permanently document information on the vehicle condition, component stress, maintenance requirements or technical events and malfunctions.

Depending on the technical equipment, the following data is stored:

 Operating status of system components (e.g. fill levels, tire pressure, battery status)

- Malfunctions or faults in important system components (e.g. lights, brakes)
- System reactions in special driving situations (e.g. air bag deployment, the intervention of stability control systems)
- information on events leading to vehicle damage

In special cases, it may be necessary to store data that would otherwise only be volatile. This may be the case if the vehicle has detected a malfunction, for example.

If you use services such as repair services or maintenance work, stored operational data can be read out and used together with the vehicle identification number, where necessary. It can be read out by service network employees (e.g. workshops and manufacturers) or third parties (e.g. breakdown services). The same applies to warranty cases and quality assurance measures.

The data is usually read out via the diagnostics connection in the vehicle, which is required by law. The operating data that is read out documents technical conditions of the vehicle or individual components and helps to diagnose mal-

functions, meet warranty obligations and improve quality. This data, in particular information on component stress, technical events, operating errors and other malfunctions, is transmitted to the manufacturer for this purpose together with the vehicle identification number if necessary. In addition, the manufacturer is subject to product liability. For this reason, the manufacturer also uses operational data from the vehicle for e.g. recalls. This data can also be used to check customer claims for warranty and guarantee.

Malfunction memories in the vehicle can be reset during repair or service work or, at your request, by a service company.

#### Comfort and infotainment functions

You can save comfort settings and customizations in the vehicle and change or reset them at any time.

Depending on the vehicle equipment, this includes the following settings:

- · Seat positions and steering wheel positions
- Suspension tuning and climate control settings
- Personalized settings (e.g. interior lighting)

You can incorporate data into the vehicle's infotainment functions yourself as part of the selected equipment.

Depending on the vehicle equipment, this includes the following data:

- Multimedia data (e.g. music, films or photos for playback in an integrated multimedia system)
- Address book data for use in conjunction with an integrated hands-free system or integrated navigation system
- Navigation destinations that have been entered
- · Data about using Internet services

This data for comfort and infotainment functions can be saved locally in the vehicle or is stored on a device that you have connected to the vehicle (e.g. smartphone, USB flash drive or MP3 player). If you have entered data yourself, you can delete it at any time.

The transfer of this data out of the vehicle takes place exclusively at your request. This applies in

particular when you are using online services according to the settings you have selected.

# Smartphone integration (e.g. Android Auto or Apple CarPlay®)

If your vehicle is equipped appropriately, you can connect your smartphone or another mobile end device to the vehicle. You can then control them using the controls integrated in the vehicle. The smartphone's picture and sound can be output via the multimedia system. Specific items of information are also sent to your smartphone. Depending on the type of integration, this includes position data, day/night mode and other general vehicle statuses. Please refer to the vehicle Operator's Manual / infotainment system operating instructions for further information.

This integration allows the use of selected smartphone apps (e.g. navigation apps, music player apps). No additional interaction – in particular active access to vehicle data – takes place between the smartphone and vehicle. The type of additional data processing is determined by the provider of the app being used. Whether you can configure settings for it and, if so, which ones,

depend on the app and your smartphone's operating system.

#### Online services

#### Wireless network connection

If your vehicle has a wireless network connection, it enables data to be exchanged between your vehicle and additional systems. The wireless network connection is made possible by the vehicle's own transmitter and receiver or by a mobile end device that you have brought into the vehicle, for example, a smartphone. Online functions can be used via the wireless network connection. This includes online services and applications/apps provided to you by the manufacturer or by other providers.

#### Manufacturer's services

Regarding the manufacturer's online services, the individual functions are described by the manufacturer in a suitable place, for example, in the Operator's Manual or on the manufacturer's website, where the relevant data protection information is also given. Personal data may be used for the provision of online services. Data is

exchanged via a secure connection, such as the manufacturer's designated IT systems. Any personal data which is collected, processed and used, other than for the provision of services, is done so exclusively on the basis of legal permission. This is the case, for example, for a legally prescribed emergency call system, a contractual agreement or when consent has been given.

You can have services and functions, some of which are subject to a fee, activated or deactivated. This excludes legally prescribed functions and services, such as an emergency call system.

#### Third-party services

If you use online services from other providers (third parties), these services are the responsibility of the provider in question and subject to that provider's data protection conditions and terms of use. As a general rule, the manufacturer has no influence on the content exchanged.

For this reason, when services are provided by third parties, please ask the service provider in question for information about the type, extent and purpose of the collection and use of personal data.

### Data protection rights

Depending on your country or the equipment and range of functions of your vehicle as well as the services you use and the services on offer, you are entitled to different data protection rights. Further information on data protection and your data protection rights can either be found on the manufacturer's website or you will receive this information as part of the various services and service offers. There you will also find the contact information for the manufacturer and its data protection officers.

At a workshop, for example, with the support of a specialist and possibly for a fee, you can have data read out which is stored only locally in the vehicle.

## MBUX multimedia system/Mercedes me connect

If the vehicle is equipped with the MBUX multimedia system or Mercedes me connect, additional data about the vehicle's operation, the use of the vehicle in certain situations, and the location of the vehicle may be compiled by the MBUX multimedia system or Mercedes me connect.

For additional information, please refer to the "MBUX multimedia system" section and/or the Mercedes me connect Terms and Conditions.

#### Event data recorder

USA only:

This vehicle is equipped with an event data recorder (EDR). The main purpose of an EDR is to record, in certain crash or near crash-like situations, such as an air bag deployment or hitting a road obstacle, data that will assist in understanding how a vehicle's systems performed. The EDR is designed to record data related to vehicle dynamics and safety systems for a short period of time, typically 30 seconds or less.

The EDR in this vehicle is designed to record such data as:

- How various systems in your vehicle were operating;
- Whether or not the driver and passenger safety belts were buckled/fastened;
- How far (if at all) the driver was depressing the accelerator and/or brake pedal; and,

· How fast the vehicle was traveling.

These data can help provide a better understanding of the circumstances in which crashes and injuries occur. NOTE: EDR data are recorded by your vehicle only if a non-trivial crash situation occurs; no data are recorded by the EDR under normal driving conditions and no personal data (e.g., name, gender, age, and crash location) are recorded. However, other parties, such as law enforcement could combine the EDR data with the type of personally identifying data routinely acquired during a crash investigation.

To read data recorded by an EDR, special equipment is required, and access to the vehicle or the EDR is needed. In addition to the vehicle manufacturer, other parties, such as law enforcement, that have the special equipment, can read the information if they have access to the vehicle or the EDR.

EDR data may be used in civil and criminal matters as a tool in accident reconstruction, accident claims, and vehicle safety. Since the Crash Data Retrieval CDR tool that is used to extract data from the EDR is commercially available,

Mercedes-Benz USA, LLC ("MBUSA") expressly disclaims any and all liability arising from the extraction of this information by unauthorized Mercedes-Benz personnel.

MBUSA will not share EDR data with others without the consent of the vehicle owners or, if the vehicle is leased, without the consent of the lessee. Exceptions to this representation include responses to subpoenas by law enforcement; by federal, state or local government; in connection with or arising out of litigation involving MBUSA or its subsidiaries and affiliates; or, as required by law.

Warning: The EDR is a component of the Restraint System Module. Tampering with, altering, modifying or removing the EDR component may result in a malfunction of the Restraint System Module and other systems.

State laws or regulations regarding EDRs that conflict with federal regulation are pre\-empted. This means that in the event of such conflict, the federal regulation governs. As of Dec 2016, 17 states have enacted laws relating to EDRs.

#### Copyright

### Free and open source software

Information on licenses for free and open-source software used in your vehicle can be found on the data carrier in your vehicle document wallet and with updates on the following website:

https://www.mercedes-benz.com/opensource

#### Registered trademarks

- Bluetooth<sup>®</sup> is a registered trademark of Bluetooth SIG, Inc.
- DTS™ is a registered trademark of DTS, Inc.
- Dolby<sup>®</sup> and MLP™ are registered trademarks of DOLBY Laboratories.
- ESP® and PRE-SAFE® are registered trademarks of Mercedes-Benz Group AG.
- HomeLink<sup>®</sup> is a registered trademark of Gentex Corporation.
- iPod<sup>®</sup> and iTunes<sup>®</sup> are registered trademarks of Apple Inc.

#### 38 General notes

- Burmester® is a registered trademark of Burmester Audiosysteme GmbH.
- Microsoft<sup>®</sup> and Windows Media<sup>®</sup> are registered trademarks of Microsoft Corporation.
- SIRIUS® is a registered trademark of Sirius XM Radio Inc.
- HD Radio™ is a registered trademark of iBiquity Digital Corporation.
- Gracenote<sup>®</sup> is a registered trademark of Gracenote, Inc.
- ZAGAT Survey® and related brands are registered trademarks of Zagat Survey, LLC.

## Brief overview of the most important points

#### Basic information

Make sure that the following prerequisites in particular have been met so that the components of the restraint system are able to provide the intended level of protection:

- Sit correctly (→ page 40).
- Fasten the seat belt correctly (→ page 41).
  - Function of the seat belt warning lamp  $(\rightarrow)$  page 43).
- The restraint system warning lamp 

   is not lit up after the self-test (→ page 42).
- The PASSENGER AIR BAG indicator lamps display the correct status of the front passenger air bag (→ page 43).

#### For clear understanding

The chapter "Occupant safety" includes information on equipment, functions and behaviors that contribute directly to safety of vehicle occupants.

The information is structured as follows:

• The most important information in brief: in this chapter, you are provided with an overview of

the relationship between the restraint system and the correct behavior of all vehicle occupants.

- Specific information: in further sections of the chapter "Occupant safety", you can find specific information on the equipment and functions of the restraint system.
- Keyword directory: you can also find certain subjects in this Operator's Manual using the keyword directory.

Information on the following subjects, among others, are not provided in the chapter "Occupant safety":

- Children in the vehicle (→ page 55)
- Driving and driving safety systems
   (→ page 211)
- Stowage areas (→ page 126)

### Defining generic terms clearly

In this Operator's Manual, the following generic terms are used:

• Occupant safety: comprises the components and system functions which help to minimize,

- as much as possible, the stresses on and consequences for vehicle occupants during an accident.
- Restraint system: comprises those components which, along with the vehicle structure, help prevent vehicle occupants from potentially coming into contact with parts of the vehicle interior. The seat belts and air bags, for example, are components of the restraint system.
- Child restraint system: you can find all information on this subject in the chapter "Children in the vehicle" (→ page 55).

#### Be diligent

For the components of the restraint system to provide the intended level of protection, it is essential that the sitting posture is correct and that the seat belt is correctly fastened.

Note that negligence when adjusting your sitting posture and fastening the seat belt may have serious consequences. Be diligent and make sure that all vehicle occupants are sitting correctly and have fastened their seat belts properly before starting every journey.

### Information on the correct seat position

The seat position must be correct in order for the components of the restraint system to provide the intended level of protection.

The seat position influences both the protection provided by the seat belt and the additional protection provided by the air bag.

The correct seat position with an almost upright posture and a correctly fastened seat belt also reduce the risk posed by the air bag when it is deployed.

When choosing the seat, take note of the available space. When you are sitting with the right posture in a nearly upright position, your head should not touch the roof.

## A

**WARNING** Risk of injury or death due to an incorrect seat position

If you deviate from the correct seat position, the air bag cannot provide its intended protective function.

Each vehicle occupant must make sure of the following.

- Put the seat in the correct position.
- Fasten seat belts correctly. Pregnant women must take particular care to ensure that the lap belt never lies across the abdomen.
- Observe the following information.

In order for the restraint system to provide the intended level of protection, observe the following information:

 Before starting your journey, adjust your seat correctly (→ page 99).

When doing so, make sure you are able to fasten your seat belt correctly. The shoulder belt strap must be routed forward from the seat belt outlet over the center of your shoulder.

- Keep your distance from the air bags, especially the front air bags. Set the driver's seat and front passenger seat as far back as possible while making sure the seat belt is fastened correctly.
- If persons are sitting on the rear seats, vehicle occupants should maintain a sufficient dis-

tance to the parts of the vehicle interior in front of them.

- Make sure there are no people, animals or objects between the vehicle occupants and an air bag.
- If you are the driver, observe the following information on the correct position of the driver's seat (→ page 99).

Hold the steering wheel only by the steering wheel rim. This allows the driver's air bag to fully deploy.

 Assume a nearly upright position, with your buttocks as far back as possible in the gap between the seat cushion and seat backrest.

This ensures that your back lies as flat and firmly as possible against the seat backrest.

- While driving, do not lean forward and do not lean against the door or side window. You may otherwise be in the deployment area of the air bags.
- Sit with your feet resting on the floor, if possible. Your thighs are slightly supported by the seat cushion

Do not put your feet up on the cockpit, for example. Your feet may otherwise be in the deployment area of the air bag.

• Fasten the seat belt correctly.

### Notes on wearing the seat belt correctly

Always fasten your seat belt correctly before starting a journey. A seat belt can provide the best level of protection only if it is worn correctly.

**WARNING** Risk of injury or death due to incorrectly fastened seat belt

If the seat belt is not worn correctly, it cannot perform its intended protective function.

In addition, an incorrectly fastened seat belt can also cause injuries, for example, in the event of an accident or when braking or changing direction suddenly.

Always ensure that all vehicle occupants have their seat belts fastened correctly and are sitting properly. ★ WARNING Risk of injury or death when additional restraint systems are not used for persons with a smaller stature

Persons under 5 ft (1.50 m) tall cannot wear the seat belt correctly without a suitable additional restraint system.

 Always secure persons under 5 ft (1.50 m) tall in a suitable restraint system.

Each vehicle occupant must observe the following notes in particular:

- . The seat belt must not be twisted:
- The shoulder belt strap must be routed forward from the seat belt outlet over the center of your shoulder.
- The shoulder belt strap should neither touch your neck nor be routed under your arm or behind your back.
- The lap belt must be routed as low down across the hips as possible.
  - In addition, push the lap belt down as far as possible across your hips and pull tight with

the shoulder belt strap. Never route the lap belt across your abdomen.

Pregnant women must also take particular care with this.

- The shoulder belt strap and lap belt must fit snugly against the body after being tightened.
- Avoid wearing bulky clothing, e.g. a winter coat.
- Never route the seat belt across sharp, pointed, abrasive or fragile objects.
- Only one person should use each seat belt at any one time.
- Never secure objects with a seat belt if the seat belt is also being used by one of the vehicle's occupants.

Also ensure that no objects, e.g. a cushion, are ever placed between a person and the seat.

### Fastening and adjusting seat belts

If the seat belt is pulled quickly or sharply, the seat belt retractor locks. The seat belt strap cannot be pulled out any further.

### 42 Occupant safety - Brief overview of the most important points



- Always engage seat belt tongue ① of the seat belt into seat belt buckle ② of the corresponding seat.
- To adjust the seat belt height: press button on the seat belt outlet and slide the seat belt outlet to the desired position.

! NOTE Deployment of components of the restraint system when the front passenger seat is unoccupied and a seat belt is buckled

When the front passenger seat is unoccupied and the seat belt tongue of the seat belt is engaged in the seat belt buckle, components of the restraint system may deploy unnecessarily on the front passenger side, e.g. the Emergency Tensioning Device.

- Only buckle the seat belts as intended.
- (i) Observe the information on child seat safety feature of the seat belt ( $\rightarrow$  page 63).

## Function of the restraint system warning lamp

When the vehicle is switched on, a self-test is performed, during which the restraint system warning lamp 👚 lights up. It goes out no later than a few seconds after the vehicle is started. The components of the restraint system are then functional.

A malfunction has occurred in the restraint system if:

- the restraint system warning lamp does not light up when the vehicle is switched on
- the restraint system warning lamp lights up continuously or repeatedly during a journey

If components of the restraint system have been deployed, the restraint system warning lamp [3] lights up continuously.

**WARNING** Risk of injury due to malfunctions in the restraint system

Components in the restraint system may be activated unintentionally or not deploy as planned in an accident.

Have the restraint system checked and repaired immediately at a qualified specialist workshop.

Mercedes-Benz recommends that you have the vehicle towed to a qualified specialist workshop.

### Function of the seat belt warning lamp

The seat belt warning lamp on the instrument display is a reminder that all vehicle occupants must wear their seat belts correctly.

The seat belt warning lamp will light up for six seconds every time the vehicle is started.

In addition, a warning tone may sound.

When the driver's and front passengers doors are closed and the driver and front passenger have fastened their seat belts, the seat belt warning will go out.

In the following cases, the seat belt warning will light up during a journey if:

- The vehicle speed exceeds 15 mph (25 km/h) and the driver's or front passenger seat belt is not fastened.
- The driver or front passenger unfastens his/her seat belt while the vehicle is in motion.

# Function of the PASSENGER AIR BAG indicator lamps (front passenger air bag)



The PASSENGER AIR BAG indicator lamps display the status of the front passenger air bag.

If the front passenger seat is occupied or a child restraint system is installed on the front passenger seat, you must make sure, both before and during a journey, that the status of the front

passenger air bag is correct for the current situation.

WARNING Risk of potentially fatal injuries due to objects trapped under the front passenger seat

Objects trapped under the front passenger seat may interfere with the function of the automatic front passenger air bag shutoff or damage the system.

- Do not stow any objects under the front passenger seat.
- When the front passenger seat is occupied, ensure that no objects have become trapped beneath the front passenger seat.

**Self-test:** when the vehicle is switched on, both the PASSENGER AIR BAG ON and OFF indicator lamps light up simultaneously for several seconds. After the self-test, you can determine the status of the front passenger air bag as follows:

 Front passenger air bag disabled: PASSENGER AIR BAG OFF lights up continuously. The front passenger air bag will not be deployed in the event of an accident. If PASSENGER AIR BAG OFF is lit, no one may use the front passenger seat.

If a rearward-facing child restraint system is installed on the front passenger seat, PASSENGER AIR BAG OFF must be lit continuously.

 Front passenger air bag enabled: PASSENGER AIR BAG ON lights up for up to 60 seconds or both the PASSENGER AIR BAG ON and OFF indicator lamps do not light up.

The front passenger air bag may be deployed during an accident. If the front passenger air bag has this status, no rearward-facing child restraint system may be installed on the front passenger seat.

(i) If you are driving with a child in the vehicle, observe the information in the chapter "Children in the vehicle" (→ page 55)

## **WARNING** Risk of injury or death due to a disabled front passenger airbag

The front passenger airbag is disabled when the PASSENGER AIR BAG OFF indicator lamp is lif.

A person in the front passenger seat could then, for example, come into contact with the vehicle interior, especially if the person is sitting too close to the cockpit.

If the front passenger seat is occupied, always ensure that:

- The classification of the person in the front passenger seat is correct and the front passenger airbag is enabled or disabled in accordance with the person in the front passenger seat.
- The front passenger seat has been moved as far back as possible.
- The person is seated correctly.
- Both before and during the journey, ensure that the status of the front passenger airbag is correct.

# Malfunction of the automatic front passenger air bag shutoff

The PASSENGER AIR BAG OFF indicator lamp and the restraint system indicator lamp light up simultaneously.

In this case, no one may use the front passenger seat and no child restraint system may be installed on the front passenger seat.

Have the automatic front passenger air bag shutoff checked and repaired immediately at a qualified specialist workshop.

Be sure to also observe the following further related subjects:

 Child restraint system on the front passenger seat (→ page 59)

# Deactivating or activating the front passenger air bag

The automatic front passenger air bag shutoff can activate or deactivate the front passenger air bag according to the situation.

This happens automatically as a result of the classification of the person or child restraint system on the front passenger seat.

You cannot manually activate or deactivate the front passenger air bag.

Also observe the following information:

- Status of the front passenger air bag: see
   "Function of the PASSENGER AIR BAG indicator lamps" (→ page 43)
- Notes on using the front passenger seat: see "Information on automatic front passenger air bag shutoff" (→ page 45)
- If you are driving with a child in the vehicle, observe the chapter "Children in the vehicle" (→ page 55)

#### Information on the child restraint system

When installing a child restraint system, observe the notes in "Children in the vehicle" ( $\rightarrow$  page 55).

# Notes on the child restraint system on the front passenger seat

A

**WARNING** Risk of injury or fatal injuries if the front passenger air bag is enabled

If the front passenger air bag is enabled, a child on the front passenger seat may be struck by the front passenger air bag in the event of an accident.

NEVER use a rearward-facing child restraint system on a seat with an ENA-BLED FRONT AIR BAG. This can result in the DEATH of or SERIOUS INJURY to the CHILD.

Also pay particular attention to the notes on rearward-facing or forward-facing child restraint systems on the front passenger seat ( $\rightarrow$  page 59).

# Information on the automatic functions of the restraint system

## Function of the automatic front passenger air bag shutoff

A person on the front passenger seat must observe the following information:

- Sit correctly (→ page 40).
- Fasten the seat belt correctly (→ page 41).

The automatic front passenger air bag shutoff can activate or deactivate the front passenger air bag according to the situation.

Make sure you observe the following information:

- Status of the front passenger air bag: see
   "Function of the PASSENGER AIR BAG indicator lamps" (→ page 43).
- When installing a child restraint system on the front passenger seat, observe the vehicle-specific information (→ page 59).

Status of the front passenger air bag in relation to the stature of the person:

Front passenger air bag deactivated:
 PASSENGER AIR BAG OFF lights up continuously.

The front passenger air bag will not be deployed in the event of an accident. If PASSENGER AIR BAG OFF is lit, no one may use the front passenger seat.

Front passenger air bag activated:
 PASSENGER AIR BAG ON lights up for up to
 60 seconds or neither the PASSENGER AIR
 BAG ON nor OFF indicator lamps light up.

The front passenger air bag may be deployed in the event of an accident. Observe the information on the correct seat position  $(\rightarrow$  page 40).

Vehicles with rear seats: a person of smaller stature should use a rear seat.

#### System limits

The front passenger air bag may be deactivated by mistake, for example, in the following situation:

- The front passenger transfers their weight by supporting themselves on a vehicle armrest.
- The front passenger sits in such a way that their weight is raised from the seat surface.
- I NOTE Deployment of components of the restraint system when the front passenger seat is unoccupied

In an accident, the components of the restraint system may deploy unnecessarily on the front passenger side if:

- There are heavy objects on the front passenger seat.
- The seat belt tongue is engaged in the seat belt buckle of the front passenger seat and the front passenger seat is unoccupied.
- Store objects in a suitable place.
- Only one person should use each seat belt at any one time.

Depending on the detected accident situation, the window curtain air bag on the front passenger side may deploy. The air bag is deployed regardless of whether the front passenger seat is occupied.

## Function of PRE-SAFE® (anticipatory occupant protection)

PRE-SAFE® is able to detect certain critical driving situations and implement pre-emptive measures to protect the vehicle occupants.

 $\mbox{\rm PRE-SAFE}^{\circledR}$  can implement the following measures independently of each other:

- Tightening the seat belts on the driver's seat and front passenger seat.
- · Closing the side windows.
- Vehicles with sliding sunroof: closing the sliding sunroof.
- Vehicles with memory function: moving the front passenger seat to a more favorable seat position.

- Vehicles with memory function in the rear passenger compartment: moving the outer rear seats to a more favorable seat position.
- Vehicles with multicontour seat: increasing the lateral support by inflating the seat side bolsters of the seat backrest.
- PRE-SAFE® Sound: provided that the multimedia system is switched on, generating a brief noise signal to stimulate the innate protective mechanism of a person's hearing.
- ! NOTE Damage caused by objects in the footwell or behind the seat

The automatic adjustment of the seat position may result in damage to the seat and/or the object.

Stow objects in a suitable place.

## Reversing the PRE-SAFE® system measures

If an accident did not occur, the pre-emptive measures that were taken will be reversed.

You will need to perform certain settings yourself.

If the seat belt pre-tensioning is not reduced, move the seat backrest back slightly. The locking mechanism will release.

# Function of PRE-SAFE® PLUS (anticipatory occupant protection plus)

PRE-SAFE® PLUS can detect certain impacts, particularly an imminent rear impact, and take preemptive measures to protect the vehicle occupants. These measures cannot necessarily prevent an imminent impact.

PRE-SAFE® PLUS can implement the following measures independently of each other:

- Tightening the seat belts on the driver's seat and front passenger seat.
- Increasing brake pressure when the vehicle is stationary. This brake application will be canceled automatically when the vehicle pulls away.

If an accident did not occur, the pre-emptive measures that were taken will be reversed.

#### System limits

The system will not initiate any action in the following situations:

- when the vehicle is backing up or
- when the vehicle is towing a trailer and there is a risk of a rear impact

The system will not initiate any brake application in the following situations:

- while you are driving
   or
- when you are entering or exiting a parking space while using Active Parking Assist

## Function of PRE-SAFE® Impulse Side

If an imminent side impact is detected, PRE-SAFE® Impulse Side can pre-emptively move the front seat vehicle occupant's upper body towards the center of the vehicle. It does this by rapidly inflating an air cushion in the outer seat side bolster of the seat backrest on the side on which the

impact is anticipated. This increases the distance between the door and the vehicle occupant.

If PRE-SAFE® Impulse Side has been deployed or is faulty, a display message reading PRE-SAFE Impulse Side Inoperative See Operator's Manual(→ page 429)will appear.

#### Seat belt adjustment function

Vehicles with PRE-SAFE®: after you have fastened the seat belt of the front seat, it may adjust itself against your body by pulling at the shoulder until somewhat tight. Do not hold the seat belt tightly while it is adjusting.

This function is a reminder that all vehicle occupants must wear their seat belts correctly.

You can activate and deactivate the seat belt adjustment function using the multimedia system ( $\rightarrow$  page 48).

## Activating/deactivating seat belt adjustment via the multimedia system

Multimedia system:

→ 🙀 >> Settings >> Vehicle

Activate or deactivate Belt Adjustment.

## Overview of the automatic measures after an accident

Depending on the type and severity of the accident, and depending on the vehicle's equipment, the following measures may be implemented, for example:

- automatic braking (post-collision brake)
- · activating the hazard warning lamps
- triggering an automatic emergency call
   (→ page 325)
- · switching off the engine

To start the vehicle again, switch the vehicle off and on once more ( $\rightarrow$  page 176). Depending on the type and severity of the accident, you may no longer be able to start the vehicle.

• switching off the fuel supply

- · unlocking the vehicle doors
- lowering the side windows
- displaying the emergency guide on the multimedia system display
- · switching on the interior lighting

## Function of the post-collision brake after an accident

Depending on the accident situation, the post-collision brake can minimise the severity of a further collision or even avoid it.

If an accident is detected, the post-collision brake can initiate automatic braking. When the vehicle has come to a standstill, the electric parking brake is automatically applied.

The driver can cancel automatic braking by taking the following actions:

- · Braking more strongly than automatic braking
- Fully depressing the accelerator pedal with force

## Purpose and function of the restraint system Overview of deployment situations (restraint sys

## Overview of deployment situations (restraint system)

Make sure that the following prerequisites in particular have been met so that the components of the restraint system are able to provide the intended level of protection:

- Sit correctly (→ page 40).
- Fasten the seat belt correctly ( $\rightarrow$  page 41).
  - Function of the seat belt warning lamp (→ page 43).
- The prestraint system warning lamp is not lit up after the self-test (→ page 42).
- The PASSENGER AIR BAG indicator lamps display the correct status of the front passenger air bag (→ page 43).

Depending on the detected deployment situation, the components of the restraint system can be activated or deployed independently of each other:

• Emergency Tensioning Device: frontal impact, rear impact, side impact, rollover

- Driver's air bag, front passenger air bag: frontal impact
- · Knee bag: frontal impact
- Side impact air bag: side impact
- Window curtain air bag: side impact, rollover, frontal impact
- Cushion air bag in the reclining rear seat: frontal impact
- PRE-SAFE® Impulse Side: side impact

The installation location of an air bag is identified by the AIRBAG symbol ( $\rightarrow$  page 54).

Observe the information on the function of the restraint system ( $\rightarrow$  page 49).

## Information on how the restraint system works

How the restraint system functions depends on the severity of the impact detected and the apparent type of accident.

For more information about types of accidents, see "Overview of deployment situations" ( $\rightarrow$  page 49).

The activation thresholds for the components of the restraint system are determined based on the evaluation of the sensor values measured at various points in the vehicle. This process is pre-emptive in nature. The triggering/deployment of the components of the restraint system must take place in good time at the start of the collision.

Factors that can be seen and measured only after a collision has occurred cannot play a decisive role in air bag deployment. Nor do they provide an indication of air bag deployment.

The vehicle may be deformed significantly without an air bag being deployed. This is the case if only parts which are relatively easily deformed are affected and the rate of vehicle deceleration is not high. Conversely, an air bag may be deployed even though the vehicle suffers only minor deformation. If very rigid vehicle parts such as longitudinal members are hit, this may result in sufficiently high levels of vehicle deceleration.

Depending on the apparent type of accident and the detected deployment situation, Emergency Tensioning Devices and/or air bags can supplement the protection offered by a correctly worn seat belt. When enabled, an air bag can provide additional protection for the respective vehicle occupant.

Potential protection provided by each air bag:

- · Knee air bag: thigh, knee and lower leg
- Driver's air bag, front passenger air bag: head and ribcage
- · Window air bag: head
- · Side air bag: ribcage and pelvis

However, no system available today can completely eliminate injuries and fatalities in every accident situation. In particular, the seat belt and air bag generally do not protect against objects penetrating the vehicle from the outside. It is also not possible to completely rule out the risk of injury caused by the air bag deploying.

Mercedes-Benz recommends that you have the vehicle towed to a qualified specialist workshop after an accident. Take this into account, particularly if an Emergency Tensioning Device is triggered or an air bag deployed.

If the Emergency Tensioning Devices are triggered or an air bag is deployed, you will hear a bang, and a small amount of powder may also be released:

- The bang will not generally affect your hearing.
- In general, the powder released is not hazardous to health but may cause short-term breathing difficulties to persons suffering from asthma or other pulmonary conditions.

Provided it is safe to do so, leave the vehicle immediately or open the window in order to prevent breathing difficulties.

Air bags and pyrotechnic Emergency Tensioning Devices contain perchlorate material, which may require special handling or environmental protection measures. National guidelines regarding waste disposal must be observed. In California, see the https://dtsc.ca.gov/. Using the search function, you will find information on perchlorate, for example.

# Information on the limited protection provided by the restraint system

## Risk due to the incorrect behavior of vehicle occupants

All vehicle occupants must make sure of the following in particular:

- They observe the information on the correct seat position (→ page 40).
- There are no heavy, sharp-edged or fragile objects in the pockets of their clothing. Store such objects in a suitable place.

# **WARNING** Risk of injury or death due to an incorrect seat position

The seat belt does not offer the intended level of protection if you have not moved the seat backrest to an almost vertical position.

In particular, you could slip beneath the seatbelt and become injured.

- Adjust the seat properly before beginning your journey.
- Always ensure that the seat backrest is in an almost vertical position and that

the shoulder belt is routed across the center of your shoulder.

#### Risk due to objects in the vehicle interior

All vehicle occupants must make sure of the following in particular:

- They observe the information on the correct seat position (→ page 40).
- There are no objects between the seat, door and door pillar (B-pillar).
- There are no hard objects, e.g. coat hangers, hanging on the grab handles or coat hooks.
- There are no heavy, sharp-edged or fragile objects in the pockets of their clothing. Store such objects in a suitable place.

▲ WARNING Risk of injury or death due to blocked seat belt buckle or seat belt anchorage

Objects next to the front seat that block the seat belt buckle or the moving seat belt anchorage on the front seat impair the function of the Emergency Tensioning Devices.

Before starting the journey, make sure that there are no objects around the seat belt buckle or between the front seat and door.

## A

**WARNING** Risk of injury from objects in the deployment area of an airbag

Objects in the deployment area of an airbag can hinder or prevent the correct deployment of the airbag.

The airbag may then deploy in an uncontrolled manner and may even cause additional injuries to the vehicle occupants by deploying. This may be the case in particular if the airbag is integrated into the seat.

- Always stow and secure objects correctly.
- Before commencing your journey, make sure that no objects are stowed in the deployment area of an airbag.

The installation location of an air bag is identified by the AIRBAG ( $\rightarrow$  page 54) symbol.

#### Risk due to installing accessories

Do not attach accessories such as mobile navigation devices, mobile phones or cup holders within the deployment area of an air bag, e.g. on the cockpit, on the door, on the side window or on the side trim.

In addition, no connecting cables, tensioning straps or retaining straps may be routed or attached to the vehicle within the deployment area of an air bag. Always comply with the accessory manufacturer's installation instructions and, in particular, the notes on suitable places for installation.



**WARNING** Risk of injury or death due to unsuitable protective covers

Unsuitable protective covers mean that air bags can no longer protect vehicle occupants as they are designed to do.

Use only protective covers approved by Mercedes-Benz for the seat in question.

In addition, the function of the automatic passenger air bag deactivation may be restricted by an unsuitable protective cover. If the front

passenger seat is occupied, ensure that the PASSENGER AIR BAG indicator lamps display the correct status of the front passenger air bag  $(\rightarrow page 43)$ .

#### Risk due to pets in the vehicle interior

WARNING Risk of accident and injury due to animals left unsecured or unattended in the vehicle

If you leave animals in the vehicle unattended or unsecured, they could possibly press buttons or switches.

An animal may:

- Activate vehicle equipment and become trapped, for example
- · Switch systems on or off and endanger other road users

Unsecured animals may be thrown around in the vehicle in the event of an accident or sudden steering and braking maneuvers and injure vehicle occupants in the process.

- Never leave animals in the vehicle unattended.
- Always correctly secure animals while driving, e.g. using a suitable animal carrier.

Risk due to modification, damage or wear to the components of the restraint system



WARNING Risk of injury or death due to modifications to the restraint system

Vehicle occupants may no longer be protected as intended if alterations are made to the restraint system.

- Never alter the parts of the restraint system.
- Never tamper with the wiring or any electronic component parts or their software.

If it is necessary to modify the vehicle to accommodate a person with disabilities, contact an authorized Mercedes-Benz Center for details.

USA only: for details, contact our Customer Assistance Center on 1-800-FOR-MERCedes (1-800-367-6372).



WARNING Risk of injury or death due to damaged or modified seat belts

Seat belts cannot provide protection in the following situations:

- · The seat belt is damaged, has been modified, is extremely dirty, bleached or dyed
- . The seat belt buckle is damaged or extremely dirty
- Modifications have been made to the Emergency Tensioning Device, seat belt anchorage or seat belt retractor

Seat belts may sustain non-visible damage in an accident, e.g. due to glass splinters.

Modified or damaged seat belts could tear or fail in the event of an accident, for example.

Modified Emergency Tensioning Devices could accidentally trigger or fail to function as intended.

- Never modify the seat belt system, for example the seat belt, seat belt buckle, Emergency Tensioning Device, seat belt anchorage and seat belt retractor.
- Make sure that the seat belts are undamaged, not worn and clean.
- Always have the seat belts checked immediately after an accident at a qualified specialist workshop.

Use only seat belts that have been approved for your vehicle by Mercedes-Benz.

**WARNING** Risk of injury due to modifications to the cover of an airbag

If you change the cover of an airbag or attach objects, e.g. even stickers, to it, the airbag may no longer function as intended.

- Never modify the cover of an airbag.
- ▶ Do not attach any objects to the cover.

The installation location of an air bag is identified by the AIRBAG symbol ( $\rightarrow$  page 54).

**WARNING** Risk of injury due to malfunctioning sensors in the door

The function of the airbags can be impaired due to modifications or incorrect work performed on the doors or door trim, or if the doors are damaged.

- Never modify the doors or parts of the doors.
- Always have work on the doors or door trim carried out at a qualified specialist workshop.

# Risk due to components of the restraint system that have already been deployed

Mercedes-Benz recommends that you have the vehicle towed to a qualified specialist workshop after an accident.

▲ WARNING Risk of burns from hot air bag components

The air bag parts are hot after an air bag has been deployed.

Do not touch the air bag parts.

Have a deployed air bag replaced at a qualified specialist workshop as soon as possible.

**WARNING** Risk of injury due to deployed airbag

A deployed airbag no longer offers any protection.

Have the vehicle towed to a qualified specialist workshop in order to have the deployed airbag replaced.

Have deployed air bags replaced immediately.

WARNING Risk of injury or death from deployed pyrotechnic Emergency Tensioning Devices

Pyrotechnic Emergency Tensioning Devices that have been deployed are no longer operational and are unable to perform their intended protective function.

Therefore, have deployed pyrotechnic Emergency Tensioning Devices immedi-

#### 54 Occupant safety

ately replaced at a qualified specialist workshop.

#### Seat belts

#### Releasing seat belts


- Press the release button in the seat belt buckle and guide the seat belt back with the seat belt tongue.
- ! NOTE Damage caused by trapping the seat belt

If an unused seat belt is not fully retracted, it may become trapped in the door or in the seat mechanism.

Always ensure that an unused seat belt is fully retracted.

### **Airbags**

### Overview of air bags



- Oriver's knee air bag
- ② Driver's air bag
- Front passenger air bag
- Window curtain air bag
- Side impact air bag

The installation location of an air bag is identified by the AIRBAG symbol.

Note the information under "Overview of deployment situations" ( $\rightarrow$  page 49).


## Information on the cushionbag in the reclining rear seat


The cushionbag offers additional occupant protection in the event of frontal impacts. When triggered, the cushionbag deploys under the seat cushion. This helps prevent the vehicle occupant from slipping off the seat cushion.

If you install a child restraint system on the reclining rear seat, always observe the additional notes ( $\rightarrow$  page 55).

## Brief overview of most important points

Safely transporting children in the vehicle





Always observe the following when transporting children:

- Never leave children unattended in the vehicle (→ page 57).
- Secure children up to a height of 5 ft (1.50 m) on the respective seat (see illustration above) properly with a suitable and approved child restraint system, and secure small children in a rearward-facing child restraint system.
- Observe the child restraint system manufacturer's installation instructions.

### Left/right rear seat (preferred seats)

Second row of seats - preferred securing system:

SOFIX mounting brackets

and

Also secure Top Tether if present (→ page 67).

Second row of seats – alternative securing system:

 $\checkmark$  Vehicle seat belt ( $\rightarrow$  page 69)

Additionally attach Top Tether if recommended by the manufacturer of the child restraint system (→ page 67).

Third row of seats, preferred securing system:

LATCH-type (ISOFIX) child seat securing system

Also secure Top Tether if present  $(\rightarrow \text{ page } 67)$ .

Third row of seats - alternative securing system:

 $\checkmark$  Vehicle seat belt ( $\rightarrow$  page 69)

Also secure Top Tether if present  $(\rightarrow page 67)$ .

#### Front passenger seat

Securing system:

★ Vehicle seat belt (→ page 69)


Be sure to observe:

 If the front passenger seat is occupied, ensure that the status of the front passenger air bag is correct for the current situation (→ page 43).

(\*) rearward-facing child restraint system only in combination with automatic air bag shutoff

### Center rear seat (second row of seats only)

Securing system:





Additionally attach Top Tether if recommended by the manufacturer of the child restraint system ( $\rightarrow$  page 67).

#### Important safety notes

#### **Basic information**

#### Be diligent

Bear in mind that negligence when securing a child in the child restraint system may have serious consequences. Always be diligent in securing a child carefully before every journey.

Never allow babies and children to travel sitting on the lap of another vehicle occupant.

To improve protection for children younger than 12 years old or under 5 ft (1.50 m) in height, Mercedes-Benz recommends you observe the following information:

- Always secure the child in a child restraint system suitable for this Mercedes-Benz vehicle.
- The child restraint system must be appropriate to the age, weight and size of the child.
- The vehicle seat must be suitable for the child restraint system to be installed:

Accident statistics show that children secured on the rear seats are generally safer than children secured on the front seats. For this reason,

Mercedes-Benz strongly advises that you install a child restraint system on a rear seat.

### The generic term "child restraint system"

The generic term "child restraint system" is used in this Operator's Manual. A child restraint system is, for example:

- · a baby car seat
- · a rearward-facing child seat
- · a forward-facing child seat
- a child booster seat Mercedes-Benz recommends using a child booster seat with a backrest and seat belt guide.

### Observe laws and legal requirements

Always observe the legal requirements when using a child restraint system in the vehicle.

## Securing systems for child restraint systems in the vehicle

Use only the following securing systems for child restraint systems:

- the LATCH-type (ISOFIX) securing rings
- the vehicle's seat belt system

• the Top Tether anchorages

Simply attaching to the LATCH-type (ISOFIX) securing rings on the vehicle can reduce the risk of installing the child restraint system incorrectly.

When securing a child with the integrated seat belt of the ISOFIX/LATCH child restraint system, always comply with the permissible gross weight for the child and child restraint system ( $\rightarrow$  page 64).

A child booster seat may be necessary to achieve proper seat belt positioning for children over 40 lbs (18 kg) in weight or until they reach a height at which they can wear a three-point seat belt properly without a child booster seat.

Mercedes-Benz recommends a suitable child booster seat with a backrest and seat belt guide.

### Observe standards for child restraint systems

All child restraint systems must meet the following standards:

- U.S. Federal Motor Vehicle Safety Standards 213
- Canadian Motor Vehicle Safety Standards 213

Confirmation that the child restraint system complies with the standards can be found on an instruction label on the child restraint system. This confirmation can also be found in the installation instructions that are included with the child restraint system.

#### Important warning notices

### Always secure a child restraint system correctly

WARNING Risk of injury or death due to incorrect installation of the child restraint system

The child can then not be protected or restrained as intended.

- Be sure to comply with the manufacturer's installation instructions for the child restraint system and its correct use.
- Make sure that the entire base of the child restraint system always rests on the sitting surface of the seat.

- Never place objects (e.g. cushions) under or behind the child restraint system.
- Use child restraint systems only with the original cover designed for them.
- Always replace damaged covers with genuine covers.
- Always observe the vehicle-specific information.
  - Installing an ISOFIX/LATCH child restraint system on the right and left rear seats (→ page 64).
  - Securing the child restraint system with the seat belt (→ page 69).
- Observe the warning labels in the vehicle interior and on the child restraint system.

▲ WARNING Risk of injury or death due to unsecured child restraint systems in the vehicle

If the child restraint system is incorrectly mounted or unsecured, it may come loose.

The child can then not be protected or restrained as intended

Unused child restraint systems could be flung around and hit vehicle occupants.

- Always comply with the manufacturer's installation instructions for the child restraint system and its correct use.
- Always fit child restraint systems correctly, even if they are transported in the vehicle unused.

### Do not modify the child restraint system

▲ WARNING Risk of injury due to modifications to the child restraint system

The child restraint system can no longer function properly. This poses an increased risk of injury.

- Never modify a child restraint system.
- Only affix accessories which have been specially approved for this child restraint system by the child restraint system's manufacturer.

### Only use child restraint systems which are in proper working condition



WARNING Risk of injury or death caused by the use of damaged child restraint sys-

Child restraint systems or their retaining systems that have been subjected to stress in an accident may not be able to perform their intended protective function.

It may be the case that the child cannot be properly restrained.

- Always immediately replace child restraint systems that have been damaged or involved in an accident.
- Have the securing systems for the child restraint systems checked at a qualified specialist workshop before installing a child restraint system again.

### Avoid direct sunlight



WARNING Risk of burns when the child seat is exposed to direct sunlight

If the child restraint system is exposed to direct sunlight or heat, parts could heat up excessively.

Children could suffer burns from these parts. particularly the metallic parts of the child restraint system.

- Always make sure that the child restraint system is not exposed to direct sunlight.
- Cover the child restraint system with a blanket, for example.
- If the child restraint system has been exposed to direct sunlight, allow it to cool before securing a child into it.
- Never leave children unattended in the vehicle.

### Observe when stopping or parking

 WARNING Risk of fatal injury due to exposure to extreme heat or cold in the vehicle.

If persons, particularly children, are subjected to prolonged exposure to intense heat or cold, there is a risk of severe injury or even death.

Never leave persons, particularly children, unattended in the vehicle.

WARNING Risk of accident and injury due to children left unattended in the vehicle

If you leave children unattended in the vehicle, they could, in particular:

- open doors, thereby endangering other persons or road users.
- get out and be struck by oncoming traffic.
- operate vehicle equipment and become trapped, for example.

In addition, the children could also set the vehicle in motion by, for example:

- releasing the parking brake.
- changing the gearbox position.
- starting the vehicle.
- Never leave children unattended in the vehicle.
- When leaving the vehicle, always take the key with you and lock the vehicle.
- Keep the key out of reach of children.

# Notes on rearward-facing and forward-facing child restraint systems on the front passenger seat

WARNING Risk of injury or fatal injury when using a rearward-facing child restraint system while the co-driver airbag is enabled

If you secure a child in a rearward-facing child restraint system on the co-driver seat and the PASSENGER AIR BAG OFF indicator lamp is off, the co-driver airbag can deploy in the event of an accident.

The child could be struck by the airbag.

- Always ensure that the co-driver airbag is disabled. The PASSENGER AIR BAG OFF indicator lamp must be lit.
- NEVER use a rearward-facing child restraint system on a seat with an ENA-BLED FRONT AIRBAG; DEATH or SERI-OUS INJURY to the CHILD can occur.

Observe the specific instructions for the rearward-facing and forward-facing child restraint systems ( $\rightarrow$  page 62).

If it is absolutely necessary to install a child restraint system on the front passenger seat, always observe the following notes:

 When using a rearward-facing child restraint system on the front passenger seat, the front passenger air bag must always be disabled. This is only the case if the PASSENGER AIR BAG OFF indicator lamp is lit continuously (→ page 43).  The front passenger air bag is enabled when the PASSENGER AIR BAG OFF indicator lamp is not lit. The front passenger air bag may be deployed during an accident. In that case, do not use rearward-facing child restraint systems.

## Information on automatic front passenger air bag shutoff

If the front passenger seat is occupied, ensure, both before and during the journey, that the status of the front passenger air bag is correct for the current situation.

A

**WARNING** Risk of injury or death due to objects between the seat surface and the child restraint system

Objects between the seat surface and the child restraint system can interfere with the function of the automatic front passenger air bag shutoff.

- Do not place any objects between the seat surface and the child restraint system.
- Make sure that the entire base of the child restraint system rests on the seat cushion of the front passenger seat.
- The backrest of a forward-facing child restraint system must, as far as possible, be resting against the seat backrest of the front passenger seat.
- Always comply with the installation instructions from the child restraint system manufacturer.

When installing a child restraint system on the front passenger seat, observe the vehicle-specific information ( $\rightarrow$  page 59).

# Rearward-facing child restraint system on the front passenger seat

If a rearward-facing child restraint system is installed on the front passenger seat, the front passenger air bag must be disabled. The PASSENGER AIR BAG OFF indicator lamp must be continuously lit ( $\rightarrow$  page 43).

WARNING Risk of injury or fatal injury when using a rearward-facing child restraint system while the co-driver airbag is enabled

If you secure a child in a rearward-facing child restraint system on the co-driver seat and the PASSENGER AIR BAG OFF indicator lamp is off, the co-driver airbag can deploy in the event of an accident.

The child could be struck by the airbag.

- Always ensure that the co-driver airbag is disabled. The PASSENGER AIR BAG OFF indicator lamp must be lit.
- NEVER use a rearward-facing child restraint system on a seat with an ENA-BLED FRONT AIRBAG; DEATH or SERI-OUS INJURY to the CHILD can occur.
- (i) Depending on the child restraint system and the stature of the child, the front passenger air bag will be enabled. The PASSENGER AIR BAG OFF indicator lamp will not light up.

The front passenger air bag may be deployed during an accident. If the front passenger air bag has this status, no rearward-facing child restraint system may be installed on the front passenger seat.

Instead, install the rearward-facing child restraint system on a suitable rear seat.

## Forward-facing child restraint system on the front passenger seat

If a forward-facing child restraint system is installed on the front passenger seat, the front passenger air bag may be automatically enabled or disabled. The status of the front passenger air bag depends on the child restraint system and the stature of the child.

The PASSENGER AIR BAG OFF indicator lamp will either light up continuously or not light up ( $\rightarrow$  page 43). Always observe the following information.

WARNING Risk of injury or death due to incorrect positioning of the child restraint system

If you secure a child in a forward-facing child restraint system on the co-driver seat and you position the co-driver seat too close to the dashboard, in the event of an accident, the child could:

- come into contact with the vehicle's interior if the PASSENGER AIR BAG OFF indicator lamp is lit, for example
- be struck by the airbag if the PASSENGER AIR BAG OFF indicator lamp is off
- Always move the co-driver seat as far back as possible. In doing so, always make sure that the shoulder belt strap is correctly routed from the seat belt outlet of the vehicle to the shoulder belt guide on the child restraint system. The shoulder belt strap must be routed forwards and downwards from the seat belt outlet. If necessary, adjust the seat belt outlet and the co-driver seat accordingly.

Always comply with the child restraint system manufacturer's installation instructions.

Be sure to also observe the following further related subjects:

 Function of the automatic front passenger air bag shutoff (→ page 43)

## Suitable child restraint systems for the transport of children

# Information on the benefit of a rearward-facing child restraint system

Transport a baby in a suitable rearward-facing child restraint system only. It is also preferable to transport a small child in a suitable rearward-facing child restraint system. In this case, the child sits in the opposite direction to the direction of travel and faces backwards.

Babies and small children have comparatively weak neck muscles in relation to the size and weight of their head. The risk of injury to the cer-

vical spine during an accident can be reduced in a rearward-facing child restraint system.

## Securing the child restraint system Adjusting the seat correctly

When installing a child restraint system on the left or right rear seat, always observe the following:

Make sure that the child's feet do not touch the front seat. If necessary, move the front seat slightly forwards.

If the head restraint of the child restraint system cannot be fully extended when it is installed in the vehicle, this will result in restrictions on the maximum size setting for certain child restraint systems. Observe the child restraint system manufacturer's installation instructions.

(i) Contact with the roof when the head restraint is fully extended and locked in place will not result in any restrictions on use.

When installing an ISOFIX/LATCH child restraint system, also observe the following:

- When using a rearward-facing child restraint system on a rear seat: adjust the front seat so that it does not touch the child restraint system.
- When using a forward-facing child restraint system with integrated child seat belt: adjust the head restraint of the respective seat so that it does not push the child restraint system forwards. If necessary, the respective head restraint can be removed. In addition, the backrest of the child restraint system must lie as flat as possible against the backrest of the vehicle seat. After the child restraint system has been removed, replace the vehicle head restraint immediately and adjust it correctly.
- The child restraint system must not be put under strain between the roof and the seat cushion and/or be installed facing the wrong direction. Where possible, adjust the seat cushion inclination accordingly.

Adjust the vehicle head restraints so that the child restraint system is not put under strain by the head restraint.

When installing a belt-secured child restraint system, also observe the following:

- When using a rearward-facing child restraint system on a rear seat: adjust the front seat so that it does not touch the child restraint system.
- Also secure Top Tether if available  $(\rightarrow page 67)$
- When using a forward-facing child restraint system with integrated child seat belt: adjust the head restraint of the respective seat so that it does not push the child restraint system forwards. If necessary, the respective head restraint can be removed. In addition, the backrest of the child restraint system must lie as flat as possible against the backrest of the vehicle seat. After the child restraint system has been removed, replace the vehicle head restraint immediately and adjust it correctly.

- The backrest of a forward-facing child restraint system must, as far as possible, be resting on the seat backrest of the rear seat.
- ► The child restraint system must not be put under strain between the roof and the seat cushion and/or be installed facing the wrong direction. Where possible, adjust the seat cushion inclination accordingly.
- Adjust the vehicle head restraints so that the child restraint system is not put under strain by the head restraint.
- Make sure that the child's feet do not touch the front seat. If necessary, move the front seat slightly forwards.
- A Depending on the vehicle equipment, always observe the following when installing a belt-secured child restraint system on the front passenger seat:
- Observe the notes on rearward-facing and forward-facing child restraint systems on the front passenger seat (→ page 59).
- When using a forward-facing child restraint system with integrated child seat belt: remove

the head restraint from the respective seat, if possible. After the child restraint system has been removed, immediately replace the head restraint and adjust it correctly.

- The backrest of the forward-facing child restraint system must, as far as possible, be resting on the seat backrest of the front passenger seat.
- The child restraint system must not be put under strain between the roof and the seat cushion and/or be installed facing the wrong direction.
- Adjust the vehicle head restraints so that the child restraint system is not put under strain by the head restraint.
- Never place objects (e.g. cushions) under or behind the child restraint system.
- Set the front passenger seat as far back as possible and move the seat into the highest position if possible. Always make sure that the shoulder belt strap is correctly routed from the seat belt outlet of the vehicle to the shoulder belt guide on the child restraint system. The shoulder belt strap must be routed for-

wards from the seat belt outlet and, where possible, downwards to the child restraint system

- Fully retract the seat cushion length adjustment.
- Adjust the seat cushion inclination so that the front edge of the seat cushion is in the highest position and the rear edge of the seat cushion is in the lowest position.
- Set the seat backrest to the most vertical position possible.

## Activating or deactivating the special seat belt retractor of the seat belt

A

WARNING Risk of injury or death if a seat belt is unfastened while the vehicle is in motion

If the seat belt is released while the vehicle is in motion, the special seat belt retractor is deactivated and the child restraint system is no longer correctly secured. The seat belt is drawn in slightly by the inertia reel and cannot be immediately closed again.

#### 64 Safely transporting children in the vehicle

- Stop the vehicle immediately in accordance with the traffic conditions.
- Activate the special seat belt retractor again and correctly secure the child restraint system.

When enabled, the child seat safety feature ensures that the seat belts of the front passenger seat and rear seats do not slacken once the child restraint system is secured.

The seat belts on the following seats are equipped with a child seat safety feature:

- Front passenger seat
- · Rear seats

#### Installing a child restraint system

- When installing a child restraint system, always observe the manufacturer's installation and operating instructions as well as the information in this Operator's Manual.
- Pull the seat belt smoothly from the seat belt outlet.
- Engage the seat belt tongue in the belt buckle.

#### Activating the special seat belt retractor:

- Pull the seat belt out fully and let the inertia reel retract it again.
   When the special seat belt retractor is activated, you should hear a ratcheting sound.
- Push the child restraint system down until the seat belt sits tightly.

#### Deactivating the special seat belt retractor:

- Press the release button of the seat belt buckle.
- Hold the seat belt tongue and guide back to the seat belt outlet.

## Installing an ISOFIX/LATCH child restraint system

WARNING Risk of accident if the rear bench seat, rear seat and seat backrest are not engaged

The rear bench seat, rear seat and seat backrest may fold forwards, even when you are driving.

- As a result, the vehicle occupant will be pushed into the seat belt with increased force. The seat belt will not be able to protect as intended and could cause additional injury.
- Objects or loads in the trunk or cargo compartment will not be restrained by the seat backrest.
- Make sure that the rear bench seat, the rear seat and the seat backrest are engaged before every trip.

If the seat backrest is not engaged and locked in place, this will be shown on the instrument display (folding the rear seat back electrically) or the red lock verification indicator will be visible (folding the rear seat back manually).

WARNING Risk of injury or death if the permissible gross mass of the child and child restraint system together is exceeded.

Too much load may be placed on the LATCHtype (ISOFIX) or iSize child restraint systems and the child may not be restrained correctly in the event of an accident, for example.

If the child is secured in a LATCH-type (ISOFIX) child restraint system with integrated seat belt, the total mass of the child and child restraint system must not exceed 73 lb (33 kg).

Always comply with the information about the mass of the child:

- in the manufacturer's installation and operating instructions for the child restraint system used
- on a label on the child restraint system, if present

Regularly check that the permissible gross mass of the child and child restraint system is still complied with.


When installing a child restraint system, observe the following:

Always observe the correct use of the seats and consider their suitability for attaching a child restraint system.

LATCH-type (ISOFIX) mounting brackets


- Before every journey, make sure that the ISO-FIX/LATCH child restraint system is engaged in both securing rings in the vehicle.
- NOTE Damage to the seat belt for the center seat during installation of the child restraint system
- Make sure that the seat belt is not trapped.

#### Vehicles with individual rear seats:



- LATCH-type (ISOFIX) mounting bracket
- Remove and stow away covers 
  of the mounting brackets in the vehicle.
- Attach the ISOFIX/LATCH child restraint system to both mounting brackets in the vehicle.
- After removing the child restraint system, reattach covers .

#### Vehicles with a rear bench seat:




- Mercedes-Maybach vehicles with reclining rear seats: tilt the backrest of the reclining rear seat back slightly before the ISOFIX/ LATCH child restraint system is installed.
- Remove upholstered lining ①.
- Vehicles without rear reclining seat: fold upholstered lining ① up.

- Turn the support on the rear side of upholstered lining by 90°.

  Upholstered lining remains folded up.
- Attach the ISOFIX/LATCH child restraint system to both mounting brackets (2) in the vehicle.
- Mercedes-Maybach vehicles with reclining rear seat: return the backrest of the reclining rear seat to an upright position. The backrest of the reclining rear seat must be in contact with the child restraint system.

#### Vehicles with a third row of seats:



Attach the ISOFIX/LATCH child restraint system to both LATCH-type (ISOFIX) mounting brackets .

### Fastening a Top Tether

A

WARNING Risk of injury or death if the rear seat backrests are not locked after Top Tether belts are installed

The rear seat backrests may fold forwards when you are driving.

As a result, child restraint systems will no longer be able to perform their intended protective function. This may also cause additional injuries.

- Always lock rear seat backrests after installing Top Tether belts.
- ▶ Observe the lock verification indicator.


If the seat backrest is not engaged and locked in place, this will be shown on the instrument display (folding the rear seat back electrically) or the red lock verification indicator will be visible (folding the rear seat back manually).

If the child restraint system is equipped with a Top Tether belt:

The risk of injury may be reduced by Top Tether. The Top Tether belt enables an

additional connection between the child restraint system attached with ISOFIX (left and right rear seats) or the seat belt (all rear seats) and the vehicle.

The Top Tether anchorages for the second row of seats are located on the rear side of the seat backrest. For the third row of seats, use the Top Tether anchorage on the rear side of the seat backrest.



Second row of seats




- If necessary, slide head restraint ① upwards (→ page 111).
- Install the ISOFIX/LATCH or belt-secured child restraint system with Top Tether. In doing so, comply with the child restraint system manufacturer's installation instructions.
- Guide Top Tether belt (3) under head restraint
   (1) between the two head restraint bars.
- If cargo compartment cover (a) is installed, guide Top Tether belt (b) downwards between cargo compartment cover (a) and seat backrest (a).

#### 68 Safely transporting children in the vehicle

- Hook Top Tether hook of Top Tether belt
   into Top Tether anchorage without twisting.
- Tension Top Tether belt (a). In doing so, comply with the child restraint system manufacturer's installation instructions.

#### Mercedes-Maybach vehicles



- If necessary, slide head restraint 

  upwards

  (→ page 111).
- Remove cover ② of Top Tether anchorage③.
- Install the ISOFIX/LATCH or belt-secured child restraint system with Top Tether. In doing so,

comply with the child restraint system manufacturer's installation instructions.



- Guide Top Tether belt (a) under head restraint between the two head restraint bars.
- Hook Top Tether hook (§) of Top Tether belt
   (§) into Top Tether anchorage (§) without twisting.
- ➤ Tension Top Tether belt <a>®</a>. In doing so, comply with the child restraint system manufacturer's installation instructions.
- If necessary, slide head restraint ① downwards (→ page 111). Make sure that you do

not interfere with the correct routing of Top Tether belt 4.

#### Securing the child restraint system with the seat belt

WARNING Risk of accident if the rear bench seat, rear seat and seat backrest are not engaged

The rear bench seat, rear seat and seat backrest may fold forwards, even when you are driving.

- As a result, the vehicle occupant will be pushed into the seat belt with increased force. The seat belt will not be able to protect as intended and could cause additional injury.
- · Objects or loads in the trunk or cargo compartment will not be restrained by the seat backrest.
- Make sure that the rear bench seat, the rear seat and the seat backrest are engaged before every trip.

If the seat backrest is not engaged and locked in place, this will be shown on the instrument display (folding the rear seat back electrically) or the red lock verification indicator will be visible (folding the rear seat back manually).

The seat belts on the following seats are equipped with a child seat safety feature:

- Front passenger seat
- · Rear seats

When enabled, the child seat safety feature ensures that the seat belts of the front passenger seat and rear seats do not slacken once the child restraint system is secured.

- For a child restraint system in the "Universal" or "Semi-Universal" category, make sure that the system has been approved for the vehicle seat.
- Install the child restraint system. The entire base of the child restraint system must always rest on the surface of the seat.
- Always make sure that the shoulder belt strap is correctly routed from the seat belt outlet of

the vehicle to the shoulder belt guide on the child restraint system.

The shoulder belt strap must be routed forwards from the seat belt outlet and, where possible, downwards to the child restraint sys-

- When installing on the rear seat: also secure Top Tether if present.
- When installing on the front passenger seat: if necessary, adjust the seat belt outlet and the front passenger seat accordingly.

#### Child safety locks

Activating or deactivating the child safety lock for the rear doors



WARNING Risk of accident and injury due to children left unattended in the vehicle

If you leave children unattended in the vehicle. they could, in particular:

· open doors, thereby endangering other persons or road users.

#### **70** Safely transporting children in the vehicle

- get out and be struck by oncoming traffic.
- operate vehicle equipment and become trapped, for example.

In addition, the children could also set the vehicle in motion by, for example:

- · releasing the parking brake.
- changing the gearbox position.
- · starting the vehicle.
- Never leave children unattended in the vehicle.
- When leaving the vehicle, always take the key with you and lock the vehicle.
- ► Keep the key out of reach of children.

**WARNING** Risk of fatal injury due to exposure to extreme heat or cold in the vehicle

If persons, particularly children, are subjected to prolonged exposure to intense heat or cold, there is a risk of severe injury or even death.

Never leave persons, particularly children, unattended in the vehicle.


WARNING Risk of accident and injury due to children left unattended in the vehicle

If children are traveling in the vehicle, they could, in particular:

- Open doors, thereby endangering other persons or road users.
- Get out and be struck by oncoming traffic.
- Operate vehicle equipment and become trapped, for example.
- Always activate the installed child safety locks if children are traveling in the vehicle
- Never leave children unattended in the vehicle.
- When leaving the vehicle, always take the SmartKey with you and lock the vehicle.


There are child safety locks for the rear doors and the rear side windows.

The child safety lock on the rear doors secures each door separately. The doors can no longer be opened from the inside.



- Press the lever in direction (activate) or (deactivate).
- Make sure that the child-proof locks are working properly.

# Activating and deactivating the child safety lock for the rear side windows



To activate/deactivate: press button ②.

The rear side window can be opened or closed in the following cases:

• Indicator lamp ① is lit: via the switch on the driver's door

 Indicator lamp is off: via the switch on the corresponding rear door or driver's door

## SmartKev

## Overview of key functions

**WARNING** Risk of accident and injury due to children left unattended in the vehicle

If you leave children unattended in the vehicle, they could, in particular:

- open doors, thereby endangering other persons or road users.
- get out and be struck by oncoming traffic.
- operate vehicle equipment and become trapped, for example.

In addition, the children could also set the vehicle in motion by, for example:

- · releasing the parking brake.
- changing the gearbox position.
- · starting the vehicle.
- Never leave children unattended in the vehicle.

- When leaving the vehicle, always take the key with you and lock the vehicle.
- ► Keep the key out of reach of children.
- I NOTE Damage to the SmartKey caused by magnetic fields
- Keep the SmartKey away from strong magnetic fields.



Vehicle key with panic alarm

- 1 Locks the vehicle
- 2 Indicator lamp
- Unlocks the vehicle

- Opens/closes the tailgate
- Panic alarm
- i If indicator lamp ② does not light up after pressing the ② or ③ button, the battery is weak or possibly discharged. Replace the battery as soon as possible.

Replace the key battery ( $\rightarrow$  page 74).

The key locks and unlocks the following components:

- Doors
- Fuel filler flap
- Tailgate

If the vehicle is not opened within approximately 40 seconds after unlocking, it locks again. Antitheft protection is activated again.

Do not keep the key together with electronic devices or metal objects. This can affect the key's functionality.

Do not keep the key in the temperature-controlled cup holder. Otherwise, the key will not be reliably detected.

## Activating/deactivating the acoustic locking verification signal

Multimedia system:

- → 🔝 >> Settings >> Vehicle
- Activate or deactivate Acoustic Lock.

## Activating/deactivating the panic alarm

#### Requirements

• The vehicle is switched off.



- To activate: press button (1) for approximately one second.
  - A visual and audible alarm is triggered.

► To deactivate: briefly press button ① again.

Press the start/stop button.
 A key belonging to the vehicle must be detected in the vehicle.

## Changing the unlocking settings

Possible unlocking functions of the SmartKey:

- · Central unlocking
- Unlocking the driver's door and fuel filler flap
- To switch between settings: press the and buttons simultaneously for approximately six seconds until the indicator lamp flashes twice.

Options when the unlocking function for the driver's door and fuel filler flap has been selected:

- To unlock the vehicle centrally: press the button twice.
- Vehicles with KEYLESS-GO: if you touch the inner surface of the door handle on the driver's door, only the driver's door and the fuel filler flap will be unlocked.

#### Deactivating the function of the key

Vehicles with KEYLESS-GO: if you deactivate the function of the key, the KEYLESS-GO functions are also deactivated. Access or drive authorization by KEYLESS-GO is then no longer possible with that particular key. Activate the function of the key so that all its functions will again be available.

You can also deactivate the function of the key to reduce the energy consumption of the key if you do not use the vehicle or a key for an extended period of time.


- ▶ Press and hold the 🔒 button on the key.
- With the key button pressed, immediately press key button twice in quick succession.

The indicator light of the key lights up once briefly and once for a long time.

- (i) You have the following options to reactivate the key:
  - Press any button on the key.
  - Start the vehicle with the key in the center console stowage space (→ page 177).

## Removing/inserting the mechanical key

## Removing the mechanical key



- Press release button ①.
  Emergency key ② is pushed out slightly.
- Pull out mechanical key ② until it engages in the intermediate position.
- Press release button **(1)** again and fully remove mechanical key **(2)**.

## Inserting the mechanical key

- Press release button ①.
- Insert mechanical key ② to the intermediate position or fully until it engages.

(i) You can use the intermediate position of mechanical key (a) to attach the key to a key ring.

## Replacing the key battery

A

**DANGER** Risk of fatal injury due to swallowing batteries

Batteries contain toxic and corrosive substances. If batteries are swallowed or otherwise enter the body, severe internal burns can occur within two hours.

There is a risk of fatal injury!

- Keep the batteries out of the reach of children.
- If the lid and/or the battery compartment do not close securely, stop using the key and keep it away from children.
- If batteries are swallowed or otherwise enter the body, seek immediate medical attention.



**ENVIRONMENTAL NOTE** Environmental damage due to improper disposal of batteries

Batteries contain pollutants. It is illegal to dispose of them with the household rubbish.

Dispose of batteries in an environmentally responsible manner. Take discharged batteries to a qualified specialist workshop or to a collection point for used batteries.

#### Requirements

• You require a CR 2032 3 V cell battery.

Mercedes-Benz recommends that you have the battery replaced at a qualified specialist workshop.

ightharpoonup Remove the mechanical key (ightharpoonup page 74).





- Press release knob 2 down fully and slide cover 1 in the direction of the arrow.
- Fold out cover (1) in the direction of the arrow and remove.
- Remove battery compartment (3) and take out the discharged battery.
- Insert the new battery into battery compartment 3. Observe the positive pole marking in the battery compartment and on the battery when doing this.
- Push in battery compartment 3.
- Re-attach cover 1 and push it until it engages.

## Problems with the key, troubleshooting

## You can no longer lock or unlock the vehicle Possible causes are:

- The key battery is weak or discharged.
- Check the battery using the indicator lamp  $(\rightarrow page 72)$ .
- Replace the key battery, if necessary  $(\rightarrow page 74).$
- Use the replacement key.
- Use the mechanical key to lock or unlock  $(\rightarrow page 78)$ .
- Have key checked at a qualified specialist workshop.

#### There is interference from a powerful radio signal source

Possible causes if the function of the key is impaired:

- high voltage power lines
- mobile phones
- electronic devices (notebooks, tablets)

- shielding due to metal objects or induction loops for electrical gate systems or automatic **barriers**
- Make sure that there is sufficient distance between the key and the potential source of interference.


### You have lost a key

- Have the key deactivated at a qualified specialist workshop.
- If necessary, have the mechanical lock replaced as well.

#### 76 Opening and closing

#### Doors


## Unlocking/opening the doors from the inside



- ➤ To unlock and open a front door: pull door handle ②.

  Locking pin ① pops up when the door is unlocked.
- To unlock a rear door: pull the rear door handle.
  The locking pin pops up when the rear door is unlocked.
- ➤ To open a rear door: pull the rear door handle again.

## Centrally locking and unlocking the vehicle from the inside



- To unlock: press 1 button.
- To lock: press button ②.
- Mercedes-Maybach vehicles: the buttons are also located on the front passenger and rear doors.

This does not lock or unlock the fuel filler flap.

The vehicle is not unlocked:

- · if you have locked the vehicle using the key
- if you have locked the vehicle using KEYLESS-GO

## Locking/unlocking the vehicle with KEYLESS-GO

#### Requirements


- The key is outside the vehicle.
- The distance between the key and the vehicle does not exceed 3 ft (1 m).
- The driver's door and the door on which the door handle is used are closed.
- I NOTE Vehicle damage due to unintentional opening of the tailgate
- When using an automatic car wash
- When using a high pressure cleaner
- Deactivate the function of the SmartKey in these situations.

or

Make sure that the SmartKey is at a minimum distance of 10 ft (3 m) away from the vehicle.

#### Observe the notes:

- on washing the vehicle in a car wash  $(\rightarrow page 344)$
- on using a high-pressure cleaner  $(\rightarrow page 346)$



- To unlock the vehicle: touch the inner surface of the door handle
- To lock the vehicle: touch sensor surface (1) or **2**.
- Convenience closing: touch recessed sensor surface 2 until the closing process has been completed.
- Further information on convenience closing  $(\rightarrow page 89)$ .

If you open the tailgate from outside, it is automatically unlocked.

## Problems with KEYLESS-GO, troubleshooting

You can no longer lock or unlock the vehicle using KEYLESS-GO

Possible causes:

- · The function of the SmartKey has been deactivated.
- The SmartKey battery is weak or discharged.
- Activate the function of the SmartKey  $(\rightarrow page 73)$ .

- Check the battery using the indicator lamp  $(\rightarrow page 72)$ .
- Replace the SmartKey battery, if necessary  $(\rightarrow page 74)$ .
- Use the replacement SmartKev.
- Use the emergency key to lock or unlock  $(\rightarrow page 78)$ .
- Have the vehicle and SmartKey checked at a qualified specialist workshop.


#### There is interference from a powerful radio signal source

Possible causes if the function of KEYLESS-GO is impaired:

- · High voltage power lines
- Mobile phones
- Electronic devices (notebooks, tablets)
- Shielding due to metal objects or induction loops for electrical gate systems or automatic barriers
- Make sure that there is sufficient distance between the SmartKey and the potential source of interference.

# Activating/deactivating the automatic locking feature

The vehicle is locked automatically when the vehicle is switched on and the wheels are turning faster than walking pace.



➤ To activate: press and hold button ② for approximately five seconds until an acoustic signal sounds.

➤ To deactivate: press and hold button **(1)** for approximately five seconds until an acoustic signal sounds.

In the following situations, there is a danger of being locked out when the function is activated:

- while the vehicle is being tow-started or pushed
- if the vehicle is being tested on a roller dynamometer

## Power closing function

**WARNING** Risk of becoming trapped when the doors close automatically


Body parts or objects can become trapped, causing injuries.

- Ensure that no body parts or objects are in the closing area.
- Automatic closing of the doors can be canceled by pulling the outer or inner door handle.


If you push the door into the lock to the first detent position, the power closing function will automatically pull the door into the lock.

## Locking/unlocking the driver's door with the mechanical key

- i If you wish to lock the vehicle entirely using the mechanical key, first press the button for locking from the inside while the driver's door is open. Then proceed to lock the driver's door using the mechanical key.
- i If you unlock and open the driver's door with the mechanical key, this triggers the burglar alarm system.
- i If you unlock the driver's door with the mechanical key, the tailgate will not be unlocked.



- Remove the mechanical key ( $\rightarrow$  page 74).
- Insert the mechanical key as far as it will go into opening (1) in the cover.
- Pull and hold the door handle.
- Pull the cover on the mechanical key as straight as possible away from the vehicle until it releases.
- Release the door handle.



- To unlock: turn the mechanical key counterclockwise to position 1.
- ► To lock: turn the mechanical key clockwise to position 1.
- Carefully press the cover onto the lock cylinder until it engages and is seated firmly.

#### Running boards

## Operation of the running boards

**Mercedes-Maybach vehicles:** the vehicle is equipped with electrically extendable running boards. If you have selected the automatic mode in the multimedia system, ( $\rightarrow$  page 80) the running board will extend automatically on the respective side when a door is opened. When the running boards are extended, check the excess width of the vehicle.

You can extend or retract the running boards manually for cleaning ( $\rightarrow$  page 80).

(i) The running boards will extend and retract only if the vehicle is stationary.

In the following cases, the running boards will retract automatically:

- If you select an off-road drive program (→ page 190).
- If you activate car wash mode (→ page 346).
- If the outside mirrors fold in automatically (→ page 165).

#### 80 Opening and closing

• If you are driving at a speed greater than 2.5 mph (4 km/h).

If you have selected the automatic mode in the multimedia system and you manually extend the running boards when the doors are closed, the running boards will remain extended. Even if you open a door and then close it again, the running boards will remain extended. Automatic mode will be reactivated only when you are driving at a speed greater than 2.5 mph (4 km/h).

# **WARNING** Risk of injury when extending or retracting the running boards

The running boards extend at the side during extension. During retraction, the running boards are integrated in the side skirt. Parts of the body could become trapped. There may be people in the range of movement. There is a risk of injury.

Always ensure that there are no people within the range of movement of the running boards. ! NOTE Damage to the running boards during extension or retraction

The running boards extend at the side during extension. During retraction, the running boards are integrated in the side skirt.

- Make sure that there is sufficient space during extension and retraction.
- NOTE Damage to the vehicle body or underbody due to low ground clearance

The running boards are attached to the vehicle body via the underbody. This limits the ground clearance.

Drive over obstacles, such as curbs, particularly carefully and slowly.

Observe the corresponding display messages in the instrument cluster ( $\rightarrow$  page 428).

# Extending and retracting the running boards via the multimedia system

Multimedia system:

- → Settings → Vehicle
  → SIDE RUNNING BOARD
- Select Extend or Retract.

## Automatically extending and retracting the running boards

- Activate or deactivate AUTOMATIC EXTEN-SION.
- i This equipment is available only for Mercedes-Maybach vehicles.

## Cargo compartment

Opening the tailgate

▲ DANGER Risk of exhaust gas poisoning


Combustion engines emit poisonous exhaust gases such as carbon monoxide. Exhaust gases can enter the vehicle interior if the tail-

gate is open when the engine is running, especially if the vehicle is in motion.

- Always switch off the engine before opening the tailgate.
- Never drive with the tailgate open.
- **NOTE** Damage to the tailgate caused by obstacles above the vehicle

The tailgate swings rearwards and upwards when it is opened.

- Make sure that there is sufficient space behind and above the tailgate.
- If the tailgate is unlocked, pull the tailgate handle and release it again immediately.
- Vehicles with HANDS-FREE ACCESS: Make a kicking movement with your foot below the bumper ( $\rightarrow$  page 84).



Pull remote operating switch (1) until the tailgate opens.

or

- Press and hold the button on the key.
- If the tailgate has stopped in an intermediate position, pull it upwards. Release it as soon as it begins to open.

If an obstacle obstructs the tailgate during the automatic opening process, blockage detection will stop the tailgate. The automatic blockage detection function is only an aid. It is not a substitute for your attentiveness.

### Closing the tailgate

WARNING Risk of injury from unsecured items in the vehicle

If objects, luggage or loads are not secured or not secured sufficiently, they could slip, tip over or be thrown around and thereby hit vehicle occupants.

There is a risk of injury, particularly in the event of sudden braking or a sudden change in direction.

- Always stow objects in such a way that they cannot be thrown around.
- Before the journey, secure objects, luggage or loads against slipping or tipping over.

Observe the notes on loading the vehicle.

Notes on closing the tailgate: your vehicle is equipped with automatic key recognition. If a key belonging to the vehicle is detected in the vehicle, the tailgate will not be locked.

Note that the tailgate will not be locked in the following situation:

 You have locked the vehicle and close the tailgate while a key belonging to the vehicle is inside the vehicle.

and

 A second key belonging to the vehicle is not detected outside the vehicle.

Automatic key recognition is only an aid and is not a substitute for your attentiveness.

- Before locking, ensure that at least one key belonging to the vehicle is outside the vehicle.
- To close the tailgate: pull the tailgate downwards slightly. Release it as soon as it begins to close.

**WARNING** Risk of becoming trapped during automatic closing of the tailgate


Body parts may become trapped. There may be people in the closing area.

Make sure that nobody is in the vicinity of the closing area during the closing process.


Use one of the following options to stop the closing process:

- Press the button on the SmartKey.
- Press or pull the remote operating switch on the driver's door.
- Press the closing or locking button on the tailgate.
- · Pull the tailgate handle.

**Vehicles with HANDS-FREE ACCESS:** it is also possible to stop the closing process by making a kicking movement below the rear bumper.



- Switch on the power supply or the vehicle.
- Push remote operating switch ① until the tailgate is fully closed.



Press closing button ① on the tailgate.

#### Vehicles with KEYLESS-GO

- Press locking button ② on the tailgate. If a key is detected outside the vehicle, the tailgate will close and the vehicle will be locked.
- Press and hold the হ্রি button on the key (with the key in the vicinity of the vehicle).

#### Vehicles with HANDS-FREE ACCESS

Make a kicking movement with your foot below the bumper (→ page 84).

## Automatic reversing function for the tailgate

The tailgate is equipped with automatic blockage detection with a reversing function. If a solid object hinders or restricts the tailgate when it is closing automatically, the tailgate will automatically open again slightly. Automatic blockage detection with a reversing function is only an aid. It is not a substitute for your attentiveness when you are closing the tailgate.

During the closing process, make sure that no body parts are in the closing area.

# **WARNING** Risk of becoming trapped despite reversing function

The reversing function will not react:

- To soft, light and thin objects, e.g. fingers
- Towards the end of the closing procedure


In these situations in particular, the reversing function cannot prevent someone being trapped.

Ensure that no body parts are in the closing area.

If someone is trapped, either:

- Press the sutton on the SmartKey.
- Press or pull the remote operating switch on the driver's door.
- Press the closing or locking button on the tailgate.
- · Pull the tailgate handle.

#### HANDS-FREE ACCESS function



With HANDS-FREE ACCESS, you can open, close or stop the closing process of the tailgate by performing a kicking movement under the rear bumper.

The kicking movement triggers the opening or closing process alternately.

Observe the notes when opening ( $\rightarrow$  page 80) and closing ( $\rightarrow$  page 81) the tailgate.

(i) Two warning tones sound when the tailgate is opening or closing.

**WARNING** Risk of burns caused by a hot exhaust system

The vehicle exhaust system can become very hot. If you use HANDS-FREE ACCESS, you could burn yourself by touching the exhaust system.

- Always ensure that you only make a kicking movement within the detection range of the sensors.
- ! NOTE Vehicle damage due to unintentional opening of the tailgate
- When using an automatic car wash
- · When using a high pressure cleaner
- Deactivate the function of the SmartKey in these situations.


or

 Make sure that the SmartKey is at a minimum distance of 10 ft (3 m) away from the vehicle.

When making the kicking movement, make sure that you are standing firmly on the ground. You could otherwise lose your balance, e.g. on ice.

Observe the following notes:

- The key is behind the vehicle.
- Stand at least 12 in (30 cm) away from the vehicle while performing the kicking movement.
- Do not come into contact with the bumper while making the kicking movement.
- Do not carry out the kicking movement too slowly.
- The kicking movement must be towards the vehicle and back again.



Detection range of the sensors

If several consecutive kicking movements are not successful, wait ten seconds.

## System limits

The system may be impaired or may not function in the following cases:

- The sensors are dirty, e.g. due to road salt or snow.
- The kicking movement is made using a prosthetic leg.

The tailgate can open or close unintentionally in the following situations:

- A person's arms or legs are moving in the sensor detection range, e.g. when polishing the vehicle or picking up objects.
- Objects are moved or placed behind the vehicle, e.g. the hose of a fuel dispenser, a charging cable or luggage
- Clamping straps, tarps or other coverings are pulled over the bumper.
- A protective mat with a length reaching over the trunk sill down into the detection range of the sensors is used.
- The protective mat is not secured correctly.
- Work is being done on the trailer hitch, trailers or rear bicycle racks.

Deactivate the function of the key ( $\rightarrow$  page 73) or do not carry the key about your person in such situations.

### Limiting the opening angle of the tailgate

#### Activating the opening angle limiter

You can limit the opening angle of the tailgate in the top half of its opening range up to a point shortly before the end position.

- Stop the opening procedure of the tailgate at the desired position.
- Press and hold the closing button on the tailgate until you hear a short acoustic signal. The opening angle limiter will be activated. The tailgate will then stop in the stored position when opened.

To open the tailgate fully, pull the handle on the outside of the tailgate again after it has stopped automatically.

#### Deactivating the opening angle limiter


Press and hold the closing button on the tailgate until two short acoustic signals sound.

## Releasing the tailgate in an emergency


#### Requirements:

• Only for Mercedes-Maybach vehicles.

## 86 Opening and closing



Remove cover 1.




Pull lever (2) in the direction of the arrow until the tailgate unlocks.

## Unlocking the tailgate with the emergency key

#### Requirements:

- Not for Mercedes-Maybach vehicles.
- The rear seat backrest has been folded forward.

• The cargo compartment cover has been removed.



- ightharpoonup Remove the emergency key (ightharpoonup page 74).
- Insert emergency key (2) into opening (1) in the trim and push it in.

  The tailgate will be unlocked.

#### Side windows

## Opening and closing the side windows

▲ WARNING Risk of entrapment when opening a side window

When opening a side window, parts of the body could be drawn in or become trapped between the side window and window frame.

- When opening, make sure that nobody is touching the side window.
- If someone is trapped, release the button immediately or pull it in order to close the side window again.

**WARNING** Risk of becoming trapped when closing a side window

When closing a side window, body parts could be trapped in the closing area in the process.

When closing, make sure that no body parts are in the closing area. If someone is trapped, release the button immediately or press the button in order to reopen the side window.


**WARNING** Risk of becoming trapped when children operate the side windows

Children could become trapped if they operate the side windows, particularly when unattended.

- Activate the child safety lock for the rear passenger compartment side windows.
- When leaving the vehicle, always take the SmartKey with you and lock the vehicle.
- Never leave children unattended in the vehicle.

#### Requirements:

• The power supply or the vehicle has been switched on.



- Closing
- Opening

The buttons on the driver's door take precedence.

- ➤ To start automatic operation: press the ☐ button beyond the point of resistance or pull and release it.
- ➤ To interrupt automatic operation: press or pull the 🖪 button again.

### 88 Opening and closing

When the vehicle is switched off, you can continue to operate the side windows.

This function is available for around four minutes or until a front door is opened.

 Vehicles with electric sunblinds on the left and right rear doors: The buttons for the rear side windows also open and close the roller sunblinds (→ page 95).

Automatic reversing function of the side windows If an obstacle impedes a side window during the closing process, the side window will open again automatically. The automatic reversing function is only an aid and is not a substitute for your attentiveness.

During the closing process, make sure that no body parts are in the closing area.

▲ WARNING Risk of becoming trapped despite there being reversing protection on the side window

The reversing function does not react:

To soft, light and thin objects, e.g. fingers.

• During resetting.

The reversing function cannot prevent someone from becoming trapped in these situations.

- During the closing process, make sure that no body parts are in the closing area.
- If someone becomes trapped, press the 自 button to open the side window again.

## Convenience opening (ventilating the vehicle before starting a journey)

A

**WARNING** Risk of entrapment when opening a side window

When opening a side window, parts of the body could be drawn in or become trapped between the side window and window frame.

When opening, make sure that nobody is touching the side window.

Release the button immediately if somebody becomes trapped.

#### Requirements

- The SmartKey is in the immediate vicinity of the vehicle.
- Press and hold the 🕝 button on the Smart-Key.

The following functions are performed:

- The vehicle is unlocked.
- The side windows are opened.
- The sliding sunroof is opened.
- The panoramic sliding roof is opened.
- The seat ventilation of the driver's seat is switched on.
- (i) If the roller sunblind of the panoramic sliding sunroof is closed, the roller sunblind is opened first.
- (i) If the roller sunblinds of the rear doors are closed, the roller sunblinds are opened first.

- ► To continue convenience opening: press and hold the 🔒 button again.

# Convenience closing (closing the vehicle from outside)

WARNING Risk of entrapment due to not paying attention during convenience closing

When the convenience closing feature is operating, parts of the body could become trapped in the closing area of the side window and the sliding sunroof.

When the convenience closing feature is operating, monitor the entire closing process and make sure that no body parts are in the closing area.

#### Requirements

 The key is in the immediate vicinity of the vehicle. Press and hold the button on the key.

The following functions are performed:

- The vehicle is locked
- The side windows are closed.
- The sliding sunroof is closed.
- The panorama roof with power tilt/sliding panel is closed.
- ► To interrupt convenience closing: release the ⊕ button.
- To continue convenience closing: press and hold the 🚊 button again.
- Convenience closing also functions with KEY-LESS-GO (→ page 76).

## Resolving problems with the side windows

WARNING Risk of becoming trapped or fatally injured if reversing protection is not activated

If you close a side window again immediately after it has been blocked, the side window will

close with increased or maximum force. The reversing function is then not active and body parts may become trapped.

- Make sure that no parts of the body are in the closing area.
- To stop the closing process, release the button or press the button again to reopen the side window.

## A side window cannot be closed and you cannot see the cause.

- Check to see whether any objects are in the window guide.
- Adjust the side windows.

## Adjusting the side windows

If a side window is obstructed during closing and reopens again immediately:

Immediately after this, pull and hold the corresponding button again until the side window

### 90 Opening and closing

has closed and hold the button for at least one more second (re-adjustment).

The side window will be closed without the automatic reversing function.

If the side window is obstructed again and reopens again immediately:

Immediately after this, pull and hold the corresponding button again until the side window has closed and hold the button for at least one more second (follow-up adjustment).
The side window will be closed without the automatic reversing function.

# The side windows cannot be opened or closed using the convenience opening feature.

Possible causes are:

- The key battery is weak or discharged.
- Check the battery using the indicator lamp (→ page 72).
- Replace the key battery, if necessary (→ page 74).

## Sliding sunroof

### Opening and closing the sliding sunroof

(i) The term "sliding sunroof" also refers to the panorama roof with power tilt/sliding panel.

WARNING Risk of becoming trapped when the sliding sunroof is being opened and closed

Body parts may become trapped in the range of movement.

- During opening and closing, make sure that no body parts are in the range of movement.
- Release the button immediately if somebody becomes trapped.

or

 Briefly press the button in any direction during automatic operation.
 The opening or closing process will be stopped. **WARNING** Risk of becoming trapped if the sliding sunroof is operated by children

Children operating the sliding sunroof could get caught in the moving parts, particularly if unattended.

- Never leave children unattended in the vehicle.
- When leaving the vehicle, always take the key with you and lock the vehicle.

▲ WARNING Risk of becoming trapped when the roller sunblind is being opened and closed

Body parts may become trapped between the roller sunblind and frame or sliding roof.

- When opening or closing, make sure that no body parts are in the roller sunblind's range of movement.
- Release the button immediately if somebody becomes trapped.

or

► Briefly press the button in any direction during automatic operation. The opening or closing process will be stopped.

NOTE Malfunction due to snow and ice

Snow and ice may cause the sliding sunroof to malfunction.

- Open the sliding sunroof only if it is free of snow and ice
- **NOTE** Damage caused by protruding objects


Objects that protrude from the sliding sunroof may damage the seals.

Do not allow anything to protrude from the sliding sunroof.

**NOTE** Damage to the sliding sunroof when a roof luggage rack is installed

When a roof luggage rack is installed, raising or opening the sliding sunroof may be restricted.

- Check whether the sliding sunroof can be raised or opened when a roof luggage rack is installed.
- If in doubt, do not raise or open the sliding sunroof.



- Raise
- Open
- 3 Close/lower

Use the button to operate the panorama roof with power tilt/sliding panel and the roller sunblind.

#### 92 Opening and closing

The panorama roof with power tilt/sliding panel can be operated only when the roller sunblind is open. **Exception:** ventilating the vehicle interior

- Check whether the sliding sunroof can be raised or opened when a roof luggage rack is installed.
- ➤ To start automatic operation: press the button beyond the point of resistance or pull and release it.
- To interrupt automatic operation: briefly press the button in any direction.


  The opening/closing process will be stopped.

Vehicles with a panorama roof with power tilt/sliding panel: the automatic raising feature is available only when the sliding sunroof is closed or raised.

Vehicles without a panorama roof with power tilt/sliding panel: the automatic opening and raising features are available only when the sliding sunroof is closed.

- To ventilate the vehicle interior: raise the sliding sunroof.
  - The roller sunblind will open slightly.

# Operating the roller sunblind for the sliding sunroof from the rear passenger compartment



- ► To open: press button ①.
- To close: pull button 1.
- i When the sliding sunroof is open, it will close first. To close the roller sunblind, you will need to pull button again.

If you press or pull button ① beyond the point of resistance, you will start automatic operation in the direction in question. You can stop automatic operation by pushing or pulling the button again.

#### Automatic reversing function of the sliding sunroof

If an obstacle obstructs the sliding sunroof during the closing process, the sliding sunroof will open again automatically. The automatic reversing function is only an aid and is not a substitute for your attentiveness.

During the closing process, make sure that no body parts are in the closing area.

**WARNING** Risk of becoming trapped despite the reversing function being active

In particular, the reversing function does not react:

- To soft, light and thin objects, e.g. fingers.
- Towards the end of the closing procedure.
- · During resetting.

- During the closing process, make sure that no body parts are in the closing area.
- Release the button immediately if somebody becomes trapped.

or

 Briefly press the button in any direction during automatic operation.
 The closing process will be stopped.

Automatic reversing function of the roller sunblind If an obstacle obstructs the roller sunblind during the closing process, the roller sunblind will open again automatically. The automatic reversing function is only an aid and is not a substitute for your attentiveness.

When closing the roller sunblind, make sure that no body parts are in the area of movement.

## **WARNING** Risk of becoming trapped despite reversing function

In particular, the reversing function does not react to soft, light and thin objects, e.g. fingers.

- When closing the roller sunblind, make sure that no body parts are in the range of movement.
- Release the button immediately if somebody becomes trapped.

or

Briefly press the button in any direction during the automatic closing process. The closing process will be stopped.

## Automatic functions of the sliding sunroof

i) The term "sliding sunroof" also refers to the panoramic sliding sunroof.

Rain closing function when driving Vehicles with a panoramic sliding sunroof: if it starts to rain, the raised sliding sunroof will automatically be lowered while the vehicle is in motion.

## Automatic lowering function

Vehicles with a panoramic sliding sunroof: if the sliding sunroof is raised at the rear, it will automatically be lowered slightly at higher speeds. At low speeds, it will be raised again automatically.

# **WARNING** Risk of becoming trapped by automatic lowering of the sliding sunroof

At higher speeds, the raised sliding sunroof will automatically be lowered slightly at the rear.

- Make sure that nobody reaches into the sliding sunroof's range of movement while the vehicle is in motion.
- If somebody becomes trapped, briefly push the sliding sunroof button forwards or backwards.
- (i) By pushing or pulling the [ button, you can interrupt the automatic functions "Rain closing function when driving" and "Automatic lowering".

## Rectifying problems with the sliding sunroof



WARNING Risk of becoming trapped or fatal injuries when the sliding sunroof is closed again

If the sliding sunroof is closed again immediately after it has been blocked or reset, it will close with increased force.

- Make sure that no parts of the body are in the closing area.
- Release the button immediately if somebody becomes trapped.

or

 Briefly press the button in any direction during the automatic closing process.
 The closing process will be stopped.

#### The sliding sunroof cannot be closed and you cannot see the cause.

(i) The term "sliding sunroof" also refers to the panorama roof with power tilt/sliding panel.

If the sliding sunroof is obstructed during closing and reopens again slightly:

Immediately after automatic reversing, pull and hold the button down again to the point of resistance until the sliding sunroof is closed.

The sliding sunroof will be closed with increased force.

If the sliding sunroof is obstructed again and opens again slightly:

Repeat the previous step.
 The sliding sunroof will be closed again with increased force.

Vehicles without a panorama roof with power tilt/sliding panel: The sliding sunroof is not operating smoothly.

Reset the sliding sunroof.

## Resetting the sliding sunroof

- Push the button up to the point of resistance repeatedly until the sliding sunroof is fully open.
- Press the button for another second.
- Close the sliding sunroof.

Vehicles with a panorama roof with power tilt/ sliding panel: The sliding sunroof or the roller sunblind is not operating smoothly.

Reset the sliding sunroof and the roller sunblind.

#### Resetting the sliding sunroof and the roller sunblind

- Pull and hold the button little by little until the sliding sunroof is fully closed.
- Pull and hold the button little by little until the roller sunblind is fully closed.
- Use automatic operation to fully open and then close the sliding sunroof.

#### Roller sun blinds

Extending or retracting the roller sunblinds on the rear side windows

**WARNING** Risk of becoming trapped when extending or retracting the roller sunblind

Body parts could become trapped in the sweep of the roller sunblind when it is being extended or retracted.

- Make sure that no body parts are in the sweep of the roller sunblind when it is being extended or retracted.
- If someone becomes trapped, briefly press the button in the opposite direction.


The opening or closing process will briefly be stopped. The roller sunblind will then return to its starting position.

**NOTE** Damage caused by objects

Objects can cause the roller sunblind to malfunction.

Ensure that the roller supplied can move freely.

The roller supplieds for the rear side windows can be operated with the buttons for the side windows in the driver's door and in the rear doors.



- Rear left side window/roller sunblind
- Rear right side window/roller sunblind

- To close fully: briefly pull the corresponding button when the side window is closed
- To open fully: briefly press the corresponding button

### Anti-theft protection

### Function of the immobilizer

The immobilizer prevents your vehicle from being started without the correct key.

The immobilizer will automatically be activated when the vehicle is switched off, and deactivated when the vehicle is switched on.

When leaving the vehicle, always take the key with you and lock the vehicle. Anyone can start the vehicle if a valid key has been left inside the vehicle.

(i) In the event the engine cannot be started (yet the vehicle's battery is charged), the system will not be operational. Contact an authorized Mercedes-Benz center or call 1-800-FOR-MERCedes (in the USA) or

1-800-387-0100 (in Canada).

## ATA (anti-theft alarm system)


## ■ Function of the ATA system

If the ATA system is activated, a visual and audible alarm is triggered in the following situations:

- · when a door is opened
- · when the tailgate is opened
- · when the hood is opened
- when interior protection is triggered
   (→ page 97)
- when the tow-away alarm is triggered
   (→ page 96)

The ATA system is activated automatically after approximately ten seconds in the following situations:

- · after locking the vehicle with the key
- after locking the vehicle using KEYLESS-GO



Indicator lamp 
 flashes when the ATA system is activated.

The ATA system is deactivated automatically in the following situations:

- after unlocking the vehicle with the key
- after unlocking the vehicle using KEYLESS-GO

- after pressing the start/stop button with the key in the stowage compartment (→ page 177)
- i If the battery is heavily discharged, the burglar alarm system is automatically deactivated to facilitate the next engine start.

#### Deactivating the ATA

Press the 📆 , 🙃 or 🤧 button on the key.

or

Press the start/stop button with the key in the stowage compartment (→ page 177)

## Deactivating the alarm using KEYLESS-GO

Grasp the outside door handle with the key outside the vehicle.

## Function of the tow-away alarm

This function may not be available in all countries.

An audible and visual alarm will be triggered if an alteration to your vehicle's angle of inclination is detected while the tow-away alarm is armed.

The tow-away alarm will automatically be armed after approximately 60 seconds:

- · after the vehicle is locked with the key
- · after the vehicle is locked using KEYLESS-GO

The tow-away alarm will be armed only when the following components are closed:

- Doors
- Tailgate

The tow-away alarm will automatically be deactivated:

- after the 🔒 or 🐒 button on the key is pressed
- after the start/stop button is pressed with the key in the stowage compartment  $(\rightarrow page 177)$
- · after the vehicle is unlocked using KEYLESS-GO
- when HANDS-FREE ACCESS is used

Information on collision detection on a parked vehicle ( $\rightarrow$  page 209).

#### Activating/deactivating the tow-away alarm

Multimedia system:

→ 🔝 >> Settings >> Quick Access

Activate or deactivate Tow-away Protection.

The tow-away alarm is activated again in the following cases:

- The vehicle is unlocked again.
- A door is opened.
- The vehicle is locked again.
- (i) If quick access is unavailable, select the Vehicle submenu in the Settings main menu to activate or deactivate the tow-away alarm.

## Function of interior protection

(i) This function may not be available in all countries.

When interior protection is armed, a visual and audible alarm is triggered if movement is detected in the vehicle interior

Interior protection is armed automatically after approximately ten seconds:

- after locking the vehicle with the key
- · after locking the vehicle using KEYLESS-GO

Interior protection is armed only when the following components are closed:

- Doors
- Tailgate

Interior protection is automatically deactivated:

- after pressing the 🔒 or 🚮 button on the kev
- after pressing the start/stop button with the key in the stowage compartment  $(\rightarrow page 177)$
- after unlocking the vehicle using KEYLESS-GO
- when using HANDS-FREE ACCESS

#### 98 Opening and closing

The following situations can lead to a false alarm:

- when there are moving objects such as mascots in the vehicle interior
- if a side window is open
- if the sunroof is open
- if the panorama roof with power tilt/sliding panel is open

### Activating/deactivating interior protection

Multimedia system:



Activate or deactivate Interior Motion Sensor.

Interior protection is activated again in the following cases:


- The vehicle is unlocked again.
- · A door is opened.
- The vehicle is locked again.
- i If quick access is unavailable, select the Vehicle menu under Settings to activate or deactivate interior protection.

## Notes on the correct driver's seat position

WARNING Risk of accident due to adjusting the vehicle settings while the vehicle is in motion

You could lose control of the vehicle in the following situations in particular:

- If you adjust the driver's seat, the head restraint, the steering wheel or the mirror while the vehicle is in motion
- If you fasten your seat belt while the vehicle is in motion
- Before starting the engine: In particular, adjust the driver's seat, head restraint. steering wheel and mirror, and fasten your seat belt.



Ensure the following when adjusting steering wheel 1, seat belt 2 and driver's seat 3:

- · You are sitting as far away from the driver's air bag as possible, taking the following points into consideration:
- You are sitting in an upright position
- Your thighs are slightly supported by the seat cushion

- Your legs are not fully extended and you can depress the pedals properly
- The back of your head is supported at eve level by the center of the head restraint
- You can hold the steering wheel with your arms slightly bent
- You can move your legs freely
- You can see all the displays on the instrument cluster clearly
- You have a good overview of the traffic conditions
- Your seat belt sits snugly against your body and passes across the center of your shoulder and across your hips in the pelvic area

## Notes on grab handles

WARNING Risk of injury due to excessive load on the grab handles

If you apply your full body weight to the grab handle or pull it abruptly, the grab handle may

#### 100 Seats and stowing

be damaged or come loose from its anchorage. This may result in injuries.

Use the grab handles only to stabilize the seating position or to assist in getting in and out of the seat.

#### Seats

### Adjusting the front seat

**WARNING** Risk of becoming trapped if the seats are adjusted by children

Children could become trapped if they adjust the seats, particularly when unattended.

- When leaving the vehicle, always take the SmartKey with you and lock the vehicle.
- Never leave children unattended in the vehicle.

You can adjust the seats when the vehicle is switched off.

**WARNING** Risk of becoming trapped when adjusting the seat

When you adjust a seat, you or other vehicle occupants could become trapped, e.g. on the seat guide rail.

When adjusting a seat, make sure that no one has any part of their body within the sweep of the seat.

Observe the safety notes on "Air bags" and "Children in the vehicle".

WARNING Risk of accident due to adjusting the vehicle settings while the vehicle is in motion

You could lose control of the vehicle in the following situations in particular:

- If you adjust the driver's seat, the head restraint, the steering wheel or the mirror while the vehicle is in motion
- If you fasten your seat belt while the vehicle is in motion

Before starting the vehicle: in particular, adjust the driver's seat, head restraint, steering wheel and mirror, and fasten your seat belt.

**WARNING** Risk of becoming trapped if the seat height is adjusted carelessly

If you adjust the seat height carelessly, you or other vehicle occupants could be trapped and thereby injured.

Children in particular could accidentally press the electrical seat adjustment buttons and become trapped.

While moving the seats, make sure that hands or other body parts do not get under the lever assembly of the seat adjustment system. WARNING Risk of injury due to head restraints not being installed or being adjusted incorrectly

If head restraints have not been installed or have not been adjusted correctly, there is an increased risk of injury in the head and neck area, e.g. in the event of an accident or when braking.

- Always drive with the head restraints installed.
- Before driving off, make sure for every vehicle occupant that the center of the head restraint supports the back of the head at about eye level.

Do not rotate the head restraints of the front and rear seats. Otherwise, you will not be able to adjust the height and angle of the head restraints correctly.

Adjust the head restraint fore-and-aft position so that it is as close as possible to the back of your head.

**WARNING** Risk of injury or death due to an incorrect seat position

The seat belt does not offer the intended level of protection if you have not moved the seat backrest to an almost vertical position.

In particular, you could slip beneath the seatbelt and become injured.

- Adjust the seat properly before beginning your journey.
- Always ensure that the seat backrest is in an almost vertical position and that the shoulder belt is routed across the center of your shoulder.

WARNING Risk of injury due to excessive load on the grab handles

If you apply your full body weight to the grab handle or pull it abruptly, the grab handle may be damaged or come loose from its anchorage. This may result in injuries.


Use the grab handles only to stabilize the seating position or to assist in getting in and out of the seat.

**WARNING** Risk of potentially fatal injuries due to objects trapped under the front passenger seat

Objects trapped under the front passenger seat may interfere with the function of the automatic front passenger air bag shutoff or damage the system.

- Do not stow any objects under the front passenger seat.
- When the front passenger seat is occupied, ensure that no objects have become trapped beneath the front passenger seat.

#### 102 Seats and stowing



- Head restraint height
- Seat backrest inclination
- Seat height
- Seat cushion length
- Seat cushion inclination
- Seat fore-and-aft position
- Save the settings with the memory function (→ page 122).

## Adjusting the front passenger seat electrically from the driver's seat

A


WARNING Risk of injury or death due to the front seat being positioned too close to the cockpit

The front airbags can also injure the occupants in the front of the vehicle.

- Always adjust the front seats so they are as far away as possible from the front airbags.
- In addition, observe the notes on correct seat adjustment.

## Requirements:

• The power supply is switched on.



You can call up the following functions for the front passenger seat:

- Seat adjustment
- · Seat heating
- · Seat ventilation
- Memory function


When the indicator lamp lights up, the front passenger seat is selected.

- Adjust the front passenger seat using the buttons on the driver's side door operating unit.
- To select the driver's seat: press button again.

  When the indicator lamp goes out, the drive

When the indicator lamp goes out, the driver's seat has been selected.

## Adjusting the front passenger seat electrically from the rear passenger compartment




- To select the front passenger seat: press button 1.
  - When the indicator lamp lights up, the front passenger seat is selected.
- Adjust the front passenger seat using the buttons on the door operating unit in the rear passenger compartment (→ page 104).

i Mercedes-Maybach vehicles: if the front passenger seat is in the foremost position, you can set the seat backrest at a very steep angle. This will provide a better forward view from the rear passenger compartment.

Despite the steep angle of the seat backrest, a person may occupy the front passenger seat.

#### 104 Seats and stowing

## Adjusting the 4-way lumbar support



- Higher
- Softer
- 3 Lower
- Firmer
- Use buttons 10 to 3 adjust the contour of the backrest.


## Adjusting the rear seat electrically

NOTE Damage to the rear seat armrest when folding the center seat backrest forward

If the rear seat armrest is folded down, it can be damaged when the center seat backrest is folded forward.

Fold the rear seat armrest upwards before folding the center seat backrest forward.


The middle seat backrest is adjusted together with the left seat.



- Head restraint height
- Seat backrest inclination
- Seat fore-and-aft position
- Save the settings with the memory function  $(\rightarrow \text{ page } 123)$ .

## Adjusting the reclining rear seat electrically

The reclining rear seats are on the driver's and front passenger sides.




- Head restraint height
- Head restraint fore-and-aft position
- Seat backrest inclination
- Combined seat cushion inclination and length
- Combined seat cushion inclination and length

- 6 Fore-and-aft position of the leg rest
- Angle of the leg rest
- Save the settings with the memory function  $(\rightarrow page 123)$ .
- The leg rest will fold down if overloaded. If this is the case, fold up the leg rest and engage it.

## Setting the fully reclined position

## Requirements:

• The power supply is switched on.




- To set the fully reclined position: press button

  - The rear seat will move into the fully reclined position.
  - The rear seat head restraint will move.
  - The leg rest will rise.
  - The front passenger seat will move as far forwards as possible.

#### 106 Seats and stowing

- The front passenger seat head restraint will be completely retracted.
- The front passenger seat backrest will move as far forwards and as far down as it will go.




To restore the standard seat settings: press button .

- Call up the settings with the memory function  $(\rightarrow page 123)$ .
- You can use the rear passenger compartment child safety lock to disable this function (→ page 71).
- (i) The leg rest will fold down if overloaded. If this is the case, fold up the leg rest and engage it.

## Attaching and removing the additional cushion of the leg rest

Use the additional cushion only when the vehicle is stationary. The additional cushion is in the vehicle.



- ➤ To attach: place the additional cushion on the leg rest.
- Pull the rubber straps laterally over the leg rest.
- To remove: remove the rubber straps from the leg rest and stow the additional cushion safely in the vehicle.

#### Folding the rear seats on the second row of seats forwards and back electrically

#### WARNING Risk of injury due to seat backrests folded forwards

If the seat backrest of the rear seat is folded forwards, persons in the third row of seats may hit parts of the seat mechanism, especially in the event of an accident, braking maneuver or abrupt change of direction.

- If there is a person in the third row of seats, the rear seat in front of them must be folded back to the driving position before the journey begins.
- Persons in the third row of seats should not rest their legs on a seat backrest that has been folded forwards

Always ensure that all vehicle occupants have their seat belts fastened correctly and are sitting properly. Particular attention must be paid to children.

If you no longer require the seat backrest to be folded down for loading or for getting in and out, fold it back into place.

WARNING Risk of becoming trapped if the seat is not engaged

The seat does not engage when folded forwards. The seat can fold backwards unexpectedly, e.g. when accelerating, braking or in the event of an abrupt change of direction or an accident.

People in the seat's sweep can become trapped.

- If a seat is folded forwards, always fold it back before driving off.
- Make sure that the seat is engaged.

If a seat on the second row of seats is not engaged, this will be shown on the multifunction display on the instrument cluster.

# Requirements:

 The area into which the rear seat is folded is clear.

- The rear seat has been folded up.
- · Vehicles with comfort seating: the center armrest is folded up.
- Vehicles with an extended center console: the stowage compartment in the center console is closed.
- Vehicles with a folding rear armrest: the rear armrest has been folded up.
- · Vehicles with center seat backrests: the center seat backrest has been folded up.

# Folding the rear seat into the front position


You can fold the seats on the second row of seats forwards for the following situations:

- For easier access to the cargo compartment
- Vehicles with a third row of seats: for getting in or out


Vehicles with a center seat backrest: the center rear seat folds forwards and backwards together with the left rear seat.

Depending on the vehicle equipment, you can fold the rear seats forwards as follows:

- Six-seater: on the right-hand side of the vehicle only
- Seven-seater with center seat backrest: both sides
- (i) To increase the size of the cargo compartment, you can move the seat backrests into the cargo compartment floor position (→ page 131).



Button on the backrest shoulder of the second row of seats



Button on the armrest of the third row of seats (seven-seater)

- When the rear door is open: briefly pull button
  - 1 on the backrest shoulder of the rear seat.

or

Briefly press button ② on the armrest of the third row of seats.

When the rear door is closed: pull and hold button 
 on the backrest shoulder of the rear seat.

Press and hold button 2 on the armrest of the third row of seats.

The head restraint will move downwards. The seat backrest will move into the front position. The rear seat will move forwards until it unlocks. The rear seat will then tip forwards.

If a seat on the second row of seats is not engaged, this will be shown on the multifunction display on the instrument cluster.

(i) You can prevent the rear seats from folding forwards when the rear door is closed by activating the child safety lock for the side windows ( $\rightarrow$  page 71).

#### Folding back the rear seat

Press button (1) on the backrest shoulder of the rear seat or 2 on the armrest of the third row of seats and hold it down until the rear seat audibly engages.

The rear seat will tip downwards and move back. The seat backrests and head restraint will then move into a suitable seat position automatically.

If a seat on the second row of seats is not engaged, this will be shown on the multifunction display on the instrument cluster.


To interrupt the folding procedure before engagement, let go of button 1. To continue the folding procedure, press and hold button again.

# Folding the rear seats forwards mechanically (emergency release)

You can also fold the rear seats forwards mechanically using release loops. The release loops are located on the outer sides and rear sides of the seats on the second row of seats.



Release loops on the second row of seats



Release loops on the rear sides of the second row of seats

- Pull one of release loops ①.
- Fold the seat backrest forwards.
- Before commencing your journey, make sure that the seat backrest and the rear bench seat are engaged.

#### Head restraints

Adjusting the front seat head restraints manually

**WARNING** Risk of accident due to adjusting the vehicle settings while the vehicle is in motion

You could lose control of the vehicle in the following situations in particular:

- If you adjust the driver's seat, the head restraint, the steering wheel or the mirror while the vehicle is in motion
- If you fasten your seat belt while the vehicle is in motion
- Before starting the engine: In particular, adjust the driver's seat, head restraint,

steering wheel and mirror, and fasten your seat belt.


WARNING Risk of injury due to head restraints not being installed or being adjusted incorrectly

If head restraints have not been installed or have not been adjusted correctly, there is an increased risk of injury in the head and neck area, e.g. in the event of an accident or when braking.

- Always drive with the head restraints installed.
- Before driving off, make sure for every vehicle occupant that the center of the head restraint supports the back of the head at about eye level.


Do not rotate the head restraints of the front and rear seats. Otherwise, you will not be able to adjust the height and angle of the head restraints correctly.

Adjust the head restraint fore-and-aft position so that it is as close as possible to the back of your head.




- To raise: pull the head restraint up.
- ➤ To lower: press release knob in the direction of the arrow and push the head restraint down.

- To move forward: press release knob (2) and pull the head restraint forward.
- To move backwards: press release knob (2) and push the head restraint backwards.
- Adjusting the front seat luxury head restraints manually



- To move forward: press release knob (1) and pull the head restraint forward.
- To move backwards: press release knob (1) and push the head restraint backwards.


# Adjusting the EASY ADJUST luxury head restraints on the front seats mechanically



- To move forward: press release knob (1) and pull the head restraint forward.
  - To move backwards: press release knob (1) and push the head restraint backwards.

- To adjust the side bolsters of the head restraint: pull or push right or left side bolster
- (i) The fore-and-aft position of the head restraint will be adjusted automatically when you adjust the seat backrest inclination using the button on the door operating unit.
- Adjusting the head restraints of the rear seats manually

Depending on the vehicle equipment, you can mechanically adjust the head restraints on the third row of seats as well as the center head restraint on the second row of seats.



Head restraint of the standard vehicle (example)

- To raise: pull the head restraint up.
- To lower (Mercedes-Maybach vehicles): push the head restraint down.


#### Vehicles with a third row of seats

The head restraints on the third row of seats have a usage position and a non-usage position. The usage position is the extended, top position in which the head restraint engages; the non-usage position is the bottom, retracted position of the head restraint. If the seats on the third row of seats are being used, the head restraint must be in the top, engaged usage position.

- ► If the third row of seats is occupied: move the head restraints to the very top and have them engage there.
- If the third row of seats is not occupied: move the head restraints to the very bottom.

#### ■ Installing/removing the head restraint of the middle rear seat on the second row

### Removing



- Release the middle rear seat backrest and fold it forward slightly (→ page 131).
- Pull the head restraint upwards as far as it will go.


Push release knob (1) in the direction of the arrow and pull out the head restraint.

#### Installing

- Insert the head restraint such that the notches on the bar are on the left when viewed in the direction of travel.
- Push the head restraint down until it engages.
- Fold the middle rear seat backrest back until it engages.

# Adjusting the luxury head restraints of the rear seats mechanically

Mercedes-Maybach vehicles: you can set only the side bolsters mechanically. You can adjust the angle of the head restraint electrically.




Head restraint of the standard vehicle (example)

- To adjust the side bolsters of the head restraint: pull or push right or left side bolster
- To adjust the angle of the head restraint: pull or push the head restraint in the direction of arrow 2.

# Attaching and removing the additional cushion of the luxury head restraint in the rear passenger compartment

Use the additional cushion only when the vehicle is stationary. The additional cushion is in the vehicle.



- Position the head restraint as far forwards as possible.
- To attach the additional cushion: hold additional cushion (1) against the head restraint and push press studs (2) into the counterpieces.

Push button (3) on the bottom of the head restraint is located in a recess.

To remove the additional cushion: release press studs and remove additional cushion

.

# Configuring the seat settings

Multimedia system:

→ Comfort → Seat Comfort

Adjusting the backrest contour in the lumbar region of the seat backrest (lumbar)

- Select Lumbar.
- Select the settings for the desired seat.
- Adjust the air cushions.

#### Adjusting the backrest side bolsters

- Select Side Bolsters.
- Adjust the air cushions for the desired seat.

# Setting the seat heating balance

- Select Seat Heating Balance.
- Adjust the heat distribution for the desired seat.

# Setting automatic seat adjustment

A

**WARNING** Risk of becoming trapped during adjustment of the driver's seat after calling up a driver profile

Selecting a user profile may trigger an adjustment of the driver's seat to the position saved under the user profile. You or other vehicle occupants could be injured in the process.

Make sure that when the position of driver's seat is being adjusted using the multimedia system, no people or body parts are in the seat's range of movement.

If a person is in danger of becoming trapped, immediately stop the adjustment process by:

a) Tapping the warning message on the media display.

or

 b) Pressing a position button of the memory function or a seat adjustment switch in the driver's door.
 The adjustment process is stopped.

#### Requirements

 Adapting the driver's seat and steering wheel position to body size: automatic seat adjustment has been switched on.

#### Multimedia system:

- → 🔝 **>>** Settings **>>** Vehicle
- ➤ Automatic Seat Adjustment

### Switching automatic seat adjustment on/off

When the active user profile is changed while the vehicle is stationary, the driver's seat, steering wheel, outside mirrors and seat contour will automatically be adapted to the driver.

- Select On or Off.
- (i) This setting is available only for individual user profiles. For the guest profile, automatic seat adjustment cannot be switched on or off.

# Adjusting driver's seat and steering wheel position to body size

The vehicle calculates a suitable driver's seat and steering wheel position on the basis of the driver's body size and sets this directly.

- To set the unit of measurement: select cm or ft/in
- Set the size using the scale.

the switches

- Select Start Positioning. The driver's seat and steering wheel position is adjusted to the body size that has been set.
- (i) If the driver's seat and steering wheel position calculated by the vehicle is not practical or comfortable, it can be manually changed at any time via the buttons. The exterior mirrors are not set via this function. Instead, they have to be set manually via
- (i) You can also configure these settings via the Mercedes me portal for your user profile. By synchronizing the profiles in the vehicle and the Mercedes me connect profiles, you can carry over these settings for your vehicle.

#### Setting the easy entry and exit feature

- Select Steering Wheel & Seat, Steering Wheel Only or Off.
- (i) If you use an individual user profile and have set your body size, this information is carried

over for the easy entry and exit feature. This will cause the driver's seat and steering wheel to move into the correct position automatically.

### Overview of massage program

- Hot Relaxing Back Combination of heat and relaxation. It starts by massaging the back. In addition, warm pressure points become noticeable, starting in the pelvic area.
- Hot Relaxing Shoulder Combination of heat and relaxation. It starts by massaging the shoulders. In addition, warm pressure points become noticeable, starting in the pelvic area.
- Activating Massage Activating massage with upward-moving massage waves.
- Classic Massage Relaxing back massage.
- Wave Massage Regenerating massage program using soothing waves across the back and in the seat cushion
- Mobilizing Massage Mobilizing Massage with upward-moving massage waves. Can promote

- deeper respiration and hence improve circulation and blood pressure.
- · Active Workout, Backrest and Active Workout. Cushion These programs require your cooperation. Alternating between tensing and releasing helps to improve blood flow to your muscles. Press against a pressure point as soon as you feel it.

# Selecting the massage program for the front seats

Multimedia system:

- → 🔝 >> Comfort >> Massage
- ▶ Select a massage program ( $\rightarrow$  page 115).
- Start the program for the desired seat .
- To set the massage intensity: switch High Intensity on or off.
- (i) For the rear seats, the massage program can be selected on the following devices (if available):
  - On the rear passenger compartment displays

The selection can be made for the rear seats on the second and third rows of seats

On the MBUX rear passenger compartment tablet

The selection is made in the same way as on the rear passenger compartment displays for the rear seats on the second row of seats.

# Resetting seat settings

Multimedia system:



- Select for the desired seat.
- Confirm the prompt.

# Switching the seat heating on/off



**WARNING** Risk of burns due to repeatedly switching on the seat heating

Repeatedly switching on the seat heating can cause the seat cushion and seat backrest padding to become very hot.

In particular, the health of persons with limited temperature sensitivity or a limited ability to react to high temperatures may be affected or they may even suffer burn-like injuries.

Do not repeatedly switch on the seat heating.

To protect against overheating, the seat heating may be temporarily deactivated after it has been switched on repeatedly.


NOTE Damage to the seats caused by objects or documents when the seat heating is switched on

When the seat heating is switched on, overheating may occur due to objects or documents placed on the seats, e.g. seat cushions or child seats. This could cause damage to the seat surface.


Make sure that no objects or documents are on the seats when the seat heating is switched on.

#### Requirements


• The power supply is switched on.







Seat heating in the rear passenger compartment



Seat heating in the third row of seats

Press button 1 repeatedly until the desired heating level is set. Depending on the heating level, up to three indicator lamps will light up. If all indicator lamps are off, the seat heating is switched off.

(i) The seat heating will automatically switch down from the three heating levels after 8, 10 and 20 minutes until the seat heating is switched off.

#### Setting the panel heating

Multimedia system:

→ 🔝 ▶ Settings ▶ Vehicle

#### >> Panel Heating


When the seat heater is switched on, the armrests, the door center panels and the center console can be heated.

Switch the function for the desired seats on or off.


# Switching the seat ventilation on/off

### Requirements:

• The power supply is switched on.



Seat ventilation in the cockpit



Seat ventilation in the rear passenger compartment

Press button • repeatedly until the desired ventilation level is set.

Depending on the ventilation level, up to three indicator lamps will light up. If all indicator lamps are off, the seat ventilation is switched off.

# Steering wheel

#### Adjusting the steering wheel manually

▲ WARNING Risk of accident due to adjusting the vehicle settings while the vehicle is in motion


You could lose control of the vehicle in the following situations in particular:

- If you adjust the driver's seat, the head restraint, the steering wheel or the mirror while the vehicle is in motion
- If you fasten your seat belt while the vehicle is in motion
- Before starting the vehicle: in particular, adjust the driver's seat, head restraint, steering wheel and mirror, and fasten your seat belt.
- **WARNING** Risk of entrapment for children when adjusting the steering wheel

Children could injure themselves if they adjust the steering wheel.

- Never leave children unattended in the vehicle.
- When leaving the vehicle, always take the key with you and lock the vehicle.

#### Unlocking



Fold release lever 1 down as far as it will go.


Adjust height and distance to the steering wheel.

#### Locking

- Fold release lever 1 up as far as it will go.
- Check and make sure that the steering column is locked by moving the steering wheel.

#### Adjusting the steering wheel electrically

The steering wheel can be adjusted when the vehicle is switched off.




- 1 To adjust the distance to the steering wheel
- To adjust the height
- Save the settings with the memory function (→ page 122).

# Switching the steering wheel heater on/off

Depending on the vehicle version, the steering wheel heater can be switched on and off using a switch on the steering wheel.

# Requirements

• The vehicle is switched on.



- To switch on: push the switch into position
- Indicator lamp 3 lights up.
- To switch off: push the switch into position 2.
  - Indicator lamp (3) will go out.

When you switch the ignition off, the steering wheel heater will switch off.

# Easy entry and exit feature

Using the easy entry and exit feature

★ WARNING Risk of accident when pulling away during the adjustment process of the easy entry and exit feature

You could lose control of the vehicle.

Always wait until the adjustment process is complete before driving off.

You and other vehicle occupants, particularly children, may become trapped.

Make sure that no one has any part of their body within the range of movement of the steering wheel and driver's seat.

If there is a risk of becoming trapped by the steering wheel:

Move the steering wheel adjustment lever.

The adjustment process is stopped.

If there is a risk of becoming trapped by the driver's seat:

- Press the switch for seat adjustment. The adjustment process is stopped.
- Never leave children unattended in the vehicle.
- When leaving the vehicle, always take the key with you and lock the vehicle.

**Vehicles with memory function:** You can stop the adjustment process by pressing one of the memory function position switches.

WARNING Risk of becoming trapped if children activate the easy entry and exit feature

Children could become trapped if they activate the easy entry and exit feature, particularly when unattended.

- Never leave children unattended in the vehicle.
- When leaving the vehicle, always take the key with you and lock the vehicle.

If the easy entry and exit feature is active, the steering wheel will move upwards and the driver's seat will move back in the following situations:

- You switch off the vehicle when the driver's door is open.
- You open the driver's door when the vehicle is switched off.

 The steering wheel will then move upwards only if it is not already as high as it will go. The driver's seat will then move backwards only if it is not already at the rear of the seat adjustment range.

The driver's seat backrest will then move forwards only if it is not already in the frontmost position.

The steering wheel and the driver's seat will move back to the last driving position in the following cases:

- You switch the power supply or the vehicle on when the driver's door is closed.
- You close the driver's door when the vehicle is switched on.

The last drive position will be saved when:

- · You switch off the vehicle.
- Vehicles with memory function: you save the seat settings via the memory function.

**Vehicles with memory function:** press one of the memory function position switches to stop the adjustment process.

# Memory function

# Function of the memory function

**WARNING** Risk of an accident if the memory function is used while driving

If you use the memory function on the driver's side while driving, you could lose control of the vehicle as a result of the adjustments being made.

- Only use the memory function on the driver's side when the vehicle is stationary.
- ▲ WARNING Risk of entrapment when adjusting the seat with the memory function

When the memory function adjusts the seat, you and other vehicle occupants – particularly children – could become trapped.

During the adjustment process of the memory function, make sure that no one has any body parts in the sweep of the seat.

If someone becomes trapped, press a preset position button or seat adjustment switch immediately.

**WARNING** Danger of entrapment when memory function is activated by children

When children activate the memory function, they can get trapped, especially if they are unsupervised.

- Never leave children unattended in the vehicle.
- When leaving the vehicle, always take the key with you and lock the vehicle.

You can use the memory function when the ignition is switched off.

Seat adjustments for up to three people can be stored and called up using the memory function.


You can save settings for the following systems:

- Front seat
- Outside mirrors

- · Head-up display
- Steering column
- · Seat contour

# Operating the memory function

### Storing



Set the desired position for all systems.

- Press memory button M and then press preset position button 1, 2 or 3 within three seconds
  - An acoustic signal sounds. The settings are stored.
- To call up: press or briefly hold preset position button 1, 2 or 3. After releasing the button, all systems are moved into the stored position.

#### Memory function in the rear passenger compartment

Function of the memory function in the rear passenger compartment

#### Operating the rear seat

Seat adjustments for the rear seat can be stored and called up using the memory function in the rear passenger compartment:

- Driver's side: two persons
- Front passenger side: one person

You can store the following settings for the rear seat:

- · Position of the seat, backrest and head restraint
- · Seat heating: distribution of the heated sections of the seat cushion and seat backrest

# Operating the front passenger seat and rear seat

Seat adjustments for the front passenger seat and the rear seat can be stored and called up using the rear seat memory function.

You can store the following settings for the front passenger seat:


 Position of the seat, backrest and head restraint

You can store the following settings for the rear seat:


- Position of the seat, backrest and head restraint
- · Seat heating: distribution of the heated sections of the seat cushion and seat backrest

### Operating the rear seat via the memory function in the rear passenger compartment

#### Storing



- Press button 1. The rear seat is selected if the indicator lamp does not light up.
- Adjust the rear seat using the buttons on the door operating unit ( $\rightarrow$  page 104).




Press memory button M and, within three seconds, press either preset position button 1 or 2.


The settings for the rear seat are stored in the corresponding preset position.

(i) You cannot store any settings on the button for straightening the fully reclined position.

# Calling up



Press button ①.
The rear seat is selected if the indicator lamp does not light up.



Press corresponding preset position button
 1 or 2.


The rear seat will move to the stored position.

Operating the front passenger seat and rear seats via the memory function in the rear passenger compartment


#### Requirements

• For selecting the front passenger seat: the power supply is switched on

# Storing




- Press button ①. The rear seat is selected if the indicator lamp does not light up.
- Adjust the rear seat using the buttons on the door operating unit ( $\rightarrow$  page 104).
- Press button 1. When the indicator lamp lights up, the front passenger seat is selected.
- Adjust the front passenger seat using the buttons on the door operating unit in the rear passenger compartment ( $\rightarrow$  page 100).
- Ensure that the indicator lamp in button (1) lights up.




- Press memory button M and, within three seconds, press preset position button 1. The settings for the front passenger seat and the rear seat are stored in the preset position.
- (i) You cannot store any settings on the buttons for setting and straightening the fully reclined position.

# Calling up




Press button ①. When the indicator lamp lights up, the front passenger seat is selected.



- Press preset position button 1.
  Both seats move into the stored position.
- You can use the rear passenger compartment child safety lock to disable this function (→ page 71).

#### Stowage areas

Notes on loading the vehicle



Combustion engines emit poisonous exhaust gases such as carbon monoxide. Exhaust gases can enter the vehicle interior if the tailgate is open when the engine is running, especially if the vehicle is in motion.

- Always switch off the engine before opening the tailgate.
- Never drive with the tailgate open.

Objects in the deployment area of an air bag may prevent the air bag from functioning correctly. Observe the notes on protection provided by the air bag.

**WARNING** Risk of injury from unsecured items in the vehicle

If objects, luggage or loads are not secured or not secured sufficiently, they could slip, tip over or be thrown around and thereby hit vehicle occupants.

There is a risk of injury, particularly in the event of sudden braking or a sudden change in direction.

- Always stow objects in such a way that they cannot be thrown around.
- Before the journey, secure objects, luggage or loads against slipping or tipping over.

# WARNING Risk of injury due to objects being stowed incorrectly

If objects in the vehicle interior are stowed incorrectly, they can slide or be thrown around and hit vehicle occupants. In addition, cup holders, open storage spaces and mobile phone receptacles cannot always retain all objects within.

There is a risk of injury, particularly in the event of sudden braking or abrupt changes in direction.

- Always store objects such that they cannot be thrown around in such situations
- Always make sure that objects do not protrude from storage spaces, parcel nets or storage nets.
- Close the lockable storage spaces before starting a journey.
- Stow and secure objects that are heavy. hard, pointed, sharp-edged, fragile or too large in the cargo compartment.

#### WARNING Risk of accident from objects in the driver's footwell and front-passenger footwell

Objects in the driver's footwell and frontpassenger footwell may impede pedal travel or block a depressed pedal.

This jeopardizes the operating and road safety of the vehicle.

Stow all objects in the vehicle securely so that they cannot get into the driver's footwell or front-passenger footwell.

- Always install the floor mats securely and as prescribed in order to ensure that there is always sufficient clearance for the pedals.
- Do not use loose floor mats and do not lay multiple floor mats on top of one another.

Vehicles with automatic front-passenger air bag shutoff: objects trapped under the frontpassenger seat may interfere with the function of the automatic front-passenger air bag shutoff or damage the system. Please observe the notes on the function of the automatic front -passenger air bag shutoff ( $\rightarrow$  page 44).

WARNING - Risk of accident or injury when using the cup holder while the vehicle is moving

The cup holder cannot secure containers while the vehicle is moving.

If you use a cup holder while the vehicle is moving, the container may be flung around and liquids may be spilled. The vehicle occu-

pants may come into contact with the liquid and if it is hot, they could be scalded. You could be distracted from traffic conditions and you may lose control of the vehicle.

- Only use the cup holder when the vehicle is stationary.
- Only use the cup holder for containers of the right size.
- Close the container, particularly if the liquid is hot.

# I NOTE Damage to the cup holder

The cup holder can be damaged when folding back the rear armrest. When open, the cup holder can be damaged by body weight.

- The rear armrest can only be folded back when the cup holder is closed.
- Do not sit or support yourself on the cup holder when it is open.

! NOTE Damage to the rear armrest due to body weight

When folded out, the rear armrest can be damaged by body weight.

Do not sit or support yourself on the rear seat armrest.

**WARNING** Risk of injury due to an open cargo compartment floor

If you drive with the cargo compartment floor open, objects could be flung around and hit vehicle occupants as a result. There is a risk of injury, particularly in the event of sudden braking or a sudden change in direction.

Always close the cargo compartment floor before a journey.

**WARNING** Risk of fire and injury from hot cigarette lighter

You can suffer burns if you touch the hot heating element or the hot socket of the cigarette lighter.

In addition, flammable materials can catch fire if:

- you drop the hot cigarette lighter.
- children e.g. hold the hot cigarette lighter to objects.
- Always hold the cigarette lighter by the knob.
- Always make sure that the cigarette lighter is out of the reach of children.
- Never leave children unattended in the vehicle.

# **WARNING** Risk of burns from the tailpipe and tailpipe trims

The exhaust tailpipe and tailpipe trims can become very hot. If you come into contact with these parts of the vehicle, you could burn yourself.

Always be particularly careful around the tailpipe and the tailpipe trims and supervise children especially closely in this area.

- Allow vehicle parts to cool down before touching them.
- (i) Leather is a natural product. It exhibits natural surface properties such as differences in structure, marks caused by growth and injury or subtle color differences. These surface properties are characteristics of leather and not material faults. Leather is also subject to a natural aging process during which the surface properties change.

The handling characteristics of your vehicle are dependent on the distribution of the load within the vehicle. You should bear the following in mind when loading the vehicle:

- Do not exceed the permissible total mass or the gross axle weight rating of the vehicle (including load and occupants). The values are specified on the vehicle identification plate on the vehicle's B-pillar.
- The load must not protrude above the upper edge of the seat backrests.

- All vehicles except Mercedes-Maybach vehicles: always use the partition net when transporting objects in the cargo compartment.
- Always place the load behind unoccupied seats if possible.
- Secure the load using the cargo tie-down rings and distribute the load evenly.

#### Notes on driving with a roof load

- Distribute the roof load and the load inside the vehicle evenly, placing heavy objects at the bottom. Also comply with the notes on loading the vehicle
- Drive attentively, and avoid abrupt starts, braking and steering as well as rapid cornering.
- When transporting roof loads and when the vehicle is fully loaded or fully occupied, select drive programs and . These are designed to focus on stability ( $\rightarrow$  page 190).
- (i) For more information on stowage compartments and stowage areas, please refer to the Digital Operator's Manual.

# Stowage spaces in the vehicle interior

Overview of the front stowage compartments



- Stowage spaces in the doors
- Stowage compartment in the armrest with USB ports (depending on vehicle equipment)
- Stowage/telephone compartment with cup holder in the front center console

- Mercedes-Maybach vehicles: stowage/telephone compartment with temperature-controlled cup holder, USB ports (depending on the vehicle equipment) and charging module for wireless charging of mobile phones (depending on the vehicle equipment) in the front center console
- Glove box

# Folding the folding table out or in

**WARNING** Risk of injury when the folding table is folded out

Vehicle occupants may bump into the folding table and injure themselves.


- ► Use the folding table only when the vehicle is stationary.
- Stow the folding table before each journey.
- NOTE Damage to the folding tables when moving the seats back

Open folding tables may be damaged when the seats are moved back.

 Make sure that the folding tables are folded in when moving the front seats back.

### Folding out

This equipment is available only for Mercedes-Maybach vehicles.



- Open rear passenger compartment armrest
- Pull the folding table forwards and upwards by recess ② or ③ and swing outwards.
- Fold the table panels apart.
- To fold in: fold the table panels together and swing in the folding table.


# Opening the stowage box in the backrest in the rear compartment

! NOTE Damage to the rear armrest due to body weight

When folded out, the rear armrest can be damaged by body weight.

Do not sit or support yourself on the rear seat armrest.

This equipment is available only for Mercedes-Maybach vehicles.



Vehicles with individual seats (example)

- Vehicles with 5-seater variant: fold down the rear armrest.
- Pull handle 1 and fold down cover 2.

Removing the handset from the storage compartment in the rear passenger compartment

#### Opening the drawer

This equipment is available only for Mercedes-Maybach vehicles with individual rear seats.



Vehicles with individual rear seats

Press button ①.

Remove the handset.

#### Closing the drawer

- Place the handset in the drawer.
- Press the handset drawer back until it engages.

#### Through-loading feature to the cargo compartment

### Folding the rear seat backrest forwards

WARNING Risk of becoming trapped when adjusting the seats

When you adjust a seat, you may trap yourself or a vehicle occupant.

When adjusting a seat, make sure that no one has any body parts in the sweep of the seat.

WARNING Risk of accident if the seat and seat backrest are not engaged

The seat and seat backrest can fold forwards.

There is a risk of the following, in particular:

- The vehicle occupant may be pressed against the seat belt. The seat belt cannot protect as intended and could cause additional injury.
- A child restraint system will no longer be properly supported or positioned and will no longer fulfill its function as intended.
- The seat backrest will not be able restrain objects or goods in the cargo compartment.

Always ensure that the seat and seat backrest are engaged, in particular:

- Before persons travel in the vehicle while sitting on a seat with the easy entry and exit feature
- After the seat has been adjusted.
- After the easy entry and exit feature has been used
- After the cargo compartment enlargement has been folded forwards


Always ensure that all vehicle occupants have their seat belts fastened correctly and are sitting properly. Particular attention must be paid to children.

If you no longer require the folded-down rear seat backrest as a load area, fold the backrest back into place.

Make sure that the red marking of the lock verification indicator is no longer visible. Otherwise, the seat backrest is not locked.

#### Requirements:

- Vehicles with a center seat backrest: the center seat backrest is not in the cargo compartment floor position.
- Vehicles with a folding rear armrest: the rear armrest has been folded up.



Seven-seater (example)

➤ To fold the left or right seat backrest forwards: briefly press one of buttons ①.


The head restraint on the seat backrest will move into a suitable position. The rear seat will fold forwards.

Vehicles with a center seat backrest: the center seat backrest will fold forwards together with the left seat backrest.

If a seat in the second row of seats is not engaged and locked, this will be shown on the multifunction display on the instrument cluster.

(i) Seven-seaters: all seat backrests can be folded forwards together using the ALL button.

# Folding the rear center seat backrest forwards separately (seven-seaters)




Fold the rear seat armrest back if necessary.

- Press release catch 3.
- ► Fold seat backrest ② forwards.
- Folding the rear seat backrest back
- **NOTE** Damage caused by trapping the seat belt when folding back the seat backrest

The seat belt could become trapped and thus damaged when the seat backrest is folded back.

Make sure that the seat belt is not trapped when folding back the seat backrest.



Seven-seater (example)

To fold back the seat backrest: briefly pull one of buttons 1.

The rear seat will fold back.

Vehicles with a center seat backrest: the center seat backrest will fold back together with the left seat backrest.

If a seat backrest is not engaged and locked, this will be shown on the multifunction display on the instrument cluster.

(i) Seven-seaters: all seat backrests can be folded back together using the ALL button.


# Folding back the center seat backrest

If only the center seat backrest in the rear passenger compartment has been folded forward separately: swivel the seat backrest backwards until it engages. ■ Folding the seat backrest on the third row of seats forwards




Left-hand-drive vehicle (example)

In the rear passenger compartment (sevenseater): briefly pull one of buttons ①.




In the cargo compartment: briefly press one of buttons .

#### Folding back the seat backrest on the third row of seats



Left-hand-drive vehicle (example)

In the rear passenger compartment: briefly press one of buttons 1. If a seat backrest is not engaged and locked, this will be shown on the multifunction display on the instrument cluster.



In the cargo compartment: briefly pull one of buttons 1

If a seat backrest is not engaged and locked, this will be shown on the multifunction display on the instrument cluster.

### EASY-PACK cargo compartment cover and partitioning net cassette

# Notes on the cargo compartment cover

WARNING Risk of injury or death due to poorly secured objects

The cargo compartment cover alone cannot secure or restrain heavy objects, items of luggage or heavy loads.

You could be hit by an unsecured load, particularly in the event of abrupt changes in direction, sudden braking or an accident.


- Always stow objects in such a way that they cannot be thrown around.
- Secure objects, luggage or loads against slipping or tipping over, e.g. by using tie downs, even if you are using the cargo compartment cover.
- **NOTE** Damage to the cargo compartment cover when loading the vehicle

The cargo compartment cover may be damaged when the vehicle is being loaded.

Do not place any objects above the lower edge of the side windows or on the cargo compartment cover.

This equipment is available for all vehicles except Mercedes-Maybach vehicles.

# Extending/retracting the cargo compartment cover



To extend: pull the cargo compartment cover back by grab handle and clip it into brackets on the left and right.

#### Retracting

- Remove the cargo compartment cover from the brackets on the left and right.
- Guide the cargo compartment cover forwards using the grab handle until it is fully retracted.

The rolled-up cargo compartment cover can be used in two positions:


- Folded 45° upwards for loading (fold down before commencing your journey)
- Horizontal position

# Installing or removing the cargo compartment cover

# Requirements:

• The cargo compartment cover is rolled up.


# Removing the cargo compartment cover



- Press end cap ① on the left or right inwards.
- Pull out the cargo compartment cover backwards.


# Storing the cargo compartment cover

The cargo compartment cover can be stored beneath the cargo compartment floor.



- Open the cargo compartment floor.
- To insert: place cargo compartment cover ① into brackets 2. Ensure it is seated correctly.
- To remove: take the cargo compartment cover out of brackets 2.

### Installing the cargo compartment cover



Place the cargo compartment cover in brackets 1 on the left and right. The end caps of the cargo compartment cover engage audibly.

# Attaching/removing the partitioning net

WARNING Risk of injury or death due to poorly secured objects

The partitioning net alone cannot secure or restrain heavy objects, items of luggage or heavy loads.


You could be hit by an unsecured load, particularly in the event of abrupt changes in direction, sudden braking or an accident.

- Always stow objects in such a way that they cannot be thrown around.
- Secure objects, luggage or loads against slipping or tipping over, e.g. by using tie downs, even if you are using the partitioning net.


For safety reasons, always use a partitioning net when transporting a load. The partitioning net can be used with or without cargo compartment enlargement

Damaged partitioning nets can no longer fulfill their functions and must be replaced. Visit a qualified specialist workshop.

This equipment is available for all vehicles except Mercedes-Maybach vehicles.



Partitioning net without cargo compartment enlargement




Partitioning net with cargo compartment enlargement

- **To attach:** extend the partition net.
- Attach the top guide rod to holders on the headliner.
- Engage hooks ② in eyelets ③ on the left and right.

- Pull on the loose ends of the lashing straps until the partitioning net is tight.
- After driving a short distance, check the tension of the partitioning net and re-tension it if necessary.
- To remove: pull the belt clamps until the lashing straps are loose.
- Remove hooks ② from eyelets ③ on the left and right.
- ▶ Remove the top guide rod from holders ①.

# Overview of the tie-down eyes in the cargo compartment

Observe the notes on loading the vehicle ( $\rightarrow$  page 126).



Tie-down eyes

The front tie-down eyes are accessible when the third row of seats is in the trunk floor position  $(\rightarrow page 131)$ .

(i) Mercedes-Maybach vehicles: both tie-down eyes on Mercedes-Maybach vehicles are located at the rear of the cargo compartment on the left and right.

# Overview of bag hooks

WARNING Risk of injury when using bag hooks with heavy objects


The bag hooks cannot restrain heavy objects or items of luggage.

Objects or items of luggage may be flung around and hit vehicle occupants.

- Only hang light objects on the bag hooks.
- Never hang hard, sharp-edged or fragile objects on the bag hooks.

Observe the notes on loading the vehicle  $(\rightarrow page 126)$ .

Subject the bag hooks to a maximum load of 6.6 lbs (3 kg) and do not attach any goods to them.



Bag hooks

# Coat hook on the tailgate

This equipment is available for all vehicles except Mercedes-Maybach vehicles.




Coat hook on the tailgate

Coat hooks are not suitable for heavy objects. Use the coat hooks only for light objects such as jackets.

# Locking and unlocking the cargo compartment floor

This equipment is available for all vehicles except Mercedes-Maybach vehicles.



Turn the emergency key a quarter turn clockwise 2 (to lock) or counter-clockwise 1 (to unlock).

# Attaching a roof luggage rack

A

**WARNING** Risk of accident due to exceeding the maximum roof load

The vehicle center of gravity and the usual driving characteristics as well as the steering and braking characteristics alter.

If you exceed the maximum roof load, the driving characteristics, as well as steering and braking, will be greatly impaired.

Never exceed the maximum roof load and adjust your driving style.

You will find information on the maximum roof load in the "Technical data" section.

!

**NOTE** Damage to the vehicle due to not observing the maximum permitted headroom clearance

If the vehicle height is greater than the maximum permitted headroom clearance, the roof and other parts of the vehicle may be damaged.

- Observe the signposted headroom clearance.
- If the vehicle height is greater than the permitted headroom clearance, do not enter.
- Observe the changed vehicle height with add-on roof equipment.
- **NOTE** Vehicle damage from non-approved roof luggage racks

The vehicle could be damaged by roof luggage racks that have not been tested and approved for Mercedes-Benz.

- Use only roof luggage racks tested and approved for Mercedes-Benz.
- Depending on the vehicle equipment, ensure that the sliding sunroof can be fully raised when the roof luggage rack is installed.
- Depending on the vehicle equipment, ensure that the tailgate can be fully

- opened when the roof luggage rack is installed
- Position the load on the roof luggage rack in such a way that the vehicle will not sustain damage even when it is in motion.
- **NOTE** Damage to the panorama roof with power tilt/sliding panel due to nonapproved roof luggage racks

The panorama roof with power tilt/sliding panel may be damaged by the roof luggage rack if you attempt to open it when using a roof luggage rack not tested and approved for Mercedes-Benz.

▶ When a roof luggage rack is installed, open the panorama roof with power tilt/ sliding panel only if this has been tested and approved for Mercedes-Benz.

The panorama roof with power tilt/sliding panel may be raised to allow ventilation of the vehicle interior.

Notes on driving with a roof load

- Evenly distribute the roof load, and place heavy objects at the bottom. Also comply with the notes on loading the vehicle  $(\rightarrow page 126)$ .
- Drive attentively, and avoid suddenly pulling away, braking and steering as well as rapid cornering.
- When transporting roof loads and when the vehicle is fully loaded or fully occupied, select drive programs and . These are designed to focus on stability ( $\rightarrow$  page 190).
- Secure the roof luggage rack to the roof railing.
- Observe the manufacturer's installation instructions.

# Cup holder

Switching the cooling or heating function for the temperature-controlled cup holder on or off

**WARNING** Risk of injury by touching the heating elements


The cup holder's heating elements may be very hot.

You can burn yourself on them.


- Do not touch the cup holder's hot heating elements.
- Ensure that no children can access the cup holder's hot heating elements.
- Never leave children unattended in the vehicle.
- I NOTE Damage to objects in the temperature-controlled cup holder

If you place objects into the temperature-controlled cup holder, they may become damaged.

Do not place objects into the temperature-controlled cup holder.



Cup holder in the front center console



Cup holder in the rear center console



Cup holder in the rear passenger compartment center console (Mercedes-Maybach four-seater vehicles)

To switch on: on cup holder (1), press button 2 repeatedly until the blue (keep cool) or red (keep warm) indicator lamp on the button lights up.

If you use the heating function, the metal insert of the cup holder will be heated. Once a certain temperature has been reached, the warning lamp will light up. Do not reach into the cup holder's metal insert when the warning lamp is lit.

To switch off: press button 2 repeatedly until the indicator lamp on the button goes out.

Clean the removable rubber mat only with clean, lukewarm water and the cup holder only with a soft cloth.

#### Sockets


Using the 12 V socket

# Requirements:

• Only connect devices up to a maximum of 240 W (20 A).

Depending on the vehicle equipment, the vehicle has the following 12 V sockets:

- In the stowage compartment in the front center console
- In the cargo compartment



Example: 12 V socket in the stowage compartment in the front center console

Lift up cap 1 of the socket and insert the plug of the device.

If you have connected a device to the 12 V socket, leave the cover of the stowage compartment open.

# Using the 115 V socket in the rear passenger compartment

DANGER Risk of fatal injuries due to a damaged connecting cable or a damaged socket

You could receive an electric shock if the connecting cable or the 115 V power socket is pulled out of the trim or is damaged or wet.

- Use only connecting cables that are dry and free of damage.
- ► When the vehicle is switched off, make sure that the 115 V power socket is dry.
- Immediately have the 115 V power socket checked or replaced at a qualified specialized workshop if it is damaged or has been pulled out of the trim.
- Never plug the connecting cable into a 115 V power socket that is damaged or has been pulled out of the trim.

▲ DANGER Risk of death due to using the socket incorrectly


In particular, you could receive an electric shock:

- If you touch the inside of the socket
- If you insert unsuitable devices or objects into the socket
- Do not touch the inside of the socket.
- Only connect suitable devices to the socket.

#### Requirements:

- Only connect devices with a suitable plug which conforms to the standards specific to the country you are in.
- Only connect devices up to a maximum of 150 W (1.3 A).
- Do not use multiple socket outlets.

Depending on the vehicle equipment, the design of the center console and stowage compartment may differ.



Using the 115 V socket in the center console of the rear passenger compartment



115 V socket in the center console of the rear passenger compartment (Mercedes-Maybach 4-seat vehicles)

- Mercedes-Maybach vehicles with individual rear seats: open the stowage compartment of the center console of the rear passenger compartment.
- Open flap 3.

Insert the plug of the device into 115 V socket

When the on-board electrical system voltage is sufficient, indicator lamp (2) lights up.

#### Overview of USB ports

Depending on the vehicle equipment, the vehicle has the following USB ports:

- in the stowage compartment of the cockpit armrest ( $\rightarrow$  page 129)
- in the front center console next to the mobile phone stowage compartment
- · in the center console in the rear passenger compartment
- vehicles with Rear Comfort Package: in the center armrest of the second row of seats in the rear passenger compartment
- Mercedes-Maybach vehicles with 5 seats in the rear passenger compartment: in the center armrest in the rear passenger compartment

- · Mercedes-Maybach vehicles with individual rear seats: in the center console of the rear passenger compartment
- vehicles with three rows of seats: to the right and left next to the seat

If the vehicle is switched on you can charge USB devices, e.g. mobile phones, at USB ports. Depending on the vehicle equipment, the charging power is up to 100 W.

# Refrigerator box

Using the refrigerator box

WARNING Risk of fire due to a covered vent grille on the refrigerator box

If you cover the vent grille for the refrigerator box. it may overheat.

Always make sure that the vent grille is not covered.

The vent grille for the refrigerator box is in the trunk.

#### 146 Seats and stowing

This equipment is available only for Mercedes-Maybach vehicles.

The refrigerator box can bear a maximum load of 7.7 lb (3.5 kg).

Store only plastic bottles in the upper compartment of the refrigerator box. The contents of the bottle must be no more than 17 fl. oz. (0.5 liters).


If you do not need to use the refrigerator box for an extended period, switch it off, defrost it and clean it. After doing so, leave the lid open for a time.

More condensation may occur during heavy use. Cleaning may be required.

The refrigerator box will reduce its cooling capacity or switch off in the following cases:


- Too many electrical consumers are turned on.
- The starter battery is not sufficiently charged.

If this is the case, the indicator lamps will flash on the button for switching the refrigerator box on and off. The cooling function will automatically switch back on as soon as there is sufficient voltage.  To install the refrigerator box in the cargo compartment or remove it, please contact a qualified specialist workshop.



Example: vehicles with individual rear seats

- Vehicles with 5-seater variant: fold down the rear armrest.
- Pull handle on stowage box ① and fold down the cover of stowage box ②.



Example: vehicles with individual rear seats

- To open: pull the handle on refrigerator box
  and fold down the cover of the refrigerator
  box.
- ➤ To switch on: press button ② repeatedly until an indicator lamp (low cooling) lights up or two indicator lamps (high cooling) light up.

To switch off: press button 2 repeatedly until both indicator lamps go out.

Wireless charging of the mobile phone and connection with the exterior antenna

Notes on wirelessly charging a mobile phone

WARNING Risk of injury due to objects being stowed incorrectly

If objects in the vehicle interior are stowed incorrectly, they can slide or be thrown around and hit vehicle occupants. In addition, cup holders, open stowage spaces and mobile phone receptacles cannot always retain all objects within.

There is a risk of injury, particularly in the event of sudden braking or a sudden change in direction.

Always stow objects so that they cannot be thrown around in such situations.

- Always make sure that objects do not protrude from stowage spaces, parcel nets or stowage nets.
- Close the lockable stowage spaces before starting a journey.
- Always stow and secure heavy, hard, pointed, sharp-edged, fragile or bulky objects in the trunk/cargo compartment.

Observe the notes on loading the vehicle.

**WARNING** Risk of fire from placing objects in the mobile phone storage compartment

Placing other objects in the mobile phone storage compartment could constitute a fire hazard.

Apart from a mobile phone, do not place any other objects in the mobile phone storage compartment, especially those made of metal.

NOTE Damage to objects caused by placing them in the mobile phone storage compartment

If objects are placed in the mobile phone storage compartment, these may be damaged by electromagnetic fields.

- ▶ Do not place credit cards, storage media, ski passes or other objects sensitive to electromagnetic fields in the mobile phone storage compartment.
- **NOTE** Damage to the mobile phone stowage compartment caused by liquids

If liquids enter the mobile phone stowage compartment, the compartment may be damaged.

Ensure that no liquids enter the mobile phone stowage compartment.

Always observe the notes for persons with electronic medical aids ( $\rightarrow$  page 31).


#### 148 Seats and stowing

- Depending on the vehicle equipment, the mobile phone is connected to the vehicle's exterior antenna via the charging module.
- The charging function and wireless connection of the mobile phone to the vehicle's exterior antenna are available only if the vehicle is switched on.
- Small mobile phones may not be able to be charged in every position of the mobile phone stowage compartment.
- Large mobile phones that do not rest flat in the mobile phone stowage compartment may not be able to be charged or connected with the vehicle's exterior antenna.
- The mobile phone may heat up during the charging process. This may also depend on the applications (apps) currently open in the background.
- To ensure more efficient charging and connection with the vehicle's exterior antenna, remove the protective cover from the mobile phone. Protective covers that are necessary for wireless charging are an exception.

#### Wireless charging of a mobile phone in the cockpit

#### Requirements:

- The mobile phone is suitable for wireless charging.
- (i) A list of compatible mobile phones can be found at: https://www.mercedes-benz-mobile.com/



Place the mobile phone as close to the center of mat as possible with the display facing upwards.

When a message is shown in the multimedia system, the mobile phone is being charged.

- Malfunctions detected during the charging process are shown in the multimedia system display.
- i The mat can be removed for cleaning, e.g. using clean, lukewarm water.

# Wirelessly charging a mobile phone in the rear passenger compartment

NOTE Damage to the drawer in the center console of the rear passenger compartment due to body weight

When open, the drawer in the center console of the rear passenger compartment can be damaged by body weight.

Do not support yourself on the open drawer.

#### Requirements:

 The mobile phone must be suitable for wireless charging. (i) A list of compatible mobile phones can be found at: https://www.mercedes-benzmobile.com/



Mat in front of the stowage compartment in the rear passenger compartment armrest



Mat in the center console of the rear passenger compartment (only Mercedes-Maybach vehicles with individual rear passenger compartment seats)

Place the mobile phone as close to the center of mat 
 as possible with the display facing upwards.

When the indicator lamp lights up, the mobile phone is being charged.

# Installing/removing the floor mats

WARNING Risk of accident due to objects in the driver's footwell


Objects in the driver's footwell may impede pedal travel or block a depressed pedal.

This jeopardizes the operating and road safety of the vehicle.

- Stow all objects in the vehicle securely so that they cannot get into the driver's footwell.
- Always install the floor mats securely and as prescribed in order to ensure that there is always sufficient room for the pedals.
- Do not use loose floor mats and do not place floor mats on top of one another.

#### 150 Seats and stowing

# Installing floor mats



- Move the corresponding seat backwards and lay the floor mat in the footwell.
- Press studs ① onto holders ②.
- Adjust the corresponding seat.
- (i) Vehicles with a third row of seats (all vehicles except Mercedes-Maybach vehicles): To install the floor mats on the third row of seats,

slide the corresponding seat on the second row of seats forwards.

# Removing floor mats

- Pull the floor mat off holders 2.
- ▶ Remove the floor mat.
- i Vehicles with a third row of seats (all vehicles except Mercedes-Maybach vehicles): To remove the floor mats on the third row of seats, slide the corresponding seat on the second row of seats forwards.


# Exterior lighting

# Information about lighting systems and your responsibility

The various lighting systems of the vehicle are only aids. The driver of the vehicle is responsible for correct vehicle illumination in accordance with the prevailing light and visibility conditions, legal requirements and traffic situation.

# Light switch

# Operating the light switch



- **←P** Left-hand parking lights
- **P**≤→ Right-hand parking lights
- Standing lights and license plate lamp
- Automatic driving lights (preferred light switch position)

D Low beam/high beam

When low beam is activated, the [=005] indicator lamp for the standing lights will be deactivated and replaced by the D low-beam indicator lamp.

- Always park your vehicle safely using sufficient lighting, in accordance with the relevant legal stipulations.
- **NOTE** Battery discharging by operating the parking lamps

Do not have the parking lamps switched on over a period of several hours.

If the battery is insufficiently charged, the standing lights or parking lights will be switched off automatically to facilitate the next engine start.

The exterior lighting (except standing and parking lights) will switch off automatically when the driver's door is opened.

· Observe the notes on surround lighting  $(\rightarrow page 156)$ .

# Automatic driving lights function

When the vehicle is switched on, the side lamps, low beam and daytime running lights will be switched on automatically depending on the ambient light.

**WARNING** Risk of accident when the low beam is switched off in poor visibility

When the light switch is set to [AUTO], the low beam may not be switched on automatically if there is fog, snow or other causes of poor visibility such as spray.

In such cases, turn the light switch to .

The automatic driving lights are only an aid. You are responsible for the vehicle lighting.

# Switching the rear fog light on/off


#### Requirements

- The light switch is in the or or position.
- ▶ Press button 0\$.

Please observe the country-specific laws on the use of rear fog lamps.

(i) Vehicles with AIRMATIC or E-ACTIVE BODY CONTROL with off-road package: when the rear fog light is switched on, off-road level +3 will not be available. If the rear fog light is switched on and off-road level +3 is activated, the vehicle will be lowered to off-road level +2.

# Operating the combination switch for the lights



- High beam
- Turn signal light, right
- Headlamp flashing
- Turn signal light, left
- Use the combination switch to select the desired function.

### Switching on high beam

- Turn the light switch to the D or AUTO position.
- Push the combination switch in the direction of arrow 1.

When high beam is activated, the indicator lamp for low beam will be deactivated and replaced by the indicator lamp for high beam **≣**□.

### Switching off high beam

Push the combination switch in the direction of arrow 1 or pull it in the direction of arrow

# Headlamp flashing

Pull the combination switch in the direction of arrow 3.

# Turn signals


To indicate briefly: push the combination switch briefly to the point of resistance in the direction of arrow 2 or 4. The corresponding turn signal light will flash three times.

To indicate permanently: push the combination switch beyond the point of resistance in the direction of arrow 2 or 4.

Vehicles with Active Lane Change Assist:

- A turn signal indicator activated by the driver may continue to operate for the duration of the lane change.
- If the driver indicated directly beforehand but a lane change was not immediately possible, the turn signal indicator may activate automatically.

# Activating/deactivating the hazard warning lights



Press button ①.


The hazard warning lights will switch on automatically if:

· the air bag has been deployed.

When the turn signal indicator is activated, the hazard warning lights will be interrupted.

#### Active headlamps

# Active headlamps function



- The headlamps follow the steering movements.
- Relevant areas are better illuminated during a journey.

The functions will be active when low beam is switched on.

Depending on the vehicle's equipment, the course of the lane in which you are driving will also be evaluated and the active headlamps function will adjust the light in advance.

# Adaptive Highbeam Assist

# Adaptive Highbeam Assist function

**WARNING** Risk of accident despite Adaptive Highbeam Assist

Adaptive Highbeam Assist does not react to:

- Road users without lights, e.g. pedestrians
- Road users with poor lighting, e.g. cyclists
- Road users whose lighting is obstructed, e.g. by a barrier

On very rare occasions, Adaptive Highbeam Assist may fail to recognize other road users with their own lighting, or may recognize them too late.

In these, or in similar situations, the automatic high beam will not be deactivated or will be activated despite the presence of other road users.

 Always observe the road and traffic conditions carefully and switch off the high beam in good time.


#### System limits

Adaptive Highbeam Assist cannot take into account road, weather or traffic conditions.

Detection may be restricted in the following cases:

- In poor visibility, e.g. fog, heavy rain or snow
- If there is dirt on the sensors or the sensors are obscured

Adaptive Highbeam Assist is only an aid. You are responsible for adjusting the vehicle's lighting to the prevailing light, visibility and traffic conditions.



Adaptive Highbeam Assist automatically switches between the following types of light:

- Low-beam headlamps
- High beam

At speeds greater than 19 mph (30 km/h):

· If no other road users are detected, high beam will switch on automatically.

The high beam will switch off automatically in the following cases:

- At speeds below 16 mph (25 km/h)
- If other road users are detected
- If street lighting is sufficient

At speeds greater than approximately 31 mph (50 km/h):

- The headlamp range of the low beam will be regulated automatically based on the distance to other road users.
- The system's optical sensor is located behind the windshield near the overhead control panel.

# Switching Adaptive Highbeam Assist on/off

# Switching on

- Turn the light switch to the AUTO position.
- Switch on high beam using the combination switch.

If Adaptive Highbeam Assist is activated, the indicator lamp will light up in the central display section of the instrument display.

#### Switching off

Switch off high beam using the combination switch.

# Switching the daytime running lamps on/off

Multimedia system:

- → 🔝 >> Settings >>> Light >> Daytime Run. Lights
- Activate or deactivate the function.

#### Setting the exterior lighting switch-off delay time

#### Requirements:

• The light switch is in the AUTO position.

Multimedia system:

→ Settings → Light

>> Exterior Lighting Delay

Set the switch-off delay time. When the vehicle's engine is switched off, the exterior lighting will be activated for the set time.

# Switching the surround lighting on/off

Multimedia system:

→ 🕍 >> Settings >> Light

>> Locator Lighting

When Locator Lighting is active, the exterior lighting lights up for 40 seconds after the vehicle is unlocked. When you start the vehicle, the surround lighting is deactivated and the automatic driving lights are activated.


Illuminated running boards: when the surround lighting is switched on, the illumination of the running boards is activated when a door is opened. If the door is not closed, the running board courtesy lighting is automatically deactivated after 40 seconds.

Activate or deactivate the function.

# Interior lighting

Adjusting the interior lighting

#### Front overhead control panel



Automatic interior lighting control


③ Front interior lighting

4 📉 Rear interior lighting

⑤ 茁 Front right reading lamp

To switch on or off: press button ① - ③
accordingly.

# Control panel in the grab handle



① Rear reading lamp

To switch on or off: press the 1 button.

# Adjusting the ambient lighting

Multimedia system:

### Setting the color

- Select Color.
- Set the desired color.

# Adjusting the brightness

Select Brightness.

Adjust the brightness.

#### Activating the brightness for zones

- Select Brightness.
- Select Brightness Zones. The ACCENT, AMBIANCE and ROOF zones can be set separately.

# Activating multi-color lighting

- Select Color.
- Select Multi-color.
- Select a color combination.

# Activating multi-color animation

- Select Color.
- Select Multi-color Animation.
  The chosen color combination will change at predefined intervals.

# Activating welcome lighting

- Select Color.
- Select Welcome.
   When the vehicle is unlocked, a special ambient lighting sequence will run.

# Activating dependency on air conditioning settings


- Select Color.
  - Select Climate. If changes are made to the temperature setting in the vehicle, the color of the ambient lighting will change briefly.

# Switching the interior lighting switch-off delay time on/off

Multimedia system:

- → Settings → Light
  → Interior Lighting Delay
- Switch the switch-off delay time on or off. When this function is active, the interior lighting lights up for a short time after the vehicle is locked.

# Windshield wiper and windshield washer system Switching the windshield wipers on/off




- 1 0 Windshield wipers off
- 2 ••• Automatic wiping, normal
- 3 •••• Automatic wiping, frequent
- 4 Continuous wiping, slow
- 5 Continuous wiping, fast

- Turn the combination switch to the corresponding position 1 5.
- Single wipe/washing: push the button on the combination switch in the direction of arrow
  - Single wipe
  - Wipes with washer fluid
- Observe the notes on washing the vehicle in a car wash (→ page 344).

Vehicles with MAGIC VISION CONTROL: in position 2 or 3 , the windshield washing process is automatically triggered if dirt is detected on the windshield unless the Add Washer Fluid message is being displayed.

# Switching the rear window wiper on/off



- 🕦 🛱 Single wipe/washing
- Single wipe: press button (1) as far as the point of resistance.
- Wiping with washer fluid: press button beyond the point of resistance.

Switching intermittent wiping on/off: press button 2.

Vehicles with rain sensor: The wipe interval will automatically adapt to the driving conditions

The symbol will appear on the instrument display when the rear window wiper is switched on.

#### Changing the windshield wiper blades

WARNING Risk of becoming trapped if the windshield wipers are switched on while wiper blades are being replaced

If the windshield wipers begin to move while you are changing the wiper blades, you can be trapped by the wiper arm.


Always switch off the windshield wipers and vehicle before changing the wiper blades.

#### Moving the wiper arms into the replacement position

- Switch the vehicle on and then off again immediately.
- Within around 15 seconds, press and hold the button on the combination switch for approximately three seconds ( $\rightarrow$  page 158). The wiper arms will move into the replacement position.


# Removing the wiper blades

Fold the wiper arms away from the windshield.



- Hold the wiper arm with one hand. With the other hand, turn the wiper blade away from the wiper arm in the direction of arrow 1 as far as it will go.
- Slide catch (2) in the direction of arrow (3) until it engages in the removal position.
- Remove the wiper blade from the wiper arm in the direction of arrow (1).

### Installing the wiper blades




- Insert the new wiper blade into the wiper arm in the direction of arrow (1).
- Slide catch ② in the direction of arrow ③ until it engages in the locking position.
- Make sure that the wiper blade is seated correctly.
- Fold the wiper arms back onto the windshield.

- Switch on the vehicle.
- Press the button on the combination switch.
   The wiper arms will return to their original
- Switch off the vehicle.

positions.

 Check the condition of the wiper blades regularly and replace them in the event of visible damage or ongoing smearing.

# Maintenance display



When the color of the maintenance displays changes from black to yellow, replace the wiper blades.

(i) The duration until the color changes varies depending on the usage conditions.


#### Replacing the windshield wiper blades (MAGIC VISION CONTROL)

#### Moving the wiper arms into the replacement position

- Switch off the vehicle.
- Within around 15 seconds, press the button on the combination switch  $(\rightarrow page 158)$ . The wiper arms will move into the replacement

position.

# Removing the wiper blades




To bring the wiper blade into position to be removed: hold the wiper arm firmly with one hand. With the other hand, turn the wiper blade in the direction of arrow beyond the point of resistance.

The wiper blade will engage in the removal position with a click.

To remove the wiper blade: press release knob 2, pull the wiper blade in the direction of arrow (3) and remove.

# Installing the wiper blades



Push the new wiper blade onto the wiper arm in the direction of arrow 1 until release knob engages.

- Press the wiper blade beyond the point of resistance in the direction of arrow on the wiper arm.
  - The wiper blade will engage with a noticeable click and move freely again.
- Fold the wiper arm back onto the windshield.
- (i) Check the condition of the wiper blades regularly and replace them in the event of visible damage or ongoing smearing.


#### Replacing the rear window wiper blade

WARNING Risk of becoming trapped if the windshield wipers are switched on while wiper blades are being replaced

If the windshield wipers begin to move while you are changing the wiper blades, you can be trapped by the wiper arm.


Always switch off the windshield wipers and vehicle before changing the wiper blades.

### Removing the wiper blade



- Switch off the vehicle.
- Fold wiper arm ② away from the rear window until it engages in the replacement position.
- Unclip wiper blade ① from wiper arm ② and remove it in the direction of arrow ③.

# Installing the wiper blades



- Position wiper blade with both lugs on holder on the wiper arm.
- Push wiper blade 1 in the direction of arrow 4 until it engages in holder 2.
- Make sure that wiper blade is seated correctly.

Fold the wiper arm from the replacement position back onto the rear window.

#### Mirrors

# Operating the outside mirrors

WARNING Risk of accident due to adjusting the vehicle settings while the vehicle is in motion

You could lose control of the vehicle in the following situations in particular:


- If you adjust the driver's seat, the head restraint, the steering wheel or the mirror while the vehicle is in motion
- If you fasten your seat belt while the vehicle is in motion
- ▶ Before starting the vehicle: in particular, adjust the driver's seat, head restraint, steering wheel and mirror, and fasten vour seat belt.

WARNING Risk of accident due to misjudgment of distance when using the front-passenger mirror

The outside mirror on the front passenger side reflects objects on a smaller scale. The objects in view are in fact closer than they appear.

Therefore, always look over your shoulder to check the actual distance between you and the road users traveling behind you.

# Folding the outside mirrors in/out



- ▶ Briefly press button ②.
- (i) If the battery has been disconnected or has discharged, the outside mirrors must be moved briefly using button 2. Only then will the automatic mirror folding function work properly.

 Mercedes-Maybach vehicles: if the extendable running boards are extended, they will retract when the outside mirrors fold in.

#### Adjusting the outside mirrors

- Press button or to select the outside mirror to be adjusted.
- Use button @ to adjust the position of the mirror glass.

#### Engaging the outside mirrors

If an outside mirror has been forcibly disengaged, proceed as follows.

- Vehicles without electrically folding outside mirrors: manually move the outside mirror into the correct position.
- Vehicles with electrically folding outside mirrors: press and hold button ②.
  You will hear a click and the mirror will audibly click into place. The outside mirror will now be set to the correct position.

### Automatic anti-glare mirrors function

A

**WARNING** Risk of acid burns and poisoning due to the anti-glare mirror electrolyte

Electrolyte may escape if the glass in an automatic anti-glare mirror breaks.

The electrolyte is hazardous to health and causes irritation. It must not come into contact with your skin, eyes, respiratory organs or clothing or be swallowed.

- If you come into contact with electrolyte, observe the following:
  - Immediately rinse the electrolyte from your skin with water and seek medical attention.
  - If electrolyte comes into contact with your eyes, immediately rinse them thoroughly with clean water and seek medical attention.
  - If the electrolyte is swallowed, immediately rinse your mouth out thoroughly. Do not induce vomiting. Seek medical attention immediately.

- Immediately change out of clothing which has been contaminated with electrolyte.
- If an allergic reaction occurs, seek medical attention immediately.

The inside rearview mirror and the outside mirror on the driver's side will automatically go into antiglare mode if light from a headlamp hits the sensor on the inside rearview mirror.

#### System limits

The system will not go into anti-glare mode if:

- The vehicle is switched off.
- · Reverse gear is engaged.
- · The interior lighting is switched on.

# Front-passenger outside mirror parking position function

i The parking position is available only in vehicles with a memory function.

The parking position makes parking easier.

In the following situations, the front-passenger outside mirror will swivel downwards in the direction of the rear wheel on the front passenger's side:


- The parking position is stored ( $\rightarrow$  page 165)
- The front-passenger mirror is selected
- · Reverse gear is engaged.

The front-passenger outside mirror will move back to its original position in the following situations:

- You shift the transmission to another transmission position
- You are traveling at speeds greater than 9 mph (15 km/h)
- You press the button for the outside mirror on the driver's side

#### Storing and calling up the parking position of the front-passenger outside mirror

#### Storing



- Select the front-passenger outside mirror using button 1.
- Engage reverse gear.
- Move the front-passenger outside mirror into the desired parking position using button 2.

#### Calling up


- Select the front-passenger outside mirror using button 1.
- Engage reverse gear. The front-passenger outside mirror will move into the stored parking position.

# Activating/deactivating the automatic mirror folding function

Multimedia system:

- → Settings → Vehicle
- Activate or deactivate Automatic Folding.

# Area permeable to radio waves on the windshield



Radio-controlled equipment such as toll systems can be mounted only on areas 
one of the windshield that are permeable to radio waves.

Areas permeable to radio waves 
 are best visible from outside the vehicle when the windshield is illuminated with an external light source.

Note this position for vehicles with:

· Infra-red reflective windshield

#### Infrared-reflective windshield function

The infrared-reflective windshield is coated and reduces the build-up of heat in the vehicle interior.

The coating shields the vehicle interior from radio waves.


# Overview of climate control systems

#### Notes on climate control

An interior air filter in combination with the prefilter in the engine compartment must always be used so that the air conditioning system, pollution level monitoring and the air filtration work correctly. Use filters recommended and approved by Mercedes-Benz. Always have maintenance work carried out at a qualified specialist workshop.

# Overview of the air conditioning control panel

The indicator lamps on the buttons indicate that the corresponding function is activated.



Control panel for 3-zone automatic climate control with stationary heater (example)

- Sets the temperature on the driver's side
- 2 Lalls up the air conditioning menu
- Sets the airflow or switches off climate control
- AUTO Sets climate control to automatic mode  $(\rightarrow page 169)$
- Defrosts the windshield
- Switches the rear window heater on/off
- Switches air-recirculation mode on/off  $(\rightarrow page 170)$

- A/C Switches the A/C function on/off  $(\rightarrow page 168)$ Switches residual heat on/off  $(\rightarrow page 170, 171)$
- Vehicles with control panel for dual-zone or 3zone automatic climate control with stationary heater: switches stationary heater on/off

Vehicles with control panel for dual-zone or 3zone automatic climate control without stationary heater: **SYNC** switches synchronization on/off ( $\rightarrow$  page 170)

- ▼ ▲ Sets the temperature on the front passenger side
- (i) Dual-zone automatic climate control equipment is available for all vehicles except Mercedes-Maybach vehicles.

#### 168 Climate control

# Overview of the rear passenger compartment operating unit



Example: USA

- Sets the temperature, left
- Sets the air distribution, left
- Sets climate control to automatic mode (→ page 169)
- Setting the airflow
- Switches climate control on/off (→ page 168)

Switching residual heat on/off( $\rightarrow$  page 171)

- Sets the air distribution, right
- Sets the temperature, right

The settings for the second and third row of seats (equipment-dependent) can be made via the rear passenger compartment operating unit, the multimedia system ( $\rightarrow$  page 169) or the MBUX rear passenger compartment tablet depending on the vehicle's equipment.

# Operating the climate control system

Switching climate control on/off

- ► To switch on: set the airflow to level 1 or higher using the \[ \] button.
- To switch off: set the airflow to level 0 using the 1921 button.

If climate control is switched off, the windows may fog up more quickly. Switch climate control off only briefly.

# Switching the climate control in the rear passenger compartment on/off

Press button 6.

(i) When climate control in the second seat row is switched off, the indicator lamp is activated and **OFF** is shown on the rear display.

# Switching the A/C function on/off using the air conditioning control panel

The A/C function heats, cools and dehumidifies the vehicle's interior air.

Press the A/C button.

Switch off the A/C function only briefly; otherwise, the windows may fog up more quickly.

Condensation may drip from the underside of the vehicle when cooling mode is active. This is not indicative of a malfunction.

#### Calling up the air conditioning menu

# Calling up the air conditioning menu using the multimedia system

Select one of the temperature displays at the lower edge of the media display.

### Activating/deactivating the A/C function via the multimedia system

Multimedia system:

#### → Climate Menu ➤ First Row of Seats

The A/C function heats, cools and dehumidifies the vehicle's interior air

Select A/C.

#### Sets climate control to automatic mode

In automatic mode, the set temperature is controlled and maintained at a constant level by the air supply.

- Press button AUTO .
- To switch to manual mode: press the аuто button.

In automatic mode, you can choose between five different air quantities using the button. Automatic mode is retained.

#### Automatically controlling the climate control in the rear passenger compartment

In automatic mode, the set temperature is regulated by the temperature of the dispensed air and the airflow.

Press button AUTO .

#### Setting the air distribution

Multimedia system:

#### Climate Menu

- ► Call up the air conditioning menu  $(\rightarrow page 168)$ .
- Select a row of seats.
- To set the air distribution: select الهجارة المجادة ا or **1,0** .
- Set the airflow.
- Several air distributions can be selected at the same time, e.g. to air-condition both the windshield and the footwell.

The climate control for the windshield can only be selected for the first seat row.

### Setting the climate control for the rear passenger compartment (multimedia system)

Multimedia system:

→ Climate Menu >> Second Row of Seats

#### Setting the temperature

- Select Second Row of Seats or Third Row of Seats.
- (i) Maybach vehicles are equipped with only the first and second seat rows.
- Set the temperature.

#### Setting the airflow

- Select Second Row of Seats or Third Row of Seats.
- (i) Maybach vehicles are equipped with only the first and second seat rows
- Set the airflow.

# Automatic regulation of the rear climate control

Select REAR AUTO.

The rear climate control is regulated automatically.

#### 170 Climate control

### Deactivating rear climate control

► Select REAR OFF.

The rear climate control is deactivated.

# Switching the synchronization function on/off via the air conditioning control panel

#### Requirements

 The vehicle is not fitted with a stationary heater.

Climate control can be set centrally using the synchronization function. The temperature and air distribution setting for the driver's side will be adopted automatically for all climate control zones.

Press the **SYNC** button.

The synchronization function will be deactivated if the settings for one of the other climate zones are changed.

# Switching the synchronization function on/off via the multimedia system

Multimedia system:

#### → Climate Menu → First Row of Seats

Climate control can be set centrally using the synchronization function. The driver's settings for temperature, air quantity and air distribution will be adopted automatically for all climate zones.

Select SYNC and switch it on or off.

#### Defrosting the windows

#### Windows fogged up on the inside

- Press the AUTO button.
- If the windows remain fogged up: press the windows remain fogged up: press

# Windows fogged up on the outside

- Switch on the windshield wipers.
- Press the AUTO button.

#### Switching air-recirculation mode on/off

Press the button.
The interior air will be recirculated.

Air-recirculation mode automatically switches to fresh air mode after a while.

(i) If air-recirculation mode is switched on, the windows may fog up more quickly. Switch on air-recirculation mode only briefly.

# Switching the residual heat on or off

#### Requirements:

• The vehicle is parked.

It is possible to make use of the residual heat from the engine to continue heating or ventilating the front compartment of the vehicle for approximately 30 minutes, depending on the temperature set.

► To activate: press A/C button.

Residual heat will be switched off automatically.

### Switching the residual heat in the rear passenger compartment on/off

#### Requirements

• The vehicle is parked.

When the residual heat of the engine is activated in the rear passenger compartment, you can heat or ventilate the rear passenger compartment for approximately 30 minutes.

 $\triangleright$  Press button (5) ( $\rightarrow$  page 168).

### Activating/deactivating ionization

Multimedia system:

#### → Climate Menu >> Air Quality

Ionization improves the quality of the vehicle's interior air. Ionization of the interior air is odorless.

select IONIZATION and activate or deactivate the function.

#### Fragrance system

Setting the fragrance system

#### Requirements

- Automatic climate control is activated.
- · The glove box will close.

Multimedia system:

¬→ Climate Menu → Air Quality

The fragrance system distributes a pleasant fragrance throughout the vehicle interior from a flacon located in the glove box.

- Select AIR FRESHENER.
- Keep pressing until the desired intensity is reached.
- Inserting or removing the flacon of the fragrance system

WARNING Risk of injury from liquid perfume

If children open the flacon, they could drink the liquid perfume or it could come into contact with their eyes.

- Do not leave children unattended in the vehicle
- Consult a doctor immediately if liquid perfume has been drunk.
- If liquid perfume comes into contact with your eyes or skin, rinse your eyes with clean water.
- If symptoms continue, consult a doctor.



**ENVIRONMENTAL NOTE** Environmental damage due to improper disposal of full flacons




Full flacons must not be disposed of together with household waste.



Hand in full flacons at a pollutant collection point.

#### 172 Climate control



- Cap
- Flacon
- To insert: slide the flacon into the holder as far as it will go.
- To remove: after opening the glove compartment, wait for approximately seven seconds and pull out the flacon.

If you do not use genuine Mercedes-Benz interior perfumes, observe the manufacturers' safety notices on the perfume packaging.

Dispose of the genuine Mercedes-Benz interior perfume flacon when it is empty and do not refill it.

#### Refillable flacon

- Unscrew the cap of the empty flacon.
- Fill the flacon with a maximum of 0.5 fl. oz. (15 ml).
- Screw the cap back onto the flacon.

Always refill the empty refillable flacon with the same perfume. Observe the separate information sheet that comes with the flacon.

#### Air vents

Adjusting the front air vents




**WARNING** Risk of burns or frostbite due to being too close to the air vents

Very hot or very cold air can flow from the air vents.

- Make sure that all vehicle occupants always maintain a sufficient distance from the air vents.
- If necessary, direct the airflow to another area of the vehicle interior.

To guarantee the flow of fresh air through the air vents into the vehicle interior, note the following:

- Always keep the vents and ventilation grilles in the vehicle interior clear.
- Keep the air inlet free of residue build-up (→ page 344).
- Optimum climate comfort is achieved with the air vents in the center position.




- To open or close center air vents: turn controller 2 up or down as far as it will go.
- To open or close side air vents: turn controller 2 to the left or right as far as it will go.
- To adjust the air direction: hold air vent 1 in the center and move it up or down or to the left or right.


#### Adjusting the rear passenger compartment air vents



Air vents in the center console




Air vents in the B-pillar



Air vents above the second and third rows of seats (all vehicles except Mercedes-Maybach vehicles)

- To set the airflow direction: hold the center of air vent 1 and move it accordingly.
- ► To open or close: turn controller ② as far as it will go.

#### 174 Climate control



Air vents above the second row of seats, towards the cargo compartment (Mercedes-Maybach vehicles)

To open or close: turn controller as far as it will go.


# Opening or closing the air vent in the glove box

! NOTE Damage to temperature-sensitive objects in the glove box

Temperature-sensitive objects stored in the glove box may be damaged by the air vent located inside it.

- Close the air vent when you heat the vehicle.
- At high outside temperatures, open the air vent and switch on the A/C function.

The automatic climate control must be switched on to cool the glove box.



- To open or close: turn controller of air vent
  - 2 clockwise or counter-clockwise.

# Driving

#### Notes on Mercedes-AMG vehicles

Observe the notes on the following topics in the Supplement, otherwise you may fail to recognize dangers.

- (i) The availability of certain functions depends on the equipment and model of the vehicle.
- Emotion Start
- AMG performance exhaust system
- AMG ceramic high-performance composite brake system
- AMG RIDE CONTROL +
- AMG ACTIVE RIDE CONTROL
- · AMG steering-wheel buttons

# Switching on the power supply or the vehicle

WARNING Risk of accident and injury due to children left unattended in the vehicle

If you leave children unattended in the vehicle. they could, in particular:


- open doors, thereby endangering other persons or road users.
- get out and be struck by oncoming traffic.
- operate vehicle equipment and become trapped, for example.

In addition, the children could also set the vehicle in motion by, for example:

- · releasing the parking brake.
- changing the gearbox position.
- starting the vehicle.
- Never leave children unattended in the vehicle.
- When leaving the vehicle, always take the key with you and lock the vehicle.
- Keep the key out of reach of children.

#### Requirements

- The key is in the vehicle and is recognized.
- The brake pedal is not depressed.



To switch on the power supply: press button once.

You can, for example, switch on the windshield wipers.

#### 176 Driving and parking

The power supply will be switched off again if the following conditions are met:

- You open the driver's door.
- You press button (1) twice more.
- To switch on the vehicle: press button twice.
  Indicator and warning lamps will light up of

Indicator and warning lamps will light up on the instrument display.

The vehicle will be switched off again if one of the following conditions is met:

- You do not start the vehicle within 15 minutes and the transmission is in position P or the electric parking brake is applied.
- You press button ① once.

# Starting the vehicle

Starting the vehicle with the start/stop button



**DANGER** Risk of death caused by exhaust gases

Combustion engines emit poisonous exhaust gases such as carbon monoxide. Inhaling these exhaust gases is hazardous to health and leads to poisoning.

Never leave the engine or, if present, the auxiliary heating running in an enclosed space without sufficient ventilation.



WARNING Risk of fire due to flammable materials in the engine compartment or on the exhaust system

Flammable materials may ignite.

 Therefore, regularly check that there are no flammable foreign materials in the engine compartment or on the exhaust system.


#### Requirements

- The key is in the vehicle and is recognized.
- Shift the transmission to position [P] or [N].
- Depress the brake pedal and press button once.
- If the vehicle does not start: switch off nonessential consumer equipment and press button ⊕ once.
- If the vehicle still does not start and the Place the Key in the Marked Space See Operator's Manual display message appears on the instrument display: start the vehicle with the key in the marked space (emergency operation mode) (→ page 177).
- (i) You can switch off the vehicle while driving. To do this, press and hold button (i) for about three seconds or press button (ii) three times within three seconds. Be sure to observe the safety notes concerning this under "Driving tips" (→ page 180).

Observe any information regarding display messages that may be shown on the instrument display.

# Starting the vehicle with the key in the marked space (emergency operation mode)

If the vehicle does not start and the Place the Key in the Marked Space See Operator's Manual message appears on the Instrument display, you can start the vehicle in emergency mode.



- Make sure that marked space (2) is empty.
- Remove key (1) from the key ring.

▶ Place key ① in marked space ② next to symbol 3.

The vehicle will start after a short time

If you remove key 1 from marked space 2, the vehicle can still be driven. For further engine starts, however, key 10 must be located in marked space 2 next to symbol 3 during the entire journey.

Have key (1) checked at a qualified specialist workshop.

#### If the vehicle does not start:

- Place key 1 in marked space 2 and leave it there.
- Depress the brake pedal and start the vehicle using the start/stop button.
- (i) You can switch on the power supply or the vehicle with the start/stop button.

Observe any information regarding display messages that may be shown on the Instrument display.

# Starting the vehicle via Remote Online Services

# Cooling or heating the vehicle interior before starting the journey

Ensure the following before starting the engine:

- The legal stipulations in the area where your vehicle is parked allow engine starting via smartphone.
- It is safe to start and run the engine where your vehicle is parked.
- . The fuel tank is sufficiently full.
- The starter battery is sufficiently charged.

# Charging the starter battery before starting the journey

You can receive a message on your smartphone when the state of charge of the starter battery is low. You can then start the vehicle with the smartphone to charge the battery. The vehicle is automatically switched off after ten minutes.

Ensure the following before starting the engine:

• The legal stipulations in the area where your vehicle is parked allow engine starting via smartphone.

#### 178 Driving and parking

- It is safe to start and run the engine where your vehicle is parked.
- The fuel tank is sufficiently full.

# Starting the vehicle (Remote Online)

**WARNING** Risk of crushing or entrapment due to unintentional starting of the engine

Limbs could be crushed or trapped if the engine is started unintentionally during service or maintenance work.

Always secure the engine against unintentional starting before carrying out maintenance or repair work.

#### Requirements

- Park position P is selected.
- The anti-theft alarm system is not activated.
- The panic alarm is not activated.
- The hazard warning light system is switched off.
- · The hood is closed.
- · The doors are closed and locked.

- The windows and sliding sunroof are closed.
- Start the vehicle using the smartphone. After every engine start, the engine runs for ten minutes.

You can carry out a maximum of two consecutive starting attempts. You must start the engine with the key before trying to start the vehicle again with the smartphone.

You can switch off the vehicle at any time as follows:

- Via the smartphone app
- By pressing the ⊕ or ⊕ button on the key
- (i) Further information can be found in the smartphone app.

# Securing the vehicle against starting before carrying out maintenance or repair work:

- Switch on the hazard warning light system or unlock the doors.
- Open a side window or the sliding sunroof.

### Notes on breaking-in a new vehicle

To preserve the engine during the first 1000 miles (1500 km):

- Drive at varying road speeds and engine speeds.
- No faster than 85 mph (140 km/h).
- Drive the vehicle in drive program c or E.
- Shift to the next gear up when the needle reaches the last third before the red range on the tachometer at the very latest.
- Do not shift down manually to brake.
- Avoid overstraining the vehicle, e.g. driving at full throttle.
- Do not depress the accelerator pedal past the point of resistance (kickdown).
- Increase the engine speed only gradually and accelerate the vehicle to full speed only after 1000 miles (1500 km).

This also applies when the engine or parts of the drivetrain have been replaced.

Please also observe the following breaking-in notes:

- With certain handling and driving safety systems, the sensors will adjust automatically while a certain distance is being driven after the vehicle has been delivered or after repairs. Full system effectiveness will be reached only once this teach-in process has concluded.
- Brake pads, brake disks and tires that are either new or have been replaced will achieve optimum braking performance and grip only after several hundred kilometers of driving. Compensate for the reduced braking effect by applying greater force to the brake pedal.

# Notes on optimizing acceleration

If all necessary requirements and activation conditions are fulfilled, the best possible acceleration can be achieved from a standstill.

Do not use optimized acceleration on public roads. Individual wheels could spin and you could lose control of the vehicle. There is an increased risk of skidding and/or accident.

Be sure to observe the safety notes and information on ESP® ( $\rightarrow$  page 214).

# Pulling away with optimized acceleration

WARNING Risk of skidding and accidents due to the wheels spinning

If you pull away using optimized acceleration, individual wheels can spin and the vehicle can skid.

There is an increased risk of skidding and accidents, especially when ESP® is switched

Make sure that there are no persons or obstacles in the vicinity of the vehicle.

# Requirements

- the vehicle is run in ( $\rightarrow$  page 178).
- the vehicle and tires are in good condition.
- the roadway has a high-grip surface.
- · the engine and transmission are at normal operating temperature.

NOTE Increased wear due to optimized acceleration

When pulling away with optimized acceleration, all components of the drivetrain are subiected to a very high load.

This can lead to increased component wear.

- Do not always pull away with optimized acceleration.
- Engage the  $\boxed{\mathbf{p}}$  drive position ( $\rightarrow$  page 196).
- Move the steering wheel to the straight-ahead position.
- Select the  $\square$  drive program ( $\rightarrow$  page 192).
- Deactivating ESP<sup>®</sup> ( $\rightarrow$  page 216).
- Depress and hold the brake pedal firmly with your left foot.
- With your right foot, fully depress the accelerator pedal.

- After no more than five seconds, take your left foot quickly off the brake, but keep the accelerator pedal depressed.
  - The vehicle will pull away at maximum acceleration.
- Switch on ESP® once the acceleration procedure is complete.

#### Ending optimized acceleration

- Remove your foot from the accelerator pedal.
- Reactivate ESP®.
- After you pull away with optimized acceleration, components of the drivetrain can become very hot, which means that optimized acceleration values may only be reached again after a few minutes.

# Notes on driving

A W

**WARNING** Risk of accident due to objects in the driver's footwell

Objects in the driver's footwell may impede pedal travel or block a depressed pedal.

This jeopardizes the operating and road safety of the vehicle.

- Stow all objects in the vehicle securely so that they cannot get into the driver's footwell.
- Always install the floor mats securely and as prescribed in order to ensure that there is always sufficient room for the pedals.
- Do not use loose floor mats and do not place floor mats on top of one another.

A

**WARNING** Risk of accident due to incorrect footwear

Incorrect footwear includes, for example:

- Shoes with platform soles
- · Shoes with high heels
- Slippers

There is a risk of an accident.

Always wear suitable footwear so that you can operate the pedals safely. **WARNING** Risk of accident if the vehicle is switched off while driving

If you switch off the vehicle while driving, safety functions are restricted or no longer available.

This may affect the power steering system and the brake force boosting, for example.

You will need to use considerably more force to steer and brake, for example.

Do not switch off the vehicle while driving.

**DANGER** Risk of death caused by exhaust gases

Combustion engines emit poisonous exhaust gases such as carbon monoxide. Inhaling these exhaust gases is hazardous to health and leads to poisoning.

Never leave the engine or, if present, the auxiliary heating running in an enclosed space without sufficient ventilation. WARNING Risk of skidding and of an accident due to shifting down on slippery road surfaces

If you shift down on slippery road surfaces to increase the engine braking effect, the drive wheels may lose traction.

- Do not shift down on slippery road surfaces to increase the engine braking effect.
- **DANGER** Risk of fatal injury due to poisonous exhaust gases

If the tailpipe is blocked or sufficient ventilation is not possible, poisonous exhaust gases such as carbon monoxide may enter the vehicle. This is the case, for example, if the vehicle gets stuck in the snow.

Keep the tailpipe and the area around the vehicle free from snow when the engine or the stationary heater is running.

Open a window on the side of the vehicle facing away from the wind to ensure an adequate supply of fresh air.

WARNING Risk of accident and injury due to being under the influence of alcohol and drugs while driving

Drinking and driving and/or taking drugs and driving are very dangerous combinations. Even a small amount of alcohol or drugs can affect your reflexes, perceptions and judgment.

The possibility of a serious or even fatal accident are greatly increased when you drink or take drugs and drive.

- Do not drink or take drugs and drive or allow anyone to drive who has been drinking or taking drugs.
- WARNING Risk of accident due to the brake system overheating

If you leave your foot on the brake pedal when driving, the brake system may overheat.

This increases the braking distance and the brake system can even fail.

- Never use the brake pedal as a footrest.
- Do not depress the brake pedal and the accelerator pedal at the same time while driving.
- **NOTE** Engine damage due to excessively high engine speeds

The engine will be damaged if you drive with the engine in the overrevving range.

- Do not drive with the engine in the overrevving range.
- **NOTE** Wearing out the brake linings by continuously depressing the brake pedal
  - Do not depress the brake pedal continuously whilst driving.
- To use the braking effect of the engine, shift to a lower gear in good time.

- ! NOTE Damage to the drivetrain and engine when pulling away
- Do not warm up the engine while the vehicle is stationary. Pull away immediately.
- Avoid high engine speeds and driving at full throttle until the engine has reached its operating temperature.
- ! NOTE Damage to the catalytic converter due to non-combusted fuel

The engine is not running smoothly and is misfiring.

Non-combusted fuel may get into the catalytic converter.

- Only depress the accelerator pedal slightly.
- Have the cause rectified immediately at a qualified specialist workshop.

NOTE Reduced battery life due to frequent short-distance trips

The 12 V battery may not be sufficiently charged when the vehicle is used only for short-distance trips. This reduces the life of the battery.

- Drive longer distances regularly to charge the battery.
- NOTE Damage to the vehicle due to not observing the maximum permitted headroom clearance

If the vehicle height is greater than the maximum permitted headroom clearance, the roof and other parts of the vehicle may be damaged.

- Observe the signposted headroom clearance.
- If the vehicle height is greater than the permitted headroom clearance, do not enter.

- Observe the changed vehicle height with add-on roof equipment.
- (i) Please bear in mind that all the speed values stated in this Operator's Manual are approximate and are subject to a certain tolerance.

# Notes on driving with a roof load, trailer or fully laden vehicle

When driving with a loaded roof luggage rack or trailer as well as with a fully laden or fully occupied vehicle, the vehicle's driving and steering characteristics change.

You should therefore bear the following in mind:

- Do not exceed the permissible roof load and towing capacity. Also observe the information in the Technical Data.
- Distribute the roof load and the load inside the vehicle evenly, placing heavy objects at the bottom. Also comply with the notes on loading the vehicle (→ page 126).
- Drive attentively, and avoid abrupt starts, braking and steering as well as rapid cornering.

### Advice on driving on salt-strewn roads

The braking effect is limited on salt-strewn road surfaces

Therefore, observe the following notes:

- Due to salt build-up on the brake disks and brake pads, the braking distance can increase considerably or result in one-sided braking.
- Maintain a much greater safety distance to the vehicle traveling in front.

Remove salt build-up as follows:

- Brake occasionally, paying attention to the traffic conditions
- Carefully depress the brake pedal at the end of the journey and when starting the next journev

#### Notes on hydroplaning

Hydroplaning can take place if a certain depth of water has built up on the road surface.

Observe the following notes during heavy precipitation or in conditions in which hydroplaning may occur:

Reduce speed

- Avoid tire ruts
- · Avoid sudden steering movements
- Brake carefully
- (i) Also observe the notes on regularly checking wheels and tires ( $\rightarrow$  page 375).

# Notes on driving through water on the road

Water ingress can damage the engine, electrics and transmission

Water can also enter the air intake of the engine and cause engine damage.

Observe the following if you have to drive through water:

- Observe the maximum permissible depth for driving through water ( $\rightarrow$  page 423).
- Drive at a walking pace at most; water can otherwise enter the vehicle interior or engine compartment.
- Vehicles traveling in front, or oncoming vehicles, can create waves which may exceed the maximum permissible depth of water.

The braking effect of the brakes is reduced after fording. Brake carefully, paying attention to the

traffic conditions until braking power has been fully restored.

#### Notes on off-road driving

WARNING Risk of accident if you do not keep to line of fall on inclines

If you drive at an angle or turn on an incline. the vehicle could slip sideways, tip and rollover.

Always drive on inclines in the line of fall (straight up or down) and do not turn.

WARNING Risk of fire caused by flammable material on hot exhaust system components

Flammable material such as leaves, grass or twigs may ignite if they come into contact with hot parts of the exhaust system.

When driving on an unpaved road or offroad, check the vehicle underside regularly.

- In particular, remove trapped plant parts or other flammable material.
- If there is damage, consult a qualified specialist workshop immediately.

When driving off-road, sand, mud and water etc., also mixed with oil, may get into the brakes. This may lead to a reduction in braking effect or even a total brake failure as a result of increased wear. The braking characteristics will vary depending on the material that has entered the system. Clean the brakes after driving off-road. If you then notice reduced braking effect or hear scraping noises, have the brake system checked at a qualified specialist workshop. Adapt your driving style to the changed braking characteristics.

! NOTE Damage caused by driving over obstacles

The vehicle can be damaged by:

- Driving onto high curbs or unpaved roads.
- Quickly driving over obstacles such as curbs, speed bumps or potholes.

- Heavy objects hitting the underbody or chassis components.
- Do not drive over obstacles that could damage the vehicle.
- Check the vehicle regularly for damage during off-road driving.
- Adjust the vehicle speed to suit the road surface conditions.
- If there is damage, consult a qualified specialist workshop immediately.
- ENVIRONMENTAL NOTE Environmental damage due to non-observance of prohibition signs

Environmental protection has priority. Treat nature with respect.

Be sure to observe prohibition signs.

### Checklist before driving off-road

Check the following points before driving off-road:

Fuel level

- Engine oil level: fill engine oil to the maximum level to ensure full gradeability (→ page 340)
- Tire-change tool kit and spare wheel
- Tires and wheels
- Further information about special all-terrain tires for retrofitting can be obtained from a qualified specialist workshop.

# Off-road driving

Read this section before driving your vehicle offroad. Practice by driving over gentler off-road terrain first.

- Observe the notes on the off-road ABS (→ page 213).
- Before driving off-road, shift the transfer case to the LOW RANGE off-road gear (vehicles with Off-road package) (→ page 200).
- Select a vehicle level suitable for off-road terrain (→ page 248). To avoid damaging the

vehicle, make sure there is always sufficient ground clearance.

- Always keep the engine running and the vehicle in gear when driving on inclines and slopes. Observe the notes on driving in mountainous terrain.
- Do not drive on unknown terrain that is not easily visible and stay on marked paths.
- · Always keep the doors and windows closed while the vehicle is in motion.
- Deactivate Active Distance Assist DISTRONIC and cruise control
- Adapt your driving style to the terrain.
- Do not use the HOLD function on steep downhill or uphill gradients with slippery or loose surfaces

# Driving on sand

When driving on sand, also observe the following instructions:

- Select the arive program.
- · Select a higher vehicle level.
- · Shift to a lower gear.

- Drive quickly to overcome the rolling resistance; the vehicle may otherwise dig itself in.
- Drive in the tracks of other vehicles if possible. Make sure that the following prerequisites are met:
  - the tire ruts are not too deep.
  - the sand is firm enough.
  - there is sufficient ground clearance.

#### Fording

Also observe the following information when fording:

- Vehicles with AIRMATIC: select the highest possible vehicle level ( $\rightarrow$  page 248).
- Vehicles with F-ACTIVE BODY CONTROL: select the highest possible vehicle level  $(\rightarrow page 257)$ .
- Drive no faster than 6 mph (10 km/h).
- Observe the maximum permissible fording depth ( $\rightarrow$  page 423).
- Switch off automatic climate control  $(\rightarrow page 169)$ .

- Ensure that a bow wave does not form as you drive
- Do not stop in the water and do not switch off the engine. Ensure the ECO start/stop function is switched off ( $\rightarrow$  page 187).

#### Driving in mountainous terrain

Also observe the following information when driving in mountainous terrain:

- Observe the values of the approach/departure angle and the maximum gradient-climbing ability ( $\rightarrow$  page 423).
- · Avoid high engine speeds.
- Use the braking power of the engine when driving downhill.
- Shift to a lower gear on uphill gradients and on long, steep downhill gradients.
- Activate DSR before driving downhill, if necessary ( $\rightarrow$  page 229).

# Check-list after driving off-road

Driving off-road places greater demands on your vehicle than driving on normal roads. Check the entire vehicle for damage and foreign bodies

every time after driving off-road. Foreign bodies in the wheels or drivetrain can lead to imbalances and therefore vibrations

- If the or or driving mode is selected: select another driving mode.
- Shift the transfer case to the on-road position HIGH RANGE.
- Deactivate DSR.
- Lower the vehicle level again to a level suitable for the road conditions, e.g. to the normal level
- · Apply the brakes to dry them after fording.
- Check that the service brake is working normally after a long downhill stretch.
- Clean the following components every time after driving off-road:
  - license plate number
  - headlamps and tail lamps
  - tires, wheels and wheel arches
  - underbody

- After driving through sand, mud, water or gravel, have the following components checked and cleaned:
  - brake disks and brake pads
  - tires and wheels
  - axle joints

# ECO start/stop function

# ■ ECO start/stop function

i Depending on the engine, the ECO start/stop function is not available in all drive programs. Observe the status display on the instrument display concerning this.

**Mercedes-Maybach vehicles:** the glide mode function is not available.

The engine will be switched off automatically in the following situations if all vehicle conditions for an automatic engine stop are met:

You brake the vehicle to a standstill in transmission position D or N.

 Vehicles with a 48 V on-board electrical system: you depress the brake pedal when traveling at a low speed.

If the system has detected one of the following situations, the engine will not stop:

- You stop at a stop sign and there is no vehicle in front of you.
- The vehicle that stopped in front of you starts up again.
- You maneuver, turn the steering wheel sharply or engage reverse gear.
- (i) If the system detects an intelligent stop inhibitor, e.g. a stop sign, the engine will not stop. If you activate the HOLD function or engage the park position P, the engine can be switched off in spite of an intelligent stop inhibitor.

The engine will restart automatically in the following cases:

- You engage transmission position **D** or **R**.
- You depress the accelerator pedal.

- The vehicle requires an automatic engine start.
- You release the brake pedal.
- Vehicles with a 48 V on-board electrical system:
  - You release the brake pedal on a downhill gradient and the vehicle does not roll.
  - The vehicle rolls on a downhill gradient and does not automatically enter glide mode at 15 mph (20 km/h).

ECO start/stop function symbols on the instrument display:

- The A symbol (green) appears when the vehicle is at a standstill: the engine was switched off by the ECO start/stop function.
- The symbol (yellow) appears when the vehicle is at a standstill: not all vehicle conditions for an engine stop have been met.
- Neither the A symbol nor the A symbol appears when the vehicle is at a standstill: an intelligent stop inhibitor, e.g. a stop sign, has been detected.


• The symbol appears: the ECO start/stop function is deactivated or there is a malfunction.

If the engine was switched off by the ECO start/ stop function and you leave the vehicle, a warning tone will sound and the engine will not be restarted. In addition, the following display message will appear on the instrument display:

# Vehicle Ready to Drive Switch the Ignition Off **Before Exiting**

If you do not switch off the vehicle, it will automatically be switched off after three minutes.

# Switching the ECO start/stop function on/off



- Press button 1. A display will appear on the Instrument Display when you switch the ECO start/stop function on / off.
- (i) A will be continuously shown on the Instrument Display while the ECO start/stop function is deactivated.

# ECO display function

The ECO display summarizes your driving characteristics from the start of the journey to its completion and assists you in achieving the most economical driving style.

You can influence consumption by doing the following:

- · driving with particular care.
- driving the vehicle in drive program **E**.
- following the gearshift recommendations.



The lettering in the segment will light up brightly, the outer edge will light up and the segment will fill up when the following driving style is adopted:

- 1 Steady speed
- ② Gentle deceleration and rolling
- Moderate acceleration

The lettering in the segment will be gray, the outer edge will be dark and the segment will empty when the following driving style is adopted:

- ① Fluctuations in speed
- ② Heavy braking
- ③ Sporty acceleration

The ECO display will show you when you have driven economically:

- The three segments will fill up completely at the same time
- The edges around all three segments will light up


The additional range achieved as a result of your driving style in comparison with a driver with a very sporty driving style will be shown in the cen-

ter of display **(a)**. The range displayed does not indicate a fixed reduction in consumption.


# ECO Assist function (vehicles with 48 V on-board electrical system)

ECO Assist analyzes data for the vehicle's expected route. This allows the system to optimally adjust the driving style for the route ahead, save fuel and recuperate.

ECO Assist is displayed on the Assistance menu( $\rightarrow$  page 286).



- Event ahead
- Distance display for the event ahead
- "Foot off the accelerator" prompt



Displayable route events (1)

The segments of distance display 2 show the distance to the event ahead as follows:

- A few segments light up: the event ahead is near.
- Many segments light up: the event ahead is further away.

When the vehicle nears the event, ECO Assist will calculate the optimal speed for maximum fuel economy and recuperative energy based on the distance, speed and gradient. The (3) Foot off the Accelerator prompt appears in the instrument display. The first segments in front of the vehicle will turn green. The remaining segments will initially stay white. If you take your foot off the accelerator pedal in good time, the remaining segments on the display will successively turn green until the event shown is reached. The drivetrain will be set for maximum fuel economy. Recuperation will charge the battery. Recuperation will be adapted to the selected drive program.

The event will be shown for a short time after it has been passed. If there is no response to the Section 1 is a second of the Accelerator prompt, the seg-

ments will remain white.

If the event involves a vehicle in front, all segments will immediately turn green once there is a response to the <a> Foot off the Accelerator</a> prompt.

For active ECO Assist in drive program . symbol 3 will appear on the instrument display and on the head-up display beside transmission position **D**. Symbol **3** will also appear when the assistant display is not selected.

If the system does not intervene during the event ahead, nothing will be displayed. The system will be passive.

ECO Assist is active only in drive programs and C.

# System limits

ECO Assist can function even more precisely if the route is adhered to when route guidance is active. The basic function is also available without active route guidance. Not all information and traffic situations can be foreseen. The quality depends on the map data.

ECO Assist is only an aid. The driver is responsible for keeping a safe distance from the vehicle in front, for vehicle speed and for braking in good

time. The driver must be ready to brake at all times, irrespective of whether the system intervenes.

The system may be impaired or may not function in the following situations:

- If visibility is poor, e.g. due to insufficient illumination of the road, highly variable shade conditions, rain, snow, fog or heavy spray.
- If there is glare, e.g. from oncoming traffic, direct sunlight or reflections.
- If there is dirt on the windshield in the area of the multifunction camera or the camera is fogged up, damaged or obscured.
- If road signs are hard to detect, e.g. due to dirt, snow or insufficient lighting, or because they are obscured.
- If the information on the navigation system's digital map is incorrect or out of date.
- If signs are ambiguous, e.g. road signs in roadworks or in adjacent lanes.

#### DYNAMIC SELECT

#### Function of DYNAMIC SELECT

- I NOTE Mercedes-AMG vehicles
- Observe the notes in the Supplement.
   You could otherwise fail to recognize dangers.

DYNAMIC SELECT allows a drive program to be selected quickly according to the current driving situation or the desired vehicle characteristics. You can select from the following drive programs.

(i) Depending on the engine and equipment, the vehicle has different drive programs.

The drive program selected appears on the Instrument Display.

- Individual
- · Individual settings
- S+ Sport+
- Particularly sporty driving

- Emphasizes the vehicle's own oversteering and understeering characteristics for an even more active driving style
- Suitable only for good road conditions, a dry surface and a clear stretch of road

#### s Sport

- Continues to offer stability but with a sporty setup
- Enables a sporty driver to adopt a more active driving style
- Suitable only for good road conditions, a dry surface and a clear stretch of road

#### **C** Comfort

- Comfortable and economical driving
- · Balance between traction and stability
- Recommended for all road conditions

### **c**<sup>®</sup> Maybach

- Available only for Mercedes-Maybach vehicles
- Maximum driving comfort for comfortable and luxurious travel

### E Eco

- Particularly economical driving
- Balance between traction and stability
- Recommended for all road conditions

#### **CV** Curve

- Available only for vehicles with E-ACTIVE BODY CONTROL
- · Comfortable driving with curve tilting function
- Balance between traction and stability
- · Recommended for all road conditions

# Offroad

- · Intervenes later if there is oversteering or understeering, thus improving traction
- · Suitable for easily negotiable off-road terrain, such as dirt tracks, gravel or sandy surfaces
- Not suitable for use on public roads

# ♠ Offroad+

 Available only for vehicles with off-road package

- Intervenes later if there is oversteering or understeering, thus improving traction
- Suitable for difficult terrain, such as steep and/or uneven terrain or for driving on rocky terrain
- Not suitable for use on public roads
- Mercedes-Maybach vehicles: in drive programs and , the extensible running boards remain retracted or retract if they have already been extended.
- Depending on the situation, the cylinder can be briefly deactivated in drive programs and [c], depending on the engine.
- The ESP® settings in drive programs and c are designed for stability. Therefore, choose one of these drive programs especially when transporting roof loads, in trailer operation and when the vehicle is fully loaded or fully occupied.

Depending on the drive program, the following systems will change their characteristics:

- Drive
  - Engine and transmission management

- Active Distance Assist DISTRONIC
- ESP®
- Vehicles with AIRMATIC or F-ACTIVE BODY CONTROL:
  - Suspension setting
  - Vehicle level
- Electric power steering

# Notes on the roof load display

Certain drive programs and ESP® settings are unsuitable for transporting a roof load.


If one of these drive programs is set or selected. the 😽 symbol is shown as a warning. When this symbol is shown, the selected drive program is not suitable for transporting a load on the roof.

The following drive programs are affected:

- Sport drive program
- Sport + drive program
- Individual drive program with the ESP® setting Sport or Sport+

- (i) The symbol is also shown in the following situations:
  - Within the themes if a corresponding drive program is saved
    - For more information on themes see .
  - Within the reset display if the previously active drive program is unsuitable for the transport of a roof load
    - For further information on the reset display, see ( $\rightarrow$  page 192).

# Selecting the drive program



 Push DYNAMIC SELECT switch forwards or backwards.
 The drive program selected will appear on the Instrument Display.

# Configuring DYNAMIC SELECT (multimedia system)

Multimedia system:

→ Settings → Vehicle → DYNAMIC SELECT

# Setting drive program I

- Select Individual Configuration.
- Select and set a category.

### Switching the reset display on or off

Switch Request at Start on or off.

Function on: the next time the vehicle is started a prompt appears asking whether the last active drive program should be restored. If the ECO start/stop function was deactivated, an additional prompt appears asking if the function should remain deactivated.

(i) The prompt only appears if the previously active settings deviate from the standard settings.

**Function off:** the next time the vehicle is started the drive program is set automatically. The

ECO start/stop function is activated automatically.

(i) This function must be activated for each user profile separately. Only when this function is activated will the drive program and ECO start/stop setting for the previous journey be saved for the respective user profile.

### Displaying vehicle data

Multimedia system:



Select Vehicle.

The vehicle data is displayed.

#### Displaying engine data

Multimedia system:

¬→ 🔝 >> Info

Select Engine.

The engine data is displayed.

(i) The actual (maximum) values that can be achieved for engine output and engine torque may deviate from the certified values within

the country-specific guidelines for permissible tolerances (basis: UN-ECE No. 85 or countryspecific guidelines).

Influencing variables that can influence this are, for example:

- Sea level
- Fuel grade
- Outside temperature
- · Operating temperature of the engine
- The values displayed serve only as orientation. The values for engine output and engine torque shown on the media display may deviate from the actual values.

# Calling up the fuel consumption indicator

Multimedia system:

¬→ 🔝 >> Info

Select Consumption.

The current and average fuel consumption will be displayed.

# Displaying the Offroad Score

Multimedia system:

→ Info

Use the Offroad Score only for off-road driving and not on public roads. When choosing the route, take into account the vehicle characteristics, the ground conditions and your driving skills. Do not let the system distract you from what is happening on the route.

Select Offroad Score.

A menu appears. You can start a new trip.

Further functions are available in the lower menu bar:

- Display the current trip via the route symbol.
- Display a list of all notes for the current trip using the list icon.

In the list, a note is displayed with a time stamp, the number of points currently achieved and the note text.

• Display the ranking by clicking on the symbol for the winner's podium.

The ranking list shows the following information:

- Profile name and profile picture (if available)
- The number of points obtained
- Date and time of the completed trip
- The places for gold, silver and bronze

#### Starting or ending a new trip

The "Start new trip" function is available when the vehicle is stationary and the engine is running.

Select Start new trip.

The display "Trip and tips" appears.

The following information is displayed:

- the vehicle inclination in longitudinal direction in percent (%)
- the lateral inclination of the vehicle in degrees (°)
- the currently achieved score for the ongoing trip
- a tip for the upcoming driving maneuver

To stop the display: select End trip. An evaluation of the trip is displayed. It shows the achieved score and a message, for example Great job!.

# Automatic transmission

**DIRECT SELECT lever** 

■ Function of the DIRECT SELECT lever

A

**WARNING** Risk of accident due to incorrect gearshifting

If the engine speed is higher than the idle speed and you engage the transmission position  $\boxed{\mathbf{D}}$  or  $\boxed{\mathbf{R}}$ , the vehicle may accelerate sharply.

If you engage the transmission position
D or R when the vehicle is at a stand-still, always depress the brake pedal firmly and do not accelerate at the same time.

**WARNING** Risk of accident and injury due to children left unattended in the vehicle


If you leave children unattended in the vehicle, they could, in particular:

- open doors, thereby endangering other persons or road users.
- get out and be struck by oncoming traffic.
- operate vehicle equipment and become trapped, for example.

In addition, the children could also set the vehicle in motion by, for example:

- releasing the parking brake.
- changing the gearbox position.
- · starting the vehicle.
- Never leave children unattended in the vehicle.
- When leaving the vehicle, always take the key with you and lock the vehicle.
- Keep the key out of reach of children.

Use the DIRECT SELECT lever to switch the transmission position. The current transmission position will be shown on the instrument display.



- Park position
- Reverse gear
- Neutral
- Drive position

# Engaging reverse gear R

Depress the brake pedal and push the DIRECT SELECT lever upwards past the first point of resistance.

# Engaging neutral N

- Depress the brake pedal and push the DIRECT SELECT lever up or down to the first point of resistance.
- (i) To shift into neutral N with the vehicle switched on, push the selector lever up or down for several seconds to the first point of resistance.

Subsequently releasing the brake pedal will allow you to move the vehicle freely, e.g. to push it or tow it away.

Proceed as follows if you want the automatic transmission to remain in neutral N even if the vehicle is switched off or the driver's door is opened:

- Depress the brake pedal and engage neutral N when the car is stationary. The N Permanently Active Risk of Rolling Away message will appear on the Instrument Display.
- Release the brake pedal.
- Switch off the vehicle.
- (i) If you then exit the vehicle leaving the key in the vehicle, the automatic transmission remains in neutral N.

The park position P is automatically re-engaged as soon as one of the following conditions is met:

- You switch to transmission position **D** or **R**.
- You press the P button.

# Engaging park position P

! NOTE Damage due to engaging park position P while the vehicle is rolling

If you shift the transmission into park position  $\boxed{\mathbf{P}}$  while the vehicle is rolling, the transmission may be damaged.

- If the vehicle is rolling, do not open a door.
- Only engage park position **P** when the vehicle is stationary.
- Observe the notes on parking the vehicle (→ page 203).
- Depress the brake pedal until the vehicle comes to a standstill.
- When the vehicle is stationary, press button

  P.
  When the transmission position display shows

When the transmission position display shows  $\boxed{\mathbf{P}}$ , the park position is engaged. If the transmission position display  $\boxed{\mathbf{P}}$  does not appear, apply the parking brake and secure the vehicle to prevent it from rolling away.

i Depending on the situation, it may take a short time until P is engaged. Therefore, always pay attention to the transmission position display.

Park position P will be engaged automatically if one of the following conditions is met:

- You switch the stationary vehicle off in transmission position \( \overline{\mathbb{D}} \) or \( \overline{\mathbb{R}} \).
- You open the driver's door when the vehicle is stationary in transmission position D or R.
- When the vehicle is rolling, you switch if off in transmission position D or R and bring it to a standstill.
- When the vehicle is rolling, you shift to transmission position N, bring the vehicle to a standstill and open the driver's door when the vehicle is stationary.
- Engaging park position P automatically is required by the vehicle.
- (i) To maneuver with an open driver's door, open the driver's door while the vehicle is stationary and engage transmission position (D) or (R) again.

# Engaging drive position D

Depress the brake pedal and push the DIRECT SELECT lever down past the first point of resistance.

When the automatic transmission is in transmission position  $\boxed{\textbf{D}}$ , it will shift gears automatically. This depends, among other things, on the following factors:


- · The selected drive program
- The position of the accelerator pedal
- The driving speed

### Manual gearshifting

Permanent setting (vehicles with Off-Road package or E-ACTIVE BODY CONTROL)

- NOTE Mercedes-AMG vehicles
- Observe the notes in the Supplement.
   You could otherwise fail to recognize dangers.

(i) For vehicles without Off-road package or E-ACTIVE BODY CONTROL, activate or deactivate the permanent setting via the multimedia system ( $\rightarrow$  page 197).



To activate/deactivate: pull rocker switch ①. If the indicator lamp is lit, manual shifting is activated. The current gear will be shown on the instrument display.

# Temporary setting



To activate: pull steering wheel paddle shifter ① or ②.

Manual shifting will be activated for a short time. Transmission position M and the current gear will appear on the instrument display.

- To deactivate: pull and hold steering wheel paddle shifter 2.
  - Transmission position **D** will appear on the instrument display.
- To permanently shift the gears manually in drive program using the steering wheel

paddle shifters, select the M setting for the transmission.

#### Shifting

- To shift up: pull steering wheel paddle shifter
- To shift down: pull steering wheel paddle shifter 1.


# Permanently activating or deactivating manual gearshifting

Multimedia system:

- → Settings → Vehicle → Driving
- Permanently switch the function on or off.

#### Gearshift recommendation

The gearshift recommendation assists you in adopting an economical driving style.



If gearshift recommendation appears next to the transmission position display, shift to the recommended gear.

# Using kickdown

Maximum acceleration: depress the accelerator pedal beyond the point of resistance.

To protect against excessively high engine speeds, the automatic transmission will shift up to the next gear when maximum engine speed has been reached.

#### Glide mode function

- ! NOTE Mercedes-AMG vehicles
- Observe the notes in the Supplement. You could otherwise fail to recognize dangers.
- (i) Mercedes-Maybach vehicles: the glide mode function is not available.

With an anticipatory driving style, glide mode helps you to reduce fuel consumption.

Glide mode is characterized by the following:

- The combustion engine is disconnected from the drivetrain and is still running in neutral.
- The transmission position display D is shown in green.
- Vehicles with 48 V on-board electrical system: the combustion engine can be switched off.
   All of the vehicle functions remain active.

Glide mode will be activated if the following conditions are met:

• Drive program **E** is selected.

- The speed is within a suitable range.
- The road's course is suitable, e.g. no steep uphill or downhill gradients or tight bends.
- There is no trailer attached to the trailer hitch, and no bicycle rack installed.
- You do not depress the accelerator or brake pedal (except for light brake applications).
- i Glide mode can also be activated if you have selected the "Eco" setting for the drive in drive program .

Glide mode will be deactivated again if one of the conditions is no longer met.

Glide mode can also be prevented by the following parameters:

- Incline
- · Downhill gradient
- Temperature
- Height
- Speed
- Operating status of the engine
- Traffic situation

#### Transfer case

#### Operation of the transfer case

WARNING Risk of skidding and having an accident when in LOW RANGE on slipperv road surfaces

The wheels can block and thus lose traction on slippery road surfaces, particularly in the following situations:

- if you release the accelerator pedal when the vehicle is in motion
- if off-road ABS intervenes when braking.
- Never select the LOW RANGE off-road gear when driving on slippery road surfaces.

WARNING Risk of accident when the transfer case is in neutral position

The vehicle may roll away unintentionally if you do not wait until the transfer case shift operation is complete.

Wait until the transfer case shift operation is complete.

This function is only available in vehicles with Offroad package.

Shift the transfer case to the on-road position HIGH RANGE or into the LOW RANGE off-road gear.

Do not switch off the engine during shift operation and do not shift the automatic transmission to another position.

# Shift ranges

- HIGH RANGE: Road position for all normal onroad driving situations
- LOW RANGE: Off-road gear for driving offroad, when fording and on steep uphill or downhill inclines

Properties of the LOW RANGE off-road gear:

- reduced maximum permissible speed: 31 mph  $(50 \, \text{km/h})$
- increased tractive power


- changing the transmission ratio by a factor of about three
- · increased drive torque

Do not use LOW RANGE in the following situations:

· when driving on public roads.

# Shifting the transfer case

### Shifting to the LOW RANGE off-road gear



### Requirements

- You are not driving on a paved or public road.
- The vehicle is stationary.

- Pull the **LOW RANGE** ① rocker switch. Indicator lamp ② will flash. The shift request stays active for a maximum of 30 seconds. If all requirements for shift operation are not fulfilled within this time, indicator lamp ② switches off again and the shift operation must be started again.
- Shift the transmission to position N.
  If shift operation is successful, the LOW
  RANGE On message appears in the Instrument Display, an audible signal sounds and indicator lamp and an indicator lamp in the instrument cluster light up continuously.
- ▶ Shift the transmission to position **D**.
- If you switch off the vehicle in LOW RANGE, it remains in LOW RANGE the next time you start the engine.
- You will not be able to switch on LOW RANGE if drive program s or is switched on.

  The vehicle switches to drive program c.

# In the on-road position, shift to HIGH RANGE Requirements

- The vehicle is started and you are not driving faster than 31 mph (50 km/h).
- Pull the LOW RANGE on rocker switch. The shift request stays active for a maximum of 30 seconds. If all requirements for shift operation have not been fulfilled within this time, shift operation must be started again.
- ➤ Shift the transmission to position N.

  If shift operation is successful, the LOW RANGE Off message appears in the Instrument Display, an audible signal sounds and the indicator lamps go out.
- ▶ Shift the transmission to position **D**.

#### Function of 4MATIC

4MATIC ensures that all four wheels are driven. Together with  $\mathsf{ESP}^\$$  and 4ETS, 4MATIC improves the traction of your vehicle whenever a driven wheel spins due to insufficient traction.

If you fail to adapt your driving style, 4MATIC can neither reduce the risk of an accident nor override the laws of physics, 4MATIC cannot take account of road, weather and traffic conditions, 4MATIC is only an aid. You are responsible especially for maintaining a safe distance from the vehicle in front, for vehicle speed, for braking in good time and for staying in lane.

(i) In wintry road conditions, the maximum effect of 4MATIC can be achieved only if you use winter tires (M+S tires), with snow chains if necessary.

# Refueling

Refueling the vehicle

WARNING Risk of fire or explosion from fuel

Fuels are highly flammable.

- Fire, open flames, smoking and creating sparks must be avoided.
- ▶ Before refueling, switch off the vehicle and, if installed, the stationary heater,

and leave them switched off during refueling.

# WARNING Risk of injury from fuels

Fuels are poisonous and hazardous to your health.

- Do not swallow fuel or let it come into contact with skin, eyes or clothing.
- Do not inhale fuel vapor.
- Keep children away from fuel.
- Keep doors and windows closed during the refueling process.

If you or other people come into contact with fuel, observe the following:

- Immediately rinse fuel off your skin with soap and water.
- If fuel comes into contact with your eyes, immediately rinse them thoroughly with clean water. Seek medical attention immediately.

- If you swallow fuel, seek medical attention immediately. Do not induce vomiting.
- Change immediately out of clothing that has come into contact with fuel.

# WARNING Risk of fire and explosion due to electrostatic charge

Electrostatic charge can ignite fuel vapor.

- Before you open the fuel filler cap or take hold of the pump nozzle, touch the metallic vehicle body.
- To avoid creating another electrostatic charge, do not get into the vehicle again during the refueling process.

# NOTE Damage caused by the wrong fuel

Vehicles with a gasoline engine:

Even small amounts of the wrong fuel could result in damage to the fuel system, the engine and the emission control system.

Only refuel with low-sulfur spark-ignition engine fuel.

This fuel may contain up to 10% ethanol. Your vehicle is suitable for use with F10 fuel.

Never refuel with one of the following fuels:

- Diesel
- Gasoline with more than 10% ethanol by volume, e.g. E15, E85, E100
- Gasoline with more than 3% methanol by volume, e.g. M15, M30, M85, M100
- Gasoline with additives containing metal

If you have accidentally refueled with the wrong fuel:

- Do not switch on the vehicle.
- Consult a qualified specialist workshop.

I NOTE Do not use diesel to refuel vehicles with a gasoline engine

If you have accidentally refueled with the wrong fuel:

- Do not switch on the vehicle. Otherwise fuel can enter the engine.
  - Even small amounts of the wrong fuel could result in damage to the fuel system and the engine. The repair costs are high.
- Consult a qualified specialist workshop.
- Have the fuel tank and fuel lines drained completely.
- I NOTE Damage to the fuel system due to overfilling the fuel tank
- Only fill the fuel tank until the pump nozzle switches off.

If too much fuel has been added due, for example, to a faulty filling pump:

Do not switch on the vehicle.


- Consult a qualified specialist workshop.
- NOTE Fuel may spray out when you remove the fuel pump nozzle
- Only fill the fuel tank until the pump nozzle switches off.

#### Requirements

• The vehicle is unlocked.

Observe the notes on service fluids and fuel.

Refuel only using fuel that has at least the octane number specified on the information label on the fuel filler flap. Otherwise, engine output may be reduced and fuel consumption increased.



- Fuel filler flap
- Bracket for fuel filler cap
- Fuel type
- QR code for rescue card
- Tire pressure table
- Press on the rear part of fuel filler flap 1.
- Turn the fuel filler cap counter-clockwise and remove it.

- Insert fuel filler cap from above into bracket
- Completely insert the pump nozzle into the tank filler neck, hook in place and refuel.
- Fill the fuel tank only until the pump nozzle switches off
- Replace the cap on the filler neck and turn clockwise until it engages audibly.
- Close fuel filler flap 1.

# **Parking**

Parking the vehicle

WARNING Risk of accident and injury caused by an insufficiently secured vehicle rolling away

If the vehicle is not securely parked sufficiently, it can roll away in an uncontrolled way even at a slight downhill gradient.

On uphill or downhill gradients, turn the front wheels so that the vehicle rolls towards the curb if it starts moving.

- Apply the parking brake.
- Switch the transmission to position **P**.
- WARNING Risk of fire caused by hot exhaust system parts

Flammable materials such as leaves, grass or twigs may ignite.

- Park the vehicle so that no flammable material can come into contact with hot vehicle components.
- In particular, do not park on dry grassland or harvested grain fields.

WARNING Risk of accident and injury due to children left unattended in the vehicle

If you leave children unattended in the vehicle. they could, in particular:

- · open doors, thereby endangering other persons or road users.
- · get out and be struck by oncoming traffic.

• operate vehicle equipment and become trapped, for example.


In addition, the children could also set the vehicle in motion by, for example:

- · releasing the parking brake.
- · changing the gearbox position.
- · starting the vehicle.
- Never leave children unattended in the vehicle.
- When leaving the vehicle, always take the key with you and lock the vehicle.
- ► Keep the key out of reach of children.
- NOTE Damage to the vehicle due to it rolling away
- Always secure the vehicle against rolling away.

! NOTE Damage due to the vehicle lowering

Vehicles with AIRMATIC or E-ACTIVE BODY CONTROL: The vehicle can lower because of temperature differences or longer non-operational times. This can cause damage to parts of the body.

When stopping the vehicle and when driving off, make sure that there are no obstacles such as curbs under or in the immediate vicinity of the body.



- Bring the vehicle to a standstill by depressing the brake pedal.
- On uphill or downhill gradients, turn the front wheels so that the vehicle rolls towards the curb if it starts moving.
- Apply the electric parking brake.

- Engage transmission position P in a stationary vehicle with the brake pedal depressed  $(\rightarrow page 196)$ .
- Switch off the vehicle by pressing button 1.
- Release the service brake slowly.
- Get out of the vehicle and lock it.
- When you park the vehicle, you can still operate the side windows and the sliding sunroof for approximately four minutes if the driver's door is closed
- (i) When you park the vehicle, you can still operate the side windows and the panoramic sliding sunroof for approximately four minutes if the driver's door is closed.

# Garage door opener

Programming buttons for the garage door opener



**DANGER** Risk of death caused by exhaust gases

Combustion engines emit poisonous exhaust gases such as carbon monoxide. Inhaling these exhaust gases is hazardous to health and leads to poisoning.

Never leave the engine or, if present, the auxiliary heating running in an enclosed space without sufficient ventilation.

WARNING Risk of injury by becoming trapped when opening and closing a garage door

When you operate or program a garage door with an integrated garage door opener, persons can become trapped or struck by the garage door if they stand within its range of movement.

Always make sure that nobody is within the range of the garage door's movement.


Only operate the following doors using the garage door opener:

- Doors with a safety stop and reversing feature
- Doors which conform to the current U.S. safety standards

Before programming the garage door opener, park the vehicle outside the garage. Make sure that the vehicle is switched on but not started.

#### Requirements

- The vehicle has been parked outside the garage or outside the range of movement of the door.
- The vehicle is switched on
- The vehicle has not been started.
- (i) The garage door opener function is always available when the vehicle is switched on.



Check if the transmitter frequency of the remote control has the frequency range of 280 to 868 MHz.

Radio equipment approval number:

- NZLMUAHL5 (USA)
- 4112A-MUAHL5 (Canada)

- Press and hold button ①, ② or ③ that you wish to program.
  Indicator lamp ④ flashes yellow.
- i It can take up to 20 seconds before the indicator lamp flashes yellow.
- Release the previously pressed button.
   Indicator lamp (4) continues to flash yellow.
- Point remote control (3) from a distance of 0.4 in (1 cm) to 3 in (8 cm) towards button (1), (2) or (3).
- Press and hold button of remote control until one of the following signals appears:
  - Indicator lamp lights up green continuously. Programming is complete.
  - Indicator lamp Islanes green. Programming was successful. Additionally, synchronization of the rolling code with the door system must be carried out.
- If indicator lamp 4 does not light up or flash green: repeat the procedure.
- Release all of the buttons.

(i) The remote control for the door drive is not included in the scope of delivery of the garage door opener.

# Synchronizing the rolling code

#### Requirements

- The door system uses a rolling code.
- The vehicle must be within range of the garage door or door drive.
- The vehicle as well as persons and objects are located outside the range of movement of the door.
- Press the program button on the door drive unit. Initiate the next step within approximately 30 seconds.
- Press previously programmed button ①, ②
   or ③ repeatedly until the door closes.
   When the door closes, programming is completed.
- i Please also read the operating instructions for the door drive.

#### Troubleshooting when programming the remote control

- Check if the transmitter frequency of remote control (5) is supported.
- Replace the batteries in remote control (5).
- Hold remote control (5) at various angles from a distance of 0.4 in (1 cm) to 3 in (8 cm) front of the inside rearview mirror. You should test every position for at least 25 seconds before trving another position.
- Hold remote control (5) at the same angles at various distances in front of the inside rear view mirror. You should test every position for at least 25 seconds before trying another position.
- On remote controls that transmit only for a limited period, press button (3) on remote control (5) again before transmission ends.
- Angle the antenna line of the garage door opener unit towards the remote control.
- (i) It is possible that older garage doors cannot be operated using the remote control in the inside rearview mirror even after you have

- successfully performed the measures described above. If this is the case, contact the Homel ink® Hotline
- (i) Support and additional information on programming:
  - on the toll free Homel ink<sup>®</sup> Hotline on 1-800-355-3515
  - on the Internet at https:// www.homelink.com/mercedes
- Opening or closing the garage door

#### Requirements

- The corresponding button is programmed to operate the door.
- Press and hold buttons (1), (2) or (3) until the door opens or closes.
- If the indicator lamp (4) flashes yellow after approx. 20 seconds: Press the previously pressed button again and keep it pressed until the door opens or closes.

#### Clearing the garage door opener memory

- Press and hold buttons (1) and (3). Indicator lamp (4) lights up vellow.
- If indicator lamp (4) flashes green: release buttons (1) and (3). The entire memory has been deleted.

# Electric parking brake

# Function of the electric parking brake (applying) automatically)

WARNING Risk of accident and injury due to children left unattended in the vehicle

If you leave children unattended in the vehicle. they could, in particular:

- open doors, thereby endangering other persons or road users.
- get out and be struck by oncoming traffic.
- · operate vehicle equipment and become trapped, for example.

In addition, the children could also set the vehicle in motion by, for example:

- · releasing the parking brake.
- · changing the gearbox position.
- · starting the vehicle.
- Never leave children unattended in the vehicle.
- When leaving the vehicle, always take the key with you and lock the vehicle.
- Keep the key out of reach of children.

# The electric parking brake is applied if the transmission is in position P and one of the following conditions is fulfilled:

- · The vehicle is switched off.
- The seat belt tongue is not inserted in the seat belt buckle of the driver's seat and the driver's door is opened.
- The transfer case is in the LOW RANGE position.
- (i) To prevent application: pull the handle of the electric parking brake ( $\rightarrow$  page 209).

# In the following situations, the electric parking brake is also applied:

- The HOLD function is keeping the vehicle stationary.
- Active Parking Assist is keeping the vehicle stationary.
- Active Distance Assist DISTRONIC is bringing the vehicle to a standstill.
- In addition, one of the following conditions must be fulfilled:
  - The vehicle is switched off.
  - The seat belt tongue is not inserted in the seat belt buckle of the driver's seat and the driver's door is opened.
  - There is a system malfunction.
  - The power supply is insufficient.
  - The vehicle is stationary for a lengthy period.

When the electric parking brake is applied, the red PARK (USA) or (©) (Canada) indicator lamp lights up in the Instrument Display.

(i) The electric parking brake is not automatically applied if the vehicle is switched off by the ECO start/stop function.

# Function of the electric parking brake (releasing automatically)

The electric parking brake is released when the following conditions are fulfilled:

- · The driver's door is closed.
- · The vehicle has been started.
- If the transmission is in position **R**, the tailgate must be closed.
- The seat belt tongue is inserted into the seat belt buckle of the driver's seat.

If the seat belt tongue is not inserted into the seat belt buckle of the driver's seat, one of the following conditions must be fulfilled:


You shift from transmission position P.

You have previously driven at speeds greater than 2 mph (3 km/h).

When the electric parking brake is released, the red PARK (USA) or (P) (Canada) indicator lamp in the Instrument Display goes out.

# Applying/releasing the electric parking brake manually

# Applying



- Push handle 1. The red PARK (USA) or (P) (Canada) indicator lamp lights up in the Instrument Display.
- The electric parking brake is only securely applied if the red PARK (USA) or (P) (Canada) indicator lamp is lit continuously.

#### Releasing

- Switch on the vehicle.
- Pull handle 

  . The red PARK (USA) or (P) (Canada) indicator lamp in the Instrument Display goes out.

#### **Emergency braking**

Press and hold handle 

.

As long as the vehicle is in motion, the Please Release Parking Brake message is displayed and the red PARK (USA) or (Canada) indicator lamp flashes.

When the vehicle has been braked to a standstill, the electric parking brake is applied. The red PARK (USA) or (Canada) indicator lamp lights up in the Instrument Display.

# Information on collision detection on a parked vehicle

If a collision is detected on the locked vehicle when the tow-away alarm is activated and collision detection is switched on, you will receive a message in the multimedia system when the vehicle is switched on

You will receive information about the following points:

- The area of the vehicle that may have been damaged.
- The force of the impact.

The following situation can lead to inadvertent activation:

- The parked vehicle is moved, for example, in a two-story garage.
- (i) Deactivate the tow-away alarm in order to prevent inadvertent activation. If you deactivate the tow-away alarm, collision detection will also be deactivated.

(i) If the battery is severely discharged, the function for detecting a collision on a parked vehicle is automatically deactivated to facilitate the next engine start.

### System limits

Detection may be restricted in the following situations:

- the vehicle is damaged without impact, for example, if an outside mirror is torn off or the paint is damaged by a key
- · an impact occurs at low speed
- · the electric parking brake is not applied
- You are responsible for your vehicle. Convince yourself that your vehicle is free of damage and roadworthy.

# Notes on parking the vehicle for an extended period

If you leave the vehicle parked for longer than six weeks, it may suffer damage through disuse.

The 12 V battery may also be impaired or damaged by heavy discharging.

(i) Further information can be obtained at a qualified specialist workshop.

# Standby mode (extension of the starter battery's period out of use)

#### Standby mode function

(i) This function is not available for all models.

If standby mode is activated, energy loss will be minimized during extended periods of non-operation.

Standby mode is characterized by the following:

- The starter battery is preserved.
- The maximum non-operational time appears on the media display.
- The connection to online services is interrupted.
- The ATA (anti-theft alarm system) is not available.
- The interior protection and tow-away alarm functions are not available.
- The function for detecting collisions for a parked vehicle is not available.

If the following conditions are fulfilled, standby mode can be activated or deactivated using the multimedia system:

- · The vehicle is switched on.
- The vehicle has not been started.

Exceeding the vehicle's displayed non-operational time may cause inconvenience; i.e. it cannot be guaranteed that the starter battery will reliably start the vehicle.

Charge the starter battery in the following situations:

- The vehicle's non-operational time must be extended.
- The state of charge of the starter battery is insufficient for standby mode.
- (i) Standby mode is automatically deactivated when the vehicle is switched on.

# Activating/deactivating standby mode (parking up the vehicle)

#### Requirements

· The vehicle is switched off.

#### Multimedia system:

- → Settings >> Vehicle
- Activate or deactivate Standby Mode.
- Select Yes.

### Driving and driving safety systems

#### Driving systems and your responsibility

Your vehicle is equipped with driving systems that assist you in driving, parking and maneuvering the vehicle. The driving systems are only aids. They are not a substitute for you paying attention to vour surroundings and do not relieve you of your responsibility pertaining to road traffic law. The driver is always responsible for maintaining a safe distance to the vehicle in front, for vehicle speed. for braking in good time and for staying in lane. Pay attention to the traffic conditions at all times and intervene when necessary. Be aware of the limitations regarding the safe use of these systems.


Driving systems can neither reduce the risk of an accident if you fail to adapt your driving style nor override the laws of physics. They cannot always

take into account road, weather or traffic conditions

(i) Some driving systems can regulate or limit the speed to a previously set value. Draw attention to the stored speed when changing drivers.

#### Information on vehicle sensors and cameras

Some driving and driving safety systems use cameras as well as radar or ultrasonic sensors to monitor the area in front of, behind or next to the vehicle.



- Multifunction camera
- Cameras in the outside mirrors
- Front radar
- Front camera
- Corner radars
- Ultrasonic sensors
- Rear-view camera

▲ WARNING Risk of accident due to restricted detection performance of vehicle sensors and cameras

If the area around vehicle sensors or cameras is covered, damaged or dirty, certain driving and safety systems cannot function correctly. There is a risk of an accident.

- Keep the area around vehicle sensors or cameras clear of any obstructions and clean.
- Have damage to the bumper, radiator grille or stone chipping in the area of the front and rear windows repaired at a qualified specialist workshop.

Keep the areas around the sensors and cameras in particular free of dirt, ice and slush (→ page 349). The sensors and cameras must not be covered and the detection areas around them must be kept clear. Do not attach additional license plate bracket, advertisements, stickers, wraps or stone chip protection films in the detection range of the sensors and cameras. Make sure

that there are no overhanging loads protruding into the detection area.

If there is damage to a bumper or the radiator grille, or after an impact, have the function of the sensors checked at a qualified specialist workshop. Have damage or stone chipping around the cameras on the front and rear passenger compartment windows repaired at a qualified specialist workshop.

# Overview of driving systems and driving safety systems

- ABS (→ page 213)
- Off-road ABS (→ page 213)
- BAS (→ page 213)
- ESP<sup>®</sup> (→ page 214)
- ESP<sup>®</sup> Crosswind Assist (→ page 215)
- ESP<sup>®</sup> trailer stabilization (→ page 215)
- EBD (→ page 217)
- STEER CONTROL (→ page 217)
- HOLD function (→ page 217)

- Hill Start Assist (→ page 218)
- ATTENTION ASSIST (→ page 218)
- Cruise control (→ page 220)
- Traffic Sign Assist (→ page 240)
- AIRMATIC (→ page 247)
- E-ACTIVE BODY CONTROL (→ page 252)
- Trailer Maneuvering Assist (→ page 277)

#### Driving Assistance Package

The following functions are part of the Driving Assistance Package. Certain functions are only available in some countries. Some functions are also available without the Driving Assistance Package, albeit with restricted functionality.

- Active Distance Assist DISTRONIC
   (→ page 222)
- Active Speed Limit Assist (country-dependent)
   (→ page 226)
- Route-based speed adaptation (countrydependent) (→ page 227)
- DSR (→ page 229)
- Active Brake Assist (→ page 235)

- Active Steering Assist (country-dependent)  $(\rightarrow page 231)$
- Active Emergency Stop Assist (countrydependent) ( $\rightarrow$  page 233)
- Active Lane Change Assist (country-dependent) ( $\rightarrow$  page 234)
- Active Stop-and-Go Assist (country-dependent) ( $\rightarrow$  page 228)
- Blind Spot Assist and Active Blind Spot Assist with exit warning ( $\rightarrow$  page 242)
- Active Lane Keeping Assist (→ page 244)

# Parking Package

- Rear view camera (→ page 261)
- 360° camera (→ page 263)
- Parking Assist PARKTRONIC (→ page 266)
- Active Parking Assist (→ page 271)

#### **Function of ABS**

The Anti-lock Brake System (ABS) regulates the brake pressure in critical driving situations:

- · During braking, for instance, at maximum fullstop braking or if there is insufficient tire traction, the wheels are prevented from locking.
- Vehicle steerability while braking is ensured.

If ABS intervenes when braking, you will feel a pulsing in the brake pedal. The pulsating brake pedal can be an indication of hazardous road conditions and can serve as a reminder to take extra care while driving.

#### System limits

- ABS is active from speeds of approx. 3 mph (5 km/h).
- · ABS may be impaired or may not function if a malfunction has occurred and the vellow ( ABS warning lamp lights up continuously after the vehicle is started.

#### Function of off-road ABS

(i) Off-road ABS is activated automatically when you select the or or drive program.

Off-road ABS is specially adapted for driving offroad:

- The front wheels lock cyclically during braking.
- The braking distance is shortened due to the digging-in effect.

#### System limits

- Off-road ABS functions at speeds below 25 mph (40 km/h).
- · If Off-road ABS intervenes, the ability to steer may be restricted.

#### Function of BAS

WARNING Risk of an accident caused by a malfunction in BAS (Brake Assist System)

If BAS is malfunctioning, the braking distance in an emergency braking situation is increased.

Depress the brake pedal with full force in emergency braking situations. ABS prevents the wheels from locking.

The Brake Assist System (BAS) supports your emergency braking situation with additional brake force.

If you depress the brake pedal quickly, BAS is activated:

- BAS automatically boosts the brake pressure.
- · BAS can shorten the braking distance.
- · ABS prevents the wheels from locking.

The brakes will function as usual once you release the brake pedal. BAS is deactivated.

#### Function of ESP®

WARNING Risk of skidding if ESP® is deactivated

If you deactivate ESP®, ESP® cannot carry out vehicle stabilization.

ESP® should only be deactivated in the following situations.

! NOTE Mercedes-AMG vehicles

Observe the notes in the Supplement. You could otherwise fail to recognize dangers.

The Electronic Stability Program (ESP®) can monitor and improve driving stability and traction in the following situations within physical limits:

- When pulling away on wet or slippery roads.
- · When braking.

If the vehicle deviates from the direction desired by the driver,  ${\sf ESP}^{\circledast}$  can stabilize the vehicle by intervening in the following ways:

- · One or more wheels are braked.
- The engine output is adapted according to the situation.

When ESP® is deactivated, the samplights up continuously:

- Driving stability will no longer be improved.
- The drive wheels could spin.
- ETS/4ETS traction control is still active.
- (i) When ESP® is deactivated, you are still assisted by ESP® when braking.

When the swarning lamp flashes, one or several wheels has reached its grip limit:

- Adapt your driving style to suit the current road and weather conditions.
- Do not deactivate ESP<sup>®</sup>.
- Only depress the accelerator pedal as far as is necessary when pulling away.

Deactivate  $\mathsf{ESP}^{\texttt{®}}$  in the following situations to improve traction:

- · When using snow chains.
- In deep snow.
- On sand or gravel.

(i) Spinning the wheels results in a cutting action, which enhances traction.

If the samp lights up continuously. FSP® is not available due to a malfunction.

Observe the following information:

- Warning and indicator lamps (→ page 485)
- Display messages (→ page 428)

#### ETS/4ETS (Electronic Traction System)

ETS/4ETS traction control is part of ESP® and makes it possible to pull away and accelerate on a slippery road.

If you select the or or drive program, a special ETS system specifically suited to off-road terrain is automatically activated.

ETS/4ETS can improve the vehicle's traction by intervening in the following ways:

- · The drive wheels are braked individually if they spin.
- More drive torque is transferred to the wheel or wheels with traction.

## Influence of drive programs on ESP®

The drive programs enable ESP® to adapt to different weather and road conditions as well as the driver's preferred driving style. Depending on the selected drive program, the appropriate ESP® mode will be activated ( $\rightarrow$  page 192).

## Function of ESP® Crosswind Assist

ESP® Crosswind Assist detects sudden gusts of side wind and helps the driver to keep the vehicle in the lane:

- ESP® Crosswind Assist is active at vehicle speeds between approx. 50 mph (80 km/h) and 125 mph (200 km/h) when driving straight ahead or cornering slightly.
- The vehicle is stabilized by means of individual brake application on one side.

### Function of ESP® trailer stabilization

WARNING Risk of accident in poor road and weather conditions

In poor road and weather conditions, the trailer stabilization cannot prevent lurching of the vehicle/trailer combination. Trailers with a high center of gravity may tip over before FSP® detects this.

Always adapt your driving style to suit the current road and weather conditions.

When you are driving with a trailer, ESP® can stabilize your vehicle if the trailer begins to swerve from side to side:

- ESP® trailer stabilization will be active at speeds above 40 mph (65 km/h).
- · Slight swerving is reduced by means of a targeted, individual brake application on one
- In the event of severe swerving, the operating energy output will also be reduced and the brakes will be applied to all wheels.

ESP® trailer stabilization may be impaired or may not function if:

• The trailer is not connected correctly or is not detected properly by the vehicle.

## Activating/deactivating ESP® (without Off-Road package or E-Active Body Control)

Multimedia system:


- → 🔝 >> Settings >> Quick Access
- ESP® can be activated/deactivated using quick access only when at least one other function is available in quick access. ESP® can otherwise be found on the Assistance menu.
- ! NOTE Mercedes-AMG vehicles
- Observe the notes in the Supplement. You could otherwise fail to recognize dangers.
- Select ESP.

ESP® is deactivated if the ESP® OFF warning lamp lights up continuously on the instrument cluster.

Observe any information on warning lamps and display messages that may be shown on the instrument cluster.

## Activating/deactivating ESP® (with Off-Road package or E-Active Body Control)

- ! NOTE Mercedes-AMG vehicles
- Observe the notes in the Supplement. You could otherwise fail to recognize dangers.



Pull rocker switch ①.

ESP® is deactivated if the ESP® OFF warning lamp lights up continuously on the instrument display.

Observe the information on warning lamps and display messages .

#### Function of EBD

Electronic Brakeforce Distribution (EBD) is characterized by the following:

- · Monitoring and regulating the brake pressure on the rear wheels.
- Improved driving stability when braking, especially on bends.

#### Function of STEER CONTROL

STEER CONTROL assists you by transmitting a noticeable steering force to the steering wheel in the direction required for vehicle stabilization.

This steering recommendation is given in the following situations:

- both right wheels or both left wheels are on a wet or slippery road surface when you brake
- the vehicle starts to skid

#### System limits

STEER CONTROL may be impaired or may not function in the following situations:

FSP® is deactivated.

- ESP® is malfunctioning.
- The steering is malfunctioning.

If ESP® is malfunctioning, you will be assisted further by the electric power steering.

#### **HOLD function**

#### HOLD function

The HOLD function holds the vehicle at a standstill without requiring you to depress the brake pedal, e.g. while waiting in traffic.

The HOLD function is only an aid. The responsibility for the vehicle safely standing still remains with the driver

## System limits

The HOLD function is only intended to provide assistance when driving and is not a sufficient means of safeguarding the vehicle against rolling away when stationary.

• The incline must not be greater than 30%.

## Activating/deactivating the HOLD function

WARNING Risk of an accident due to the HOLD function being active when you leave the vehicle

If the vehicle is only braked with the HOLD function it could, in the following situations, roll away:

- If there is a malfunction in the system or in the power supply.
- If the HOLD function is deactivated by depressing the accelerator pedal or brake pedal, e.g. by a vehicle occupant.
- Always secure the vehicle against rolling away before you leave it.

#### Requirements

- The vehicle is stationary.
- The driver's door is closed or the seat belt on the driver's side is fastened.
- The vehicle has been started or has been automatically switched off by the ECO start/ stop function.

- The electric parking brake is released.
- Active Distance Assist DISTRONIC is deactivated.
- The transmission is in position  $\boxed{\mathbf{D}}$ ,  $\boxed{\mathbf{R}}$  or  $\boxed{\mathbf{N}}$ .

### Activating the HOLD function

- Depress the brake pedal, and after a short time quickly depress further until the Hold display appears in the Instrument Display.
- Release the brake pedal.

#### Deactivating the HOLD function

- Depress the accelerator pedal to pull away.
- Depress the brake pedal until the Hold display disappears from the Instrument Display.

The HOLD function is deactivated in the following situations:

- Active Distance Assist DISTRONIC is activated.
- The transmission is shifted to position **P**.
- The vehicle is secured with the electric parking brake.

In the following situations, the vehicle is held by transmission position [P] and/or by the electric parking brake:

- The seat belt is unfastened and the driver's door is opened.
- · The vehicle is switched off.
- There is a system malfunction.
- The power supply is insufficient.

#### **Function of Hill Start Assist**

Hill Start Assist holds the vehicle for a short time when you pull away on a hill under the following conditions:

- The transmission is in position  $\mathbf{D}$  or  $\mathbf{R}$ .
- The electric parking brake is released.

This gives you enough time to move your foot from the brake pedal to the accelerator pedal and depress it before the vehicle begins to roll away.

## **WARNING** Risk of accident and injury due to the vehicle rolling away

After a short time, Hill Start Assist no longer holds the vehicle.

Swiftly move your foot from the brake pedal to the accelerator pedal. Do not leave the vehicle when it is being held by Hill Start Assist.

#### ATTENTION ASSIST

## ■ Function of ATTENTION ASSIST

ATTENTION ASSIST assists you on long, monotonous journeys, e.g. on highways and trunk roads. If ATTENTION ASSIST detects indicators of fatigue or increasing lapses in concentration on the part of the driver, it suggests taking a break.

ATTENTION ASSIST is only an aid. It cannot always detect fatigue or lapses in concentration in time. The system is not a substitute for a well-rested and attentive driver. On long journeys, take regular breaks in good time that allow for adequate recuperation.

You can choose between two settings:

- Standard: normal system sensitivity.
- Sensitive: higher system sensitivity. The driver is warned earlier and the attention level detected by ATTENTION ASSIST is adapted accordingly.

If drowsiness or increasing lapses in concentration are detected, the ATTENTION ASSIST: Take a Break! warning appears in the Instrument Display. You can acknowledge the message and take a break where necessary. If you do not take a break and ATTENTION ASSIST continues to detect increasing lapses in concentration, you will be warned again after a minimum of 15 minutes.



You can have the following status information for ATTENTION ASSIST displayed in the assistance menu of the on-board computer:

- The length of the journey since the last break.
- The attention level determined by ATTENTION ASSIST:
  - the fuller the circle, the higher the attention level determined
  - as your attention wanes, the circle in the center of the display becomes smaller

If ATTENTION ASSIST is unable to calculate the attention level and cannot issue a warning, the System Suspended message appears.

If a warning is given in the Instrument Display, the multimedia system offers to search for a rest area. You can select a rest area and start navigation to this rest area. This function can be activated and deactivated in the multimedia system.

If ATTENTION ASSIST is deactivated, the The symbol appears in the assistance graphic in the Instrument Display. After the vehicle is started, ATTENTION ASSIST is automatically activated. The last selected sensitivity level remains stored.

#### System limits

ATTENTION ASSIST is active in the 37 mph (60 km/h) to 124 mph (200 km/h) speed range.

Particularly in the following situations, ATTENTION ASSIST only functions in a restricted manner and warnings may be delayed or not occur:

- If you have been driving for less than approximately 30 minutes.
- If the road condition is poor (uneven road surface or potholes).
- · If there is a strong side wind.
- If you adopt a sporty driving style (high cornering speeds or high rates of acceleration).
- . If Active Steering Assist is activated and active  $(\rightarrow page 231)$ .
- If the time has been set incorrectly.
- If you change lanes and vary your speed frequently in active driving situations.

The ATTENTION ASSIST drowsiness or alertness assessment is reset and restarted when continuing the journey in the following situations:

If you switch off the vehicle.

 If you unfasten your seat belt and open the driver's door (e.g. to change drivers or take a break).

## Setting ATTENTION ASSIST

Multimedia system:

→ Settings → Assistance → Attention Assist

## Setting options

Select Standard, Sensitive or Off.

#### Suggesting rest areas

- Select Suggest Rest Area.
- Activate or deactivate the function. If ATTENTION ASSIST detects fatigue or an increasing lack of attention, it will suggest a rest area in the vicinity.
- Select the suggested rest area.
  You will be guided to the selected rest area.

#### Speed control cruise control

#### Function of cruise control

Cruise control regulates the speed to the value selected by the driver.

If you accelerate to overtake, for example, the stored speed is not deleted. If you remove your foot from the accelerator pedal after overtaking, cruise control will resume speed regulation back to the stored speed.

You can store any speed above 15 mph (20 km/h) up to the maximum design speed.

Observe the notes on driving systems and your responsibility; you may otherwise fail to detect dangers ( $\rightarrow$  page 211).

Mercedes-AMG vehicles: cruise control is available up to a maximum speed of 155 mph (250 km/h).

## Displays in the Instrument Display

- ি (gray): cruise control is selected but not yet activated.
- (green): cruise control is active.

A stored speed appears along with the  $\fill$  display.

i The segments between the stored speed and the end of the segment display light up in the speedometer.

#### System limits

Cruise control may be unable to maintain the stored speed on uphill gradients. The stored speed is resumed when the gradient evens out.

Change into a lower gear in good time on long and steep downhill gradients. Take particular note of this when driving a laden vehicle. By doing so, you will make use of the braking effect of the engine. This relieves the load on the brake system and prevents the brakes from overheating and wearing too quickly.

Do not use cruise control in the following situations:

 in traffic situations which require frequent changes of speed, e.g. in heavy traffic, on winding roads

- on slippery roads. Accelerating can cause the drive wheels to lose traction and the vehicle could then skid
- when visibility is poor

## Operating cruise control


WARNING Risk of accident due to stored speed

If you call up the stored speed and this is lower than your current speed, the vehicle decelerates

Take into account the traffic situation. before calling up the stored speed.

## Requirements:

- ESP® must be activated, but not intervening.
- The vehicle speed is at least 15 mph (20 km/h).
- The transmission is in position **D**.



## Operating cruise control

Press the rocker switches on the steering wheel control panel up or down to the desired position.

## Activating cruise control

Select with the right rocker switch.

## Activating cruise control

Press rocker 1 switch SET/+ up or SET/down.

The current speed is stored and maintained by the vehicle

Select RES/9 with the left rocker switch. The last stored speed is called up and maintained by the vehicle.

If the last stored speed has previously been deleted, the current vehicle speed is stored.

(i) When you switch off the vehicle, the last speed stored is deleted.

## Increasing or decreasing the stored speed

1 mph (1 km/h): press rocker switch 1 up **SET/+** or down **SET/-** to the pressure point.

or

5 mph (10 km/h): press rocker switch 10 up SET/+ or down SET/- beyond the pressure point.

Accelerate the vehicle to the desired speed and press rocker switch 1 up SET/+.

### Adopting a detected speed

- Activate cruise control.
- If a traffic sign has been detected and is displayed in the instrument cluster; select RESIP with the left rocker switch.

The maximum permissible speed shown by the traffic sign is stored and the vehicle maintains or does not exceed this speed.

#### Deactivating cruise control

Select **CNCL** with the left rocker switch.

## Deactivating cruise control

- ▶ Select with the right rocker switch.
- i If you brake, deactivate ESP® or if ESP® intervenes, cruise control is deactivated.

#### Active Distance Assist DISTRONIC

Function of Active Distance Assist DISTRONIC
Active Distance Assist DISTRONIC maintains the set speed when you are driving freely. If vehicles are detected ahead, the set distance is maintained, if necessary until the vehicle comes to a

standstill. The vehicle accelerates or brakes depending on the distance to the vehicle in front and the set speed. The speed and distance to the vehicle in front are set and saved using the steering wheel.

#### Available speed range:

- Vehicles without Driving Assistance Package:
   15 mph (20 km/h) 120 mph (200 km/h)
- Vehicles with Driving Assistance Package: 15 mph (20 km/h) - 130 mph (210 km/h)
- The maximum speed is reduced when you are driving in the LOW RANGE off-road gear (→ page 199).

Other features of Active Distance Assist DISTRONIC:

- Adjusts the driving style depending on the selected drive program (fuel-saving, comfortable or dynamic)
- Initiates acceleration to the stored speed if the turn signal indicator is switched on to change to the overtaking lane
- · Vehicles with Driving Assistance Package:

- Reacts to stationary vehicles detected in urban speed ranges (except bicycles and motorcycles)
- Takes one-sided overtaking restrictions into account on highways or on multi-lane roads with separate roadways (countrydependent)

Vehicles with Driving Assistance Package and Parking Package: if the vehicle has been braked to a standstill on multi-lane, separate roadways by Active Distance Assist DISTRONIC, it can automatically follow the vehicle in front when driving off again within 30 seconds. If a critical situation is detected when you are driving off, a visual and acoustic warning is given indicating that the driver must now take control of the vehicle. The vehicle is not accelerated any further.

Observe the notes on driving systems and your responsibility; you may otherwise fail to recognize dangers ( $\rightarrow$  page 211).

#### Active Distance Assist DISTRONIC displays on the instrument display



#### Assistant display

- Route-based speed adaptation: type of route event ( $\rightarrow$  page 227)
- Vehicle in front
- Distance indicator
- Set specified distance
- Active Lane Change Assist lane change display

#### Permanent status display of Active Distance Assist DISTRONIC

- (white): Active Distance Assist DISTRONIC selected, specified distance set
- (white vehicle, green speedometer): Active Distance Assist DISTRONIC active. specified distance set and no vehicle detected
- (green): Active Distance Assist DISTRONIC active, specified distance set and vehicle detected
- : Route-based speed adaptation active  $(\rightarrow page 227).$

The stored speed is shown along with the permanent status display and highlighted on the speedometer. When Active Distance Assist DISTRONIC is passive, the speed is graved out.

- On highways or high-speed major roads, the green vehicle symbol is displayed cyclically when the vehicle is ready to pull away.
- (i) If you depress the accelerator pedal beyond the setting of the Active Distance Assist DISTRONIC, the system is switched to passive

mode. The Suspended message will appear on the instrument display.

### Display on the speedometer

The stored speed is highlighted on the speedometer. If the speed of the vehicle in front or the speed adjustment for the route event ahead is less than the stored speed, the segments in the speedometer light up. The instrument display shows the deactivation of Active Distance Assist DISTRONIC, as well as alterations to the speed due to manual or automatic adoption of the maximum permissible speed.

## System limits

The system may be impaired or may not function in the following situations, for example:

- · In snow, rain, fog, heavy spray, direct sunlight or highly variable light conditions, or if there is glare.
- If there is swirling dust, e.g. when you are driving off-road or on sandy surfaces.
- The windshield in the area of the camera is dirty, fogged up, damaged or covered.
- If the radar sensors are dirty or covered.

- In parking garages or on roads with steep uphill or downhill gradients.
- If there are narrow vehicles in front, such as bicycles or motorcycles.

In addition, on slippery roads, braking or accelerating can cause one or several wheels to lose traction and the vehicle could then skid.

Do not use Active Distance Assist DISTRONIC in these situations.

WARNING Risk of accident from acceleration or braking by Active Distance Assist DISTRONIC

Active Distance Assist DISTRONIC may accelerate or brake in the following cases, for example:

- If the vehicle pulls away using Active Distance Assist DISTRONIC.
- If the stored speed is called up and is considerably faster or slower than the currently driven speed.

- If Active Distance Assist DISTRONIC no longer detects a vehicle in front or does not react to relevant objects.
- Always carefully observe the traffic conditions and be ready to brake at all times.
- Take into account the traffic situation before calling up the stored speed.

▲ WARNING Risk of accident due to insufficient deceleration by Active Distance Assist DISTRONIC

Active Distance Assist DISTRONIC brakes your vehicle with up to 50% of the possible deceleration. If this deceleration is not sufficient, Active Distance Assist DISTRONIC alerts you with a visual and acoustic warning.

- Adjust your speed and maintain a suitable distance from the vehicle in front.
- Brake the vehicle yourself and/or take evasive action.

WARNING Risk of accident if detection function of Active Distance Assist DISTRONIC is impaired

Active Distance Assist DISTRONIC does not react or has a limited reaction:

- when driving on a different lane or when changing lanes
- to pedestrians, animals, bicycles or stationary vehicles, or unexpected obstacles
- to complex traffic conditions
- to oncoming vehicles and crossing traffic

As a result, Active Distance Assist DISTRONIC may neither give warnings nor intervene in such situations.


Always observe the traffic conditions carefully and react accordingly.

## Operating Active Distance Assist DISTRONIC

#### Requirements

- The electric parking brake is released.
- ESP<sup>®</sup> is activated and is not intervening.

- The transmission is in position **D**.
- The driver's door is closed
- Check of the radar sensor system has been successfully completed.
- · Parking Assist PARKTRONIC is not being used to park the vehicle or to exit from a parking space.
- DSR is deactivated.
- Vehicles with Off-road package: the drive program is deactivated.



To operate Active Distance Assist **DISTRONIC:** press the rocker switches on the steering wheel control unit up or down to the desired position.

#### Activating/deactivating Active Distance Assist DISTRONIC

Press button .

Activating Active Distance Assist DISTRONIC

To activate without a stored speed: press rocker switch 1 up SET/+ or down SET/-, or select RESI® with the left rocker switch.

or

- To activate with a stored speed: select RESI® with the left rocker switch.
- Remove your foot from the accelerator pedal. The current speed is stored and maintained by the vehicle.

### Adopting a detected speed limit

- Activate Active Distance Assist DISTRONIC.
- If a traffic sign has been detected and is displayed in the instrument display: select RESI® with the left rocker switch.

The maximum permissible speed on the traffic sign is adopted as the stored speed. The vehicle adapts its speed to that of the vehicle in front, but only up to the stored speed.

#### Pulling away with Active Distance Assist DISTRONIC

Activate Active Distance Assist DISTRONIC and remove your foot from the brake pedal.

Select RESI® with the left rocker switch.

or

Depress the accelerator pedal briefly and firmly.

The functions of Active Distance Assist DISTRONIC continue to be carried out.

## Deactivating Active Distance Assist DISTRONIC

★ WARNING Risk of an accident due to Active Distance Assist DISTRONIC being active when you leave the driver's seat

If you leave the driver's seat while the vehicle is being braked by Active Distance Assist DISTRONIC only, the vehicle can roll away.

- Always deactivate Active Distance Assist DISTRONIC and secure the vehicle to prevent it from rolling away before you leave the driver's seat.
- Select CNCL with the left rocker switch.
- i If you brake, deactivate ESP® or if ESP® intervenes, Active Distance Assist DISTRONIC is deactivated.

## Increasing or decreasing the speed

1 mph (1 km/h): press rocker switch 1 up SET/+ or down SET/- to the pressure point.

or

5 mph (10 km/h): press rocker switch (1) up SET/H or down SET/H beyond the pressure point.

or

Accelerate the vehicle to the desired speed and press rocker switch (1) up SET/+1.

## Changing the specified distance to the vehicle in front

- To reduce the specified distance: press the right rocker switch up (\( \sum\_{\text{\cong}} \)).
- To increase the specified distance: press the right rocker switch down ().

## Function of Active Speed Limit Assist

If a change in the speed limit of 12 mph (20 km/h) or more is detected and automatic adoption of speed limits is activated, the new speed limit is automatically adopted as the stored speed ( $\rightarrow$  page 241).

The vehicle's speed is adjusted when it is level with the traffic sign at the latest. In the case of signs indicating entry into an urban area, the speed is adapted according to the speed permitted within the urban area. The speed limit display on the instrument display is always updated when the vehicle is level with the traffic sign.

If there is no speed restriction on an unlimited stretch of road (e.g. on a highway), the recommended speed is automatically adopted as the stored speed. The system uses the speed stored on an unlimited stretch of road as the recommended speed. If you do not alter the stored speed on an unlimited stretch of road, the recommended speed is 80 mph (130 km/h).

If Active Distance Assist DISTRONIC has been put into passive mode by pressing the accelerator pedal, only speed limits which are higher than the set speed are adopted.

Observe the notes on driving systems and your responsibility; you may otherwise fail to recognize dangers ( $\rightarrow$  page 211).

#### System limits

The system limits of Traffic Sign Assist apply to the detection of traffic signs ( $\rightarrow$  page 240).

Speed limits below 12 mph (20 km/h) are not automatically adopted by the system as the stored speed. Temporary speed restrictions (e.g. for a certain time or due to weather conditions) cannot be properly detected by the system. The maximum permissible speed applying to a vehicle with a trailer is not detected by the system.

Adjust the speed in these situations.

WARNING Risk of accident due to Active Speed Limit Assist adapting the vehicle's speed

The speed adopted by Active Speed Limit Assist may be too high or incorrect in some individual cases, such as:

- at speed limits below 12 mph (20 km/h)
- in wet conditions or in fog
- · when towing a trailer

- Ensure that the driven speed complies with traffic regulations.
- Adjust the driving speed to suit current traffic and weather conditions.

## Function of route-based speed adaptation

When Active Distance Assist DISTRONIC is activated, the vehicle speed will be adapted accordingly to the route events ahead. Depending on the drive program selected, the vehicle negotiates a route event ahead in an economical, comfortable or dynamic manner. When the route event has been passed, the vehicle accelerates again to the stored speed. The set distance to the vehicle in front, vehicles detected ahead and speed restrictions ahead are taken into account.

You can activate and deactivate route-based speed adaptation in the multimedia system  $(\rightarrow page 228).$ 

The following route events are taken into account:

- Bends
- T-intersections, traffic circles and toll stations
- Turns and exits

- · Traffic iams ahead (only with Live Traffic Information )
- When the toll station is reached. Active Distance Assist DISTRONIC adopts the speed as the stored speed.

Also, the speed is reduced if the turn signal indicator to change lanes is switched on and one of the following situations is detected:

- · Turning at intersections
- Driving on slowing-down lanes
- Driving on lanes adjacent to slowing-down lanes

The driver is responsible for choosing the right speed and observing other road users. This applies in particular to intersections, traffic circles and traffic lights because route-based speed adaptation does not brake the vehicle to a standstill.

When route guidance is active, the first speed adjustment is carried out automatically. If the turn signal indicator is switched on, the selected route is confirmed and further speed adjustment is activated.

Speed adaptation is canceled in the following cases:

- If the turn signal indicator is switched off before the route event
- If the driver depresses the accelerator or brake pedal during the process.

### System limits

Route-based speed adaptation does not take right of way regulations into account. The driver is responsible for complying with road traffic regulations and driving at a suitable speed.

The speed adaptation made by the system may not always be suitable, particularly in the following situations:

- the road's course not clearly visible
- · Road narrowing
- varying maximum permissible speeds in individual lanes, forexample at toll stations
- · wet road surfaces, snow or ice
- · when towing a trailer

In these situations the driver must intervene accordingly.

## ▲ WARNING Risk of accident in spite of route-based speed adaptation

Route-based speed adaptation can malfunction or be temporarily unavailable in the following situations:

- If the driver does not follow the calculated route
- If map data is not up-to-date or available
- · In the event of roadworks
- In bad weather or road conditions
- If the accelerator pedal is depressed
- In the event of electronically displayed speed limitations
- Adapt the speed to the traffic situation.

## Setting route-based speed adaptation

#### Requirements

- Active Distance Assist DISTRONIC is activated.
- . ECO Assist is active.

#### Multimedia system:

- → 🔝 **>>** Settings **>>** Assistance
- **▶** Route-based Speed
- Activate or deactivate the function. When the function is active, the vehicle speed is adjusted depending on the route events ahead.
- (i) Further information on route-based speed adaptation ( $\rightarrow$  page 227).

## Function of Active Stop-and-Go Assist

Active Stop-and-Go Assist helps you when in traffic jams on multi-lane roads with separate roadways by automatically pulling away within up to 60 seconds and with moderate steering maneuvers. It orients itself using the vehicle in front and lane markings. Active Stop-and-Go Assist automatically maintains a safe distance from the vehicle in front and vehicles cutting in.

Active Stop-and-Go Assist requires you, as the driver, to keep your hands on the steering wheel at all times so that you are able to intervene at any time to correct the course of the vehicle and keep it in lane. Observe the notes on driving sys-

tems and your responsibility; you may otherwise fail to recognize dangers ( $\rightarrow$  page 211).

Active Stop-and-Go Assist activates automatically as soon as all of the requirements are met: The status display appears on the instrument display when the function is active.

#### Requirements:

- You are in a traffic jam on a highway or highspeed major road.
- Active Distance Assist DISTRONIC is activated. and active ( $\rightarrow$  page 224).
- Active Brake Assist is available (→ page 235).
- · Active Steering Assist is activated and active  $(\rightarrow page 233).$
- You are traveling no faster than 35 mph (60 km/h).

#### System limits

The system limitations of Active Distance Assist DISTRONIC and Active Steering Assist apply to Active Stop-and-Go Assist.

### Activating/deactivating Active Traffic Jam Assist

Multimedia system:

→ Settings → Quick Access

## Select .

## **DSR (Downhill Speed Regulation)**

#### ■ Function of DSR

DSR is an aid to assist you when driving downhill. It keeps the speed of travel at the selected target speed. The steeper the downhill gradient, the greater the DSR braking effect on the vehicle. On flat stretches of road and uphill gradients, the DSR brakes the vehicle minimally or not at all.

When DSR is activated and the transmission is in position D, R or N, DSR controls the driving speed. The target speed can be set to a value between 1 mph (2 km/h) and 11 mph (18 km/h). By braking or accelerating, you can drive at a higher or lower speed than the target speed at anv time.

If you drive faster than 28 mph (45 km/h) or change the drive program (except in \( \sqrt{1} \),

DSR switches off automatically. The Gold message will then appear on the instrument display. The status indicator on the instrument display goes out. You also hear a warning tone.

Mercedes-Maybach vehicles: in drive program the DSR function is likewise not available.

#### Information on DSR

WARNING Risk of skidding and accident when DSR is activated on slippery road surfaces

If the driven speed and the target speed differ, the wheels may lose traction.

Take into account the road surface and the difference between the driving speed and target speed before activating DSR.

Observe the notes on driving systems and your responsibility; you may otherwise fail to recognize dangers ( $\rightarrow$  page 211).

You are always responsible for keeping control of the vehicle and for assessing whether the downhill gradient can be negotiated. Depending on road surface and tires, DSR may not always be able to

keep to the target speed. Select a target speed suitable for the environmental conditions and also apply the brakes yourself if required.

## Activating/deactivating DSR (with Offroad package or E-ACTIVE BODY CONTROL)


### Requirements:

 You are driving at 24 mph (40 km/h) or slower.

If the current vehicle speed is too high, the Max. Speed 24 mph message appears on the instrument display.

- You have not selected drive program s or

  S.
  .
- Active Distance Assist DISTRONIC is deactivated.



- To activate: pull rocker switch (1). Indicator lamp (2) lights up.
  - The  $\mathfrak{S}$  symbol appears on the instrument display.
- ➤ To deactivate: pull rocker switch ①. Indicator lamp ② and the ☐ symbol go out.

## Activating/deactivating DSR (without Offroad package or E-Active Body Control

#### Requirements

 You are driving at 24.8 mph (40 km/h) or slower.

If the current vehicle speed is too high, the Max. Speed 24 mph message appears on the multifunction display.


Active Distance Assist DISTRONIC is deactivated.

### Multimedia system:

- → Settings
- >> Schnellzugriff (Quick access)
- Select DSR.

  The DSR symbol appears on the multifunction display when the function is activated.
- i) When you switch to the \( \bigsim \) drive program, the function is automatically activated.

## Changing the target speed



To increase/reduce the target speed: press rocker switch 1 up SET/+ or down SET/- to the point of resistance. The selected target speed is increased or reduced by 1 mph (1 km/h) and appears next

to the symbol on the instrument display.

## Active Steering Assist

## ■ Function of Active Steering Assist

Active Steering Assist is available up to a speed of 130 mph (210 km/h). The system helps you to stay in the center of the lane by means of moderate steering interventions. Depending on the speed at which you are driving, Active Steering Assist uses the vehicles ahead and lane markings as a reference.

Depending on the country, Active Steering Assist can use the surrounding traffic as a reference in the lower speed range. If necessary. Active Steering Assist can then also provide assistance when driving outside the center of the lane to form an emergency corridor, for example.

If the detection of lane markings and vehicles ahead is impaired, Active Steering Assist switches to passive mode. The system provides no support in this case.

### Status display of Active Steering Assist

- (gray): activated and passive
- (green): activated and active

- (red): system limits detected
- (white, red hands): "hands on the steering wheel" prompt
- (i) During the transition from active to passive status, the symbol is shown as enlarged and flashing. When the passive state is reached, the symbol is displayed in gray.
- (i) Depending on the selected vehicle settings. Active Steering Assist may be unavailable.

## Steering and touch detection

The driver is required to keep their hands on the steering wheel at all times and be able to intervene at any time to correct the course of the vehicle and keep it in lane. The driver must expect a change from active to passive mode or vice versa at any time.



If the system detects that the driver has not steered the vehicle for a considerable period of time or has removed their hands from the steering wheel, display appears. If the driver still does not steer the vehicle, a warning tone sounds in addition to the visual warning message.

If the driver does not react to the warning for a considerable period, the system may initiate an emergency stop ( $\rightarrow$  page 233).

The warning is not issued or is stopped if the driver provides the system with feedback:

· The driver steers the vehicle.

 Depending on the country: the driver presses a steering wheel button or operates Touch Control

The warning is not issued or is stopped as soon as the system detects that the driver is touching the steering wheel or steering.

If Active Steering Assist detects that a system limit has been reached, a visual warning is issued and a warning tone sounds.

Observe the notes on driving systems and your responsibility; you may otherwise fail to recognize dangers ( $\rightarrow$  page 211).

## System limits

Active Steering Assist has a limited steering torque for lateral guidance. In some cases, the steering intervention is not sufficient to keep the vehicle in the lane or to drive through exits.

The system may be impaired or may not function in the following instances:

 There is poor visibility, e.g. due to snow, rain, fog, heavy spray, highly variable light conditions or strong shadows on the road.

- There is glare, e.g. from oncoming traffic, direct sunlight or reflections.
- Insufficient illumination of the road.
- The windshield is dirty, fogged up, damaged or covered in the vicinity of the camera, e.g. by a sticker.
- No, or several, unclear lane markings are present for one lane, or the markings change quickly, such as in a construction area or at intersections.
- The lane markings are worn away, dark or covered up, e.g. by dirt or snow.
- If the distance to the vehicle in front is too short and thus the lane markings cannot be detected.
- · The road is narrow and winding.
- There are obstacles in the lane or projecting out into the lane, such as object markers.

The system does not provide assistance in the following conditions:

- · On tight bends and when turning.
- · When crossing intersections.

- At traffic circles or toll stations.
- · When towing a trailer.
- When the tire pressure is too low.
- Vehicles with E-ACTIVE BODY CONTROL: in drive program [CV] and at lean level 2 and 3

WARNING Risk of accident if Active Steering Assist unexpectedly stops functioning

If the system limits of Active Steering Assist are reached there is no guarantee that the system will remain active or will keep the vehicle in lane

- Always keep your hands on the steering wheel and observe the traffic carefully.
- Always steer the vehicle paying attention to traffic conditions.

WARNING Risk of accident if Active Steering Assist unexpectedly intervenes

The detection of lane markings and objects may malfunction and cause unexpected steering interventions.

Steer according to traffic conditions.

## Activating/deactivating Active Steering Assist

#### Requirements

- ESP® is activated, but is not intervening.
- · Active Distance Assist DISTRONIC is activated.

Multimedia system:

- → Settings → Quick Access
- ► Select Steering Assist.

## **Function of Active Emergency Stop Assist**



If the system detects that the driver has not steered the vehicle for a considerable period of time or has removed their hands from the steering wheel, display 
appears. If the driver still does not steer the vehicle, or gives no confirmation to the system, a warning tone sounds in addition to the visual warning message.

If the driver still does not respond to the warning. the Beginning Emergency Stop message appears in the Instrument Display. If the driver still does not respond. Active Distance Assist DISTRONIC reduces the speed. The vehicle is decelerated in stages to a standstill.

Depending on the country, at speeds below 40 mph (60 km/h) the hazard warning lights switch on automatically.

When the vehicle is stationary, the following actions are carried out:

- The vehicle is secured with the electric parking brake.
- Active Distance Assist DISTRONIC is ended.
- The vehicle is unlocked.

 If possible, an emergency call is placed to the Mercedes-Benz emergency call center.

The driver can cancel the deceleration at any time by performing one of the following actions:

- Steering
- · Braking or accelerating
- Deactivating Active Distance Assist DISTRONIC

### **Active Lane Change Assist**

## Function of Active Lane Change Assist

Active Lane Change Assist supports the driver when changing lanes by applying steering torque if the driver activates a turn signal indicator.

Observe the notes on driving systems and your responsibility; you may otherwise fail to recognize dangers ( $\rightarrow$  page 211).

Assistance when changing lanes is provided if all the following conditions are met:

You are driving on a freeway or road with multiple lanes in the direction of travel.

- The neighboring lane is separated by a broken lane marking.
- No vehicle is detected in the adjacent lane.
- The vehicle speed is between 50 mph (80 km/h) and 110 mph (180 km/h).
- Active Lane Change Assist is switched on in the multimedia system.
- · Active Steering Assist is activated and active.

If no vehicle is detected in the adjacent lane and a lane change is permitted, the lane change begins after the driver has activated the turn signal indicator. This is shown to the driver with a green arrow next to the steering wheel symbol. The message Lane Change to the Left, for example, also appears. If Active Lane Change Assist has been activated with the turn signal indicator but a lane change is not immediately possible, a gray arrow appears next to the steering wheel symbol, which remains green.

As soon as the lane change assistance starts, the turn signal indicator is automatically activated.

If the assistant display is shown when changing lanes, an additional arrow appears on it pointing towards the adjacent lane ( $\rightarrow$  page 222).

If a lane change is not possible, the arrow is faded out after a few seconds and a new lane change must be initiated. An immediate lane change is only possible on freeway sections without speed limits

If the system is impaired, Active Lane Change Assist may be canceled. If it is canceled, the Lane Change Canceled message appears on the instrument display.

In addition, a warning tone may sound, depending on the situation.

A

WARNING Risk of accident when changing lane to an occupied adjacent lane

Lane Change Assist cannot always clearly detect if the adjacent lane is free.

The lane change might be initiated although the adjacent lane is not free.

- ▶ Before changing lanes, make sure that the neighboring lane is free and there is no danger to other road users.
- Monitor the lane change.

## WARNING Risk of accident if Lane Change Assist unexpectedly stops functioning

If the system limitations for Lane Change Assist have been reached, there is no guarantee that the system will remain active.

Lane Change Assist cannot then assist you by applying steering torque.

► Always monitor the lane change and keep your hands on the steering wheel. Observe the traffic conditions and steer and/or brake if necessary.

#### System limits

The system limits of Active Steering Assist apply to Active Lane Change Assist ( $\rightarrow$  page 231).

The system may also be impaired or may not function in the following situations:

- The sensors in the rear bumper are dirty, damaged or covered by a sticker or ice and snow, for example.
- The exterior lighting shows a defect.
- The Active Lane Change Assist sensors adjust automatically while a certain distance is being driven after the vehicle has been delivered. Active Lane Change Assist is unavailable during this teach-in process; no arrow appears next to the Active Steering Assist symbol when the turn signal indicator is activated

## Selecting Active Lane Change Assist Multimedia system:

→ Settings → Assistance

- >> Active Lane Change Assist
- Select the function.

#### Active Brake Assist

#### ■ Function of Active Brake Assist

Active Brake Assist consists of the following functions:

- Collision warning
- · Autonomous braking function
- Situation-dependent brake force boosting
- Vehicles with Driving Assistance Package: Evasive Steering Assist and cornering function

Active Brake Assist can help you to minimize the risk of a collision with vehicles, cyclists or pedestrians or to reduce the effects of such a collision.

If Active Brake Assist has detected a risk of collision, a warning tone will sound and the Active Brake Assist warning lamp will light up.

Vehicles with PRE-SAFE®: depending on the country, an additional haptic warning will occur in the form of slight, repeated tensioning of the seat belt.

If you do not react to the warning, autonomous braking can be initiated in critical situations.

In especially critical situations, Active Brake Assist can initiate autonomous braking directly. In this case, the warning lamp and warning tone occur simultaneously with the braking application.

If you apply the brake yourself in a critical situation or apply the brake during autonomous braking, situation-dependent brake force boosting will occur. The brake pressure will increase up to maximum full-stop braking if necessary.

Observe the notes on driving systems and your responsibility; you may otherwise fail to recognize dangers ( $\rightarrow$  page 211).



If autonomous braking or situation-dependent brake force boosting has occurred, display (1) will

appear on the instrument display and then automatically disappear after a short time.

If the autonomous braking function or situation-dependent brake force boosting is triggered, additional preventive measures for occupant protection (PRE-SAFE®) may also be initiated.

A

WARNING Risk of an accident caused by limited detection performance of Active Brake Assist

Active Brake Assist cannot always clearly identify objects and complex traffic situations.

In such cases, Active Brake Assist might:

- Give a warning or brake without reason
- Not give a warning or not brake

Active Brake Assist is only an aid. The driver is responsible for maintaining a sufficiently safe distance to the vehicle in front, vehicle speed and for braking in good time.

Always pay careful attention to the traffic situation; do not rely on Active Brake Assist alone. Be prepared to brake or swerve if necessary.

If Active Brake Assist is deactivated or the functions are restricted, e.g. due to activation of another driving system, the of splay message will appear on the instrument display.

If the system is unavailable due to dirty or damaged sensors or due to a malfunction, or if the functions are restricted, the sign warning lamp will appear on the driver's display.

Also observe the system limits of Active Brake Assist.

## The individual subfunctions are available in various speed ranges

The distance warning function can issue a warning in the following situations:

 From approximately 4 mph (7 km/h), if your vehicle is critically close to a vehicle, cyclist or pedestrian, you will hear an intermittent warning tone and the distance warning lamp will light up on the instrument display.

Vehicles with PRE-SAFE®: depending on the country, an additional haptic warning will occur in the form of slight, repeated tensioning of the seat belt.

Brake immediately or take evasive action, provided it is safe to do so and the traffic situation. allows this

#### Collision warning (vehicles without Driving Assistance Package)

The collision warning can aid you in the following situations with an intermittent warning tone and a warning lamp:

- From approximately 4 mph (7 km/h), if your vehicle is critically close to a vehicle, cyclist or pedestrian, you will hear an intermittent warning tone and the distance warning lamp will light up on the instrument display.
  - Vehicles with PRE-SAFE®: depending on the country, an additional haptic warning will occur in the form of slight, repeated tensioning of the seat belt.
- At speeds up to approximately 155 mph (250 km/h) when approaching vehicles ahead

- At speeds up to approximately 50 mph (80 km/h) when approaching stationary vehicles, moving pedestrians, and cyclists ahead
- At speeds up to approximately 37 mph (60 km/h) when approaching crossing cyclists

## Collision warning (vehicles with Driving Assistance Package)

The collision warning can aid you in the following situations with an intermittent warning tone and a warning lamp:

- At speeds up to approximately 155 mph (250 km/h) when approaching vehicles ahead
- At speeds up to approximately 62 mph (100 km/h) when approaching stationary vehicles
- At speeds up to approximately 50 mph (80 km/h) when approaching moving pedestrians and cyclists ahead
- At speeds up to approximately 43 mph (70 km/h) when approaching stationary pedestrians, crossing vehicles and stationary and crossing cyclists

## Autonomous braking function (vehicles without Driving Assistance Package)

If the vehicle is traveling at speeds above approximately 4 mph (7 km/h), the autonomous braking function may intervene in the following situations:

- At speeds up to approximately 124 mph (200 km/h) when approaching vehicles ahead
- At speeds up to approximately 50 mph (80 km/h) when approaching cyclists ahead
- At speeds up to approximately 37 mph (60 km/h) when approaching moving pedestrians, crossing cyclists, and stationary vehicles

### Autonomous braking function (vehicles with Driving Assistance Package)

If the vehicle is traveling at speeds above approximately 4 mph (7 km/h), the autonomous braking function may intervene in the following situations:

- At speeds up to approximately 155 mph (250 km/h) when approaching vehicles ahead
- At speeds up to approximately 62 mph (100 km/h) when approaching stationary vehicles

- At speeds up to approximately 50 mph (80 km/h) when approaching cyclists ahead
- At speeds up to approximately 43 mph (70 km/h) when approaching stationary and moving pedestrians, crossing vehicles and stationary and crossing cyclists

## Situation-dependent brake force boosting (vehicles without Driving Assistance Package)

Situation-dependent brake force boosting may intervene from a speed of approximately 4 mph (7 km/h) in the following situations:

- At speeds up to approximately 155 mph (250 km/h) when approaching vehicles ahead
- At speeds up to approximately 50 mph (80 km/h) when approaching stationary vehicles and cyclists ahead
- At speeds up to approximately 37 mph (60 km/h) when approaching moving pedestrians and crossing cyclists

## Situation-dependent brake force boosting (vehicles with Driving Assistance Package)

Situation-dependent brake force boosting may intervene from a speed of approximately 4 mph (7 km/h) in the following situations:

- At speeds up to approximately 155 mph (250 km/h) when approaching vehicles ahead
- At speeds up to approximately 62 mph (100 km/h) when approaching stationary vehicles
- At speeds up to approximately 50 mph (80 km/h) when approaching cyclists ahead
- At speeds up to approximately 37 mph (60 km/h) when approaching stationary and moving pedestrians, crossing vehicles, and stationary and crossing cyclists

## Canceling a brake application of Active Brake Assist

You can cancel a brake application of Active Brake Assist at any time by:

- sharply depressing the accelerator pedal or with kickdown
- · releasing the brake pedal

Active Brake Assist may cancel the brake application when one of the following conditions is fulfilled:

- You maneuver to avoid an obstacle
- There is no longer a risk of collision
- An obstacle is no longer detected in front of your vehicle

## Evasive Steering Assist (only vehicles with Driving Assistance Package)

Evasive Steering Assist has the following characteristics:

- The ability to detect stationary or moving pedestrians.
- Assistance through power-assisted steering if a swerving maneuver is detected.
- Activation through an abrupt steering movement during a swerving maneuver.
- Assistance during swerving and straightening of the vehicle.
- Reaction from a speed of approximately 12 mph (20 km/h) up to a speed of approximately 43 mph (70 km/h).

You can prevent the assistance at any time by actively steering.

### Cornering function (only vehicles with Driving Assistance Package)

If the system detects a risk of a collision with an oncoming vehicle when turning across an oncoming lane, autonomous braking can be initiated at speeds below 9 mph (15 km/h) before you have left the lane in which you are driving.

#### WARNING Risk of accident despite Evasive Steering Assist

Evasive Steering Assist cannot always recognize objects or complex traffic situations clearly.

Moreover, the steering support provided by Evasive Steering Assist is not sufficient to avoid a collision.

- Always pay careful attention to the traffic situation; do not rely on Evasive Steering Assist alone.
- Be prepared to brake or swerve if necessary.

- ► End the support by actively steering in non-critical situations
- Drive at an appropriate speed if there are pedestrians close to the path of your vehicle.

#### System limits

Full system performance is not available for a short time after switching on the vehicle or after driving off. Depending on the environmental conditions, it may take a few minutes before full system performance is available.

The system may be impaired or may not function. particularly in the following situations:

- In snow, rain, fog, heavy spray, direct sunlight or highly variable light conditions, or if there is glare.
- · If the sensors are dirty, fogged up, damaged or covered
- If the sensors are impaired due to interference from other radar sources, e.g. strong radar reflections in parking garages.
- If a loss of tire pressure or a defective tire has been detected and displayed.

- If DSR is active.
- In complex traffic situations where objects cannot always be clearly identified.
- If pedestrians or vehicles move quickly into the sensor detection range.
- If pedestrians are hidden by other objects.
- If the typical outline of a pedestrian cannot be distinguished from the background.
- If a pedestrian is not detected as such, e.g. due to special clothing or other objects.
- If the driver's seat belt is not fastened.
- · On bends with a tight radius.
- (i) The Active Brake Assist sensors adjust automatically while a certain distance is being driven after the vehicle has been delivered. Active Brake Assist is unavailable or only partially available during the teach-in process.

### Activating/deactivating Active Brake Assist

### Requirements

The vehicle is switched on.

#### Multimedia system:

→ Settings → Assistance

- > Active Brake Assist
- Select the desired setting.

#### Deactivating Active Brake Assist

- i It is recommended that you always leave Active Brake Assist activated
- Select Off.

The distance warning function, the autonomous braking function and Evasive Steering Assist are deactivated.

The system is switched on again the next time the vehicle is started.

i) If Active Brake Assist is deactivated, the symbol appears in the status bar of the Instrument Display.

#### Traffic Sign Assist

## ■ Function of Traffic Sign Assist

Traffic Sign Assist detects traffic signs with the multifunction camera ( $\rightarrow$  page 211). It assists

you by displaying detected speed limits and overtaking restrictions in the Instrument Display.

Observe the notes on driving systems and your responsibility; you may otherwise fail to recognize dangers ( $\rightarrow$  page 211).


Since Traffic Sign Assist also uses the data stored in the navigation system, it can update the display in the following situations without detecting traffic signs.

The camera also detects traffic signs with a restriction indicated by an additional sign (e.g. when wet). These are only displayed if a restriction applies or if the system cannot clearly determine whether the restriction applies.

## Warning when the maximum permissible speed is exceeded

The system can warn you if you unintentionally exceed the maximum permissible speed. Depending on the country, you can set in the multimedia system by how much the maximum permitted speed may be exceeded before a warning is given. You can specify whether the warning is to be just a visual warning or an acoustic one as well.

## Display in the Instrument Display



Instrument display in the widescreen cockpit

- Maximum permissible speed
- Maximum permissible speed when there is a restriction
- 3 Additional sign with restriction

The system can show up to two traffic signs simultaneously. The system always prioritizes displaying speed limits. Up to one traffic sign with a maximum permissible speed can be shown in the head-up display. If two speed signs are shown in the driver display, e.g. in the case of detected restrictions, the value of the left-hand speed limit

1 is always transmitted to the TEMPOMAT or

Active Distance Assist DISTRONIC for acceptance and shown in the head-up display.

(i) Vehicles with a standard Instrument Display: a + symbol next to a traffic sign in the Instrument Display indicates that additional traffic signs have been detected. These can also be displayed in the media display and optionally in the head-up display.

If Traffic Sign Assist cannot determine the maximum permissible speed (e.g. due to missing signs), the following display appears:

This is displayed continuously if the vehicle is in a country where Traffic Sign Assist is not supported. Traffic Sign Assist is not available in all countries.

(i) Also observe the information on display messages in Traffic Sign Assist ( $\rightarrow$  page 428).

## System limits

The system may be impaired or may not function particularly in the following situations:

- If there is poor visibility, e.g. due to insufficient illumination of the road, highly variable shade conditions, rain, snow, fog or heavy spray.
- If there is glare, e.g. from oncoming traffic. direct sunlight or reflections.
- If there is dirt on the windshield in the vicinity of the multifunction camera or if the camera is fogged up, damaged or obscured.
- If the traffic signs are hard to detect, e.g. due to dirt, snow or insufficient lighting, or because they are obscured.
- If the information on the navigation system's digital map is incorrect or out of date.
- If signs are ambiguous, e.g. road signs in roadworks or in adjacent lanes.
- If you turn sharply when passing traffic signs outside the camera's field of vision.

## Setting Traffic Sign Assist

#### Requirements:

 Only vehicles with Driving Assistance Package: Active Distance Assist DISTRONIC and ECO Assist must be activated for the automatic adoption of speed limits.

#### Multimedia system:

→ 🔝 >> Settings >> Assistance >> Traffic Sign Assist

### Activating or deactivating automatic adoption of speed limits (only vehicles with Driving Assistance Package)

- Select Limit Adoption.
- Switch the function on or off. The speed limits detected by Traffic Sign Assist are automatically adopted by Active Distance Assist DISTRONIC.
- i) If one of the following systems is activated. the detected speed can be manually adopted as the speed limit:
  - Active Distance Assist DISTRONIC
  - Cruise control

Variable limiter

Further information about Active Distance Assist DISTRONIC: ( $\rightarrow$  page 224).

### Displaying detected traffic signs in the media display

- Select Display in Central Display.
- Switch the function on or off.

## Setting the type of warning

► Select Visual & Audible, Visual or Off.

#### Setting the warning threshold

This value determines the speed at which a warning is issued when exceeded.

- Select Warning Threshold.
- Set the desired speed.

## Blind Spot Assist and Active Blind Spot Assist with exit warning

# Function of Blind Spot Assist and Active Blind Spot Assist with exit warning

Blind Spot Assist and Active Blind Spot Assist use two lateral, rear-facing radar sensors to monitor

the area up to 130 ft (40 m) behind and 10 ft (3 m) next to your vehicle.

If a vehicle is detected at speeds above approximately 8 mph (12 km/h) and this vehicle subsequently enters the monitoring range directly next to your vehicle, the warning lamp in the outside mirror lights up red.

#### Status display:

- (gray): system is activated but inoperative
- (green): system is activated and operational

If a vehicle is detected close to your vehicle and you switch on the turn signal indicator in the corresponding direction, a double warning tone sounds and the red warning lamp in the outside mirror flashes. If the turn signal indicator remains switched on, all other detected vehicles are indicated only by the flashing of the red warning lamp.

If you overtake a vehicle quickly, no warning is given.

# **WARNING** Risk of accident despite Active Blind Spot Assist

Active Blind Spot Assist does not react to the following:

- if you overtake a vehicle too closely so that it is in the blind spot area
- if vehicles traveling at a much faster speed approach and then overtake

Active Blind Spot Assist may not give warnings or intervene in such situations.

Always pay careful attention to the traffic situation and maintain a safe distance at the side of the vehicle.

Observe the notes on driving systems and your responsibility; you may otherwise fail to recognize dangers ( $\rightarrow$  page 211).

## Exit warning

The exit warning is an additional function of Blind Spot Assist and can warn vehicle occupants about approaching vehicles when leaving the vehicle when stationary.

## WARNING Risk of accident despite exit warning

The exit warning neither reacts to stationary objects nor to persons or road users approaching you at a greatly differing speed.

The exit warning cannot warn drivers in these situations.

Always pay particular attention to the traffic situation when opening the doors and make sure there is sufficient clearance.

If there is a vehicle in the monitoring range, this is indicated in the outside mirror. If a vehicle occupant opens the door on the side with the warning. a warning tone sounds and the warning lamp in the outside mirror starts to flash.

This additional function is available only when Blind Spot Assist is active. When the exit warning is activated, it can warn vehicle occupants for up to three minutes after switching the vehicle off. The exit warning is no longer available once the warning lamp in the outside mirror flashes three times.

The exit warning is only an aid and not a substitute for the attention of vehicle occupants. The responsibility for opening and closing the doors and for leaving the vehicle remains with the vehicle occupants.

#### System limits

Blind Spot Assist and Active Blind Spot Assist may be limited in the following situations, in particular:

- if there is dirt on the sensors or the sensors are obscured
- in poor visibility, e.g. due to fog, heavy rain or snow
- if there are narrow vehicles, e.g. bicycles or motorbikes
- if the road has very wide or narrow lanes
- if vehicles are not driving in the middle of their lane

Warnings may be issued in error when driving close to crash barriers or similar continuous lane borders. Always make sure that there is sufficient distance to the side for other traffic or obstacles.

Warnings may be interrupted when you are driving alongside long vehicles (e.g. trucks) for a prolonged time.

Blind Spot Assist is not operational when reverse gear is engaged.

Blind Spot Assist and the exit warning are not operational when a trailer is coupled to the vehicle and the electrical connection has been correctly established.

The exit warning may be limited in the following situations:

- · when the sensors are covered by adjacent vehicles in narrow parking spaces
- when people approach the vehicle
- in the event of stationary or slowly moving objects

## Function of brake application (Active Blind Spot Assist)

If Active Blind Spot Assist detects a risk of a side impact in the monitoring range, a course-correcting brake application is carried out. This is designed to help you avoid a collision.

The course-correcting brake application is available in the speed range between approximately 20 mph (30 km/h) and 125 mph (200 km/h).

**WARNING** Risk of accident despite brake application of Active Blind Spot Assist

A course-correcting brake application cannot always prevent a collision.

- Always steer, brake or accelerate yourself, especially if Active Blind Spot Assist warns you or makes a course-correcting brake application.
- Always maintain a safe distance at the sides.



If a course-correcting brake application occurs, the red warning lamp flashes in the outside mirror and a warning tone sounds. In addition, display

indicating the danger of a side collision appears in the Instrument Display.

In rare cases, the system may make an inappropriate brake application. This brake application may be interrupted at any time if you steer slightly in the opposite direction or accelerate.

#### System limits

Note the system limitations of Active Blind Spot Assist; you may otherwise not recognize the dangers (→ page 242).

Either a course-correcting brake application appropriate to the driving situation, or none at all, may occur in the following situations:

- Vehicles or obstacles, e.g. crash barriers, are located on both sides of your vehicle.
- A vehicle approaches too closely on the side.
- You have adopted a sporty driving style with high cornering speeds.
- You brake or accelerate significantly.

- A driving safety system intervenes, e.g. ESP<sup>®</sup> or Active Brake Assist.
- ESP<sup>®</sup> is deactivated.
- A loss of tire pressure or a defective tire is detected
- You are driving with a trailer and the electrical connection to the trailer hitch has been correctly established.
- Activating/deactivating Blind Spot Assist or Active Blind Spot Assist Multimedia system:
- → Settings → Assistance
- Activate or deactivate Blind Spot Assist.
- Activate or deactivate Act. Blind Spot Assist.

## Active Lane Keeping Assist

■ Function of Active Lane Keeping Assist

Active Lane Keeping Assist monitors the area in front of your vehicle by means of a multifunction camera (→ page 211). It serves to protect you

against unintentionally leaving your lane. You will be warned by vibration pulses in the steering wheel and guided back into your lane by a coursecorrecting brake application.

Active Lane Keeping Assist is available in the speed range between 37 mph (60 km/h) and 124 mph (200 km/h).

Active Lane Keeping Assist can neither reduce the risk of an accident if you fail to adapt your driving style nor override the laws of physics. It cannot take into account road, weather or traffic conditions. Active Lane Keeping Assist is only an aid. You are responsible for maintaining a safe distance, for vehicle speed, for braking in good time and for staying in lane.

The status of Active Lane Keeping Assist is displayed in the on-board computer:

- (green): Active Lane Keeping Assist is active and operating.
- /=\ (gray): Active Lane Keeping Assist is active but not operating.
- ted or there is a malfunction.



If a lane-correcting brake application occurs, display 
 will appear on the instrument display.

The system does not apply the brake on the corresponding side if you activate the turn signal indicator.

Vehicles with Driving Assistance Package: if the system detects an obstacle, such as another vehicle in the adjacent lane, it will apply the brake regardless of the turn signal indicator.

You will be warned by vibrations in the steering wheel in the following circumstances:

- Active Lane Keeping Assist detects a lane marking.
- A front wheel drives over this lane marking.

Conditions for a course-correcting brake application (vehicles without Driving Assistance Package) Lane markings were detected on both sides of the lane. The front wheel drives over a continuous lane marking.

(i) A brake application may be interrupted at any time by steering slightly in the opposite direction

## Conditions for a course-correcting brake application (vehicles with Driving Assistance Package)

- A continuous lane marking was detected and driven over with the front wheel
- A lane marking and an oncoming vehicle, an overtaking vehicle or vehicles driving parallel to your vehicle were detected in the adjacent lane. The front wheel drives over the lane marking.
- (i) A brake application may be interrupted at any time by steering slightly in the opposite direction.

#### System limits

No lane-correcting brake application will occur in the following situations:

- You clearly and actively steer, brake or accelerate.
- If a driving safety system intervenes, such as ESP<sup>®</sup>, Active Brake Assist or Active Blind Spot Assist.
- You have adopted a sporty driving style with high cornering speeds or high rates of acceleration.
- When ESP® is deactivated.
- When you are driving with a trailer and the electrical connection to the trailer has been correctly established.
- If a loss of tire pressure or a defective tire is detected and displayed.

If you deactivate the Active Lane Keeping Assist warning and the lane markings were not clearly detected, it is possible that no lane-correcting brake application will take place ( $\rightarrow$  page 246).

The system may be impaired or may not function particularly in the following situations:

- If there is poor visibility, e.g. due to insufficient illumination of the road, highly variable shade conditions, rain, snow, fog or heavy spray.
- If there is glare, e.g. from oncoming traffic, the sun or reflections.
- If there is dirt on the windshield in the vicinity of the multifunction camera or if the camera is fogged up, damaged or obscured.
- If there are no lane markings or several unclear lane markings are present for one lane, e.g. around roadworks.
- If the lane markings are worn, dark or covered.
- If the distance to the vehicle in front is too short and thus the lane markings cannot be detected.
- If the lane markings change quickly, e.g. lanes branch off, cross one another or merge.
- If the road is very narrow and winding.
- Vehicles with Driving Assistance Package: if the radar sensors in the rear bumper are dirty

or covered in snow and an obstacle is detected in your lane, no lane-correcting brake application takes place.

## Activating/deactivating Active Lane Keeping Assist

Multimedia system:

- → 🔝 >> Settings >> Quick Access
- ➤ Active Lane Keeping Assist
- Activate or deactivate the function.
- Setting Active Lane Keeping Assist Multimedia system:
- → 🔝 **>>** Settings **>>** Assistance
- ➤ Active Lane Keeping Assist

## Activating or deactivating the haptic warning

- Select Warning.
- Activate or deactivate the function.

#### **AIRMATIC**

#### ■ Function of AIRMATIC

- **NOTE** Mercedes-AMG vehicles
- Observe the notes in the Supplement. You could otherwise fail to recognize dangers.

AIRMATIC is an air suspension system with an allround level control system, which also ensures the best possible suspension and constant ground clearance, even with a laden vehicle. When driving at speed, the vehicle is lowered automatically to improve driving safety and to reduce fuel consumption. You also have the option of manually adjusting the vehicle level.

AIRMATIC includes the following components and functions:

- all-round air suspension
- · speed-dependent lowering of the vehicle level
- via the level button ( rocker switch) a higher vehicle level can be selected for greater ground clearance

- · Vehicles with ADS PLUS: also Adaptive Damping System with constant adjustment of damping characteristics for improved driving comfort
- Operation with a trailer or bicycle rack: if transport equipment, such as a trailer or a bicycle rack, is attached to the trailer hitch and the electrical connection has been correctly established, the vehicle always remains at normal level in all drive programs with the exception of and . In drive programs and , the vehicle is lowered above speeds of approx. 19 mph (30 km/h)to normal level.

## Differences between different vehicle levels compared to the normal level:

Vehicles without Off-road package

- · Car wash level:
  - Approx. +3.5 in (+90 mm)
- Off-road level +1:
  - Mercedes-Maybach vehicles: +2.0 in (+50 mm)
  - All other models: +2.4 in (+60 mm)

- Sport:
  - Approx. -0.6 in (-15 mm)
- Sport + or entry/exit level:
  - Approx. -1.0 in (-25 mm)

Vehicles with Off-road package

- Off-road level +3 or car wash level:
  - Approx. +3.5 in (+90 mm)
- Off-road level +2:
  - Approx. +2.4 in (+60 mm)
- Off-road level +1:
  - Approx. +1.2 in (+30 mm)
- Sport:
  - Approx. -0.6 in (-15 mm)
- Sport + or entry/exit level:
  - Approx. -1.0 in (-25 mm)

When car wash mode is activated, the vehicle is raised to a significantly higher level for automated car washes. When driving at speeds above approximately 12 mph (20 km/h) car wash mode is deactivated and the vehicle lowered to the vehicle level previously set ( $\rightarrow$  page 346).

If the entry/exit level function is activated, the vehicle is lowered to the Sport + level to facilitate entering/exiting the vehicle. When driving at speeds of approximately 19 mph (30 km/h) or above, the entry/exit level is deactivated and the vehicle is raised ( $\rightarrow$  page 251).

## System limits

AIRMATIC may not be available or have only limited availability in the following cases:

 The overheating protection has been activated due to frequent level changes within a short time. The same warning lamp appears in the Instrument Display.

After the cooling phase, the system is again available without restriction.

## Setting the vehicle level (vehicles with AIR-MATIC)

**WARNING** Risk of accident because vehicle level is too high

Driving characteristics may be impaired.

The vehicle can drift outwards, for example, when steering or cornering.

Choose a vehicle level which is suited to the driving style and the road surface conditions.

**WARNING** Risk of entrapment from vehicle lowering

When lowering the vehicle, people could become trapped if their limbs are between the vehicle body and the tires or underneath the vehicle.

Make sure no one is underneath the vehicle or in the immediate vicinity of the wheel arches when the vehicle is being lowered.

**WARNING** Risk of becoming trapped due to the vehicle lowering

Vehicles with AIRMATIC or level control: when you unload luggage or leave the vehicle, the vehicle first rises slightly and then returns to the set level shortly afterwards.

You or anyone else in the vicinity of the wheel arches or the underbody could thus become trapped.

The vehicle can also be lowered after being locked.

- When leaving the vehicle, make sure that nobody is in the vicinity of the wheel arches or the underbody.
- I NOTE Damage due to vehicle lowering


Parts of the body could be damaged when the vehicle is lowered.

- Make sure that there are no obstacles such as curbs underneath or in the immediate vicinity of the body when the vehicle is being lowered.
- **NOTE** Mercedes-AMG vehicles
- Observe the notes in the Supplement.
   You could otherwise fail to recognize dangers.

## Requirements

- The vehicle has been started.
- · Vehicles without Off-road package:
  - The vehicle is not moving faster than 37 mph (60 km/h).
- · Vehicles with Off-road package:
  - Off-road level +1: the vehicle is not moving faster than 62 mph (100 km/h).
  - Off-road level +2: the vehicle is not moving faster than 40 mph (65 km/h).
  - Off-road level +3: the vehicle is not moving faster than 12 mph (20 km/h) and the rear fog lamp is not switched on.
- When operating with a trailer or bicycle rack and the trailer socket is correctly contacted:
  - The vehicle is being driven no faster than 19 mph (30 km/h).
- i) Use the normal level in trailer operation. Highlevel driving is not permitted in trailer operation on public roads.

## Raising the vehicle (vehicles without Off-road package)



Push rocker switch (1) forwards. Indicator lamp (2) flashes while the vehicle is being raised to off-road level +1 and lights up continuously when the raising process is complete.

Off-road level +1 set remains stored even after the vehicle has been switched off


The vehicle is lowered again to the vehicle level of the selected drive program in the following situations:

- When driving faster than 50 mph (80 km/h).
- When driving briefly between 40 mph (65 km/h) and 50 mph (80 km/h).
- You select a different drive program.

## Lowering the vehicle (vehicles without Off-road package)

Pull rocker switch 1. The vehicle is lowered to the height of the currently selected drive program. Indicator lamp 2 flashes while the vehicle is being lowered and goes out when the lowering process is complete.

## Raising the vehicle (vehicles with Off-road package)



Push rocker switch forwards. The vehicle rises to the next higher vehicle level. Following indicator lamps ② flash while the vehicle is being raised and light up continuously when the raising process is complete.

- Off-road level +1: one indicator lamp
- Off-road level +2: two indicator lamps
- Off-road level +3: three indicator lamps

The off-road level set remains stored even after the vehicle has been switched off.

In the following situations, the vehicle is lowered to the next lower vehicle level:

- In off-road level +3:
  - When driving faster than 12 mph (20 km/h).
  - You switch on the rear fog lamps.
- In off-road level +2:
  - When driving faster than 50 mph (80 km/h).
  - When driving briefly between 40 mph (65 km/h) and 50 mph (80 km/h).
- In off-road level +1:

- When driving faster than 68 mph (110 km/h).
- When driving briefly between 62 mph (100 km/h) and 68 mph (110 km/h).
- (i) If you select a different drive program, the vehicle is lowered to the vehicle level of the selected drive program.

## Lowering the vehicle (vehicles with Off-road package)

Pull rocker switch ①.

The vehicle is lowered to the next lower vehicle level. Indicator lamps ② of the currently selected off-road gear flash while the vehicle is being lowered.

Following indicator lamps ② light up continuously when the lowering process is complete.

- Off-road level +2: two indicator lamps
- · Off-road level +1: one indicator lamp
- Normal level: no indicator lamp

The vehicle level set remains stored even after the vehicle has been switched off.

### Setting the entering and exiting level (AIR-MATIC)

#### Requirements

- The vehicle has been started.
- · The vehicle is moving at speeds below 20 mph (30 km/h).

#### Multimedia system:

- ¬→ 🔝 >> Settings
- >> Schnellzugriff (Quick access)
- Select Lower When Getting In On. The vehicle is lowered to low level -2 to facilitate entering and exiting. The selection is stored and the entry/exit level remains stored even after the vehicle is switched off.

In the following situations, the vehicle will be raised to the currently selected vehicle level:

- Entry/Exit Lowering OFF is selected.
- After restarting, the vehicle is moving faster than 20 mph (30 km/h).
- (i) The availability of this function depends on the vehicle equipment.

(i) Further information on AIRMATIC  $(\rightarrow page 247)$ .

# Lowering and raising the rear of the vehicle

WARNING Risk of entrapment from vehicle lowering


When lowering the vehicle, people could become trapped if their limbs are between the vehicle body and the tires or underneath the vehicle.

Make sure no one is underneath the vehicle or in the immediate vicinity of the wheel arches when the vehicle is being lowered

### Requirements:

- · all vehicle doors are closed
- there is no trailer coupled
- there is no bicycle rack installed
- the battery is sufficiently charged (if necessary, start the engine)

# Lowering the rear of the vehicle



- Apply the electric parking brake.
- Shift the transmission to position **P**  $(\rightarrow page 196)$ .
- Pull switch 1 in the load compartment trim briefly.

Indicator lamp (2) flashes until the vehicle has been lowered.

The vehicle is lowered at the rear axle by approx. 1.5 in (40 mm). When the vehicle has been lowered, indicator lamp ② remains lit.

Lowering is interrupted in the following situations:

- a vehicle door is opened.
- switch (1) is pulled again.
- the vehicle is being driven faster than 1.2 mph (2 km/h).
- (i) The vehicle is automatically set to the level of the drive program selected if you drive at speeds greater than 1.2 mph (2 km/h).

speeds greater than 1.2 mpn (2 km/n).

If indicator lamp ② flashes twice and the rear of the vehicle does not lower:

- Make sure that the requirements are met.
- (i) Lowering the rear of the vehicle allows the vehicle to be loaded more easily. Observe the notes on loading the vehicle when doing this (→ page 126).

# Raising the rear of the vehicle

Check if the battery is sufficiently charged. If necessary, start the engine.

- Pull switch ① briefly.Indicator lamp ② goes out.
  - The vehicle will be raised to the currently selected level.
- The vehicle is automatically set to the level of the drive program selected if you drive at speeds greater than 1.2 mph (2 km/h).

If the vehicle cannot be raised:

 Ensure that the battery is sufficiently charged; if necessary, start the engine.
 The raising process continues.

#### E-ACTIVE BODY CONTROL

- Function of E-ACTIVE BODY CONTROL
- ! NOTE Mercedes-AMG vehicles
- Observe the notes in the Supplement. You could otherwise fail to recognize dangers.

E-ACTIVE BODY CONTROL is an electrohydraulic suspension system with variable damping for improved driving comfort. The all-round level con-

trol system ensures the best possible suspension and constant ground clearance, even with a laden vehicle. When driving at speed, the vehicle is lowered automatically to improve driving safety and to reduce energy consumption. The suspension setting is adjusted depending on the road surface, vehicle load and the drive program selected. In addition, there is the option of setting the vehicle level manually.

The ROAD SURFACE SCAN function detects areas of unevenness in the road before you drive over them by means of a multifunction camera. This reduces chassis movements.

The damping is adjusted individually to each wheel and depends on the following factors:

- Driving style, e.g. sporty
- Road condition, e.g. bumps
- · Drive program

E-ACTIVE BODY CONTROL is comprised of the following functions and components:

- Vehicles with Driving Assistance Package: ROAD SURFACE SCAN
- · Curve inclination function CURVE

- · Recovery mode
- Individual wheel control
- Air suspension with automatic level control
- speed-dependent lowering of the vehicle level
- via the level button (ভিন্ত rocker switch) a higher vehicle level can be selected for greater ground clearance
- ADS PLUS (Adaptive Damping System with constant adjustment of damping characteristics)

# Suspension setting and vehicle level per drive program

Drive program S

- The suspension setting is firmer.
- The vehicle is set to Sport level.
- ROAD SURFACE SCAN is deactivated.
- The curve inclination function is deactivated.

# Drive program St

- The suspension setting is even firmer.
- The vehicle is set to Sport + level.

- ROAD SURFACE SCAN is deactivated.
- The curve inclination function is active.

# Drive program C

- The suspension setting is comfortable.
- The vehicle is set to the normal level.
- When driving at speeds above approximately 87 mph (140 km/h), the vehicle is lowered.
- When driving at speeds below approximately 25 mph (40 km/h), the vehicle is raised.
- · ROAD SURFACE SCAN is active.
- The curve inclination function is deactivated.

# Drive program C

- The suspension setting is very comfortable.
- The vehicle is set to the normal level.
- When driving at speeds above approximately 87 mph (140 km/h), the vehicle is lowered.
- When driving at speeds below approximately 25 mph (40 km/h), the vehicle is raised.
- ROAD SURFACE SCAN is active.
- The curve inclination function is active.

# Drive program CV

- The suspension setting is comfortable.
- The vehicle is set to the normal level
- When driving at speeds above approximately 87 mph (140 km/h), the vehicle is lowered.
- When driving at speeds below approximately 25 mph (40 km/h), the vehicle is raised again.
- ROAD SURFACE SCAN is active.
- The curve inclination function is active.

# Drive program **E**

- The suspension setting is comfortable.
- The vehicle is set to the normal level.
- When driving at speeds above approximately 87 mph (140 km/h), the vehicle is lowered.
- When driving at speeds below approximately 25 mph (40 km/h), the vehicle is raised again.
- ROAD SURFACE SCAN is deactivated.
- · The curve inclination function is deactivated.

# Drive program 🖘

- The suspension setting is suitable for easily negotiable off-road terrain.
- The vehicle is set to off-road level +1.
- · ROAD SURFACE SCAN is deactivated.
- The curve inclination function is deactivated.
- When the necessary conditions are met, recovery mode and individual wheel control can be activated.
- · Vehicles without Off-road package:
  - When driving at speeds above approximately 50 mph (80 km/h) the vehicle is lowered.
  - When driving at speeds below approximately 28 mph (45 km/h), the vehicle is raised.
- · Vehicles with Off-road package:
  - When driving at speeds above approximately 71 mph (115 km/h), the vehicle is lowered.

 When driving at speeds below approximately 47 mph (75 km/h), the vehicle is raised.

# Drive program 💫

- The suspension setting is suitable for difficult off-road terrain.
- The vehicle is set to off-road level +1.
- When driving at speeds above approximately 50 mph (80 km/h), the vehicle is lowered.
- When driving at speeds below approximately 28 mph (45 km/h), the vehicle is raised.
- ROAD SURFACE SCAN is deactivated.
- The curve inclination function is deactivated.
- Recovery mode or individual wheel control can be activated.

# Drive program [\*

- You can call up individual suspension settings here.
- (i) Operation with a trailer or bicycle rack: if transport equipment, such as a trailer or a bicycle rack, is attached to the trailer hitch

and the electrical connection has been correctly established, the curve inclination function is off and the vehicle always remains at normal level in all drive programs with the exception of and . In drive programs and . In drive programs and . The vehicle is lowered above speeds of approx. 19 mph (30 km/h)to normal level.

# Differences between different vehicle levels compared to the normal level:

Vehicles without Off-road package

- · Car wash level:
  - Approx. +3.5 in (+90 mm)
- Off-road level +1:
  - Mercedes-Maybach vehicles: +2.0 in (+50 mm)
  - All other models: +2.4 in (+60 mm)
- · Sport:
  - Approx. -0.6 in (-15 mm)
- · Sport + or entry/exit level:
  - Approx. -1.0 in (-25 mm)

Vehicles with Off-road package

- Off-road level +3 or car wash level:
  - Approx. +3.5 in (+90 mm)
- Off-road level +2:
  - Approx. +2.4 in (+60 mm)
- Off-road level +1:
  - Approx. +1.2 in (+30 mm)
- · Sport:
  - Approx. -0.6 in (-15 mm)
- Sport + or entry/exit level:
  - Approx. -1.0 in (-25 mm)

When car wash mode is activated, the vehicle is raised to a significantly higher level for automated car washes. When driving at speeds above approximately 12 mph (20 km/h) car wash mode is deactivated and the vehicle lowered to the vehicle level previously set ( $\rightarrow$  page 346).

(i) Car wash level is 1.3 in (30 mm) above the maximum vehicle height (off-road level). Take note of the significantly higher vehicle level in car wash mode, particularly when driving into underground car parks, in order to avoid possible damage.

If the entry/exit level function is activated, the vehicle is lowered to the Sport + level to facilitate entering/exiting the vehicle. When driving at speeds of approximately 19 mph (30 km/h) or above, the entry/exit level is deactivated and the vehicle is raised ( $\rightarrow$  page 251).

#### System limits

E-ACTIVE BODY CONTROL may not be available or have only limited availability in the following cases:

• The overheating protection has been activated due to frequent level changes within a short time. The warning lamp appears in the Instrument Display.

After the cooling phase, the system is again available without restriction.

#### ■ Function of ROAD SURFACE SCAN

(i) This function is not available in all countries. The ROAD SURFACE SCAN function monitors the road in front of your vehicle using a multifunction

camera (→ page 211). ROAD SURFACE SCAN detects unevenness in the road surface, e.g. bumps, before the vehicle drives over them. Chassis movements are reduced and driving comfort is increased.

ROAD SURFACE SCAN is automatically activated if the following conditions are met:

- Drive program C or CV is selected.
- The vehicle is set to the normal level.
- You are driving at a speed between 4 mph (7 km/h) and 112 mph (180 km/h).

# System limits

ROAD SURFACE SCAN may be impaired or may not function in the following situations:

- If the road is insufficiently lit, e.g. at night.
- · In snow, rain, fog, heavy spray, direct sunlight or highly variable light conditions, or if there is glare.
- If the windshield in the area of the multifunction camera is dirty, fogged up, damaged or covered.

- If the road surface has no optical structure or reflects light.
- If you are driving too close to the vehicle in front.
- If sections of the route have a very small radius of curvature.
- During abrupt driving maneuvers, e.g. heavy braking or sudden acceleration.

Observe the notes on cleaning the multifunction camera ( $\rightarrow$  page 349).

# Function of recovery mode

WARNING Risk of injury due to the vehicle moving up and down

During recovery mode, the vehicle moves up and down and can cause injuries.

When activating recovery mode, make certain that no one is in the vicinity of the vehicle. ! NOTE Risk of damage due to the vehicle moving up and down

When recovery mode is activated, the vehicle springs back in and out automatically and thus moves up and down. Bottoming out can damage the underbody.

Make sure that when recovery mode is activated, there is sufficient ground clearance.

Recovery mode is a function of the suspension which can assist the driver on loose surfaces (e.g. sand, snow) when freeing a vehicle which has become stuck.

The vehicle body rocks in slow, vertical motions when recovery mode has been activated. This temporarily puts the wheels under greater load, which means they have increased traction and the vehicle is freed.

You can activate free driving mode via Off-road Assist ( $\rightarrow$  page 260).

#### Function of individual wheel control

A

**WARNING** Risk of becoming trapped due to the vehicle lowering

The vehicle can be lowered when the individual wheel control function has been activated. Body parts could become trapped if they are between the vehicle body and the tires or underneath the vehicle.

- Make sure that nobody is under the vehicle or in the immediate vicinity of the wheel arches when individual wheel control is activated.
- NOTE Risk of damage due to the vehicle moving up and down

The vehicle can be lowered or raised on one or more wheels when the individual wheel control function has been activated. Vehicle parts could be damaged due to contact with objects.

Make sure that the vehicle has sufficient. room to move when the individual wheel control function has been activated.

Individual wheel control is a function of the suspension, which can be used to set the vehicle level for each wheel individually. This can help to improve alignment of the body when driving offroad.

You can activate individual wheel control via Offroad Assist ( $\rightarrow$  page 260).

# Adjusting the vehicle level (vehicles with E-ACTIVE BODY CONTROL)

WARNING Risk of accident because vehicle level is too high

Driving characteristics may be impaired.

The vehicle can drift outwards, for example, when steering or cornering.

Choose a vehicle level which is suited to the driving style and the road surface conditions.

**A** WARNING Risk of entrapment from vehicle lowering

When lowering the vehicle, people could become trapped if their limbs are between the vehicle body and the tires or underneath the vehicle.

Make sure no one is underneath the vehicle or in the immediate vicinity of the wheel arches when the vehicle is being lowered.

WARNING Risk of becoming trapped due to the vehicle lowering

Vehicles with AIRMATIC or level control: when you unload luggage or leave the vehicle, the vehicle first rises slightly and then returns to the set level shortly afterwards.

You or anyone else in the vicinity of the wheel arches or the underbody could thus become trapped.

The vehicle can also be lowered after being locked.

When leaving the vehicle, make sure that nobody is in the vicinity of the wheel arches or the underbody.

**NOTE** Damage due to vehicle lowering

Parts of the body could be damaged when the vehicle is lowered.


Make sure that there are no obstacles. such as curbs underneath or in the immediate vicinity of the body when the vehicle is being lowered.

#### Requirements

- The vehicle has been started.
- Vehicles without Off-road package:
  - The vehicle is not moving faster than 37 mph (60 km/h).
- Vehicles with Off-road package:
  - Off-road level +1: the vehicle is not moving faster than 62 mph (100 km/h).
  - Off-road level +2: the vehicle is not moving faster than 40 mph (65 km/h).

- Off-road level +3: the vehicle is not moving faster than 12 mph (20 km/h) and the rear fog lamp is not switched on.
- When operating with a trailer or bicycle rack and the trailer socket is correctly contacted:
  - The vehicle is being driven no faster than 19 mph (30 km/h).
- i Use the normal level in trailer operation. Highlevel driving is not permitted in trailer operation on public roads.

# Raising the vehicle (vehicles without Off-road package)



Push rocker switch forwards.
Indicator lamp flashes while the vehicle is being raised to off-road level +1 and lights up continuously when the raising process is complete.

Off-road level +1 set remains stored even after the vehicle has been switched off.


The vehicle is lowered again to the vehicle level of the selected drive program in the following situations:

- When driving faster than 50 mph (80 km/h).
- When driving briefly between 40 mph (65 km/h) and 50 mph (80 km/h).
- · You select a different drive program.

# Lowering the vehicle (vehicles without Off-road package)

Pull rocker switch ①.
 The vehicle is lowered to the height of the currently selected drive program. Indicator lamp
 ② flashes while the vehicle is being lowered and goes out when the lowering process is complete.

### Raising the vehicle (vehicles with Off-road package)



Push rocker switch (1) forwards. The vehicle rises to the next higher vehicle level.

Following indicator lamps (2) flash while the vehicle is being raised and light up continuously when the raising process is complete.

- Off-road level +1: one indicator lamp
- Off-road level +2: two indicator lamps
- Off-road level +3: three indicator lamps

The off-road level set remains stored even after the vehicle has been switched off.

In the following situations, the vehicle is lowered to the next lower vehicle level:

- In off-road level +3:
  - When driving faster than 12 mph (20 km/h).
  - You switch on the rear fog lamps.
- In off-road level +2:
  - When driving faster than 50 mph (80 km/h).
  - When driving briefly between 40 mph (65 km/h) and 50 mph (80 km/h).
- In off-road level +1:

- When driving faster than 68 mph (110 km/h).
- When driving briefly between 62 mph (100 km/h) and 68 mph (110 km/h).
- (i) If you select a different drive program, the vehicle is lowered to the vehicle level of the selected drive program.

# Lowering the vehicle (vehicles with Off-road package)

Pull rocker switch 1.

The vehicle is lowered to the next lower vehicle level. Indicator lamps 2 of the currently selected off-road gear flash while the vehicle is being lowered.

Following indicator lamps 2 light up continuously when the lowering process is complete.

- Off-road level +2: two indicator lamps
- Off-road level +1: one indicator lamp
- Normal level: no indicator lamp

The vehicle level set remains stored even after the vehicle has been switched off.

# Setting Off-road Assist

#### Requirements

- the vehicle is stationary
- the vehicle is set to off-road level 1 or 2
- the Off-road or Off-road Plus (only vehicles with Off-road package) drive program has been selected
- · the ignition is switched on
- all doors and the hood are closed
- the transmission is not engaged in position P
- · there is no trailer coupled
- the vehicle is outdoors
- the detected lateral inclination of the vehicle must not exceed approx. 15°
- · the system is within its operating temperature
- the on-board voltage is sufficiently high

Multimedia system:

→ Settings → Assistance → Offroad Assistant

#### Recovery mode

Recovery mode assists the driver when pulling away on rough terrain, such as sand or snow.

- Select Recovery Mode.
- Select Start
  - Recovery mode is activated.
- ► Select Stop to stop recovery mode.

Recovery mode is automatically deactivated in the following situations:

- you are actually traveling faster than 9 mph (15 km/h)
- after a running time of 30 seconds
- it is detected that an object has hit the underbody of the vehicle hard
- · not all conditions are met
- (i) Further information on recovery mode  $(\rightarrow page 256)$ .

#### Individual wheel control

Individual wheel control enables the vehicle level to be set separately for each wheel.

- Select Individual Wheel Ctrl..
- Set the vehicle level for the desired wheel.
- You can also use the touchscreen to set the level for two or more wheels at the same time.
- Select Reset to set all wheels to the default setting.

Individual wheel control is automatically deactivated in the following situations:

- you are traveling faster than 9 mph (15 km/h)
- it is detected that an object has hit the underbody of the vehicle hard
- · not all conditions are met
- (i) Further information on individual wheel control (→ page 256).

#### Rear view camera

# Function of the rear view camera

The rear view camera is only an aid. It is not a substitute for your attention to the surroundings. Responsibility for safe maneuvering and parking remains with you. Make sure that there are no persons, animals, objects, etc. in the maneuvering area while maneuvering and parking.

(i) You can open the cover of the rear view camera manually ( $\rightarrow$  page 266).

The guide lines in the media display show the distances to your vehicle. The distances displayed apply only to road level.


Depending on the vehicle equipment, you can select from the following views:

- Normal view
- · Wide-angle view
- Trailer view

The area behind the vehicle is displayed as a mirror image, as in the inside rear-view mirror.

### Vehicles without Parking Assist PARKTRONIC

The following camera views are available in the multimedia system:




Normal view

- 1 Yellow guide line, vehicle width (driven surface) depending on the current steering angle (dvnamic)
- 2 Yellow guide line at a distance of approximately 3.3 ft (1.0 m) from the rear area
- Yellow lanes marking the course the tires will take with the current steering angle (dynamic)
- Bumper
- Red guide line at a distance of approximately 1.0 in (0.3 m) from the rear area



Wide-angle view




Trailer view (vehicles with a trailer hitch)

Yellow guide line, locating aid

- Red guide line at a distance of approximately 1.0 ft (0.3 m) from the ball head of the trailer hitch
- Ball head of the trailer hitch

#### Vehicles with Parking Assist PARKTRONIC

The following camera views are available in the multimedia system:



- Normal view
- Yellow lanes marking the course the tires will take with the current steering angle (dynamic)
- Yellow guide line, vehicle width (driven surface) depending on the current steering angle (dynamic)

- (a) Red guide line at a distance of approximately 1.0 in (0.3 m) from the rear area
- Yellow warning indicator of Parking Assist PARKTRONIC: obstacles at a distance between approximately 2.0 ft (0.6 m) and 3.3 ft (1.0 m)
- Red warning display of Parking Assist PARKTRONIC: obstacles are very close (approximately 1.0 ft (0.3 m) or less)
- Orange warning display of Parking Assist PARKTRONIC: obstacles are a medium distance away (between approximately 1.0 ft (0.3 m) and 2.0 ft (0.6 m))



Wide-angle view



Trailer view (vehicles with a trailer hitch)

- 1 Yellow guide line, locating aid
- Red guide line at a distance of approximately 1.0 ft (0.3 m) from the ball head of the trailer hitch
- Ball head of the trailer hitch

# System failure

If the rear view camera is not operational, the following display appears in the multimedia system.



The rear view camera will not function or will function only partially in the following situations:

- The tailgate is open.
- . There is heavy rain, snow or fog.
- The ambient light is poor, e.g. at night.
- Cameras, or vehicle components in which the cameras are installed, are damaged, dirty or covered. Observe the information on vehicle sensors and cameras ( $\rightarrow$  page 211).
- (i) Do not use the rear view camera in these types of situations. You could otherwise injure others or collide with objects when parking the vehicle.

For technical reasons, the standard height of the vehicle may be altered if the vehicle is carrying a heavy load and can result in inaccuracies in the guide lines and in the display of the generated images.

(i) The contrast of the display may be impaired by direct sunlight or by other light sources. e.g. when driving out of a garage. In this case, pay particular attention.

Have the display repaired or replaced if. forexample, pixel errors considerably restrict its use

#### 360° camera

#### Function of the 360° Camera

The 360° Camera is a system that consists of four cameras. The cameras cover the immediate vehicle surroundings. The system assists you when you are parking or at exits with reduced visibility, forexample,

The views of the 360° Camera are always available when the vehicle is being driven forwards up to a speed of approx. 10 mph (16 km/h) and when it is being backed up.

The 360° Camera is only an aid and may show a distorted view of obstacles, show them incorrectly or not show them at all. It is not a substitute for your attention to the surroundings. Responsibility for safe maneuvering and parking remains with vou. Make sure that there are no persons, animals or objects etc., in the maneuvering area while maneuvering and parking.

The system evaluates images from the following cameras:

- · Rear view camera
- Front camera
- Two side cameras in the outside mirrors
- (i) You can open the cover of the rear view camera manually ( $\rightarrow$  page 266).

#### Views of the 360° Camera

You can select from different views:



- Wide-angle view, front
- Top view with image from the front camera

- Top view with images from the side cameras in the outside mirrors
- 4 Wide-angle view, rear
- Top view with image from the rear view camera
- Top view with trailer view (vehicles with a trailer hitch)

#### Top view



- Lane indicating the route that the vehicle will take at the current steering wheel angle
- Warning display of Parking Assist PARKTRONIC
- Your vehicle from above

The color of the individual segments of warning display (2) is based on the distance to the detected obstacle:

- Yellow segments: obstacles at a distance between approx. 2.0 ft (0.6 m) and 3.3 ft (1.0 m)
- Orange segments: obstacles at a distance between approx. 1.0 ft (0.3 m) and 2.0 ft (0.6 m)
- Red segments: obstacles at a very short distance of approx. 1.0 ft (0.3 m) or less

When Parking Assist PARKTRONIC is operational and no object is detected, the segments of the warning display are shown in gray.

#### Guide lines



- Yellow lane marking the course that the tires will take at the current steering wheel angle (dynamic)
- Yellow guide line, vehicle width (driven surface) depending on the current steering wheel angle (dynamic)
- Red guide line at a distance of approximately1.0 in (0.3 m) from the rear area
- Mark at a distance of approx. 3.3 ft (1.0 m)
- (i) When Active Parking Assist is active, lanes (ii) are displayed in green.

The guide lines in the media display show the distances to your vehicle. The distances apply to road level.

In trailer mode, the guide lines are shown at the level of the trailer hitch.

#### Trailer view (vehicles with a trailer hitch)

If you select trailer view and no trailer is coupled to the vehicle, the following display appears:



- Yellow guide line, locating aid
- 2 Red guide line at a distance of approximately 1.0 ft (0.3 m) from the ball head of the trailer hitch
- Ball head of the trailer hitch




When the electrical connection is established between the vehicle and the trailer, the display changes to the side camera view.

This view supports maneuvering processes with a trailer.

# Side view of the mirror cameras

The sides of the vehicle can be seen in this view.



- Guide line of external vehicle dimensions with outside mirrors folded out
- Marker of the wheel contact points

# System failure

If the system is not ready for operation, the following message appears in the media display:



#### System limits

The 360° Camera will not function or will function only partially in the following situations:

- The doors are open.
- · The outside mirrors are folded in.
- The tailgate is open.
- There is heavy rain, snow or fog.
- · The ambient light is poor, e.g. at night.
- Cameras or the vehicle components in which the cameras are installed – are damaged, dirty or covered. Observe the information on vehicle sensors and cameras (→ page 211).
- (i) Do not use the 360° Camera under such circumstances. You could otherwise injure others or collide with objects when parking the vehicle.

For technical reasons, the standard height of the vehicle may be altered if the vehicle is carrying a heavy load and can result in inaccuracies in the guide lines and in the display of the generated images.

- (i) The contrast of the display may be impaired by abrupt, direct sunlight or by other light sources, e.g. when you are driving out of a garage. In this case, pay particular attention.
- (i) Have the display repaired or replaced if, forexample, pixel errors considerably restrict its use.

See the notes on cleaning the  $360^{\circ}$  Camera ( $\rightarrow$  page 349).

# Calling up the view of the 360° Camera using reverse gear

- Engage reverse gear.
- Select the desired view in the multimedia system (→ page 263).
- ▶ If the image from the rear view camera is not shown after reverse gear is engaged: switch off the vehicle, press and hold the rear button, switch on the vehicle and engage reverse gear again.

# Opening the camera cover of the rear view camera

Multimedia system:

- → 🔝 **>>** Settings **>>** Assistance
- >> Camera & Parking
- Select Open Camera Cover.
- (i) The camera cover closes automatically after a while or after an ignition cycle.

# Parking Assist PARKTRONIC

# ■ Function of Parking Assist PARKTRONIC

Parking Assist PARKTRONIC is an electronic parking assistance system with ultrasound. It monitors the area around your vehicle using multiple sensors on the front bumper and on the rear bumper. Parking Assist PARKTRONIC shows you the distance between your vehicle and a detected obstacle visually and audibly.

Parking Assist PARKTRONIC is only an aid. It is not a substitute for your attention to the surroundings. The responsibility for safe maneuvering and parking remains with you. Make sure that there are no persons, animals or objects in the maneu-

vering area while maneuvering and parking in/ exiting parking spaces.

In the standard setting, an intermittent warning tone sounds from a distance of approximately 1.0 ft (0.3 m) to an obstacle in front and approximately 3.3 ft (1.0 m) to an obstacle behind. A continuous warning tone sounds from a distance of approximately 0.7 ft (0.2 m). Using the Warn Early All Around setting in the multimedia system, the warning tones for front and side impact protection can be set to sound at a greater distance of approximately 3.3 ft (1.0 m) in front and 2.0 ft (0.6 m) on the sides ( $\rightarrow$  page 271).

(i) The Warn Early All Around setting is always active in the rear of the vehicle.

### Parking Assist PARKTRONIC display in the multimedia system



Vehicles without 360° Camera



Vehicles with 360° Camera

If you have not selected the menu Camera & Parking and an obstacle is detected in the path of travel, a PARKTRONIC Parking Assist pop-up window is displayed in the multimedia system at speeds below 6 (10 km/h) mph (1).

The color of the individual segments of the warning display is based on the distance to the detected obstacle:

• Yellow segments: obstacles at a distance between approx. 2.0 ft (0.6 m) and 3.3 ft (1.0 m)

- Orange segments: obstacles at a distance between approx. 1.0 ft (0.3 m) and 2.0 ft (0.6 m)
- Red segments: obstacles at a very short distance of approx. 1.0 ft (0.3 m) or less

# Display of Parking Assist PARKTRONIC in the head-up display



Optionally, obstacles detected by Parking Assist PARKTRONIC from a distance of approximately 3.3 ft (1.0 m) in front ② and 2.0 ft (0.6 m) on the sides ③ can also be displayed in the head-up display.

#### System limits


Parking Assist PARKTRONIC does not necessarily take into account the following obstacles:

- Obstacles below the detection range, e.g. persons, animals or objects.
- Obstacles above the detection range, e.g. overhanging loads, overhangs or loading ramps of trucks.

The sensors must be free of dirt, ice and slush. Otherwise, they may not function correctly. Clean the sensors regularly, especially after driving offroad, taking care not to scratch or damage them  $(\rightarrow page 211)$ .

Vehicles with trailer hitch: Parking Assist PARKTRONIC is deactivated for the rear zone when you establish an electrical connection between your vehicle and a trailer.

# Problems with Parking Assist PARKTRONIC



Example: vehicles with 360° Camera

When rear segments of or all-round segments light up red and the symbol appears in the Instrument Display, Parking Assist PARKTRONIC may have been deactivated due to signal interference. Start the vehicle again and check if Parking Assist PARKTRONIC is working at a different location.

If a warning tone also sounds for approximately two seconds every time the vehicle is started, it may be due to one of the following causes:

- The sensors are dirty: clean the sensors and observe the notes on care of vehicle parts  $(\rightarrow page 349)$ .
- · Parking Assist PARKTRONIC has been deactivated due to a malfunction: restart the vehicle. If the problem persists, consult a qualified specialist workshop.

# Function of the passive side impact protection

Passive side impact protection is an additional Parking Assist PARKTRONIC function that warns the driver about obstacles at the side of the vehicle. A warning is issued when obstacles are detected between the front and rear detection range. In order for an object on the side to be detected, the sensors in the front and rear bumper must first detect the object while you are driving past it.

During the parking procedure or maneuvering, objects are detected as the vehicle drives past. If vou steer in the direction of a detected obstacle and there is a risk of a lateral collision, a warning

is issued and the segments light up in color on the display.

The segment color changes depending on the distance to the detected obstacle:


- Yellow: approximately 1.0 2.0 ft (30 60 cm)
- Red: less than approximately 1.0 ft (30 cm)

In order for lateral front or rear segments to be displayed, the vehicle must first travel a distance of at least half a vehicle's length. Once the vehicle has traveled the length of the vehicle, all of the lateral front and rear segments can be displayed.



Parking Assist PARKTRONIC display: vehicles without a 360° camera

- Operational front and rear
- Operational front, rear and sides
- Obstacle detected at the front right (yellow) and rear (red)



Parking Assist PARKTRONIC display: vehicles with a 360° camera

- Operational front and rear
- Operational front, rear and sides
- Obstacles detected at the front right (red)

Saved obstacles at the sides are deleted in the following situations, for example:

- You park the vehicle and switch it off.
- · You open the doors.

After the engine is restarted, obstacles at the sides must be detected again before a new warning can be issued.

# System limits

The system limits for Parking Assist PARKTRONIC apply to passive side impact protection.

The following objects are not detected, for example:

- Pedestrians who approach the vehicle from the side
- Objects placed next to the vehicle
- Activating/deactivating Parking Assist PARKTRONIC using the multimedia system
- NOTE Risk of an accident from objects at close range

Parking Assist PARKTRONIC may not detect certain objects at close range.

When parking or maneuvering the vehicle, pay particular attention to any objects which are above or below the sensors, e.g. flower pots or drawbars. The vehicle or other objects could otherwise be damaged.

#### Requirements

- The camera menu is open.
- Or: Active Parking Assist is active.
- Or: the PARKTRONIC pop-up window appears.
- ► Tap Pv on the media display.

If the indicator lamp in the pi button is not lit, Parking Assist PARKTRONIC is active. If the indicator lamp is lit or the pi symbol appears on the instrument cluster, Parking Assist PARKTRONIC is not active.

(i) Parking Assist PARKTRONIC is automatically activated when the vehicle is started.

Alternatively, Parking Assist PARKTRONIC can be activated or deactivated in the quick access menu.

#### Setting the warning tones of Parking Assist **PARKTRONIC**

Multimedia system:

→ Settings → Assistance >> Camera & Parking

#### Adjusting the volume of the warning tones

- Select Warning Tone Volume.
- Set a value.

### Adjusting the pitch of the warning tones

- Select Warning Tone Pitch.
- Set a value.

Specifying the starting point for the warning tones You can specify whether the Parking Assist PARKTRONIC warning tones should commence when the vehicle is further away from an obstacle.

- Select Warn Early All Around.
- Activate or deactivate the function.

### Activating/deactivating audio fadeout

You can specify whether the volume of a media source in the multimedia system is to be reduced when Parking Assist PARKTRONIC sounds a warning tone.

- Select Audio Fadeout During Warning Tones.
- Activate or deactivate the function.

### **Active Parking Assist**

# Function of Active Parking Assist

Active Parking Assist is an electronic parking assistance system, which uses ultrasound with the assistance of the rear view camera and 360° camera. When you are driving forwards at up to approximately 22 mph (35 km/h), the system automatically measures parking spaces on both sides of the vehicle.

Active Parking Assist offers the following functions:

Vehicles with rear view camera

Parking in parking spaces parallel to the road

Vehicles with 360° camera

- · Parking in parking spaces parallel to the road
- · Parking in parking spaces perpendicular to the road (optionally either forwards or reverse)

- · Parking in parking spaces that can only be detected as such due to markings (e.g. at the roadside)
- Exiting parking spaces if you have parked using Active Parking Assist

As soon as all requirements are met for searching for parking spaces, the display appears on the instrument display.

When Active Parking Assist has detected parking spaces, the (P) display appears on the instrument display. The arrows show on which side of the road detected parking spaces are located. They are then shown in the media display.

Vehicles with rear view camera: the parking space can be selected as desired. The vehicle is parked in reverse.

Vehicles with 360° camera: the parking space can be selected as desired. Depending on the location of the parking space, the parking direction (forwards or reverse) can also be selected as desired.

When Active Parking Assist is activated, the turn signal indicators are activated based on the calculated path of your vehicle.

The parking procedure is supported by accelerating, braking, steering and gear changes.

Active Parking Assist is only an aid. It is not a substitute for your attention to the surroundings. The responsibility for safe maneuvering and parking remains with you. Make sure that no persons, animals or objects etc. are in the maneuvering range.

Active Parking Assist will be canceled in the following situations:

- · You begin steering.
- You apply the electric parking brake.
- You engage park position P.
- · ESP® intervenes.
- You open the doors or the tailgate while driving.

#### System limits

If the exterior lighting is faulty, Active Parking Assist may not function, depending on the defect.

Also observe the system limits of the following systems:

- Rear view camera (→ page 261)
- 360° camera (→ page 263)

Objects located above or below the detection range of the sensors, e.g. overhanging loads, overhangs or loading ramps of goods vehicles, or the borders of parking spaces, are not detected during measurement of the parking space. They are then not taken into account when calculating the parking procedure either. In some circumstances, Active Parking Assist may therefore guide you into the parking space incorrectly.

WARNING Risk of accident due to objects located above or below the detection range of Active Parking Assist

If there are objects above or below the detection range, the following situations may arise:

- Active Parking Assist may steer too early.
- The vehicle may not stop in front of these objects.

There is a danger of collision!

In these situations, do not use Active Parking Assist.

Extreme weather conditions, such as snow or heavy rain, may lead to a parking space being measured inaccurately. Parking spaces that are partially occupied by trailer drawbars might not be identified as such or may be measured incorrectly. Only use Active Parking Assist on level, high-grip ground.

Do not use Active Parking Assist in the following situations:


- In extreme weather conditions, e.g. when there is ice or packed snow, or in heavy rain.
- When transporting a load that protrudes beyond the vehicle.
- On steep uphill or downhill gradients of more than approximately 15%.
- When snow chains are installed.
- · When a trailer or bicycle rack is attached.
- Directly after a tire change or when spare tires are installed.
- If the tire pressure is too low or too high.

• If the suspension is out of alignment, e.g. after you have bottomed out on a curb.


Active Parking Assist may also display parking spaces that are not suitable for parking, such as:

- Parking spaces where parking is prohibited.
- · Parking spaces on unsuitable surfaces.

# Parking with Active Parking Assist



Press button ①.



The media display shows the view of Active Parking Assist. Area 2 displays detected parking spaces (4) and vehicle path (3).

- (i) Vehicle path (3) shown on the media display may differ from the actual vehicle path.
- If a parking space is displayed: stop the vehicle.
- Select desired parking space 4 and confirm.

- If necessary, select the parking direction (forwards or reverse), and confirm. Vehicle path (3) is shown, depending on selected parking space (4) and the parking direction.
- i The turn signal indicator is switched on automatically when the parking procedure begins.

You are responsible for selecting the turn signal indicator in accordance with the traffic conditions. If necessary, select the turn signal indicator accordingly.

WARNING Risk of accident due to vehicle swinging out while parking or pulling out of a parking space

While parking or exiting a parking space, the vehicle swings out and can drive onto areas of the oncoming lane.

This could cause you to collide with objects or other road users.

Pay attention to objects and other road users.

- Where necessary, stop the vehicle or cancel the parking procedure with Active Parking Assist.
- If, for example, the Please Engage Reverse Gear message appears on the media display: select the corresponding transmission position

The vehicle drives into the selected parking space.

(i) During the parking procedure with Active Parking Assist, the lane markings are displayed in green in the camera image.

On completion of the parking procedure, the Parking Assist Finished, Take Control of Vehicle display message appears. Further maneuvering may still be necessary.

- After completion of the parking procedure, safeguard the vehicle against rolling away. When required by legal stipulations or local conditions: turn the wheels toward the curb.
- i) You can stop the vehicle and change the transmission position during the parking procedure. The system then calculates a new

vehicle path. If no new vehicle path is available, the system can change the transmission position again or cancel the parking procedure.


# Exiting a parking space with Active Parking Assist

#### Requirements

The vehicle has been parked with Active Parking Assist.

Please note that you are responsible for the vehicle and surroundings during the entire parking procedure.

Start the vehicle.



Press button ①. The media display shows the view of Active Parking Assist.



- If the vehicle has been parked perpendicular to the direction of travel: in area 2. select direction of travel (3) Left or Right.
- (i) The vehicle path shown on the media display may differ from the actual vehicle path.
- Confirm direction of exit (3) to drive out of the parking space.
- (i) The turn signal indicator is switched on automatically when the exiting procedure begins.

You are responsible for selecting the turn signal indicator in accordance with the traffic conditions. If necessary, select the turn signal indicator accordingly.

WARNING Risk of accident due to vehicle swinging out while parking or pulling out of a parking space

While parking or exiting a parking space, the vehicle swings out and can drive onto areas of the oncoming lane.

This could cause you to collide with objects or other road users.

- Pay attention to objects and other road users.
- Where necessary, stop the vehicle or cancel the parking procedure with Active Parking Assist.
- If, for example, the Please Engage Forward Gear message appears on the media display: select the corresponding transmission position.

The vehicle moves out of the parking space. The turn signal indicator is switched off automatically.

After the procedure for exiting the parking space has been completed, a warning tone and the

Parking Assist Finished, Take Control of Vehicle message prompt you to take control of the vehicle.

The vehicle is not automatically braked and may roll away. You have to accelerate, brake, steer and change gear yourself again.

# Maneuvering assistance

# ■ Function of Drive Away Assist

Drive Away Assist can reduce the severity of an impact when you are pulling away. If an obstacle is detected in the direction of travel, the vehicle's speed is briefly reduced to approx. 1 mph (2 km/h). If a critical situation is detected, the symbol appears on the media display.

Drive Away Assist can be deactivated or activated in the Maneuvering Assistance menu.

(i) You can cancel an intervention by Drive Away Assist at any time by deactivating Parking Assist PARKTRONIC.

**WARNING** Risk of accident caused by limited detection performance of Drive Away Assist

Drive Away Assist cannot always clearly identify objects and traffic situations.

- Always pay careful attention to the traffic situation; do not rely on Drive Away Assist alone.
- Be prepared to brake or swerve as necessary, provided the traffic situation permits and that it is safe to take evasive action.

Drive Away Assist is only an aid. It is not a substitute for your attention to the surroundings. The responsibility for safe maneuvering and parking remains with you. Make sure that no persons, animals or objects etc. are in the maneuvering range.

A risk of collision may occur in the following situations, forexample:

• If the driver mixes up the accelerator and brake pedals.

• If an incorrect transmission position is engaged.

Drive Away Assist is active under the following conditions:

- If Parking Assist PARKTRONIC is activated.
- If you shift the transmission position to R or
   D when the vehicle is stationary.
- If the detected obstacle is less than approx. 3.3 ft (1.0 m) away.
- If the maneuvering assistance function is activated in the multimedia system.

#### System limits

The performance of Drive Away Assist is limited on inclines.

When driving with a trailer, Drive Away Assist is not available.

(i) Also observe the system limits of Parking Assist PARKTRONIC (→ page 266).

#### ■ Function of Cross Traffic Alert

(i) Cross Traffic Alert is only available for vehicles with Blind Spot Assist or Active Blind Spot Assist. Cross Traffic Alert can warn drivers of any crossing traffic when backing up and maneuvering out of a parking space. The radar sensors in the bumper also monitor the area adjacent to the vehicle. If a critical situation is detected, the symbol appears on the media display and the vehicle can be braked automatically.

If the radar sensors are obstructed by vehicles or other objects, detection is not possible.

Cross Traffic Alert is active under the following conditions:

- The vehicle is backing up at walking pace.
- Maneuvering assistance is activated (→ page 277).
- i) Also observe the instructions on Blind Spot Assist and Active Blind Spot Assist (→ page 242).

#### System limits

Cross Traffic Alert is not available on inclines.

Cross Traffic Alert is not available when driving with a trailer.

# Activating/deactivating the maneuvering assis-

Multimedia system:

- → Settings → Assistance >> Camera & Parking
- Switch Maneuvering Assistance on or off.
- (i) The maneuvering assistant must be active for the function of Drive Away Assist (→ page 275) and Cross Traffic Alert
  - $(\rightarrow page 276)$ .

# **Trailer Maneuvering Assist**

- Function of Trailer Maneuvering Assist
- (i) This function is an on-demand feature  $(\rightarrow page 24)$ .
- WARNING Risk of accident due to unsuitable trailers

Trailers with a steered axle or a fifth wheel cannot be used with Trailer Maneuvering Assist.

Due to this, the trailer cannot be maneuvered in the desired direction and you can cause a collision or the trailer can rollover.

- Only use Trailer Maneuvering Assist with trailers with fixed drawbars and axles.
- **NOTE** Damage to trailers with a stabilization device against swerving

In the case of trailers with a stabilization device against swerving, the trailer or trailer tow hitch could be damaged.

- If a trailer coupling with Trailer Maneuvering Assist is used, only use trailers without a stabilization device against swerving.
- **NOTE** Damage due to overhanging loads in front or drawbar installations

The vehicle and the trailer may be damaged during maneuvering due to overhanging loads at the front of the trailer or drawbar installations.

Pay attention to overhanging loads or drawbar installations while maneuvering.

Trailer Maneuvering Assist will assist you when you are backing up with a trailer. By means of a turning angle sensor in the trailer coupling. Trailer Maneuvering Assist monitors the articulation angle between the vehicle and trailer and adjusts it to a specified value.

Trailer Maneuvering Assist is only an aid. It is not a substitute for your attention to the surroundings. The responsibility for safe maneuvering and parking remains with you. Make sure that there are no persons, animals or objects in the maneuvering area while you are maneuvering and parking in / exiting parking spaces.

You can either enter the articulation angle value directly via the multimedia system or use a straightening maneuver. When you carry out a straightening maneuver, the system will calculate the articulation angle automatically and align the vehicle/trailer combination with the trailer's current direction.

Trailer Maneuvering Assist must be taught in before it can adjust the articulation angle  $(\rightarrow page 278)$ .

Observe the notes on trailer operation  $(\rightarrow page 279)$ .

#### System limits

Observe the system limits of the following functions:

- Active Parking Assist (→ page 271)
- 360° camera (→ page 263)
- Rear-view camera (→ page 261)

The system may be impaired or may not function in the following situations:

 The gradient is greater than approximately 15%.

# Using Trailer Maneuvering Assist

#### Requirements


- The vehicle has been started and is stationary.
- A trailer has been detected.
- The gradient is less than approximately 15%.

• The electric parking brake is not applied.

### Teaching in Trailer Maneuvering Assist

- Drive forwards a short distance with the car/ trailer combination.
  - The completed teach-in process is shown on the media display.
- The maximum articulation angle depends on the length of the trailer. This is calculated by the system by driving the vehicle forwards, including cornering. Before the length of the trailer has been calculated, the maximum articulation angle is approximately 23°. The longer the trailer is, the higher the maximum articulation angle (max. approximately 60°).

# Using Trailer Maneuvering Assist



- Engage reverse gear **R**.
- Press button ①. The camera image is shown on the media display.
- ➤ To adjust the articulation angle: select ✓. Swipe left or right on the media display or touchpad to change the articulation angle.

or

To activate the straightening maneuver: select **‡** .

The system calculates the articulation angle in such a way that the direction of the trailer at the time of activation is maintained. There is a short countersteering movement of the trailer while the vehicle is reversed, which then guides it back to the desired line. In this way. the vehicle is aligned straight with the trailer and, at the same time, the direction of the trailer is maintained.

- Accelerate and brake as required.
- (i) Pay attention to your surroundings and be ready to brake at all times.

### Trailer hitch

# Notes on trailer operation

- **NOTE** Mercedes-AMG vehicles
- Observe the notes in the Supplement. You could otherwise fail to recognize dangers.

# WARNING Risk of accident due to unsuitable ball neck

If you install an unsuitable ball neck, the trailer hitch and the rear axle may be overloaded.

This can significantly impair the driving characteristics and the trailer may become loose. There is a risk of fatal injury.

- Only install a ball neck that complies with the permissible dimensions and is designed for the requirements of trailer operation.
- Do not modify the ball neck or the trailer hitch.

The values approved by the manufacturer can be found on the identification plates and in the "Technical data" section under "Trailer hitch" for the towing vehicle ( $\rightarrow$  page 425).

# ▲ WARNING Risk of accident due to vehicle/trailer combination swerving

If you drive too fast in trailer operation, the vehicle/trailer combination may start to swerve.

This could cause you to lose control of the vehicle/trailer combination. The vehicle/ trailer combination may even rollover.

- Under no circumstances should you try to straighten the vehicle/trailer combination by increasing your speed.
- Reduce the speed and do not countersteer.
- Brake if necessary.
- **NOTE** Damage to the engine resulting from overheating
- If you subsequently have a trailer coupling retrofitted, depending on the vehicle type, changes to the engine cooling system may be required.

In the case of retrofitting a trailer coupling, please observe the attachment points on the vehicle frame.

Retrofitting a trailer hitch is permissible only if a trailer load is specified in your vehicle documents. If this is not the case, the vehicle is not approved for trailer operation.

Further information can be obtained at a qualified specialist workshop.

For a detachable trailer coupling, it is essential to comply with the operating instructions of the trailer coupling manufacturer.

Couple and uncouple the trailer carefully. If you do not connect the trailer to the towing vehicle correctly, the trailer may become detached.

Observe the following notes on the tongue weight:

- Do not use a tongue weight that exceeds or falls below the permissible tongue weight
- Use a tongue weight as close as possible to the maximum tongue weight

Do not exceed the following values:

- · Permissible towing capacity
- Permissible rear axle load of the towing vehicle
- Permissible gross weight of the towing vehicle
- · Permissible gross weight of the trailer
- Maximum permissible speed of the trailer

Ensure the following before starting a journey:

- The tire pressure on the rear axle of the towing vehicle is set for a maximum load
- The lighting of the connected trailer is operational

In the event of increased rear axle load, the car/trailer combination must not exceed a maximum speed of 62 mph (100 km/h) for reasons concerning the operating permit. This also applies in countries in which the permissible maximum speed for car/trailer combinations is above 62 mph (100 km/h).

Vehicles with AIRMATIC or E-ACTIVE BODY CONTROL: if the socket of the trailer hitch is occupied, e.g. by a trailer or rear bicycle rack, the vehicle is

set to the normal level at speeds greater than 19 mph (30 km/h). This is done regardless of which drive program has been selected.

# Attaching the ball neck


A

**WARNING** Risk of accident and injury due to incorrectly installed ball neck

If the ball neck is not properly mounted and secured, it may come loose along with the trailer while the vehicle is in motion and endanger other road users. There is a risk of fatal injuries.

- Mount and secure the ball neck as described in the installation instructions of the ball neck manufacturer.
- With the ball neck mounted, always make sure it is properly secured before commencing a journey.

# Attaching the ball neck



- Secure the vehicle against rolling away.
- Remove cover cap 
  from the ball neck mount in the direction of the arrow.
- Store cover cap 1 such that it cannot move around.
- Comply with the installation instructions of the ball neck manufacturer.

Observe the notes on loading the vehicle.

# Coupling up/uncoupling a trailer

WARNING Risk of injury due to a change in vehicle level

Vehicles with level control system: the vehicle level may be changed unintentionally, e.g. by other persons. If you couple or uncouple the trailer during this time, you may become trapped. In addition, other people could become trapped if their limbs are between the vehicle body and the tires or underneath the vehicle.

Observe the following when coupling or uncoupling:

- Do not open or close any doors or the tailgate.
- Do not initiate the level control system and do not operate DYNAMIC SELECT.
- Do not lock or unlock the vehicle.

The trailer will be correctly detected by the vehicle only if the following conditions are met:

- . The trailer is connected correctly.
- The trailer lighting system is in working order.

A correctly connected trailer influences, among other things, the functions of the following systems.

- FSP® trailer stabilization.
- · Trailer Maneuvering Assist
- Active Lane Keeping Assist
- Parking Assist PARKTRONIC
- Active Parking Assist
- Blind Spot Assist or Active Blind Spot Assist
- · Drive Away Assist
- · Cross Traffic Alert
- · Rear view camera
- 360° camera
- AIRMATIC
- F-ACTIVE BODY CONTROL

Vehicles without level control system: the ball head height will change depending on the vehicle's load. In this case, use a trailer with a heightadjustable drawbar.

#### Coupling up a trailer

! NOTE Damage to the starter battery due to full discharge

Charging the trailer battery using the power supply of the trailer can damage the starter battery.

Do not use the vehicle's power supply to charge the trailer battery.

Information about a suitable ball neck for Mercedes-Benz vehicles can be obtained from a qualified specialist workshop, e.g. an authorized Mercedes-Benz Center.

- Secure the vehicle against rolling away.
- Remove the cover cap from the ball neck mount and store it in a safe place (→ page 280).
- Position the trailer on a level surface behind the vehicle and couple it up to the vehicle.
- Establish the electrical connection between the vehicle and the trailer.

Accessories can be connected to the permanent power supply up to 180 W and to the power supply that is switched on via the ignition lock.

# Uncoupling a trailer

A

WARNING Risk of being crushed and becoming trapped when uncoupling a trailer

When uncoupling a trailer with an engaged inertia-activated brake, your hand may become trapped between the vehicle and the trailer drawbar.

- Do not uncouple trailers with an engaged overrun brake.
- ! NOTE Damage during uncoupling with an engaged overrun brake

The vehicle may be damaged if you uncouple with an engaged overrun brake.

Do not uncouple trailers with an engaged overrun brake. **WARNING** Risk of becoming trapped when disconnecting the trailer cable

**Vehicles with level control system:** the vehicle may lower when you disconnect the trailer cable.

This could result in other people becoming trapped if their limbs are between the vehicle body and the tires or underneath the vehicle.

- Make sure nobody is underneath the vehicle or in the immediate vicinity of the wheel arches when you disconnect the trailer cable.
- Secure the vehicle against rolling away.
- Disconnect the electrical connection between the vehicle and the trailer.
- Uncouple the trailer.
- Remove the ball neck and, in doing so, observe the installation instructions from the ball neck manufacturer.
- Place the cover on the ball neck mount.

# Vehicle towing instructions

The vehicle is not suitable for the use of tow bar systems that are used for flat towing or dinghy towing, for example. Attaching and using tow bar systems can result in damage to the vehicle. When you are towing a vehicle with tow bar systems, safe driving characteristics cannot be guaranteed for the towing vehicle or the towed vehicle. The vehicle-trailer combination may swerve from side to side.

Observe the following information:

- Permitted towing methods (→ page 366)
- The notes on towing the vehicle with both axles on the ground ( $\rightarrow$  page 368)

# A

computer

**WARNING** Risk of accident if the instrument display fails

If the instrument display has failed or is malfunctioning, function restrictions in systems relevant to safety cannot be detected.

The operating safety of your vehicle may be impaired.

- Drive on carefully.
- Have the vehicle checked immediately at a qualified specialist workshop.
- A

**WARNING** Risk of distraction from information systems and communications equipment

If you operate information systems and communication devices integrated in the vehicle when driving, you could be distracted from the traffic situation. This could also cause you to lose control of the vehicle.

- Only operate this equipment when the traffic situation permits.
- If you cannot be sure of this, stop the vehicle whilst paying attention to road and traffic conditions and operate the equipment with the vehicle stationary.
- NOTE Mercedes-AMG vehicles
- Observe the notes in the Supplement.
   You could otherwise fail to recognize dangers.

You must observe the legal requirements for the country in which you are currently driving when operating the on-board computer.

The on-board computer shows only display messages and warnings from specific systems on the instrument display. You must therefore ensure that your vehicle is always safe to operate.

If the operating safety of your vehicle is impaired, park the vehicle immediately and in accordance with the traffic conditions. Contact a qualified specialist workshop.

# Overview of instrument display



Left display area of the instrument display (example: speedometer): speedometer/time/ date/trip computer From Start and From Reset/range/audio/angle of incline and approach

The segments on the speedometer indicate the statuses of the following systems: cruise control/limiter/Active Distance Assist DISTRONIC

- Outside temperature
- Digital speedometer
- Time
- (5) Right display area of the instrument display (example: tachometer): tachometer/average fuel consumption/ECO display/navigation/G-

meter/assistant display/4MATIC/suspension/power meter/power availability display of the electric motor (equipment-dependent)

The fuel supply will be interrupted to protect the engine when the red mark on the tachometer (overrevving range) is reached.

Index points

#### 286 Instrument display and on-board computer


These show the selected display or menu content.

Coolant temperature display During normal operation, the coolant temperature display is permitted to rise to 248°F (120°C).

Vehicles with 48 V on-board electrical system: POWER and CHARGE display (electrical drive support and recuperation power of the electric motor)

- Selected drive program
- Selected transmission position
- Center display area of the instrument display (example: standard display for trip): Assistance/Telephone/Navigation/Trip/Media/ Radio/Styles and displays/Service/Power meter (equipment-dependent)
- 1 Fuel level, fuel filler flap location indicator, range

# Overview of the buttons on the steering wheel



- Back/Home button, on-board computer Press and hold: shows standard display
- 2 Touch Control, on-board computer
- Control panel for cruise control or Active Distance Assist DISTRONIC
- Control panel for MBUX multimedia system: Voice Control System

★ Displays favorites

VOL: control knob, adjusts the volume or switches the sound off (press)

Makes/accepts a call

Rejects/ends a call

- Calls up the home screen
- Touch Control multimedia system
- → Back button
- Brightness control to adjust the lighting in the Instrument Display and in the control elements of the vehicle interior

#### Operating the on-board computer

Observe the legal requirements for the country in which you are currently driving when operating the on-board computer.



The on-board computer is operated using the lefthand Touch Control and the left-hand back/home button.

When the on-board computer is being operated, different acoustic signals will sound as operating feedback, e.g. when you reach the end of a list.

The following menus are available:

- Assistance
- Phone
- Navigation
- Trip
- Radio
- Media

- Designs & Disp.
- Service
- (i) You can find information about the possible settings and selections on the menus in the Digital Operator's Manual.

The menus can be called up from the menu bar on the instrument display.

- To call up the menu bar: briefly press the lefthand back button until the menu bar is displayed.
- Vehicles without Active Distance Assist DISTRONIC: press the houtton to call up the menu bar of the on-board computer.
- To scroll on the menu bar: swipe to the left or right on the left-hand Touch Control.
- To call up a menu, submenu or possible settings on the menu, or confirm a selection or **setting:** press the left-hand Touch Control.
- To scroll through displays or lists on the menu, or select display content, a function, an entry or a display: swipe upwards or downwards on the left-hand Touch Control.

To exit a submenu: press the left-hand back button.

#### Operating the head-up display

- To switch on the head-up display: swipe upwards on the menu bar on the left-hand Touch Control.
- To switch to the head-up display: swipe upwards on the left-hand Touch Control.
- To set the display areas of the head-up display: swipe upwards or downwards on the lefthand Touch Control.

#### Displaying full-screen menus

You can display the following menus full-screen on the instrument display:

- Assistance
- Trip
- Navigation
- On the corresponding menu, use the left-hand Touch Control to scroll to the end of the list.

#### 288 Instrument display and on-board computer

Press the left-hand Touch Control. The selected menu will be displayed fullscreen.

# Overview of displays in the instrument display

Displays on the instrument display:

Active Parking Assist (→ page 273)

Parking Assist PARKTRONIC switched off (→ page 270)

 $\bigcirc$  DSR ( $\rightarrow$  page 229)

 $\bigcirc$  Cruise control ( $\rightarrow$  page 220)

Active Distance Assist DISTRONIC (→ page 222)

Reference Active Brake Assist (→ page 235)

Active Steering Assist (→ page 231)

Active Stop-and-Go Assist (→ page 229)

✓ Active Lane Keeping Assist (→ page 244)

Active Lane Change Assist (→ page 234)

♠ ECO start/stop function (→ page 186)

**HOLD** HOLD function (→ page 217)

■ Adaptive Highbeam Assist (→ page 154)

**Vehicles with Traffic Sign Assist:** detected instructions and traffic signs ( $\rightarrow$  page 240).

For an overview of the indicator and warning lamps, see ( $\rightarrow$  page 485).

## Head-up Display

Function of the head-up display

I NOTE Mercedes-AMG vehicles


Observe the notes in the Supplement. You could otherwise fail to recognize dangers.

The head-up display projects the following information into the driver's field of vision above the cockpit, for example:

- · Driving speed
- Information from the navigation system
- Information from the driving systems and driving safety systems
- Some warning messages

Depending on the vehicle's equipment, different content may be shown in the three areas of the head-up display ( $\rightarrow$  page 289).

# Display content



- Navigation instructions
- ② Current speed
- Oetected instructions and traffic signs
- Set speed in the driving system (e.g. cruise control)

## System limits

The visibility of the displays will be affected by the following conditions:

- Seat position
- Image position setting
- Ambient light
- Wet road surface
- · Objects on the display cover
- Polarization in sunglasses
- (i) In extreme sunlight, sections of the display may appear washed out. You can correct this by switching the head-up display off and on again.

# Setting the head-up display using the on-board computer

On-board computer:

#### THEAD-UP DISPLAY

The following head-up display settings or displays can be selected or shown:

Position


- Brightness
- Messages
- · Assistance status
- Telephone
- Audio
- · Voice Control System
- To select the settings menu: swipe to the right on the left-hand Touch Control. Settings menu (5) will be selected.
- To call up the Settings menu: press the lefthand Touch Control.
- To adjust the position: swipe upwards or downwards on the left-hand Touch Control.
- To adjust the brightness: swipe to the left or right on the left-hand Touch Control.

#### Setting messages, assistance status, telephone, audio and the Voice Control System

- Press the left-hand Touch Control. The list of setting options will be displayed.
- Swipe upwards or downwards on the left-hand Touch Control.

To choose settings: press the left-hand Touch Control.

#### Selecting what the head-up display shows



#### (Example)

- Switching the head-up display on/off
- Left display area Navigation system Inclination, gradient and compass Average consumption G-meter
- Central display area Speedometer

# 290 Instrument display and on-board computer

Set speed in the driver assistance system, e.g. cruise control

Warnings from driver assistance systems, e.g. distance warning

Right display area

Traffic Sign Assist

Vehicle level

Differential

Distribution of the drive torques, 4MATIC

(→ page 200)

- Assistant display
- To adjust the position, brightness and lower display area
- 6 Index points
- Lower display area (example: left display area)

You can hide display areas ② to ④ that are not required.

 In audio mode, the station name or track will be shown temporarily when the audio source is being actively operated. In addition, the latest calls will be displayed when the telephone list on the instrument display is actively operated.

- Swipe upwards on left-hand Touch Control.
- Press the left-hand Touch Control.

# Switching the Head-up Display on/off via the multimedia system

Multimedia system:

- → 🔝 **>>** Settings **>>** Quick Access
- Select HUD. The Head-up Display is activated.

#### Overview and operation

#### Notes on the MBUX multimedia system

WARNING Risk of distraction from information systems and communications equipment


If you operate information systems and communication devices integrated in the vehicle when driving, you could be distracted from the traffic situation. This could also cause you to lose control of the vehicle.

- Only operate this equipment when the traffic situation permits.
- If you cannot be sure of this, stop the vehicle whilst paying attention to road and traffic conditions and operate the equipment with the vehicle stationary.

You must observe the legal requirements for the country in which you are currently driving when operating the multimedia system.

Depending on the equipment, the scope of function and product designation of your MBUX multimedia system may differ from the description and images in this Operator's Manual. For example. route guidance with augmented reality is not available in all equipment variants.

# Overview of the MBUX multimedia system



- Touch Control and control panel for the MBUX multimedia system
- Media display with touch functionality

- Touchpad
- Controller

Turn: adjusts the volume

Press briefly: switches the mute function on/off

Press and hold: switches the MBUX multimedia system or media display on or off

- 6 Buttons for navigation, radio/media and telephone
- 6 Buttons for vehicle functions/system settings and favorites/themes

Further operating options:


- · Conducting a voice dialog with the Voice Control System.
- · Operating functions contact-free with the MBUX Interior Assistant.
- (i) You can find further information about operation as well as about applications and services in the Digital Operator's Manual.

# Anti-theft protection

This device is equipped with technical provisions to protect it against theft. Further information on

anti-theft protection can be obtained from an authorized Mercedes-Benz Center.

#### Home screen overview



- ① Depending on the display, calls up the first three applications or the home screen
- Calls up the profile
- Calls up the global search

- SOS NOT READY (only when the Mercedes-Benz emergency call system is not available)
- Mercedes me connect active
- Transmission of vehicle position active


- Signal strength of the mobile phone network, network display, battery status of the mobile phone connected, time
- Calls up the Notifications Center
- Calls up an application using the symbol

- Application and current information
- Quick-access, e.g. enter home address
- Index points and selected display area
- Calling up the air conditioning menu
- (a) Calls up SUGGESTIONS, THEMES and **FAVORITES**
- (i) If Mercedes me connect (5) is active, the vehicle is linked with Mercedes me connect. Vehicle data is then transmitted to the back end system. What data is transmitted depends on which services are activated. Further details can be found in the Mercedes me connect terms and conditions and data protection information. The function is countrydependent.

If transmission of vehicle position (6) is active. Mercedes me connect services have been activated for this vehicle which access the vehicle's geoposition. In which instances the geoposition is transmitted depends on the particular services. Further details can be found in the Mercedes me connect terms and conditions and data protection information. The function is country-dependent.

# Operating the MBUX multimedia system

# **Using Touch Control**



- ☐ Calls up the home screen
- Touch Control
- 3 Press briefly: returns to the previous display
- Press the rocker switch down briefly: shows favorites

★ Press the rocker switch down and hold: adds favorites and themes

**VOL** Turn controller: adjusts the volume

Press controller: switches off the sound Press the rocker switch up: makes or

accepts a call Press the rocker switch down: rejects or

Navigation through the menus is carried out with Touch Control (2) with single-finger swipes.

- To select a menu option: swipe and press.
- To move the digital map: swipe in any direction.


# Using the touchscreen

ends a call

- Select menu options, symbols or characters by pressing briefly.
- To navigate in menus: swipe up, down, left or right.
- To use handwriting to enter characters: write the character with one finger on the touchscreen.

- To zoom in and out of the map: move two fingers together or apart.
- To call up the global menu: press and hold on the touchscreen until the OPTIONS menu appears.
- (i) For more information on operation, please refer to the Digital Operator's Manual.


# Using the touchpad



- Returns to the previous display
- ② [III] Calls up the audio control menu Swiping to the left of right: selects the previous or next radio station/music track
- 3 Calls up the home screen
- Touchpad

- ➤ To select a menu option: swipe and press.
- ➤ To use handwriting recognition: write a character on the touchpad.
- To open or close the Notifications Center: swipe down or up with two fingers.
- To zoom in and out of the map: move two fingers together or apart.

#### Calling up applications using buttons



- ① Falls up vehicle functions
- 2 NAVI Calls up navigation
- 3 RADIO Calls up radio or media
- 4 TEL Calls up the telephone

- ⑤ Press briefly: calls up favorites Press and hold: adds a favorite or theme
- Alternatively, tap on the touchscreen.
- Call up the application ( $\rightarrow$  page 292).

# Functions of the Voice Control System

WARNING Risk of distraction from information systems and communications equipment

If you operate information systems and communication devices integrated in the vehicle when driving, you could be distracted from the traffic situation. This could also cause you to lose control of the vehicle.

- Only operate this equipment when the traffic situation permits.
- If you cannot be sure of this, stop the vehicle whilst paying attention to road and traffic conditions and operate the equipment with the vehicle stationary.

For your own safety, always observe the following points when operating mobile communications equipment and especially your voice control system:

- Observe the legal requirements for the country in which you are driving.
- If you use the voice control system in an emergency your voice can change and your telephone call, e.g. an emergency call, can thereby be delayed.
- Familiarize vourself with the voice control system functions before starting the journey.


With the Voice Control System, various applications in the MBUX multimedia system are operable using voice input. The Voice Control System is operational approximately thirty seconds after the ignition is switched on and is available for the driver's seat and front passenger seat.

The following multimedia system applications can be operated:

- Telephone
- Text messages
- Navigation

- Address book
- Radio
- Media
- · Vehicle functions

# Starting the Voice Control System



Press rocker switch (1) up.

or

Say "Hello Mercedes".

#### Overview of the MBUX Interior Assistant

A

**WARNING** Risk of injury from the camera's laser radiation

This product uses a classification 1 laser system. If the housing is opened or damaged, laser radiation may damage your retina.

- Do not open the housing.
- Always have maintenance work and repairs carried out by a qualified specialist workshop.

This product complies with the requirements of the FDA 21 CFR 1040.10 and 1040.11 with exception of the variations according to the FDA Laser Notice No. 50 from 24. June 2007. The camera is located in the overhead control panel.

If the vehicle is equipped with the MBUX Interior Assistant, selected functions of the multimedia system can be operated contact-free. The MBUX Interior Assistant can differentiate between driver and front passenger interactions and detects specific hand positions (poses).

# System limits, display messages and notes for rectification

The system may be impaired or may not function in the following situations:

 The camera in the overhead control panel may heat up due to operating conditions. As a result the camera may switch off temporarily, particularly during longer periods of operation and at high outside temperatures.

Do not touch or cover the camera and wait until the camera has cooled down and is available again.  The camera is covered, dirty, fogged up or scratched.

Wait until the camera has cooled down before cleaning the camera lens.

Clean the outside of the camera lens with a dry or damp cotton cloth. Do not use microfiber cloths. Do **not** remove the cover when cleaning.

- Recognition can be impaired by reflective clothing, an adverse color of clothing or by accessories, for example.
- Clothing being worn (hat, shawl, scarf) may be limiting the detection area of the camera.

Keep the camera's field of vision clear.

The camera is not operational.

Consult an authorized Mercedes-Benz Center.

# The MBUX Interior Assistant supports the following interactions:

Interaction area	Interaction	Description
In front of the media display or above the touchpad	Proximity to the control element	The Interior Assistant recognizes the approach of the hand towards a control element.
		Depending on the active application, the display will be adjusted in the media display. Some functions differentiate between driver and front passenger.  No specific hand position is required.
Above the center console	Defined pose	A favorite is called up with a defined pose.
Below the inside rearview mirror	Brief up and down movements	With brief up and down movements below the inside rearview mirror the reading light for the driver or the front passenger is switched on or off.
Above the front passenger seat	Stretching out a hand above the front passenger seat	By stretching out a hand above the front passenger seat the search light is switched on. If you withdraw a hand from this area, the search light is switched off again.

#### Switching the reading light and search light and on or off

#### Requirements

- For the reading light:
  - The function is available when it is dark.

- The hand movement takes place in the interaction area below the inside rearview mirror.
- For the search light:
  - The function is available when it is dark.

- The hand movement takes place in the interaction area above the front passenger seat.
- The seat belt on the front passenger seat must **not** be inserted in the seat belt buckle.

# Switching the reading light on and off



 Briefly move a hand up or down beneath the inside rearview mirror.
 The reading light is switched on or off for the driver or the front passenger.

# Switching the search light on and off



- To switch on: reach across the front passenger seat with a hand.
   The search light is switched on for the driver.
- To switch off: take a hand back away from the front passenger seat.

  The search light is switched off again.

# Information on profiles, themes, suggestions and favorites

For electrically adjustable seats observe the following notes. ▲ WARNING Risk of becoming trapped during adjustment of the driver's seat after calling up a driver profile

Selecting a user profile may trigger an adjustment of the driver's seat to the position saved under the user profile. You or other vehicle occupants could be injured in the process.

Make sure that when the position of driver's seat is being adjusted using the multimedia system, no people or body parts are in the seat's range of movement.

If there is a risk of someone becoming trapped, immediately stop the adjustment process by:

 a) Pressing the warning message on the media display.

or

 b) Pressing a position button of the memory function or a seat adjustment switch in the driver's door.
 The adjustment process is stopped.

The driver's seat is equipped with an access preventer

If the driver's door is open, the driver's seat will not be set after calling up the driver's profile.

Profiles store your vehicle settings and settings for the multimedia system. If the vehicle is used by several drivers, the driver can select their own profile without changing the stored profile settings of other drivers.

(i) Information on profiles from Mercedes me connect can be found in the Digital Operator's Manual

Vehicle settings are, for example, driver's seat. steering wheel and mirror settings, climate control and ambient lighting. For the settings of the multimedia system, you can select, for example, radio stations, previous destinations as well as themes. suggestions and favorites.

For recurring driving situations, such as long drives on the freeway, you can save your preferred settings in a theme in the vehicle. In a theme you can save the display of the digital map, your preferred radio station and preferred drive program, for example.

The vehicle can learn the habits of the driver. It then offers suggestions for the most probable navigation destinations, media sources, radio stations or contacts. The requirements for that are the selection of a profile, your consent to the recording of data and sufficient collected data.

Favorites provide quick access to applications that are used often. You can select favorites from categories or add them directly to an application.

# Configuring profiles, themes and suggestions

Multimedia system:







#### Creating a new profile

- ► Select + Create Profile.
- Select an avatar.
- Enter the name and confirm with **OK**.
- Select Continue > .
- Select Current Settings.
- Select Save.

- Activate Bluetooth® and select Connect. Phone, to connect a mobile phone with the user profile.
- Select Finish

#### Selecting profile options

Select ••• for a profile.

The following functions are available:

- Editing, resetting or deleting a profile
- Resetting themes or favorites
- Configuring suggestions

# Configuring suggestions

- Select ••• for a profile.
- Select Suggestion Settings.
- Switch Allow Destination Suggestions, Allow Music Suggestions and Allow Contact Suggestions on or off.
- To deactivate the learning function for one day: activate Deact. Learning for 24 h. For 24 hours no new actions will be trained and no data recorded for the active profile. Suggestions will continue to be shown.

Example: if the option is switched on and a route to a new destination has been calculated, this destination would not be taken into account for the learning function.

### Creating new themes

- ► Select 🞧.
- Select THEMES.
- Select + Create Theme.

The settings saved in the theme are shown.

- ➤ Select Continue > .
- Select Audio and Navigation and store the active settings in the theme.
- ➤ Select Continue > .
- Select an entry screen.
- Select Continue .
- Select an image.
- Enter the names into the entry field and confirm with OK.
- Select Save.

# System settings

# Overview of the system settings menu

In the system settings menu, you can make settings in the following menus and control elements:

- Display
  - Styles
  - Instrument lighting
  - Display brightness
  - Edge lighting
  - Day/night design
- · Control elements:
  - Keyboard language and handwriting recognition
  - Sensitivity of the touchpad
  - Sensitivity of the Touch Controls
- Voice Control System
- Sound
  - Entertainment
  - Navigation and traffic announcements

- Telephone
- Voice amplification to the rear
- · Connectivity:
  - Wi-Fi, Bluetooth®, NFC
- Time & date
- Language
- · Units for distance
- Software updates
- Data import/export
- PIN protection
- System reset

# Information on important system updates

Important system updates may be necessary for the security of your multimedia system's data. Install these updates, or else the security of your multimedia system cannot be ensured.

A system update consists of three steps:

- Downloading or copying of the data required for installation
- · Installation of the downloaded system update

- Activation of the downloaded system update by restarting the system
- (i) If automatic software updates are activated. the system updates will be downloaded automatically.

The multimedia system provides a message when a system update is available.

You have the following selection options:

#### Accept and Install

The system update will be downloaded in the background.

#### Information

Information about the pending system update is displayed.

#### Later

The system update can be downloaded manually at a later time.

#### Deep system updates

Deep system updates access vehicle or system settings and can therefore only be carried out when the vehicle is stationary and the ignition is switched off.

If the download of a deep system update is complete and the downloaded system update is ready for installation, you will be informed of this after the next ignition cycle, for example.

(i) Park the vehicle safely in a suitable location before starting the installation.

Requirements for the installation:

- · The vehicle is switched off.
- · Notes and warnings have been read and accepted.
- The electric parking brake has been applied.

If all requirements have been fulfilled, the downloaded system update is installed. The multimedia system cannot be operated while the downloaded system update is being installed and vehicle functions are restricted

If errors should occur during the installation, the multimedia system automatically attempts to restore the previous version. If restoration of the previous version is not possible, a symbol appears on the media display. Consult a qualified specialist workshop to resolve the problem.

#### Setting up a Wi-Fi hotspot

#### Requirements:

- To set up the Wi-Fi connection of the multimedia system with external hotspots: your vehicle does not have a permanently installed communication module.
- The device to be connected supports at least one of the types of connection described.

#### Multimedia system:



#### Activating/deactivating Wi-Fi

Select Wi-Fi.

# Connecting the multimedia system with an external hotspot using Wi-Fi

The type of connection established must be selected on the multimedia system and on the device to be connected.

- (i) The connection procedure may differ depending on the device. Follow the instructions that are shown in the display. Further information can be found in the manufacturer's operating instructions.
- Select Internet Settings.
- Select Connect via Wi-Fi.
- Select Add Hotspot.

#### Connecting using a QR code

- Select the options of the desired Wi-Fi network.
- Select Connect using QR code.
- Scan the displayed QR code with the device to be connected.

The Wi-Fi connection is established.

#### Connecting using a security key

- Select the options of the desired Wi-Fi network.
- Select Connect Using Security Key.

- Have the security key displayed on the device to be connected (see the manufacturer's operating instructions).
- Enter this security key on the multimedia system.
- Confirm the entry with **ok**.

### Connecting using a WPS PIN

- Select the options of the desired Wi-Fi network.
- Select Connect via WPS PIN Input.
   The multimedia system generates an eightdigit PIN.
- Enter this PIN on the device to be connected.
- Confirm the entry.

### Connecting using a button

- Select the options of the desired Wi-Fi network.
- Select Connect via WPS PBC.
- Select "Connect via WPS PBC" in the options on the device to be connected (see the manufacturer's operating instructions).

- Press the WPS button on the device to be connected.
- Select Continue in the multimedia system.

#### Activating automatic connection

- Select Connect via Wi-Fi.
- Select the options of the desired Wi-Fi network.
- Activate Permanent Internet Connection.

#### Connecting with a known Wi-Fi network

- Select Connect via Wi-Fi.
- Select a Wi-Fi network.

The connection is established again.

# Configuring the multimedia system as a Wi-Fi hotspot for external devices

The type of connection established depends on the device to be connected. The function must be supported by the multimedia system and by the device to be connected. The type of connection established must be selected on the multimedia system and on the device to be connected.

Select Vehicle Hotspot.

Select Connect Device to Vehicle Hotspot.

#### Connecting using WPS PIN generation

- Select Connect via WPS PIN Generation.
- Enter the PIN shown in the media display on the device to be connected and confirm.

#### Connecting using WPS PIN entry

- Select Connect via WPS PIN Input.
- Enter the PIN that is shown on the external device's display on the multimedia system.

#### Connecting using a button

- Select Connect via WPS PBC.
- Press the push button on the device to be connected (see the manufacturer's operating instructions).
- Select Continue.

# Connecting using a security key

Select Connect Device to Vehicle Hotspot. A security key is displayed.

- Select the vehicle from the device to be connected. The vehicle is displayed with the DIRECT-MBLIX XXXXX network name
- Enter the security key which is shown in the media display on the device to be connected.
- Confirm the entry.

#### Connecting using NFC

- Select Connect via NFC.
- Activate NFC on the mobile device (see the manufacturer's operating instructions).
- Hold the device to be connected at the vehicle's NFC interface.
- Select Finished. The mobile device is now connected to the multimedia system hotspot via NFC.

# Generating a new security key

- Select Vehicle Hotspot.
- Select Generate Security Key. A connection will be established with the newly created security key.

To save a security key: select Save. When a new security key is saved, all existing Wi-Fi connections are then disconnected. If the Wi-Fi connections are being re-established, the new security key must be entered.

#### System language

# Notes on the system language

This function allows you to determine the language for the menu displays and the navigation announcements. The selected language affects the characters available for entry. The navigation announcements are not available in all languages. If a language is not available, the navigation announcements will be in English.

# Setting the system language

Multimedia system:

¬→ 🔝 >> Settings >> System

- Set the language.

i) If you are using Arabic map data, the text information can also be shown in Arabic on the navigation map. To do so, select العربية as the language from the language list. Navigation announcements are then also made in Arabic

# Resetting the multimedia system (reset function)

**WARNING** Risk of accidents due to failure of multimedia display functions

While the multimedia system is being reset, its functions such as the rear view camera are not available.

Only reset the multimedia system when the vehicle is stationary.

#### Multimedia system:

→ Settings → System → Reset

Personal data is deleted, for example:

- Station presets
- · Connected mobile phones

- Vehicles with rear telephony: handset connection
- Individual user profiles
- i The guest profile is reset when the settings are restored to the factory settings.
- (i) Vehicles with rear telephony: the handset must be in the cradle while the system is reset.

A prompt appears again asking whether you really wish to reset.

 Select Yes.
 The multimedia system is reset to the factory settings. If you have set a PIN for your system, this will also be reset

#### Navigation

#### Notes on navigation

### Route guidance with augmented reality

A

WARNING Risk of accident and injury as a result of distraction, incorrect depiction or wrong interpretation of the display

The camera image of the augmented reality display is not suitable as a guide for driving.

- Always keep an eye on the actual traffic situation.
- Avoid extended observation of the camera image.

▲ WARNING Risk of accident and injury due to imprecise positioning of additional information

The additional information from the augmented reality display may be inaccurate and is not a substitute for observing and assessing the actual driving situation.

Always keep an eye on the actual traffic situation when carrying out all driving maneuvers.

# Switching navigation on

Multimedia system:



Alternatively: press the NAVI button.

The map displays the current vehicle position.

The navigation menu is shown.

The navigation menu is hidden if route guidance is active.

- To show: tap on the touchscreen.
  - The menu is hidden automatically.

# Navigation overview



Example: digital map with navigation menu

- Enters a POI or address and additional destination entry options
- Interrupts route guidance (if route guidance is active)
- Repeats a navigation announcement and switch navigation announcements on or off
- Calls up the ON THE WAY menu

- To show Route Overview
- To select Alternative Routes
- Report Traffic Incident (Car-to-X)
- To call up the TRAFFIC menu
- To display Traffic Announcements
- To display Area Alerts
- To display Provider Information

- To show Route List
- To call up the POSITION menu
- Save Position
- To display Compass
- Quick-access and settings
  - To show Traffic
  - To show Parking

- To show Highway Information
- Via Advanced options to use View. Announcements and Route

### Entering a destination

Multimedia system:





- Federal state or province in which the vehicle is located
- Enters a POI or address
- List with additional destination entry options
- Deletes an entry

- (5) OK Confirms an entry
- Switches to handwriting recognition
- Enters a space
- Switches to voice input
- Sets the written language

- Switches to digits, special characters and symbols
- Switches to upper-case or lower-case letters Enter the destination in 2. The entries can
  - be made in any order.

The following entries can be made, for example:

- · City, street, house number
- · Street, city
- ZIP code
- · POI name or POI category, e.g. Parking
- Contact name
- Select a search result in list 3.
- $\triangleright$  Calculate the route ( $\rightarrow$  page 308).
- i You can find further information about destination entry, e.g. three-word addresses, in the Digital Operator's Manual.

#### Changing country

- Select the indicator for federal state or province ①.
- Select the federal state or the province in 1.
- Enter the country indicator.
- Select the country on list 3.
- Select the federal state or the province from list (3).

## Using online search

(i) Requirements: the media display shows an Internet connection in the status line with the symbol.

Destination entry uses online map services. If the on-board search finds no suitable destinations or if you change countries, the online search is available.

For the destination you can enter an address, a POI or a three-word address.

- Enter the destination in input line 2.
  The search results are displayed.
- Select the destination in the list.

  The detailed view for the route is displayed.
- Select country indicator ①.

or

- Select the provider for the online service from the countries list.
- Enter the destination in input line 2.
- Select the destination in the list.

# Calculating a route and using settings for route guidance

# Requirements

- The destination has been entered.
- The destination address is shown.

#### Multimedia system:





- No route yet.
  - A route has been mapped.

Select .

The route to the destination is calculated. Route guidance begins.

or

- Select Set as Waypoint.
   The destination address is set as the next intermediate destination.

Or

Select Start New Route Guidance. The destination address is set as the new destination. The previous destination and the intermediate destinations are deleted. Route guidance to the new destination begins.

#### Selecting route settings

- Select .
- Select Advanced.
- Select Route.
- Select the route type.
- ► Take traffic information into consideration with Dynamic Route Guidance ∑.

- Select route options with Avoid Options.
- Activate Suggest Alternative Route.
   Alternative routes are calculated for every route.
- Activate Activate Commuter Route.

  If the requirements are met, the multimedia system automatically detects that the vehicle is on a commuter route. Route guidance begins without voice output.

# Activating route guidance with augmented reality

- During route guidance, tap on the camera symbol on the media display.
   The camera image will be shown instead of the navigation map before a turning maneuver and will show additional information.
- To return to the navigation map: tap on the camera symbol again.

# Displaying additional information in the camera image

- Select .
- Select Advanced.
- Select Augmented Reality.

Activate Street Names and House Numbers. During route guidance, street names and house numbers are shown in the camera image.

# Using map functions

Multimedia system:

¬→ 🖟 >> Navigation

#### Setting the map scale

- To zoom in: tap twice quickly with one finger on the media display.
- ➤ To zoom out: tap with two fingers on the media display.

# Moving the map

- Move one finger in any direction on the touchscreen.
- ➤ To reset the map to the current vehicle position: press → briefly.

# Selecting map orientation

Tap repeatedly on the compass symbol on the map.

The view changes in the sequence 3D, 2D Heading Up to 2D North Up.

#### Switching freeway information on/off

- Select .
- Activate or deactivate Highway Information.

#### Using services

#### Requirements

- There is an Internet connection.
- · Mercedes me connect is available.
- You have set up a user account in the Mercedes me Portal.
- The vehicle is connected to a user account and you have accepted the conditions of use for the service.
  - Further information can be found at: https://www.mercedes.me
- · The service is available.

- The service has been activated at an authorized Mercedes-Benz Center.
- The following additional conditions apply to the Parking service:
  - The navigation services option is available, subscribed to and activated in the Mercedes me Portal
  - The parking service is part of the scope of the Navigation Services.

#### Multimedia system:

→ 🔝 >> Navigation

# Displaying the traffic situation with Live Traffic Information

- Select 🔯 .
- Activate Traffic.
- Select Advanced.
- Select View.
- Select Map Elements.

 Activate Traffic Incidents, Free Flowing Traffic and Delay.

If traffic information has been received, then traffic incidents such as roadworks, road blocks, local reports (e.g. fog) and warning messages are displayed.

The traffic delay is displayed for the current route. Traffic delays lasting one minute or longer are taken into consideration.

# Displaying hazard warnings with Car-to-X-Communication

If hazard warnings are available these can be shown as symbols on the map. The display depends on the settings for the Traffic and Traffic Incidents options.

Set the options. If Traffic is switched off and Traffic Incidents is switched on, the symbols are shown on the prospective route.

# Displaying weather information and other map contents

- ➤ Select 🔯 .
- Select Advanced.

- Select View.
- Select Map Elements.
- Scroll up and show the ONLINE MAP CON-TENT category.
- Switch on a service, e.g. Weather. Current weather information is displayed on the navigation map, e.g. temperature or cloud cover.

# Parking service

NOTE Damage to the vehicle due to not observing the maximum permitted headroom clearance

If the vehicle height is greater than the maximum permitted headroom clearance, the roof and other parts of the vehicle may be damaged.

- Observe the signposted headroom clearance.
- If the vehicle height is greater than the permitted headroom clearance, do not enter.

- Observe the changed vehicle height with add-on roof equipment.
- NOTE Vehicle damage due to failure to observe local information and parking conditions

The data is based on the information provided by the respective service providers.

Mercedes-Benz does not guarantee the accuracv of the information provided in relation to the car park or parking area.

- Always observe the local information and conditions.
- This service is not available in all countries.
- Select and activate Parking.
- Tap on **P** in the map.
- Select a parking option. The map shows the parking options in the vicinity.

The following information is displayed (if available):

- · Destination address, distance from current vehicle position and arrival time
- Information on the car park, e.g.
  - Opening times
  - Parking charges
  - Current occupancy
  - Maximum parking time
  - Maximum access height

The maximum access height shown by the parking service does not replace the need for observation of the actual circumstances.

- Available payment options (Mercedes pay, coins, bank notes, cards)
- Details on parking tariffs
- Number of available parking spaces
- Payment method (e.g. at parking meters)
- Services/facilities at the parking option
- Telephone number

ightharpoonup Calculate the route ( $\rightarrow$  page 308).

#### Notes on the dashcam

NOTE Risk of legal consequences due to violation of legal regulations and data protection provisions

You are legally responsible for operation and use of the dashcam functions.

The legal requirements relating to operation and use of the dashcam can vary depending on the country in which the dashcam is operated.

This function is not permitted in all countries.

- Before using the dashcam, read up on the content of the legal regulations, in particular the data protection requirements in the respective country of use.
- Observe the legal regulations, in particular the data protection requirements.

- (i) Observe the following notes for safe operation:
  - Use USB-IF certified USB storage media.

    The USB-IF is a non-profit society and stands for USB Implementers Forum.

    Based on the USB specification, the USB-IF certifies e.g. USB versions, corresponding cables and plugs as well as methods for supplying energy via the USB interface.
  - Frequent and continuous high-speed overwriting can damage the USB storage media.

# Selecting a USB device for a video recording with the dashcam

# Requirements:

At least one USB device is connected with the multimedia system .

### Multimedia system:

- → Mercedes me & Apps
- Dashcam
- Select the USB device.

(i) When USB devices contain multiple partitions, recorded video files are not always displayed in the recording list.

Mercedes-Benz recommends that you use USB devices with one partition.

# Starting or stopping video recording with the dashcam

#### Requirements

- A USB device is connected with the multimedia system.
- The vehicle is switched on.

### Multimedia system:

#### Dashcam

- If several USB devices are connected with the multimedia system, select a USB device (→ page 312).
- Select the Individual Recording or Loop Recording recording mode. If Individual Recording is selected and the memory is full the recording stops.

If Loop Recording has been selected, several short video files are recorded. When the memory limit is reached, the oldest video file is deleted and recording is continued automatically.

- (i) If Loop Recording is selected, the dashcam app can only overwrite the last 100 video files due to the system limit.
- To start: select Start Recording. The length of the recording is shown. The Please do not remove the storage medium. message appears. The video file is stored on the LISB device
- To end: select End Recording.

A report may appear in the following cases:

- For the Individual Recording recording mode: the memory is full or there are only a few minutes recording time available. The video recording stops or will be stopped imminently. Change the USB device or delete a video file.
- · If a video recording has started and a national border is detected, the National Border Crossed. Please observe the country-spe-

cific regulations on video recording. message appears.

This function is not available in all countries

• The camera is not functional, the Camera Unavailable message appears.

Have the camera checked in an authorized Mercedes-Benz Center

# Telephone

#### Telephony

Notes on telephony

WARNING Risk of distraction from operating integrated communication equipment while the vehicle is in motion.

If you operate communication equipment integrated in the vehicle when driving, you could be distracted from the traffic situation. This could also cause you to lose control of the vehicle.

- Only operate this equipment when the traffic situation permits.
- If you cannot be sure of this, stop the vehicle whilst paying attention to road and traffic conditions and operate the equipment with the vehicle stationary.

WARNING Risk of accident from operating mobile communication equipment while the vehicle is in motion

Mobile communication devices distract the driver from the traffic situation. This can also cause the driver to lose control of the vehicle.

- As a driver, only operate mobile communication devices when the vehicle is stationary.
- As a vehicle occupant, use mobile communication devices only in the designated area, e.g. in the rear passenger compartment.

You must observe the legal requirements for the country in which you are currently driving when

operating mobile communication equipment in the vehicle.

# A

# **WARNING** Risk of injury due to objects being stowed incorrectly

If objects in the vehicle interior are stowed incorrectly, they can slide or be thrown around and hit vehicle occupants. In addition, cup holders, open stowage spaces and mobile phone receptacles cannot always retain all objects within.

There is a risk of injury, particularly in the event of sudden braking or a sudden change in direction.

- Always stow objects so that they cannot be thrown around in such situations.
- Always make sure that objects do not protrude from stowage spaces, parcel nets or stowage nets.
- Close the lockable stowage spaces before starting a journey.
- Always stow and secure heavy, hard, pointed, sharp-edged, fragile or bulky

objects in the trunk/cargo compartment.

Observe the additional information on stowing mobile communications devices correctly:

Loading the vehicle (→ page 126)
 Bluetooth® connection:

The menu view and the available functions in the telephone menu are in part dependent on the Bluetooth® profile of the connected mobile phone. Full functionality is only available if the mobile phone supports both of the following Bluetooth® profiles:

- PBAP (Phone Book Access Profile)
  - The contacts on the mobile phone are shown automatically on the multimedia system.
- MAP (Message Access Profile)
  - The mobile phone message functions can be used on the multimedia system.

Irrespective of this,  ${\sf Bluetooth}^{\it @}$  audio functionality can by used with any mobile radio unit.

For information on the range of functions of the mobile radio unit to be connected, see the manufacturer's operating instructions.

#### Network connection:

The following cases can lead to the call being disconnected while the vehicle is in motion:

- You switch into a transmission/reception station, in which no communication channel is free
- The SIM card used is not compatible with the network available
- A mobile phone with "Twincard" is logged into the network with the second SIM card at the same time

The multimedia system supports calls in HD Voice® for improved speech quality. A requirement for this is that the mobile phone and the mobile phone network provider of the person you are calling support HD Voice® .

Depending on the quality of the connection, the voice quality may fluctuate.

Further information can be obtained from an authorized Mercedes-Benz Center or at: https:// www.mercedes-benz.com/connect

# ■ Telephone menu overview



- Bluetooth® device name of the currently connected mobile phone/of the mobile phone
- Bluetooth® device name of the currently connected mobile phone/of the mobile phone (two phone mode)
- 3 Battery status of the connected mobile phone
- Signal strength of the mobile phone network
- Options
- O Device manager
- Messages

- Numerical pad
- Ontact search

# Telephony operating modes overview

Depending on your equipment, the following telephony operating modes are available:

- A mobile phone is connected to the multimedia system via Bluetooth<sup>®</sup>.
- Two mobile phones are connected with the multimedia system via Bluetooth® (two phone mode).
  - You can use all the functions of the multimedia system with the mobile phone in the foreground.
  - You can receive incoming calls and messages with the mobile phone in the background.

You can interchange the mobile phone in the foreground and background.

# Connecting a mobile phone

#### Requirements

- Bluetooth<sup>®</sup> is activated on the mobile phone (see the manufacturer's operating instructions).
- Bluetooth<sup>®</sup> is activated on the multimedia system.

Multimedia system:



#### Searching for a mobile phone

- ➤ Select 📵.
- Select Connect New Device.

#### Connecting a mobile phone

Authorization follows using secure simple pairing.

- Select a mobile phone.
- A code is displayed in the multimedia system and on the mobile phone.
- If both codes match, confirm the code on the mobile phone.

# Functions in the telephony menu


In the telephony menu you have the following functions, for example:

- Making calls, e.g.:
  - Accepting a call
  - End Call
  - Create Confer. Call
  - Accepting or rejecting a waiting call
- Managing contacts, e.g.:
  - Downloading mobile phone contacts
  - Managing the format of a contact's name
  - Saving a contact as a favorite
- Receiving and sending messages, e.g.:
  - Using the read-aloud function
  - Dictating a new message

#### Mercedes me app

#### Mercedes me calls

Making a call via the overhead control panel



- me button for service or information calls
- SOS button cover
- 3 SOS button (emergency call system)

Making a Mercedes me call

Press me button ①.

#### Making an emergency call

- To open the cover of SOS button 2, press it briefly.
- Press and hold SOS button (3) for at least one second.

If a Mercedes me call is active, an emergency call can still be triggered. This has priority over all other active calls.

### Information about the Mercedes me call

A call to the Mercedes-Benz Customer Center has been initiated via the me button in the overhead control panel or the multimedia system  $(\rightarrow page 317)$ .

Using the voice dialog system you access the desired service:

- · Accident and Breakdown Management
- Mercedes-Benz Customer Center for general information about the vehicle

You can find information on the following topics:

Activation of Mercedes me connect

- Operating the vehicle
- Nearest authorized Mercedes-Benz Center
- Other products and services from Mercedes-Benz

Data is transferred during the connection to the Mercedes-Benz Customer Center ( $\rightarrow$  page 319).

# ■ Calling the Mercedes-Benz Customer Center using the multimedia system

#### Requirements

- · Access to a mobile phone network is available.
- · The contract partner's mobile network coverage is available in the respective region.
- The vehicle must be switched on so that vehicle data can be transferred automatically.

#### Multimedia system:



Call Mercedes me connect. After confirmation, the multimedia system sends the required vehicle data. The data transfer is shown in the media display.

Then you can select a service and be connected to a specialist at the Mercedes-Benz Customer Center

# Calling the Mercedes-Benz customer center after automatic accident or breakdown detection

#### Requirements:

- The vehicle has detected an accident or breakdown situation.
- The vehicle is stationary.
- The hazard warning lights are switched on.
- i This function is not available in all countries.

The vehicle can detect accident or breakdown situations under certain circumstances.

Requirements for collision detection in the context of accident management:

- The vehicle is equipped with an anti-theft alarm system (ATA) (code 551).
- The vehicle is equipped with the interior protection (code 882).
- The vehicle is equipped with the Anti-Theft Protection Package (code P54).

 The collision detection service with theft notification has been activated on Mercedes me connect.

If a collision is detected when the tow-away alarm is armed on a locked vehicle, you will receive a notification in the multimedia system when you switch the vehicle on.

Find out at an authorized Mercedes-Benz Center if this functions is available in your country.

In the event an accident or breakdown is detected, the emergency guide shows safety notes in the multimedia system display. This may take a few seconds.

i The availability of collision detection depends on the vehicle.

In the event an accident or breakdown is detected, the emergency guide shows safety notes in the multimedia system display.

After quitting the emergency guide display on the multimedia system, a prompt appears asking whether you would like to get support from the Mercedes-Benz customer center.

- Select Call.
  - The vehicle data is sent automatically (→ page 321).
  - The Mercedes-Benz customer center takes your call and organizes the breakdown and accident assistance.

You may be charged for these services.

- Depending on the severity of the accident, an automatic emergency call can be initiated. This has priority over all other active calls (→ page 325).
- in addition, if the Mercedes me connect service "Telediagnostics" is active, a similar prompt can appear after a delay in the event of a breakdown. If you are already in contact with the Mercedes-Benz customer center or have already received support, this prompt can be ignored or declined.
- i If you answer the prompt for support from the Mercedes-Benz customer center with Later, the message will be hidden and appear again later.

The prompt triggered by the Mercedes me connect service "Telediagnostics", can either be confirmed or declined. After being declined, this will not be shown again.

#### Arranging a service appointment via a Mercedes me call

If you have activated the maintenance management service, relevant vehicle data is transferred automatically to the Mercedes-Benz customer center. You will then receive individual recommendations regarding the maintenance of your vehicle.

Regardless of whether you have consented to the maintenance management service, the multimedia system reminds you after a certain amount of time that a service is due. A prompt appears asking if you would like to make an appointment.

To arrange a service appointment: select Call. After your agreement, the vehicle data is transferred and the Mercedes-Benz customer center takes your preferred appointment date. The information is then sent to your desired service outlet.

This will contact you to confirm the appointment and if necessary consult about the details

(i) If you select Later after the service message appears, the message is hidden and reappears at a later time.

# Data transferred during a Mercedes me call

When you make a service call via Mercedes me, data is transmitted. This enables targeted advice and a smooth service.

The following requirements must be fulfilled for the transfer of the data:

- · The vehicle is switched on.
- The required data transfer technology is supported by the mobile phone network provider.
- The quality of the mobile connection is sufficient.

Multi-stage transfer depends on the following factors:

- Reason for the initiation of the call
- The available mobile phone transmission technology

- The activated Mercedes me connect services
- The service selected in the voice control system
- i The scope of the transmitted data depends on the vehicle model and equipment. For technical reasons, not all data is available at all times

#### Data transfer if Mercedes me connect services are not activated

If no Mercedes me connect services are activated, the following data is transferred:

- · Vehicle identification number
- Time of the call
- Reason for the initiation of the call
- · Country indicator of the vehicle
- Set language for the multimedia system
- Telephone number of the communication platform installed in the vehicle

If a call is made for a service appointment via the service reminder, the following data is also transmitted:

· Current mileage and maintenance data

If a call is made after automatic accident or breakdown detection using the multimedia system, the following data is also transmitted:

- · Current mileage and maintenance data
- Current vehicle location

If Accident and Breakdown Management is called via the voice control system, the following data can also be called up from the vehicle by the Mercedes-Benz Customer Center:

Current vehicle location

# Data transfer if Mercedes me connect services are activated

An overview of the data transmitted can be found in the respective terms of use for Mercedes me connect services. These can be obtained in the Mercedes me Portal: https://me.secure.mercedes-benz.com

# Data processing

The data transmitted within the scope of the call is deleted from the processing system after the call is finished, in so far as this data is not being used for other activated Mercedes me connect services.

The incident-specific data is processed and stored in the Mercedes-Benz Customer Center and, if required to process the incident, forwarded to the service partner authorized by the Mercedes-Benz Customer Center. Please take note of the data protection information on the Mercedes me Internet page https://www.mercedes.me or in the recorded message immediately after calling the Mercedes-Benz Customer Center.

(i) The recorded message is not available in every country.

#### Mercedes me connect

Information on Mercedes me connect

Mercedes me connect consists of multiple services.

You can use the following services via the multimedia system and the overhead control panel, for example:

- Accident and Breakdown Management (me button or situation-dependent display in the multimedia system)
- Mercedes-Benz Emergency Call System (automatic emergency call and SOS button)

The Mercedes me connect Accident and Breakdown Management and the Mercedes-Benz emergency call centers are available to you around the clock.

The me button and the SOS button can be found on the vehicle's overhead control panel ( $\rightarrow$  page 317).

You can also call the Mercedes-Benz customer center using the multimedia system ( $\rightarrow$  page 317).

Please note that Mercedes me connect is a Mercedes-Benz service. In emergencies, first call the national emergency services using the standard national emergency service telephone numbers. In emergencies, you can also use the

Mercedes-Benz emergency call system  $(\rightarrow page 325)$ .

Observe the conditions of use for Mercedes me connect and other services. These can be obtained in the Mercedes me Portal: https:// me.secure.mercedes-benz.com

Further information about Mercedes me connect services can be obtained in the Mercedes me Portal: https://me.secure.mercedes-benz.com

# Information on Mercedes me connect Accident and Breakdown Management

(i) Accident and Breakdown Management is not available in every country. Contact an authorized Mercedes-Benz Center to find out whether this function is available in your country.

The Accident and Breakdown Management can include the following functions:

• Supplement to the Mercedes-Benz emergency call system ( $\rightarrow$  page 325)

If necessary, the contact person at the Mercedes-Benz emergency call center forwards the call to Mercedes me connect Accident and Breakdown Management, Forwarding the call is however not possible in all countries

 Breakdown assistance by a technician on location and/or the towing away of the vehicle to the nearest authorized Mercedes-Benz Center

You may be charged for these services.

· Addition to the emergency guide after automatic accident or breakdown detection  $(\rightarrow page 318)$ 

In the event of a breakdown or accident, further vehicle data is sent which enables optimal support by the Mercedes-Benz customer center and the authorized service partner or breakdown assistance.

 Addition to the Mercedes me connect service Telediagnostics

With the Telediagnostics function, specific wear and failure reports are recorded by the service provider, in so far as these can be clearly interpreted and are available through the monitoring of components that are subject to diagnostics.

If your vehicle detects a breakdown or threat of a breakdown, you may be prompted via the multimedia system to contact the Mercedes-Benz customer center for further help. This prompt in the multimedia system only appears when the vehicle is stationary.

(i) These services are subject to technical restrictions such as the mobile phone coverage, mobile network quality and the ability of the processing systems to interpret the transferred data. In some circumstances, this can result in delays or the failure of the information to appear in the multimedia system.

Please note that the service and breakdown call is a Mercedes-Benz service. In emergencies, be sure to contact the usual national emergency number first or use the Mercedes-Benz emergency call system ( $\rightarrow$  page 324).

More information about Mercedes me connect services can be obtained in the Mercedes me Portal: https://me.secure.mercedes-benz.com

## Data transferred during Mercedes me connect call services

The data transferred during a Mercedes me connect call depends on:

- . The reason for initiation of the call
- The service that is selected in the voice control system
- · The activated Mercedes me connect services

You can find out which data is transferred when using the services in the currently valid Mercedes me connect terms of use and the data protection information for Mercedes me connect. You can find these in your Mercedes me user account.

# Overview of the Mercedes me & Apps menu

When you log in with a user account to the Mercedes me Portal, then services and offers from Mercedes-Benz will be available to you.

For more information consult an authorized Mercedes-Benz Center or visit the Mercedes me Portal: https://me.secure.mercedes-benz.com

(i) Make sure you always keep the Mercedes me Apps updated.

You can call up the menu using Mercedes me & Apps in the multimedia system.


In the Mercedes me & Apps menu, the following options can be available:

 Connecting the vehicle with the Mercedes me user account

- Deleting a connection between a user account Mercedes me and the vehicle
- · Calling up the Mercedes me services
- Calling up apps such as In-Car Office or the web browser depending on availability

#### Web browser overview

The web browser is started using the Mercedes me & Apps menu.



- URL entry
- Bookmarks
- Web page, back
- Web page, forwards
- To refresh/stop
- Options
- (i) Websites cannot be shown while the vehicle is in motion.

# Overview of Smartphone Integration

With Smartphone Integration, you can use certain functions on your mobile phone via the multimedia system display.

Only one mobile phone at a time can be connected via Smartphone Integration to the multimedia system. Also for use with two phone mode with Smartphone Integration, only one additional

mobile phone can be connected via Bluetooth® to the multimedia system.

The full range of functions for Smartphone Integration is only possible with an internet connection. The appropriate application must be downloaded on the mobile phone to use Smartphone Integration. The mobile phone must be switched on and connected to a USB port with the symbol on the multimedia system using a suitable cable.

#### 324 MBUX multimedia system

Apps for Smartphone Integration

- Apple CarPlay<sup>®</sup>
- Android Auto
- (i) For safety reasons, the first activation of Smartphone Integration on the multimedia system must be carried out when the vehicle is stationary and the parking brake is applied.

You can start Apple CarPlay<sup>®</sup> or Android Auto from the device manager.

(i) Mercedes-Benz recommends disconnecting the connecting cable only when the vehicle is stationary.

#### Overview of transferred vehicle data

When using Smartphone Integration, certain vehicle data is transferred to the mobile phone. This enables you to get the best out of selected mobile phone services. Vehicle data is not directly accessible.

The following system information is transmitted:

- Software release of the multimedia system
- System ID (anonymized)

The transfer of this data is used to optimize communication between the vehicle and the mobile phone.

To do this, and to assign several vehicles to the mobile phone, a vehicle identifier is randomly generated.

This has no connection to the vehicle identification number (VIN) and is deleted when the multimedia system is reset ( $\rightarrow$  page 304).

The following driving status data is transmitted:

- · Transmission position engaged
- Distinction between parked, standstill, rolling and driving
- Day/night mode of the instrument display
- · Drive type

The transfer of this data is used to alter how content is displayed to correspond to the driving situation.

The following position data is transmitted:

- Coordinates
- Speed
- Compass direction

Acceleration direction

This data is used by the mobile phone to improve the accuracy of the navigation (e.g. for continuation in a tunnel).

### Mercedes-Benz emergency call system

# Information on the Mercedes-Benz emergency call system

Your vehicle is equipped with the Mercedes-Benz emergency call system ("eCall"). This feature can help save lives in the event of an accident. eCall in no way replaces assistance provided from dialing 911.

Mercedes-Benz eCall only functions in areas where mobile phone coverage is available from the wireless service providers. Insufficient network coverage from the wireless service providers may result in an emergency call not being transmitted.

eCall is a standard feature in your Mercedes-Benz vehicle. In order to function as intended, the system relies on the transmission of data detailed in

the "Mercedes-Benz emergency call system data transmission" section that follows ( $\rightarrow$  page 326).

To disable eCall, a customer must visit an authorized Mercedes-Benz Service department to deactivate the vehicle's communication module

Deactivation of this module prevents the activation of any and all Mercedes me connect services. After the deactivation of eCall, automatic emergency call and manual emergency call will not be available.

The vehicle must be switched on before an automatic emergency call can be made.

- (i) eCall is activated at the factory.
- (i) eCall can be deactivated by an authorized Mercedes-Benz dealer. Please note that in the event ownership of the vehicle is transferred to another owner in its deactivated state. eCall will remain deactivated unless the new owner visits an authorized Mercedes-Benz dealership to reactivate the system.

## Overview of the Mercedes-Benz emergency call system

eCall can help to reduce the time between an accident and the arrival of emergency services at the site of the accident. It helps locate an accident site in places that are difficult to access. However, even if a vehicle is equipped with eCall, this does not mean the system is ON. As such, eCall does not replace dialing 911 in the event of an accident

An emergency call can be made automatically or manually.

Only make emergency calls if you or others are in need of rescue. Do not make an emergency call in the event of a breakdown or a similar situation.

# Messages on the display

SOS NOT READY: the vehicle is not on or eCall not available.

During an active emergency call, <schar> appears in the display.

You can find more information on the regional availability of eCall at: https://www.mercedesbenz-mobile.com/extra/ecall/

(i) If there is a malfunction of the emergency call system, the loudspeakers, microphone, airbag or the SOS button, for example, are faulty.

You can recognize a malfunction in the emergency call system by the following displays:

- A corresponding message will also appear in the Instrument Display.
- The SOS button lights up red continuously.

## Triggering an automatic Mercedes-Benz emergency call

#### Requirements:

- The vehicle is switched on.
- The starter battery is sufficiently charged.

The Mercedes-Benz emergency call system triggers an emergency call automatically in the following cases:

- After activation of the restraint systems such as airbags or Emergency Tensioning Devices after an accident
- After an emergency stop automatically initiated by Active Emergency Stop Assist

### 326 MBUX multimedia system

The emergency call has been made:

- A voice connection is made to the Mercedes-Benz emergency call center.
- A message with accident data is transmitted to the Mercedes-Benz emergency call center.
   The Mercedes-Benz emergency call center can transmit the vehicle position data to one of the emergency call centers.

The SOS button in the overhead control panel flashes until the emergency call is finished.

It is not possible to immediately end an automatic emergency call.

If no connection can be made to the emergency services either, a corresponding message appears in the media display.

Dial the local emergency number on your mobile phone.

If an emergency call has been initiated:

 Remain in the vehicle if the road and traffic conditions permit you to do so until a voice connection is established with the emergency call center operator.

- Based on the call, the operator decides whether it is necessary to call rescue teams and/or the police to the accident site.
- If no vehicle occupant answers, an ambulance is sent to the vehicle immediately.

# Triggering a manual Mercedes-Benz emergency call

- To use the SOS button in the overhead control panel: press the SOS button at least one second long (→ page 317).
- To use voice control: use the Voice Control System voice commands.

The emergency call has been made:

- A voice connection is made to the Mercedes-Benz emergency call center.
- A message with accident data is transmitted to the Mercedes-Benz emergency call center.
   The Mercedes-Benz emergency call center can transmit the vehicle position data to one of the emergency call centers.

- Remain in the vehicle if the road and traffic conditions permit you to do so until a voice connection is established with the emergency call center operator.
- Based on the call, the operator decides whether it is necessary to call rescue teams and/or the police to the accident site.

If no connection can be made to the emergency services either, a corresponding message appears in the media display.

Dial the local emergency number on your mobile phone.

# Ending an unintentionally triggered manual Mercedes-Benz emergency call

Using the multifunction steering wheel: select

Depress the button for several seconds.

# Data transfer of the Mercedes-Benz emergency call system

In the event of an automatic or manual emergency call the following data is transmitted, for example:

· Vehicle's GPS position data

- GPS position data on the route (a few 300 feet (100 m) before the incident)
- Direction of travel
- Vehicle identification number
- Vehicle drive type
- Number of people detected in the vehicle
- Whether Mercedes me connect is available or not
- Whether the emergency call was initiated manually or automatically
- · Time of the accident
- · Language setting on the multimedia system

Data transmitted is vehicle information. For any questions about the collection, use and sharing of the eCall system data, please contact MBUSA's Customer Assistance Center at 800-FOR-MFRC.

For Canada, please contact MBC's Customer Assistance Center at 1-800-387-0100.

Customer requests for covered information should be submitted via the same channels.

For accident clarification purposes, the following measures can be taken up to an hour after the emergency call has been initiated:

- The current vehicle position can be determined
- A voice connection to the vehicle occupants can be established

# 328 MBUX multimedia system

# Radio & media

Overview of the symbols and functions in the media menu

Symbol	Designation	Function
•	Play	Select to start or continue playback.
0	Rest	Select to pause the playback.
בו	Repeat a track	Select to repeat the current track or the active playlist.  Select once: the active playlist is repeated.  Select twice: the current track is repeated.  Select three times: the function is deactivated.
×	Random playback	Select to play back the tracks in random order.
	Skip forwards/back	Select to skip to the next or to the previous track.
*	Options	Select to show additional options.
<b>=</b>	Categories	Select to show or search through available categories (e.g. playback lists, albums, artists, etc.).
P	Search	Select to search in the active menu. You can search for artists, genres or moods, for example.

Symbol	Designation	Function
	Settings	Select to make settings.
	Home	Select to return to the home screen.
	Messaging	Select to call up messaging.
	Full screen	Select to switch to full screen mode.

The following functions and settings are available in the media menu:

- · Connecting external data storage media with the multimedia system (e.g. using USB or Bluetooth®)
- · Playing back audio or video files

# Authorizing a Bluetooth® audio device for media playback

#### Requirements:

• Bluetooth® is activated on the multimedia system and audio equipment.

- The audio equipment supports the Bluetooth<sup>®</sup> audio profiles A2DP and AVRCP.
- The audio equipment is "visible" for other devices.

Multimedia system:





With Bluetooth® audio, you can play back music files from an external data storage medium, e.g. your smartphone, using the MBUX multimedia system.

To play back audio files using the multimedia system, authorize the external data storage medium on the MBUX multimedia system.

# Authorizing a new Bluetooth® audio device

- Select Connect New Device.
- Select an audio device. Authorization starts. A code is displayed on the multimedia system and on the mobile phone.
- If the codes are identical, confirm on the audio equipment.
- Select Only as Bluetooth Audio Device. The Bluetooth® audio equipment is connected with the multimedia system.

# 330 MBUX multimedia system

# Connecting previously authorized $\mathsf{Bluetooth}^{\circledR}$ audio equipment

Select a Bluetooth® audio device from the list. The connection is being established.

# Overview of the symbols and functions in the radio menu

Symbol	Designation	Function
	Home	Select to return to the home screen.
( <b>3</b> )	Messaging	Select to call up messaging.
M/M	Skip forwards/back	Select to skip to the next or to the previous station.
•	Settings	Select to have further options shown. Settings can be made to the following additional functions, for example:  • Navigation and traffic announcements  • Frequency fix function  • Radio additional text  • Emergency warnings  The setting options are country-dependent.

Symbol	Designation	Function
HD	HD radio™	Select to switch the HD Radio™ function on or off. This function is not available in all countries.
M	Silent function	Select to switch off the sound.
•	Store radio stations	Select to save a station in the presets.
∷≡₁	Station list	Select to have the station list shown.
P	Search	Select to search in the active menu. You can search for artists, genres or moods, for example.

# Additional functions of TuneIn radio

(i) A relatively large volume of data can be transmitted when using TuneIn radio.

### 332 MBUX multimedia system

Symbol	Designation	Function
Ŏ.	Settings	The following additional settings are available in the Tuneln Radio menu:  Selecting stream Logging on to or out of the Tuneln account
*	Favourites	Select during playback to save the station currently set as a favorite.
	Play/Pause	Select to start, stop or continue playback.
	Browse	Select to choose a category and then a radio station.

#### Additional functions of the satellite radio

SIRIUS XM® satellite radio offers more than 175 digital-quality radio channels providing commercial-free music, sports, news and entertainment, for example. SIRIUS XM® satellite radio employs a fleet of high-performance satellites to broadcast

around the clock throughout the USA and Canada. The satellite radio program is available for a monthly fee. Information about this can be obtained from a Sirius XM® Service Center and at https://www.siriusxm.com (USA) or https://www.siriusxm.ca (Canada).

(i) Sirius, XM and all related marks and logos are trademarks of Sirius XM Radio Inc. and its subsidiaries. All other marks, channel names and logos are the property of their respective owners. All rights reserved.

Symbol	Designation	Function
Ö	Settings	The following additional settings are available in the satellite radio menu:  Activate child safety lock to lock channels with adult content  Set alarm program for music and sport alerts  Create TuneMix lists to listen to music seamlessly
	Playback control	Select to show the timeline.  Tap any point on the timeline to skip forwards or back.  Navigate to the end of the timeline to return to live mode.
0	Play	Select to start or continue playback.
0	Rest	Select to pause the playback.

Depending on the frequency band selected, different functions are available to you.

Select the desired frequency band in the radio menu head runner.

Calling up Tuneln Radio

Requirements

### 334 MBUX multimedia system

- The TuneIn Radio service is activated in the Mercedes me Portal
- The data volume is available.
   Depending on the country, data volume may need to be purchased.
- A fast Internet connection for data transmission free of interference
- Data volume can be purchased directly from a mobile phone network provider via the Mercedes me Portal.
- (i) The functions and services are countrydependent. For more information, consult an authorized Mercedes-Benz Center.

### Multimedia system:

- → 🔝 **>>** Radio
- Select TuneIn Radio. The TuneIn menu appears. The last station set starts plaving.
- i The connection quality depends on the local mobile phone reception.

## Setting up satellite radio

#### Requirements:

- Satellite radio equipment is available.
- Registration with a satellite radio provider has been completed.
- If registration is not included when purchasing the system, your credit card details will be required to activate your account.

#### Multimedia system:

- → ☐ → ☐ Radio → SiriusXM
  → ☐ Options
- Select Service Information.

The service information screen appears showing the radio ID and the current subscription status.

- Establish a telephone connection.
- Follow the service staff's instructions. The activation process may take up to ten minutes.
- (i) You can also have the satellite service activated online. To do so, please visit https://

www.siriusxm.com (USA) or https://www.siriusxm.ca (Canada).

## Music and sport alerts

Multimedia system:

→ Radio → SiriusXM → C

## Setting music and sport alerts

This function enables you to program an alert for your favorite artists, tracks or sporting events. Music alerts can be saved whilst a track is being played and sport alerts can be saved during a live game. You can also specify sport alerts via the menu option. The system then continuously searches through all the channels.

Set a music or sports alert, to be informed of matches in the Live program.

### Activating the music information function

► Activate Music Alerts ✓.

## Setting a music alert

Select Add Alert.

### Activating sports information

▶ Activate Activate Sports Alerts <a>
▼</a>.

### Setting a sport alert

- Select Add Alert.
- Select the team name or league in the dialog window.

#### Deleting individual sports and music alerts

Select Manage Music Alerts.

or

- Select Manage Sports Alerts.
- Select an artist or track.

or

- Select a team.
- Select Delete Selected Entries.
  - All highlighted alerts are deleted.

## Deleting all sports and music alerts

Select Manage Music Alerts.

or

- Select Manage Sports Alerts.
- Select Delete All Entries.
  All alerts are deleted.

# Sound settings

# Overview of functions in the sound menu

The setting options and functions available depend on the sound system installed. You can find out which sound system is installed in your vehicle in the Digital Operator's Manual.

# Standard sound system and Advanced sound system

The following functions are available:

- Equalizer
  - Treble, mid-range and bass
- Balance and fader
- Volume
  - Automatic adjustment

# Burmester® surround sound system and Burmester® high-end 3D surround sound system

The following functions are available:

- Equalizer
  - Treble, mid-range and bass
- · Balance and fader
- Sound focus
- VIP seat (Burmester® high-end 3D surround sound system only)
- · Sound profiles
- Volume
  - Automatic adjustment

## ASSYST PLUS service interval display

## Function of the ASSYST PLUS service interval display

The ASSYST PLUS service interval display on the instrument display informs you of the time or distance remaining before the next service due date.

You can hide this service display using the back button on the steering wheel.

Depending on how the vehicle is used, the ASSYST PLUS service interval display may shorten the service interval, e.g. in the following cases:

- · Mainly short-distance driving
- When the engine is often left idling for long periods
- In the event of frequent cold start phases

Mercedes-Benz recommends avoiding such operating conditions.

You can obtain information concerning the servicing of your vehicle from a qualified specialist workshop, e.g. an authorized Mercedes-Benz Center.

# Displaying the service due date

On-board computer:

→ Service → ASSYST PLUS

The next service due date is displayed.

To exit the display: press the back button on the steering wheel.

Bear in mind the following related topic:

 Operating the on-board computer (→ page 286).

# Information on regular maintenance work

! NOTE Premature wear through failure to observe service due dates

Maintenance work which is not carried out at the right time or incompletely can lead to increased wear and damage to the vehicle.

Adhere to the prescribed service intervals.

 Always have the prescribed maintenance work carried out at a qualified specialist workshop.

# Notes on special service requirements

The prescribed service interval is based on normal operation of the vehicle. Have the maintenance work carried out more often than prescribed if operating conditions are difficult or the vehicle is subject to increased stress.

The ASSYST PLUS service interval display is only an aid. It is the responsibility of the driver of the vehicle to have maintenance work carried out more often than prescribed due to actual operating conditions and/or stresses.

Examples of arduous operating conditions:

- Regular city driving with frequent intermediate stops
- · Mainly short-distance driving
- Frequent operation in mountainous terrain or on poor road surfaces

- When the engine is often left idling for long periods
- Operation in particularly dusty conditions and/or if air-recirculation mode is frequently used

In these or similar operating conditions, have the interior air filter, air filter, engine oil and oil filter, for example, changed more frequently. If subject to increased stress, check the tires more. Further information can be obtained at a qualified specialist workshop.

### Battery disconnection periods

The ASSYST PLUS service interval display can calculate the service due date only when the battery is connected.

Display and note down the service due date on the instrument display before disconnecting the battery ( $\rightarrow$  page 336).

# Maintenance Management

# Notes about Maintenance Management

If the Maintenance Management service is activated, relevant data is automatically transferred to the Mercedes-Benz customer center.

The customer center transmits the data to the service partner that you have entered on the Mercedes me website at: http:// www.mercedes.me. You will then receive individual recommendations regarding the maintenance of your vehicle.

- (i) The calculation of the optimal transmission time of the maintenance request to the service partner is subject to technical limitations that may cause the maintenance recommendation to be perceived as too early or too late or not to be made at all. In this case, you can conveniently arrange a maintenance appointment with the customer center via the maintenance reminder in the multimedia system.
- Maintenance Management and the maintenance reminder in the multimedia system are not available in every country. Contact an

authorized Mercedes-Benz Center to find out whether this function is available in your coun-

## Data transferred when using Maintenance Management

When the service is activated, relevant data is automatically transferred to determine the required scope of maintenance as well as malfunction detection and malfunction rectification.

Details on data transfer can be found in the data protection information for the Mercedes me connect services. These can be found at: https:// www.mercedes.me under "My Mercedes me account". "Terms of use".

(i) Maintenance Management and the maintenance reminder in the multimedia system are not available in every country.

# Telediagnosis

## Notes about Telediagnosis

This service is not available in all countries.

The vehicle can detect if certain wear parts need to be replaced or if malfunctions have occurred in vehicle systems. If the Telediagnosis service is activated, relevant data is automatically transmitted to the manufacturer. If fault conditions are detected by the vehicle system self-diagnosis, the system transmits recommendations for action to the Mercedes-Benz customer center depending on the fault detected. The customer center transmits the data to the service partner that you have entered on the Mercedes me website at: http://www.mercedes.me.

For selected faults, the notification that a malfunction has been detected may appear in the multimedia system with a request to contact the Mercedes-Benz customer center. From this message, a call can be made directly to the customer center for assistance.

- (i) The transmission of a notification to the multimedia system depends on the country, vehicle model and equipment and requires a fast data connection, over which the service provider has no influence.
- (i) Reliable fault detection is subject to technical limitations. Therefore, only a limited selection

of faults can be detected and recommendations for action transmitted to the customer center and the service partners. Mercedes-Benz AG is continuously working on the expansion of this service. The fault detection depends on the country, vehicle model and equipment.

# Data transferred when using Telediagnostics

When the service is activated, relevant data is automatically transferred to determine the required scope of maintenance as well as malfunction detection and malfunction rectification.

Details on data transfer can be found in the data protection information for the Mercedes me connect services. These can be found at: https://www.mercedes.me under "My Mercedes me account". "Terms of use".

(i) The scope of the data transmitted depends on the vehicle model and equipment. For technical reasons, not all data is available at all times.

#### Engine compartment

# Opening and closing the hood

A

WARNING Risk of accident due to driving with the hood unlocked

The hood may open and block your view.

- Never release the hood when driving.
- Before every trip, ensure that the hood is locked.



**WARNING** Risk of accident and injury when opening and closing the hood

The hood may suddenly drop into the end position.

There is a risk of injury for anyone in the hood's range of movement.

Do not open or close the hood if there is a person in the hood's range of movement.

# ▲ WARNING Risk of burns when opening the hood

If you open the hood in the event of an overheated engine or fire in the engine compartment, the following situations may occur:

- You may come into contact with hot gases.
- You may come into contact with other escaping hot operating fluids.
- Before opening the hood, allow the engine to cool down.
- In the event of a fire in the engine compartment, keep the hood closed and call the fire service.

# **WARNING** Risk of injury due to moving parts

Components in the engine compartment may continue to run or start unexpectedly even when the drive system is switched off.

Observe the following if you must open the hood:

- Switch off the vehicle.
- Never touch the danger zones surrounding moving components, e.g. the rotation area of the fan.
- Remove jewelery and watches.
- Keep items of clothing and hair away from moving parts.

# **WARNING** Risk of injury from touching live components

The ignition system and the fuel injection system operate with a high voltage. You could receive an electric shock.

Never touch components of the ignition system or fuel injection system when the vehicle is switched on.

The live components include the following, for example:

- Ignition coils
- Fuel injectors

• Electric lines to the ignition coils and the fuel injectors

**WARNING** Risk of burns from hot component parts in the engine compartment

Certain component parts in the engine compartment can be very hot, e.g. the engine, the cooler and parts of the exhaust system.


Allow the engine to cool down and only touch component parts described in the following.

**WARNING** Risk of injury from using the windshield wipers when the hood is open


If the windshield wipers start moving when the hood is open, you could be trapped by the wiper linkage.

Always switch off the windshield wipers and the vehicle first if you need to open the hood.

# Opening the hood



To release the hood, pull on handle ①.



Push handle ② of the hood catch upwards and lift the hood until it opens automatically.

# Closing the hood

! NOTE Damage to the hood

If the hood is closed manually, there is a risk of dents.

▶ Do not close the hood manually.

- Lower the hood to a height of around 8 in (20 cm) and then allow it to fall, applying a little force as you let it go.
- If the hood can still be lifted slightly, open the hood again and close it with a little more force until it engages correctly.

## Engine oil

■ Checking the engine oil level using the onboard computer

#### Requirements

- The engine has been warmed up.
- The vehicle is parked on a level surface.
- The engine is running at idle speed.
- The hood is closed.

The engine oil level is determined during driving. Determining the engine oil level can take up to 30 minutes with a normal driving style and even longer with an active driving style.

## → Service → Engine Oil Level

One of the following messages will appear on the instrument display:

- Measuring Engine Oil Level...: measurement of the oil level is not yet possible.
- Repeat the request after a maximum of 30 minutes' driving.
- Engine Oil Level OK and the bar display for indicating the oil level on the instrument display is green and is between "min" and "max": the oil level is correct.
- Engine Oil Level Add 1,1 qts. and the bar display for indicating the oil level on the instrument display is orange and is below "min":
- Add 1.1 US qt (1 I) of engine oil.
- Reduce Engine Oil Level and the bar display for indicating the oil level on the instrument display is orange and is above "max":

- Drain off any excess engine oil that has been added. To do so, consult a qualified specialist workshop.
- For Engine Oil Level Switch Ignition On
- Switch on the vehicle to check the engine oil level.
- Engine Oil Level System Inoperative: The oil level sensor is defective or not connected.
- Consult a qualified specialist workshop.
- Engine Oil Level System Currently Unavail.
- Close the hood.
- Refilling engine oil

**WARNING** Risk of burns from hot component parts in the engine compartment

Certain component parts in the engine compartment can be very hot, e.g. the engine, the cooler and parts of the exhaust system.

Allow the engine to cool down and only touch component parts described in the following. **WARNING** Risk of fire and injury from engine oil

If engine oil comes into contact with hot component parts in the engine compartment, it may ignite.

- Make sure that no engine oil is spilled next to the filler opening.
- Allow the engine to cool off and thoroughly clean the engine oil from component parts before starting the vehicle.
- NOTE Engine damage caused by an incorrect oil filter, incorrect oil or additives
- Do not use engine oils or oil filters which do not correspond to the specifications explicitly prescribed for the service intervals.
- Follow the instructions on the service interval display for changing the engine oil and observe the prescribed change intervals.
- Do not use additives.

! NOTE Damage caused by adding too much engine oil

Excessive engine oil can damage the engine or the catalytic converter.

- Have excess engine oil removed in a qualified specialist workshop.
- (i) Depending on driving style, the vehicle consumes up to 0.9 US qt (0.8 liters) of oil per 600 miles (1,000 km). The oil consumption may also be higher than this when the vehicle is new or if you frequently drive at high engine speeds.
- Depending on the engine, the cap may be located in different positions in the engine compartment.



- Turn cap ① counter-clockwise and remove it.
- ► Refill engine oil.
- Replace cap ① and turn it clockwise until it engages.
- Check the oil level again (→ page 340).

# Checking the coolant level

**WARNING** Risk of burns from hot component parts in the engine compartment


Certain component parts in the engine compartment can be very hot, e.g. the engine, the cooler and parts of the exhaust system.

Allow the engine to cool down and only touch component parts described in the following.

WARNING Risk of scalding from hot coolant

If you open the cap, you could be scalded.

- Let the motor cool down before opening the cap.
- When opening the cap, wear protective gloves and safety glasses.
- Open the cap slowly to release pressure.



- Park the vehicle on a level surface.
- Check the coolant temperature display on the instrument display.
  - The coolant temperature must be in the bottom quarter of the temperature indicator.
- Slowly turn cap (1) counter-clockwise to release overpressure.

Continue turning cap (1) counter-clockwise and remove it.

The coolant level is correct in the following cases:

- If the engine is cold, the coolant is up to marker bar 2.
- If the engine is warm, the coolant is up to 0.6 in (1.5 cm) over the marker bar 2.
- If necessary, refill with coolant that has been approved for Mercedes-Benz.
- Further information on coolant ( $\rightarrow$  page 418).

# Refilling the windshield washer system

WARNING Risk of burns from hot component parts in the engine compartment


Certain component parts in the engine compartment can be very hot, e.g. the engine, the cooler and parts of the exhaust system.

Allow the engine to cool down and only touch component parts described in the following.

**WARNING** - Risk of fire and injury from windshield washer concentrate

Windshield washer concentrate is highly flammable. It could ignite if it comes into contact with hot engine component parts or the exhaust system.

Make sure that no windshield washer concentrate spills out next to the filler opening.



- Remove cap ① by the tab.
- Add washer fluid.
- (i) Further information about the windshield washer fluid (→ page 419).

# Keeping the air/water duct free

Keep the area between the hood and the windshield free of deposits, e.g. ice, snow or leaves.

# Cleaning and care

Information on washing the vehicle in a car wash

WARNING Risk of accident due to reduced braking effect after washing the vehicle

The braking effect is reduced after washing the vehicle.

After the vehicle has been washed, brake carefully while paying attention to the traffic conditions until the braking effect has been fully restored. ! NOTE Damage from automatic braking

If one of the following functions is activated, the vehicle will brake automatically in certain situations:

- · Active Brake Assist
- Active Distance Assist DISTRONIC
- HOLD function
- · Active Parking Assist

To avoid damage to the vehicle, deactivate these systems in the following or similar situations:

- During towing.
- In a car wash.
- ! NOTE Damage due to unsuitable car wash
- Before driving into a car wash make sure that the car wash is suitable for the vehicle dimensions.

- ► Ensure there is sufficient ground clearance between the underbody and the guide rails of the car wash.
- Ensure that the clearance width of the car wash, in particular the width of the guide rails, is sufficient.

To avoid damage to your vehicle when using a car wash, ensure the following beforehand:

- · Active Distance Assist DISTRONIC is deactivated.
- The HOLD function is switched off.
- The 360° camera or the reversing camera is switched off.
- · The side windows and sliding sunroof are completely closed.
- The outside mirrors are folded in.
- The blower for the ventilation and heating is switched off.
- The windshield wiper switch is in position **0**.
- The key is at a minimum distance of 10 ft (3 m) away from the vehicle. Otherwise, the tailgate could open unintentionally.

- For car washes with a conveyor system:
  - Neutral **N** is engaged.
  - If you would like to leave the vehicle while it is being washed, make sure the key is located in the vehicle. Park position P will otherwise be engaged automatically.
- (i) To prevent damage to the tires or rims, drive straight and into the center of the guide rails of the car wash.
- (i) If, after the car wash, you remove the wax from the windshield and wiper rubbers, this will prevent smearing and reduce wiper noise.

#### Automatic car wash mode

In car wash mode, the vehicle is prepared for driving into an automatic car wash. Car wash mode can be activated at a speed of up to 12 mph  $(20 \text{ km/h}) (\rightarrow \text{page } 346).$ 

The following settings are adjusted when car wash mode is activated:

- The outside mirrors will be folded in.
- To prevent the windshield washer system from starting up automatically, the rain sensor will be deactivated.

- The rear window wiper will be deactivated.
- Mercedes-Maybach vehicles: The running boards will be retracted.
- The air conditioning system will be set to airrecirculation mode.
- · Parking Assist PARKTRONIC will be deactivated.
- Vehicles with 360° camera: The front image will be activated after approximately eight seconds.
- Vehicles with AIRMATIC: The vehicle will be raised to the maximum possible chassis level( $\rightarrow$  page 248).

If raising takes longer than 25 seconds, the following message will appear on the instrument display:

Preparation for Automatic Car Wash Incomplete See Media Display. After some time, the vehicle will automatically continue being raised.

Vehicles with E-ACTIVE BODY CONTROL: The vehicle will be raised to the maximum possible chassis level( $\rightarrow$  page 257).

If raising takes longer than 25 seconds, the following message will appear on the instrument display:

Preparation for Automatic Car Wash Incomplete See Media Display. After some time, the vehicle will automatically continue being raised.

If one of the settings cannot be selected, this will be shown by the **X** symbol next to the respective setting.

Above a speed of 12 mph (20 km/h), car wash mode will be deactivated automatically.

The following settings will be reset when car wash mode is deactivated:

- The outside mirrors will be folded out.
- The rain sensor will be activated.
- The rear window wiper will be activated.
- The air conditioning system will be set to fresh air mode.
- Parking Assist PARKTRONIC will be reset to the previously selected setting.

- Mercedes-Maybach vehicles: The running boards will remain retracted.
- Vehicles with 360° camera: The front image will be deactivated at speeds above 11 mph (18 km/h).
- Vehicles with AIRMATIC: The vehicle will be lowered to the previously set chassis level.
- Vehicles with E-ACTIVE BODY CONTROL: The vehicle will be lowered to the previously set chassis level.

# Activating/deactivating automatic car wash mode

#### Requirements:

- The vehicle is stationary.
- . The engine is running.

Multimedia system:

→ 🙀 ➤ Settings ➤ Quick Access

## Activating automatic car wash mode

- Select Automatic Car Wash Mode.
- Select Start.

If one of the settings cannot be selected, this is displayed by an X behind the respective setting.

 For an overview of the settings made when activating automatic car wash mode (→ page 344).

## Deactivating automatic car wash mode

- Select Stop.
  - The automatic car wash settings are reset.
- (i) The automatic car wash mode is automatically deactivated as soon as a speed of 12 mph (20 km/h) is exceeded.

## Information on using a power washer

A

**WARNING** Risk of an accident when using power washers with round-spray nozzles

The water jet can cause externally invisible damage.

Components damaged in this way may unexpectedly fail.

- Do not use a power washer with roundspray nozzles.
- Have damaged tires or chassis parts replaced immediately.

To avoid damage to your vehicle when using a power washer, ensure the following:

- The key is at a minimum distance of 10 ft (3 m) away from the vehicle. Otherwise, the tailgate could open unintentionally.
- Keep a minimum distance of 11.8 in (30 cm) from the vehicle.
- Vehicles with decorative foil: parts of your vehicle are covered with decorative foil. Maintain a minimum distance of at least 27.6 in (70 cm) between the foiled parts of the vehicle and the nozzle of power washer. Move the power washer nozzle around when cleaning your vehicle. The water temperature of the power washer must not exceed 140 °F (60 °C).
- Observe the information on the correct distance in the operating instructions of the equipment manufacturer.

• Do not point the nozzle of the power washer directly at any sensitive parts, e.g. tires, gaps, electrical components, batteries, illuminants or louvers.

# Washing the vehicle by hand

- **NOTE** Engine damage due to water ingress
- Take care not to point the water iet directly towards the air inlet grille below the hood

Observe the relevant legal requirements (e.g. in some countries, washing by hand is permitted only in specially designated wash bays).

- Use a mild cleaning agent (e.g. car shampoo).
- Wash the vehicle with lukewarm water using a soft car sponge. When doing so, do not expose the vehicle to direct sunlight.
- Carefully hose the vehicle off with water and dry using a chamois.
- Observe the notes on the care of car parts  $(\rightarrow page 349).$

### Notes on paintwork/matt finish paintwork care

To avoid damaging the paintwork and interfering with the driving assistance systems, please observe the following notes:

#### Paint

- Insect remains: soak with insect remover and rinse off the treated areas afterwards.
- · Bird droppings: soak with water and rinse off afterwards
- Tree resin, oils, fuels and greases: remove by rubbing gently with a cloth soaked in petroleum ether or lighter fluid.
- Coolant and brake fluid: remove with a damp cloth and clean water
- Tar stains: use tar remover.
- Wax: use silicone remover.
- · Do not attach stickers, films or similar materials. Have film attached to the bumper only at a qualified specialist workshop.
- Remove dirt immediately, where possible.

#### Matt finish

- Use only care products approved for Mercedes-Benz.
- Do not attach stickers, films or similar materials. Have film attached to the bumper only at a qualified specialist workshop.
- Do not polish the vehicle and alloy wheels.
- Use only car washes that correspond to the latest engineering standards.
- Do not use any car wash program with a final hot wax treatment.
- Do not use paint cleaners, buffing or polishing products or gloss preservers, e.g. wax.

In the event of paintwork damage:

- Always have paintwork repairs carried out at a qualified specialist workshop.
- Make sure the radar sensors function (→ page 211).

# Notes on cleaning decorative films

Observe the "Notes on paintwork/matte finish paintwork care" ( $\rightarrow$  page 347). They also apply to matte decorative films.

Observe the notes on cleaning decorative films to avoid damage.

## Cleaning

- For cleaning, use plenty of water and a mild cleaning agent without additives or abrasive substances (e.g. a car shampoo approved for Mercedes-Benz).
- Remove dirt as soon as possible. Avoid rubbing too hard in order not to damage the decorative film irreparably.
- If there is dirt on the finish or if the decorative film is dull: use the paint cleaner recommended and approved for Mercedes-Benz.
- Insect remains: soak with insect remover and rinse off the treated areas afterwards.
- Bird droppings: soak with water and rinse off afterwards.

 To prevent water stains, dry a film-wrapped vehicle with a soft, absorbent cloth after every car wash.

## Avoiding damage to the decorative film

- The service life and color of decorative films are impaired by:
  - Sunlight
  - Temperature (e.g. hot air blower)
  - Weather conditions
  - Stone chippings and dirt
  - Chemical cleaning agents
  - Oily products
- Do not use polish on matte decorative film. Polishing will have the effect of shining the film-wrapped surface.
- Do not treat matte or structured decorative films with wax. Permanent stains may occur.

Scratches, corrosive deposits, areas affected by corrosion and damage caused by incorrect care cannot always be completely repaired. In this case, contact a qualified specialist workshop.

You can obtain more information on care and cleaning agents from the manufacturer.

In the case of film-wrapped surfaces, visual differences may occur between the surfaces that were not protected by a decorative film after a decorative film has been removed.

(i) Have work or repairs to decorative films carried out at a qualified specialist workshop (e.g. at an authorized Mercedes-Benz Center).

## Notes on care of car parts

WARNING Risk of entrapment if the windshield wipers are switched on while the windshield is being cleaned

If the windshield wipers are set in motion while you are cleaning the windshield or wiper blades, you can be trapped by the wiper arm.

Always switch off the windshield wipers and the vehicle before cleaning the windshield or wiper blades.

To avoid damage to the vehicle, observe the notes on cleaning and care of the following car parts:

#### Wheels and rims

- Use water and acid-free alloy wheel cleaners.
- Do not use acidic alloy wheel cleaners to remove brake dust. This could damage wheel bolts and brake components.
- To avoid corrosion of the brake discs and pads, drive the vehicle for a few minutes after cleaning before parking it. The brake discs and pads will warm up and dry out.

#### Windows



**NOTE** Damage to electronic components due to excess fluids

When cleaning the windows from the inside. fluids such as cleaning agents or water may run down and get behind trim parts of the vehicle interior and cause damage to electronic components.

- Use cleaning agents as sparingly as possible.
- Immediately absorb any excess fluids.

- Clean the windows inside and outside with a damp cloth and with a cleaning agent recommended for Mercedes-Benz
- · Do not use dry cloths or abrasive or solventbased cleaning agents to clean the insides of windows.
- (i) After changing the wiper blades or treating the vehicle with wax, clean the windshield thoroughly with cleaning agents recommended for Mercedes-Benz Failure to observe the application instructions may result in damage, smear marks or glare spots.
- (i) Remove external fogging or dirt on the windshield in front of the multifunction camera. Otherwise, driving systems and driving safety systems may be impaired or unavailable  $(\rightarrow page 211).$

### Wiper blades

- Move the wiper arms into the replacement position ( $\rightarrow$  page 159).
- · With the wiper arms folded out, clean the wiper blades with a damp cloth.

(i) Make sure that the wiper blades are coated. The coating may leave residue on a cloth. Do not rub the wiper blades excessively or clean them too often.

## Exterior lighting

- Clean the lenses with a wet sponge and mild cleaning agent (e.g. car shampoo).
- Use only cleaning agents or cleaning cloths that are suitable for plastic lenses.

#### Sensors

- Clean the sensors in the front and rear bumpers with a soft cloth and car shampoo
   (→ page 211).
- When using a power washer, maintain a minimum distance of 11.8 in (30 cm).

# Running boards

- Use water and acid-free cleaning agents.
- Do not clean the aluminum trim inserts of the running board with alkaline or acidic cleaning agents such as wheel cleaners. Do not use acidic alloy wheel cleaners to remove brake dust. The aluminum trim inserts could otherwise be damaged.

## Reversing camera and 360° Camera

- Open the camera cover with the multimedia system (→ page 266).
- Use clean water and a soft cloth to clean the camera lens
- Do not use a power washer.

#### Trailer hitch

- Observe the notes on care in the trailer hitch manufacturer's operating instructions.
- Do not clean the ball neck with a power washer or solvent.
- Remove traces of rust on the ball (e.g. using a wire brush).
- · Remove dirt with a lint-free cloth.
- After cleaning, lightly oil or grease the ball head.
- Before using trailers with anti-torsional coupling, observe the manufacturer's operating instructions.

#### Notes on care of the interior

A

**WARNING** Risk of injury from plastic parts breaking off after the use of solvent-based care products

Care and cleaning products containing solvents can cause surfaces in the cockpit to become porous. When the airbags are deployed, plastic parts may break away.

Do not use any care or cleaning products containing solvents to clean the cockpit.

A

**WARNING** Risk of injury or fatal injuries from bleached seat belts

Bleaching or dyeing seat belts can severely weaken them.

This can, for example, cause seat belts to tear or fail in an accident.

Never bleach or dye seat belts.

To avoid damage to the vehicle, observe the following notes on cleaning and care:

- · Clean with lukewarm soapy water.
- Do not use chemical cleaning agents.
- Do not dry by heating them to over 176°F (80°C) or exposing them to direct sunlight.

### Display

- Switch off the display and let it cool down.
- Clean the surface carefully with a microfiber cloth and a suitable display care product (TFT-LCD).
- Do not use any other agents.

## Head-up display

- Clean with a soft, non-static, lint-free cloth.
- · Do not use cleaning agents.

#### Plastic trim

- · Clean with a damp microfiber cloth.
- · For heavy soiling: use a cleaning agent recommended for Mercedes-Benz.
- · Do not attach stickers, films or similar materials.

 Do not allow cosmetics, insect repellent or sun cream to come into contact with the plastic trim

#### Real wood and trim elements

- Clean with a microfiber cloth.
- Black piano-lacquer look: clean with a damp cloth and soapy water.
- For heavy soiling: use a cleaning agent recommended for Mercedes-Benz.
- Do not use solvent-based cleaning agents, polishes or waxes.

#### Headliner

• Clean with a brush or dry shampoo.

#### Carpet

• Use a carpet and textile cleaning agent recommended for Mercedes-Benz.

#### Steering wheel made of genuine leather or DINA-MICA



**NOTE** Damage caused by wrong cleaners

Do not use solvent-based cleaning agents such as tar remover or wheel

cleaner; neither should you use polishes or waxes. Otherwise you may damage the finish.

- Clean with a damp cloth and 1% soapy water solution and then wipe with a dry cloth.
- · For heavy soiling: use a cleaning agent recommended for Mercedes-Benz.
- · Leather care: use a leather care agent that has been recommended for Mercedes-Benz.
- Do not allow the leather to become too damp.
- Do not use a microfiber cloth.
- (i) Leather is a natural product. It exhibits natural surface properties such as differences in structure, marks caused by growth and injury or subtle color differences. These surface properties are characteristics of leather and not material malfunctions. Leather is also subject to a natural aging process during which the surface properties change.

#### Genuine leather seat covers

 Vacuum up dirt such as crumbs or dust and then clean the seat covers with a damp cotton

cloth and wipe down with a dry cloth. Regularly clean the seat covers.

- For heavy soiling: use a leather care agent recommended for Mercedes-Benz aftercare.
- Leather care: use a leather care agent that has been recommended for Mercedes-Benz.
- Do not use a microfiber cloth
- Do not allow the leather to become too damp.
- Do not use oil-based cleaning and care products.
- i Leather is a natural product. It exhibits natural surface properties such as differences in structure, marks caused by growth and injury or subtle color differences. These surface properties are characteristics of leather and not material malfunctions. Leather is also subject to a natural aging process during which the surface properties change. Waves or wrinkling in the seat cover may occur due to the stress on the seat; this is caused by the natural leather material. Regular cleaning and care of the leather reduces soiling, wear marks and aging damage and thus significantly extends its life

span. Clothing that can leave stains (e.g. jeans) may discolor the leather.

#### DINAMICA seat covers

- Vacuum up dirt such as crumbs or dust and then use a damp cloth to clean.
- · Do not use a microfiber cloth.

#### Imitation leather seat covers

- Vacuum up dirt such as crumbs or dust and then use a damp cotton cloth and a 1% soap solution to clean the entire seat cover. Do not spot clean.
- Use cleaning and care products recommended for Mercedes-Benz.
- · Do not use a microfiber cloth.
- Do not use oil-based cleaning and care products.


#### Fabric seat covers

 Vacuum up dirt such as crumbs or dust and then use a damp microfiber cloth and a 1% soap solution to clean the entire seat cover. Do not spot clean.

- Use cleaning and care products recommended for Mercedes-Benz.
- Do not use oil-based cleaning and care products.

### Emergency

## Removing the safety vest




A compartment for storing safety vests can be found in the door stowage compartments on all the doors.

To remove: pull out safety vest bag 1 by loop

- Open safety vest bag (1) and take out the safety vest.
- To stow: fold the reflective safety vest, roll it up and stow it in safety vest bag 1.
- Slide safety vest bag along the lower edge of the armrest into the safety vest compartment. When doing so, ensure that loop (2) hangs out well within reach.
- Remove a new reflective safety vest from its packaging material before sliding it into the safety vest compartment. The packaging material may otherwise cause it to slip out or make removing it difficult.

Observe the legal requirements in each country.



- Maximum number of washes
- Maximum wash temperature
- 3 Do not bleach
- On not iron
- Do not tumble dry
- O Do not dry clean
- O Class 2 safety vest

The requirements defined by the legal standard are only fulfilled if the safety vest is the correct size and is fully closed.

Replace the safety vest in the following cases:

• The reflective strips are damaged or dirty

#### 354 Breakdown assistance


- The maximum permissible number of washes is exceeded
- The fluorescence has faded, e.g. due to continuous exposure to sunlight.

Dispose of the safety vest in an environmentally responsible manner.

• To do so, contact your local waste disposal company.

## Warning triangle

Removing the warning triangle (not plug-in hybrid)




- Remove warning triangle 1.
- Setting up the warning triangle



- Fold side reflectors (1) upwards to form a triangle and attach at the top using upper pressstud 2.
- Fold legs (3) down and out to the side.

# First-aid kit (soft sided) overview



In the as-delivered state, the first-aid kit (soft sided) is in the cargo compartment on the righthand side behind service flap 1.

### Flat tire

Notes on flat tires

WARNING Risk of accident due to a flat tire

A flat tire severely affects the driving characteristics as well as the steering and braking of the vehicle.

#### Tires without run-flat characteristics:

- Do not drive with a flat tire.
- Change the flat tire immediately with an emergency spare wheel or spare wheel. Alternatively, consult a qualified specialist workshop.

#### Tires with run-flat characteristics:

Observe the information and warning notes on MOExtended tires (run-flat tires).

In the event of a flat tire, the following options are available depending on your vehicle's equipment:

- Vehicles with MOExtended tires: it is possible to continue the journey for a short period of time. Make sure you observe the notes on MOExtended tires (run-flat tires)  $(\rightarrow page 355)$ .
- Vehicles with a TIREFIT kit: you can seal the tire so that it is possible to continue the journey for a short period of time. To do this, use the TIREFIT kit ( $\rightarrow$  page 356).

- Vehicles with Mercedes me connect: you can make a call for breakdown assistance via the overhead control panel in the case of a breakdown ( $\rightarrow$  page 317).
- All vehicles: change the wheel  $(\rightarrow)$  page 397).
- (i) The emergency spare wheel is only available in certain countries.

# Notes on MOExtended tires (run-flat tires)

WARNING Risk of accident when driving in limp-home mode

When driving in emergency mode the handling characteristics are impaired.

- ▶ Do not exceed the specified maximum speed of the MOExtended tires.
- Avoid any abrupt steering and driving maneuvers as well as driving over obstacles (curbs, pot holes, off-road). This applies, in particular, to a loaded vehicle.
- Stop driving in the emergency mode if vou notice:

- · Banging noise
- Vehicle vibration
- · Smoke which smells like rubber
- Continuous FSP® intervention
- · Cracks in the tire side walls
- After driving in emergency mode, have the rims checked by a qualified specialist workshop with regard to their further use.
- The defective tire must be replaced in every case.

With MOExtended tires (run-flat tires), you can continue to drive your vehicle even if there is a total loss of pressure in one or more tires. However, the tire affected must not show any clearly visible damage.

You can recognize MOExtended tires by the MOExtended marking which appears on the side wall of the tire.

Vehicles with tire pressure monitoring system: MOExtended tires may only be used in conjunc-

#### 356 Breakdown assistance

tion with an activated tire pressure monitoring system.

If a pressure loss warning message appears in the driver's display, proceed as follows:

- · Check the tire for damage.
- If driving on, observe the following notes.

# Driving distance possible in emergency mode after the pressure loss warning:


Load condition	Driving distance possi- ble in emergency mode
Partially laden	50 miles (80 km)
Fully laden	19 miles (30 km)

The driving distance possible in emergency mode may vary depending on the driving style. Observe the maximum permissible speed of 50 mph (80 km/h).

If a tire has gone flat and cannot be replaced with an MOExtended tire, you can use a standard tire as a temporary measure.

# Storage location of the TIREFIT kit (not plug-in hybrid)

The TIREFIT kit is located under the cargo floor.



Example: TIREFIT kit

Tire sealant bottle

Tire inflation compressor

Depending on the vehicle version, the TIREFIT kit may be located in another position under the cargo floor.

### Using the TIREFIT kit

#### Requirements

- Tire sealant bottle and tire inflator compressor are ready for use (→ page 356).
- TIREFIT sticker is present.
- · Gloves are present.

You can use TIREFIT tire sealant to seal perforation damage of up to 0.16 in (4 mm), particularly those in the tire tread. You can use TIREFIT in outside temperatures down to -4 °F (-20 °C).

**WARNING** Risk of accident when using tire sealant

The tire sealant may be unable to seal the tire properly, especially in the following cases:

- There are large cuts or punctures in the tire (larger than damage previously mentioned)
- · The wheel rims have been damaged
- After journeys with very low tire pressure or with flat tires

- Do not continue driving.
- Consult a qualified specialist workshop.

## WARNING Risk of injury and poisoning from tire sealant

The tire sealant is harmful and causes irritation. Do not allow it to come into contact with the skin, eyes or clothing, and do not swallow it. Do not inhale tire sealant fumes. Keep the tire sealant away from children.

If you come into contact with the tire sealant. observe the following:

- ► Rinse off the tire sealant from your skin immediately using water.
- If tire sealant gets into your eyes, thoroughly rinse out the eyes using clean water.
- If tire sealant has been swallowed, immediately rinse out the mouth thoroughly and drink plenty of water. Do not induce vomiting and seek medical attention immediately.

- Change out of any clothes contaminated with tire sealant immediately.
- If allergic reactions occur, seek medical attention immediately.
- NOTE Overheating due to the tire inflation compressor running too long
- ▶ Do not run the tire inflation compressor for longer than ten minutes without interruption.

Comply with the manufacturer's safety notes on the sticker on the tire inflation compressor.

Have the tire sealant bottle replaced in a qualified specialist workshop every five years.

Do not remove any foreign objects that have entered the tire.



- Affix part of the TIREFIT sticker to the instrument cluster within the driver's field of vision
- Affix part 2 of the TIREFIT sticker near the valve on the wheel with the defective tire.

#### 358 Breakdown assistance



- Pull plug (a) with the cable and hose (5) out of the tire inflation compressor housing.
- Push the plug of hose (a) into flange (b) of tire sealant bottle (ii) until the plug engages.
- Place tire sealant bottle ① head downwards into recess ② of the tire inflation compressor.



- Remove the valve cap from valve on the faulty tire.
- Screw filling hose (a) onto valve (7).
- Insert plug (4) into a 12-V-socket in your vehicle.
- Switch on the vehicle.
- Switch on the tire inflation compressor using On/Off switch 3.

The tire is inflated. First, tire sealant is pumped into the tire. The pressure may briefly rise to approximately 500 kPa (5.0 bar/73 psi).

Do not switch off the tire inflation compressor during this phase!

Let the tire inflation compressor run for a maximum of ten minutes.

The tire should then have attained a tire pressure of at least 200 kPa (2.0 bar/29 psi).

If tire sealant leaks out, make sure you clean the affected area as quickly as possible. It is preferable to use clean water.

If you get tire sealant on your clothing, have it cleaned as soon as possible with perchloroethylene.

# If, after ten minutes, a tire pressure of 200 kPa (2.0 bar/29 psi) has not been attained:

- Switch off the tire inflation compressor.
- Unscrew the filling hose from the valve of the defective tire.

Please note that tire sealant may leak out when unscrewing the filling hose.

 Drive forwards or in reverse very slowly for approximately 33 ft (10 m). Pump up the tire again. After a maximum of ten minutes the tire pressure must be at least 200 kPa (2.0 bar/ 29 psi).

WARNING Risk of accident due to the specified tire pressure not being achieved

If the specified tire pressure is not achieved after the specified time, the tire is too badly damaged. The tire sealant cannot repair the tire in this instance.

The braking characteristics as well as the driving characteristics may be greatly impaired.

- Do not continue driving.
- Consult a qualified specialist workshop.

## If, after ten minutes, a tire pressure of 200 kPa (2.0 bar/29 psi) has been attained:

- Switch off the tire inflation compressor.
- Unscrew the filling hose from the valve of the defective tire.

WARNING Risk of accident from driving with sealed tires

A tire temporarily sealed with tire sealant impairs the handling characteristics and is not suitable for higher speeds.

- Adapt your driving style accordingly and drive carefully.
- Do not exceed the maximum speed limit with a tire that has been repaired using tire sealant.
- Observe the maximum permissible speed of 50 mph (80 km/h) for a tire sealed with tire sealant.

NOTE Staining caused by leaking tire sealant

After use, excess tire sealant may leak out from the filling hose.

Therefore, place the filling hose in the plastic bag that contained the TIREFIT kit.

**ENVIRONMENTAL NOTE** Environmental pollution caused by environmentally irresponsible disposal

Tire sealant contains pollutants.

- Have the tire sealant bottle disposed of professionally, e.g. at an authorized Mercedes-Benz Center.
- Stow the tire sealant bottle and the tire inflation compressor.
- Pull away immediately.
- Stop driving after approximately ten minutes and check the tire pressure using the tire inflation compressor.

The tire pressure must now be at least 130 kPa (1.3 bar/19 psi).

WARNING Risk of accident due to the specified tire pressure not being attained

If the specified tire pressure is not reached, the tire is too badly damaged. The tire sealant cannot repair the tire in this instance.

#### 360 Breakdown assistance

The braking and driving characteristics may be greatly impaired.

- Do not continue driving.
- Consult a qualified specialist workshop.

In cases such as the one mentioned above, contact an authorized Mercedes-Benz Center. Or call 1-800-FOR-MERCedes (in the USA) or 1-800-387-0100 (in Canada).

To increase the tire pressure: switch on the tire inflation compressor.



To reduce the tire pressure: press pressure release button 1 next to manometer 2.

- When the tire pressure is correct, unscrew the filling hose from the valve of the sealed tire.
- Screw the valve cap onto the valve of the sealed tire.
- Pull the tire sealant bottle out of the tire inflation compressor.
   The filling hose stays on the tire sealant bottle.
- Drive to the nearest qualified specialist workshop and have the tire, tire sealant bottle and filling hose replaced there.

# Battery (vehicle)

Notes on the 12 V battery

**WARNING** Risk of an accident due to work carried out incorrectly on the battery

Work carried out incorrectly on the battery can, for example, lead to a short circuit. This can restrict functions relevant for safety systems and impair the operating safety of your vehicle.

You could lose control of the vehicle in the following situations in particular:

- When braking
- In the event of abrupt steering maneuvers and/or when the vehicle's speed is not adapted to the road conditions
- In the event of a short circuit or a similar incident, contact a qualified specialist workshop immediately.
- Do not drive on.
- Always have work on the battery carried out at a qualified specialist workshop.
- Further information on ABS (→ page 213)
- Further information on  $ESP^{\mathbb{R}}(\rightarrow page 214)$

For safety reasons, Mercedes-Benz recommends that you use only batteries that have been approved for your vehicle by Mercedes-Benz.

## All vehicles except vehicles with a lithium-ion batterv

WARNING Risk of explosion due to electrostatic charge

Electrostatic charge can ignite the highly explosive gas mixture in the battery.

To discharge any electrostatic charge that may have built up, touch the metal vehicle body before handling the battery.

The highly flammable gas mixture is created while the battery is charging and during starting assistance.

WARNING Danger of chemical burns from the battery acid

Battery acid is caustic.

- Avoid contact with the skin, eyes or clothing.
- Do not lean over the battery.
- Do not inhale battery gases.
- Keep children away from the battery.

Immediately rinse battery acid off thoroughly with plenty of clean water and seek medical attention immediately.

#### All vehicles



**ENVIRONMENTAL NOTE** Environmental damage due to improper disposal of batteries



Batteries contain pollutants. It is illegal to dispose of them with the household rubbish.



Dispose of batteries in an environmentally responsible manner. Take discharged batteries to a qualified specialist workshop or to a collection point for used batteries.

If you have to disconnect the 12 V battery, contact a qualified specialist workshop.

Comply with safety notes and take protective measures when handling batteries.



Risk of explosion if the 12 V battery is used improperly.



Fire, naked flames and smoking are prohibited when you are handling the battery. Avoid creating sparks.



Electrolyte or battery acid is corrosive. Avoid contact with the skin, eves or clothing. Wear suitable protective clothing, in particular gloves, an apron and a face mask. Immediately rinse electrolyte or acid splashes off with clean water. Consult a doctor immediately.



Do not place heavy objects on the surface of the battery or use the battery to support a person in any way.



Wear safety glasses.



Keep children away.

#### 362 Breakdown assistance




Observe this Operator's Manual.

Observe the following if you do not intend to use the vehicle over an extended period of time:

- Non-plug-in hybrid: switch to standby mode (→ page 210).
- Alternatively: connect the battery to a battery charger approved by Mercedes-Benz or consult a qualified specialist workshop to disconnect the battery.

## Notes on the 48 V battery



Work carried out incorrectly on the battery can, for example, lead to a short circuit. This can restrict functions relevant for safety systems and impair the operating safety of your vehicle.

You could lose control of the vehicle in the following situations in particular:

- When braking
- In the event of abrupt steering maneuvers and/or when the vehicle's speed is not adapted to the road conditions
- In the event of a short circuit or a similar incident, contact a qualified specialist workshop immediately.
- Do not drive on.
- Always have work on the battery carried out at a qualified specialist workshop.
- Further information on ABS (→ page 213)
- Further information on  $ESP^{\mathbb{R}}(\rightarrow page 214)$

For safety reasons, Mercedes-Benz recommends that you use only batteries that have been approved for your vehicle by Mercedes-Benz.



**ENVIRONMENTAL NOTE** Environmental damage due to improper disposal of batteries



Batteries contain pollutants. It is illegal to dispose of them with the household trash.



**Li-ion** Dispose of batteries in an environmentally responsible manner. Take discharged batteries to a qualified specialist workshop or to a collection point for used batteries.

If you have to disconnect the 48 V battery, contact a qualified specialist workshop.

Comply with safety notes and take protective measures when handling batteries.



Risk of explosion if the 48 V battery is used improperly.



The surface of the 48 V battery may be hot.



Fire, naked flames and smoking are prohibited when you are handling the battery. Avoid creating sparks.



Electrolyte or battery acid is corrosive. Avoid contact with the skin, eyes or clothing. Wear suitable protective clothing, in particular gloves, an apron and a face mask. Immediately rinse off splashes of electrolyte or acid with plenty of clean water. Consult a doctor immediately.



Do not place heavy objects on the surface of the battery or use the battery to support a person in any way.



Do not perform any work on the battery. Always have any work on the battery carried out at a qualified specialist workshop. Do not disconnect the battery yourself. Do not remove the battery yourself. Do not attempt to open the battery.



Keep children away.



Wear safety glasses.



Observe this Operator's Manual.

Observe the following if you do not intend to use the vehicle over an extended period of time:

• Non-plug-in hybrid: switch to standby mode  $(\rightarrow page 210)$ .

## Notes on starting assistance and charging the 12 V battery

#### All vehicles

When charging the battery and during starting assistance, always use the jump-start connection point in the engine compartment.



NOTE Damage to the battery due to overvoltage

When charging using a battery charger without a maximum charging voltage, the battery or the on-board electronics may be damaged.

Only use battery chargers with a maximum charging voltage of 14.8 V.

## WARNING Risk of explosion due to the ignition of hydrogen gas

If there is a short circuit or sparks are created, there is a danger of hydrogen gas igniting when you charge the battery.

- Make sure that the POSITIVE terminal of a connected battery does not come into contact with vehicle parts.
- Never place metal objects or tools on a battery.
- When connecting and disconnecting the battery, always observe the sequence of battery terminals described.
- During starting assistance, always take care to connect only battery terminals of identical polarity.
- During starting assistance, observe the sequence described for connecting and disconnecting the jumper cables.
- Do not connect or disconnect the battery terminals with the engine running.

#### 364 Breakdown assistance

# **WARNING** Risk of explosion due to a mixture of explosive gases

A mixture of explosive gases can escape from the battery during charging and jump starting.

- Fire, open flames, smoking and creating sparks must be avoided.
- Make sure that there is sufficient ventilation.
- Do not stand over the battery.

# **WARNING** Risk of explosion from a frozen battery

A discharged battery may freeze at temperatures slightly above or below freezing point.

During starting assistance or battery charging, battery gas can be released.

Always allow a battery to thaw before charging it or performing starting assistance.

If the indicator/warning lamps on the instrument cluster do not light up at low temperatures, it is very likely that the discharged battery has frozen. In this case, you may neither jump-start the vehicle nor charge the battery.

The service life of a battery that has been thawed may be dramatically shortened. The starting characteristics may be impaired, especially at low temperatures.

It is recommended that you have a thawed battery checked at a qualified specialist workshop.

#### All vehicles

! NOTE Damage caused by numerous or extended attempts to start the engine

Numerous or extended attempts to start the engine may damage the catalytic converter due to non-combusted fuel.

Avoid numerous and extended attempts to start the engine.

Observe the following points during starting assistance and when charging the battery:

 Use only undamaged jumper cables/charging cables with a sufficient cross-section and insulated terminal clamps.

- Non-insulated parts of the terminal clamps must not come into contact with other metal parts while the jumper cable/charging cable is connected to the battery/jump-start connection point.
- The jumper cable/charging cable must not come into contact with any parts that may move when the engine is running.
- Always make sure that neither you nor the battery is electrostatically charged.
- Keep away from fire and naked flames.
- · Do not lean over the battery.

Observe the additional following points when charging the battery:

- Use only battery chargers tested and approved for Mercedes-Benz.
- Read the battery charger's operating instructions before charging the battery.


Observe the additional following points during starting assistance:

- Starting assistance may be provided only using vehicles, batteries or other jump start devices with a nominal voltage of 12 V.
- The vehicles must not touch.
- Vehicles with gasoline engines: jump-start the vehicle only when the engine and exhaust system are cold.

## Starting assistance and charging the 12 V battery

### Requirements

- The vehicle is secured with the electric parking brake.
- Vehicles with automatic transmission: the transmission is in position P.
- The vehicle and all electrical consumers are switched off.
- The hood is open.



Example: engine compartment

- Slide cover 1 of POSITIVE contact 2 on the jump-starting connection point in the direction of the arrow.
- Connect POSITIVE contact 2 on your vehicle to the positive terminal of the donor battery using the jumper cable/charging cable.

Always begin with POSITIVE contact 2 on vour own vehicle first.

- During starting assistance: start the engine of the donor vehicle and run it at idle speed.
- Connect the negative terminal of the donor battery and ground point 3 of your own vehicle using the jumper cable/charging cable. Begin with the donor battery first.
- During starting assistance: start the engine of vour own vehicle.
- During the charging process: start the charging process.
- **During starting assistance:** let the engines run for several minutes.
- During starting assistance: before disconnecting the jumper cable, switch on an electrical consumer in your own vehicle, e.g. the rear window defroster or lighting.

When the starting assistance/charging process is complete, perform the following steps:

First, remove the jumper cables/charging cables from ground point (3) and the negative

#### 366 Breakdown assistance

terminal of the donor battery, then POSITIVE contact ② and the positive terminal of the donor battery. Begin each time with the contacts on your own vehicle first.

 After removing the jumper cables/charging cables, close cover of POSITIVE contact
 2.

Further information can be obtained at a qualified specialist workshop.

## Replacing the 12 V battery

Observe the notes on the 12 V battery  $(\rightarrow)$  page 360).

Mercedes-Benz recommends that you have the 12 V battery replaced at a qualified specialist workshop, e.g. at an authorized Mercedes-Benz Center.

Observe the following notes if you want to replace the battery yourself:

• Always replace a faulty battery with a battery that meets the specific vehicle requirements.

The vehicle is equipped with a battery using AGM (Absorbent Glass Mat) technology or a lithium-ion battery. Full vehicle functionality is guaranteed only with an AGM battery or lithium-ion battery. For safety reasons, Mercedes-Benz recommends that you use only batteries that have been tested and approved for your vehicle by Mercedes-Benz.

- Carry over detachable parts, such as vent hoses, elbow fitting or terminal covers from the battery being replaced.
- Make sure that the vent hose is always connected to the original opening on the side of the battery.

Install any existing or supplied cell caps. Otherwise, gases or battery acid could escape.

• Make sure that detachable parts are reconnected in the same way.

## Tow starting or towing away

Overview of the permitted towing methods (not plug-in hybrid)

! NOTE Damage from automatic braking

If one of the following functions is activated, the vehicle will brake automatically in certain situations:

- Active Brake Assist
- Active Distance Assist DISTRONIC
- HOLD function
- · Active Parking Assist

To avoid damage to the vehicle, deactivate these systems in the following or similar situations:

- During towing.
- In a car wash.

Mercedes-Benz recommends transporting your vehicle in the case of a breakdown, rather than towing it away.

For towing with both axles on the ground, use a tow rope or tow rod. Do not use tow bar systems.

!	<b>NOTE</b> Damage to the vehicle due to towing away incorrectly
<b>&gt;</b>	Observe the instructions and notes on towing away.

# Permitted towing methods

Vehicle equipment/towing method			
	Both axles on the ground	Front axle raised	Rear axle raised
4MATIC vehicles	Yes, for a maximum of 31 miles (50 km) at 31 mph (50 km/h)	No	No
Vehicles with rear wheel drive	Yes, for a maximum of 31 miles (50 km) at 31 mph (50 km/h)	No	Yes, if the steering wheel is fixed in the center position with a steering wheel lock

# Towing away the vehicle with both axles on the ground

- Observe the notes on the permitted towing methods (→ page 366).
- Make sure that the battery is connected and charged.

A discharged battery has the following effects:

- the vehicle cannot be switched on
- the electric parking brake cannot be released or applied
- the transmission cannot be shifted to position [N] or [P]
- If the transmission cannot be shifted to position N, or the multifunction display in the instrument cluster does not show anything, the vehicle must be transported away (→ page 369). A towing vehicle with lifting equipment is required for vehicle transportation.

NOTE Damage due to towing away at excessively high speeds or over long distances

The drivetrain could be damaged when towing at excessively high speeds or over long distances.

- A towing speed of 30 mph (50 km/h) must not be exceeded.
- A towing distance of 30 miles (50 km) must not be exceeded.

**WARNING** Risk of accident when towing a vehicle which is too heavy

If the vehicle to be tow-started or towed away is heavier than the permissible gross mass of your vehicle, the following situations can occur:

- The towing eye may become detached.
- The vehicle/trailer combination may swerve or rollover.
- Before tow-starting or towing away, check if the vehicle to be tow-started or

towed away exceeds the permissible gross mass.

- Information on the gross vehicle weight rating of the vehicle can be found on the vehicle identification plate (→ page 411).
- Do not open the driver's door or front passenger door as the transmission may otherwise shift to position **P** automatically.
- Install the towing eye ( $\rightarrow$  page 371).
- ► Fasten the towing device.
- NOTE Damage due to incorrect connection of the tow bar
- Only connect the tow rope or tow bar to the towing eyes.
- (i) You can also attach the tow bar to the trailer hitch.
- Deactivate the automatic locking mechanism (→ page 78).
- Do not activate the HOLD function.
- ▶ Deactivate the tow-away alarm ( $\rightarrow$  page 97).

- Deactivate Active Brake Assist ( $\rightarrow$  page 239).
- Shift the transmission to position  $\mathbb{N}$  ( $\rightarrow$  page 195).
- Release the electric parking brake.
- WARNING Risk of accident due to limited safety-related functions during the towing process

Safety-related functions are limited or no longer available in the following situations:

- . The vehicle is switched off.
- The brake system or power steering system is malfunctioning.
- The energy supply or the on-board electrical system is malfunctioning.

When your vehicle is towed away, significantly more effort may be required to steer and brake than is normally required.

- Use a tow bar.
- Make sure that the steering wheel can move freely before towing the vehicle away.

**NOTE** Damage due to excessive tractive power

If you pull away sharply, the tractive power may be too high and the vehicles could be damaged.

▶ Pull away slowly and smoothly.

## Loading the vehicle for transport

- Observe the notes on towing away  $(\rightarrow page 368)$ .
- Connect the towing device to the towing eve in order to load the vehicle.
- (i) You can also attach the tow bar to the trailer hitch.
- Shift the automatic transmission to position N.
- The automatic transmission may be locked in position [P] in the event of damage to the electrics. To shift to N, supply the on-board electrical system with power ( $\rightarrow$  page 365).

- Load the vehicle onto the transporter.
- Shift the automatic transmission to position Ρ.
- Use the electric parking brake to secure the vehicle against rolling away.
- Secure the vehicle only by the wheels.

## Vehicles with ADS PLUS (Adaptive Damping System PLUS)

WARNING Risk of an accident when transporting vehicles with Adaptive Damping System PLUS


When transporting vehicles with Adaptive Damping System PLUS, the vehicle/trailer combination may begin to rock and start to skid.

- Load the vehicle correctly onto the transporter.
- Secure the vehicle on all four wheels with suitable tensioning straps.

#### 370 Breakdown assistance


- Do not exceed the maximum permissible speed of 35 mph (60 km/h) when transporting.
- ! NOTE Damage to the vehicle from securing it incorrectly
- After loading, the vehicle must be secured on all four wheels. Otherwise, the vehicle could be damaged.
- A minimum distance of 8 in (20 cm) upwards and 4 in (10 cm) downwards must be kept to the transport platform.
- Secure the vehicle on all four wheels after loading.

# 4MATIC vehicles/vehicles with automatic transmission



- Make sure that the front and rear axles come to rest on the same transportation vehicle.
- I NOTE Damage to the drive train due to incorrect positioning of the vehicle
- Do not position the vehicle above the connection point of the transport vehicle.


## Towing eye storage location



Example: towing eye

Towing eye 1 is located under the cargo floor.

## Installing and removing the towing eye



- Press the mark on cover (1) inwards and remove.
- Screw in the towing eye clockwise at least seven revolutions as far as it will go and tighten it. If the towing eye cannot be screwed in as described above, this may be because

the thread is dirty. The towing operation cannot be performed.

Vehicles with a trailer hitch: vehicles with a trailer hitch do not have a rear bracket for the towing eve. Fasten the tow bar to the trailer hitch.

- After removing the towing eye, snap cover 1 into the bumper.
- **NOTE** Damage to the vehicle due to incorrect use of the towing eye or trailer hitch

When a towing eye or trailer hitch is used to recover a vehicle, the vehicle may be damaged in the process.

- Only use the towing eye or trailer hitch to tow away or tow start the vehicle.
- Do not use the towing eye or trailer hitch to tow the vehicle during recovery.

## Tow-starting the vehicle

#### Vehicles with automatic transmission.

NOTE Damage to the automatic transmission due to tow starting

The automatic transmission may be damaged in the process of tow starting vehicles with automatic transmission

- Vehicles with automatic transmission. must not be tow started.
- Vehicles with automatic transmissions must not be tow-started.

## Electrical fuses

Notes on electrical fuses

WARNING Risk of accident and injury due to overloaded lines

If you manipulate or bridge a faulty fuse or if you replace it with a fuse with a higher amperage, the electric line could be overloaded.

#### 372 Breakdown assistance

This could result in a fire.

- Always replace faulty fuses with specified new fuses containing the correct amperage.
- ! NOTE Damage due to incorrect fuses

Using incorrect fuses can result in damage to electrical components or systems or their functions being considerably restricted.

 Use only fuses approved for Mercedes-Benz with the respective specified fuse rating.

Blown fuses must be replaced with fuses of the same rating, which you can recognize by the color and the label. The fuse ratings and further information to be observed can be found in the fuse assignment diagram.

Fuse assignment diagram: on the fuse box in the cargo compartment ( $\rightarrow$  page 373).

! NOTE Damage or malfunctions caused by moisture

Moisture may cause damage to the electrical system or cause it to malfunction.

- When the fuse box is open, make sure that no moisture can enter the fuse box.
- When closing the fuse box, make sure that the seal of the lid is positioned correctly on the fuse box.

If the newly inserted fuse also blows, have the cause traced and rectified at a qualified specialist workshop.

Ensure the following before replacing a fuse:

- The vehicle is secured against rolling away.
- All electrical consumers are switched off.
- · The vehicle is switched off.

The electrical fuses are located in various fuse boxes:

 Fuse box in the engine compartment on the left-hand side of the vehicle, when viewed in the direction of travel (→ page 372)

- Fuse box on the driver's side of the cockpit
   (→ page 373)
- Fuse box in the front passenger footwell
   (→ page 373)
- Fuse box in the cargo compartment on the right-hand side of the vehicle, when viewed in the direction of travel (→ page 373)

# Opening and closing the fuse box in the engine compartment

#### Requirement

You need a dry cloth and a screwdriver.

Observe the notes on electrical fuses  $(\rightarrow page 371)$ .


## Opening

A

**WARNING** Risk of injury from using the windshield wipers when the hood is open

If the windshield wipers start moving when the hood is open, you could be trapped by the wiper linkage.

Always switch off the windshield wipers and vehicle before opening the hood.



- Remove any existing moisture from the fuse box using a dry cloth.
- Loosen screws 2 and remove fuse box lid 1 from the top.

## Closing

- Check whether the seal is positioned correctly in the lid.
- Insert the lid into the holder at the rear of the fuse box.
- Fold down the lid of the fuse box and tighten screws 2.
- Close the hood.

## Opening and closing the fuse box in the cockpit

 Observe the notes on electrical fuses  $(\rightarrow page 371)$ .

The fuse box is on the driver's side on the side of the cockpit under a cover.

Mercedes-Benz recommends you have the fuse box opened at an authorized Mercedes-Benz Center.

## Opening and closing the fuse box in the front passenger footwell

Contact a Mercedes-Benz service center for further information.

## Opening and closing the fuse box in the cargo compartment

Observe the notes on electrical fuses  $(\rightarrow page 371)$ .

Open the side cover.



Remove cover ①.

# 374 Breakdown assistance

The fuse assignment diagram is on the side of the fuse box.

## Notes on noise or unusual handling characteristics

Make sure there are no vibrations, noises or unusual handling characteristics when the vehicle is in motion. This may indicate that the wheels or tires are damaged. Hidden tire damage could also be causing the unusual handling characteristics.

If you suspect that a tire is defective, reduce your speed immediately and have the tires and wheels checked at a qualified specialist workshop.

# Notes on regularly inspecting wheels and tires

WARNING Risk of injury through damaged tires

Damaged tires can cause tire pressure loss.

Check the tires regularly for signs of damage and replace any damaged tires immediately.

## WARNING Risk of hydroplaning due to insufficient tire tread

Insufficient tire tread will result in reduced tire grip.

In heavy rain or slush the risk of hydroplaning is increased, in particular where speed is not adapted to suit the conditions.

Thus, you should regularly check the tread depth and the condition of the tread across the entire width of all tires.

Minimum tread depth for:

• Summer tires: 1/8 in (3 mm)

M+S tires: ½in (4 mm)

For safety reasons, replace the tires before the legally-prescribed limit for the minimum tread depth is reached.

Carry out the following checks on all wheels regularly, at least once a month or as required, for example, prior to a long journey or driving offroad:

Check the tire pressure (→ page 376).

- Visually inspect wheels and tires for damage.
- · Check the valve caps.
- Visually inspect the tire tread depth and the tire contact surface across the entire width

The minimum tread depth for summer tires is 1/8 in (3 mm) and for winter tires 1/6 in (4 mm).



Six marks 1 show where the bar indicators (arrow) are integrated into the tire tread. They are visible once a tire tread depth of approximately 1/16 in (1.6 mm) has been reached.

## Notes on snow chains



**WARNING** Risk of accident due to incorrectly installed snow chains

If you have installed snow chains on the front wheels, they may drag against the vehicle body or chassis components.

- Never install snow chains on the front wheels.
- Only install snow chains on the rear wheels in pairs.
- NOTE Damage to components of the vehicle body or chassis due to mounted snow chains

If you mount snow chains to the front wheels of 4MATIC vehicles, you may damage components of the vehicle body or chassis.

- Only mount snow chains to the rear wheels of 4MATIC vehicles.
- Snow chains are only permissible for certain wheel/tire combinations. You can obtain infor-

mation about this from an authorized Mercedes-Benz Center.

- For safety reasons, only use snow chains that have been specifically approved for your vehicle by Mercedes-Benz, or snow chains with the same quality standard.
- Comply with the installation instructions of the snow chain manufacturer.
- If snow chains are installed, the maximum permissible speed is 30 mph (50 km/h).
- Vehicles with Active Parking Assist: do not use Active Parking Assist when snow chains are installed.
- You can deactivate ESP<sup>®</sup> to pull away
   (→ page 216). This allows the wheels to spin, achieving an increased driving force.

#### Tire pressure

#### Notes on tire pressure



WARNING Risk of accident due to insufficient or excessive tire pressure

Underinflated or overinflated tires pose in particular the following risks:

- The tires can burst.
- The tires can wear excessively and/or unevenly.
- The driving characteristics as well as the steering and braking characteristics may be greatly impaired.
- Comply with the recommended tire pressures and check the tire pressure of all tires, including the spare wheel, regularly:
- Monthly
- When the load changes
- Before embarking on a longer journey

- If operating conditions change, e.g. offroad driving
- Adjust the tire pressure, if necessary.

Tire pressure which is too high or too low can:

- Shorten the service life of the tires.
- · Cause increased tire damage.
- · Adversely affect driving characteristics and thus driving safety, e.g. due to hydroplaning.

## WARNING Risk of accident due to too low a tire pressure

Tires with pressure that is too low can overheat and burst as a consequence.

In addition, they also suffer from irregular wear, which can significantly impair the braking properties and the handling characteristics.

Avoid excessively low tire pressure.

Tire pressure which is too low can cause:

Tire defects as a result of overheating

- Impaired handling characteristics
- · Irregular wear
- Increased fuel consumption

## WARNING Risk of accident due to too high a tire pressure

Tires with excessively high pressure can burst. In addition, they also suffer from irregular wear, which can significantly impair the braking properties and the handling characteristics.

Avoid excessively high tire pressures.

Tire pressure which is too high can cause:

- · Increased braking distance
- Impaired handling characteristics
- Irregular wear
- Impaired driving comfort
- Susceptibility to damage

## **A** WARNING Risk of accident due to repeated pressure drop in the tires

The wheels, valves or tires could be damaged.

Too low a tire pressure can lead to the tires bursting.

- Examine the tires for foreign objects.
- Check whether the tire has a puncture or the valve has a leak
- If you are unable to rectify the damage. contact a qualified specialist workshop.

You can find information on the recommended tire pressures for the vehicle's factory-installed tires on the following labels:

- Tire and Loading Information placard on the B-pillar of your vehicle ( $\rightarrow$  page 382).
- Tire pressure table on the inside of the fuel filler flap ( $\rightarrow$  page 378).

Observe the maximum tire pressure  $(\rightarrow page 388)$ .

Use a suitable pressure gauge to check the tire pressure. The outer appearance of a tire does not

#### 378 Wheels and tires

permit any reliable conclusion about the tire pressure.

Only correct tire pressure when the tires are cold. Conditions for cold tires:

- The vehicle has been parked with the tires out of direct sunlight for at least three hours.
- The vehicle has traveled less than 1 mile (1.6 km).

The vehicle's tires heat up when driving. As the temperature of the tires increases, so too does the tire pressure.

Vehicles with a tire pressure monitoring system: you can also check the tire pressure using the onboard computer (→ page 380).

The tire pressure recommended for increased load/speed in the tire pressure table can affect the ride comfort.

**WARNING** Risk of accident due to unsuitable accessories on tire valves

If you mount unsuitable accessories onto tire valves, the tire valves may be overloaded and

malfunction, which can cause tire pressure loss.

Only screw standard valve caps or valve caps specifically approved by Mercedes-Benz for your vehicle onto the tire valve.


## Notes on trailer operation

Always inflate the rear axle tires to the recommended tire pressure on the tire pressure table for increased load.

## Tire pressure table

The tire pressure table is on the inside of the fuel filler flap.


(i) The data shown in the images is example data.



The tire pressure table shows the recommended tire pressure for all tires approved for this vehicle. The recommended tire pressures apply for cold tires under various operating conditions, i.e. loading and/or speed of the vehicle.

If one or more tire sizes precede a tire pressure, the following tire pressure information is only valid for those tire sizes and their respective load condition.

The load conditions "partially laden" and "fully laden" are defined in the table for different numbers of passengers and amounts of luggage. The actual number of seats may differ from this.



Some tire pressure tables only show the rim diameter instead of the complete tire size, e.g. R18. The rim diameter is part of the tire size and can be found on the tire side wall ( $\rightarrow$  page 389).

- Tire and Loading Information placard  $(\rightarrow page 382)$
- Maximum tire pressures (→ page 388)

## Checking the tire pressure manually

- Read the tire pressure recommended for the current operating conditions from the tire and loading information placard or the tire pressure table. Observe the notes on tire pressure.
- Remove the valve cap of the tire to be checked.
- Press the tire pressure gauge securely onto the valve
- Read the tire pressure.
- If the tire pressure is lower than the recommended value, increase the tire pressure to the recommended value.
- If the tire pressure is higher than the recommended value, release air. To do so, press down the metal pin in the valve, e.g. using the tip of a pen. Then check the tire pressure again using the tire pressure gauge.
- Screw the valve cap onto the valve.

### Further related subjects:

- Notes on tire pressure (→ page 376)
- Tire pressure table (→ page 378)

 Tire and loading information placard  $(\rightarrow page 382)$ 

## Tire pressure monitoring system

Function of the tire pressure monitoring system

**DANGER** Risk of accident due to incorrect tire pressure

Each tire, including the spare (if provided). should be checked monthly when cold and inflated to the inflation pressure recommended by the vehicle manufacturer on the vehicle placard or tire inflation pressure label. (If vour vehicle has tires of a different size than the size indicated on the vehicle placard or tire inflation pressure label, you should determine the proper tire inflation pressure for those tires.)

As an added safety feature, your vehicle has been equipped with a tire pressure monitoring system (TPMS) that illuminates a low tire pressure telltale when one or more of your tires is significantly under-inflated. Accordingly, when

the low tire pressure telltale illuminates, you should stop and check your tires as soon as possible, and inflate them to the proper pressure. Driving on a significantly under-inflated tire causes the tire to overheat and can lead to tire failure. Under-inflation also reduces fuel efficiency and tire tread life, and may affect the vehicle's handling and stopping ability. Please note that the TPMS is not a substitute for proper tire maintenance, and it is the driver's responsibility to maintain correct tire pressure, even if under-inflation has not reached the level to trigger illumination of the TPMS low tire pressure telltale.

Your vehicle has also been equipped with a TPMS malfunction indicator to indicate when the system is not operating properly. The TPMS malfunction indicator is combined with the low tire pressure telltale. When the system detects a malfunction, the telltale will flash for approximately one minute and then remain continuously illuminated. This sequence will continue upon subsequent vehicle start-ups as long as the malfunction exists.

When the malfunction indicator is illuminated, the system may not be able to detect or signal low tire pressure as intended. TPMS malfunctions may occur for a variety of reasons, including the installation of replacement or alternate tires or wheels on the vehicle that prevent the TPMS from functioning properly.



The system checks the tire pressure and the tire temperature of the tires fitted to the vehicle by means of a tire pressure sensor.

The tire pressure and the tire temperature appear on the on-board computer ( $\rightarrow$  page 380).

If there is a substantial pressure loss or if the tire temperature is excessive, you will be warned with display messages ( $\rightarrow$  page 480) or the  $\boxed{\textcircled{1}}$  warning lamp on the instrument display ( $\rightarrow$  page 500).

The tire pressure monitoring system is only an aid. It is the driver's responsibility to set the tire pressure to the recommended cold tire pressure suitable for the operating situation.

In most cases, the tire pressure monitoring system will automatically update the new reference values after you have changed the tire pressure. You can, however, also update the reference values by restarting the tire pressure monitoring system manually ( $\rightarrow$  page 381).

### System limits

The system may be impaired or may not function particularly in the following situations:

- incorrect reference values were taught in
- sudden pressure loss caused by a foreign object penetrating the tire, for example
- there is a malfunction caused by another radio signal source

# Checking the tire pressure with the tire pressure monitoring system

#### Requirements

· The vehicle is switched on.

On-board computer:

#### ¬→ Service → Tires

One of the following displays appears:

• Current tire pressure and tire temperature of the individual wheels:



- Tire pressure will be displayed after driving a few minutes
- Tire Pressure Monitor Active: the teach-in process of the system is not yet complete. The tire pressures are already being monitored.
- Compare the tire pressure with the recommended tire pressure for the current operating

condition ( $\rightarrow$  page 378). Additionally, observe the notes on cold tires ( $\rightarrow$  page 376).

- The values displayed on the on-board computer may deviate from those of the tire pressure gauge as they refer to sea level. At high elevations, the tire pressure values indicated by a pressure gauge will be higher than those shown by the on-board computer. In this case. do not reduce the tire pressure.
- Restarting the tire pressure monitor

### Requirements

• The recommended tire pressure is correctly set for the respective operating status at all of the wheels ( $\rightarrow$  page 376).

Restart the tire pressure monitor in the following situations:

- The tire pressure has changed.
- The wheels or tires have been changed or newly fitted.

On-board computer:

#### ¬→ Service ➤ Tires

- Swipe downwards on the Touch Control on the left-hand side of the steering wheel. The Use Current Pressures as New Reference Values message is shown on the instrument display.
- To restart, press the Touch Control on the lefthand side of the steering wheel. The Tire Press. Monitor Restarted message is shown on the instrument display.

Current warning messages are deleted and the yellow (!) warning lamp goes out.

After you have been driving for a few minutes, the system checks whether the current tire pressure is within the specified range. The current tire pressure is then accepted as a reference value and monitored.

Be sure to also pay attention to the following related topic:

Notes on tire pressure (→ page 376)

## Loading the vehicle

Notes on the Tire and Loading Information placard

**WARNING** Risk of accident from overloaded tires


Overloaded tires may overheat and burst as a consequence. Overloaded tires can also impair the steering and handling characteristics and lead to brake failure.

- Observe the load rating of the tires.
- ► The load rating must be at least half the permissible axle load of the vehicle.
- Never overload the tires by exceeding the maximum load.

The Tire and Loading Information placard is on the B-pillar on the driver's side of the vehicle.



1 Tire and Loading Information placard



The data shown in the illustration is example data.

The Tire and Loading Information placard shows the following information:

 Maximum number of seats ② according to the maximum number of people permitted to travel in the vehicle.

- Maximum permissible load (3) comprises the gross weight of all vehicle occupants, load and luggage.
- Recommended tire pressures (1) for cold tires. The recommended tire pressures are valid for the maximum permissible load and up to the maximum permissible vehicle speed.

#### Please also note:

- Information on permissible weights and loads on the vehicle identification plate  $(\rightarrow page 411)$ .
- Information on tire pressure in the tire pressure table ( $\rightarrow$  page 378).

#### Further related subjects:

- Determining the maximum permissible load  $(\rightarrow page 383)$
- Notes on tire pressure (→ page 376).

## Steps for Determining Correct Load Limit

The following steps have been developed as required of all manufacturers under Title 49. Code of U.S. Federal Regulations, Part 575, pursuant to

the "National Traffic and Motor Vehicle Safety Act of 1966".

- ▶ (1): Locate the statement "The combined weight of occupants and cargo should never exceed XXX kg or XXX lbs." on your vehicle's placard.
- (2): Determine the combined weight of the driver and passengers that will be riding in vour vehicle.
- (3): Subtract the combined weight of the driver and passengers from XXX kg or XXX lbs.
- (4): The resulting figure equals the available amount of cargo and luggage load capacity. For example, if the "XXX" amount equals 1,400 lbs. and there will be five 150 lb passengers in your vehicle, the amount of available cargo and luggage load capacity is 650 lbs.  $(1,400 - 750 (5 \times 150) = 650 \text{ lbs.})$
- (5): Determine the combined weight of luggage and cargo being loaded on the vehicle. That weight may not safely exceed the available cargo and luggage load capacity calculated in Step 4.

- (6): If your vehicle will be towing a trailer, load from your trailer will be transferred to your vehicle. Consult this manual to determine how this reduces the available cargo and luggage load capacity of your vehicle.
- (i) Not all vehicles are permitted to tow a trailer. Towing a trailer is only permitted if a trailerhitch is installed. Please consult an authorized Mercedes-Benz dealer if you have any guestions about towing a trailer with your vehicle.

Even if you have calculated the total load carefully. you should still make sure that the maximum permissible gross weight and the maximum gross axle weight rating of your vehicle are not exceeded. Details can be found on the vehicle identification plate.

Have your loaded vehicle - including driver. occupants and load - weighed on a vehicle weighbridge.

The measured values may not exceed the maximum permissible values stated on the vehicle identification plate.

#### 384 Wheels and tires

#### Further related subjects:

- Calculation example for determining the maximum load (→ page 384)
- Tire and Loading Information placard (→ page 382)
- Tire pressure table (→ page 378)
- Vehicle identification plate (→ page 411)

# Calculation example for determining the maximum load

The following table shows examples of how to calculate total and load capacities with varying seating configurations and different numbers and sizes of occupants. The following examples use a maximum load of 1500 lbs (680 kg). **This is for** 

illustration purposes only. Make sure you are using the actual load limit for your vehicle stated on your vehicle's Tire and Loading Information placard ( $\rightarrow$  page 382).

The higher the weight of all the occupants, the smaller the maximum load for luggage.

#### Step 1

	Example 1	Example 2
Combined maximum weight of occupants and load (data from the Tire and Loading Information placard)	1500 lbs (680 kg)	1500 lbs (680 kg)

	Example 1	Example 2
Number of people in the vehicle (driver and occupants)	5	1
Distribution of the occupants	Front: 2 Rear: 3	Front: 1
Weight of occupants	Occupant 1: 150 lbs (68 kg) Occupant 2: 180 lbs (82 kg) Occupant 3: 160 lbs (73 kg) Occupant 4: 140 lbs (63 kg) Occupant 5: 120 lbs (54 kg)	Occupant 1: 200 lbs (91 kg)
Total weight of all occupants	750 lbs (340 kg)	200 lbs (91 kg)


# Step 3

	Example 1	Example 2
Permissible load (maximum gross vehicle weight rating from the Tire and Loading Information placard minus the gross weight of all occupants)	1500 lbs (680 kg) - 750 lbs (340 kg) = 750 lbs (340 kg)	1500 lbs (680 kg) - 200 lbs (91 kg) = 1300 lbs (589 kg)

#### 386 Wheels and tires

## Tire labeling

## Overview of tire labeling




- Uniform Tire Quality Grading Standards
- ② DOT (Department of Transportation), (TIN) Tire Identification Number
- Maximum tire load (→ page 388)
- Maximum tire pressure (→ page 388)

- 6 Manufacturer
- Tire characteristics (→ page 389)
- Tire size designation, load-bearing capacity, speed rating and load index (→ page 389)
- Tire name
- (i) The data shown in the illustration is example data.

# Tire Quality Grading

In accordance with the US Department of Transportation's "Uniform tire Quality Grading Standards", tire manufacturers are required to grade their tires on the basis of the following three performance factors:



- 1 Tread wear grade
- Traction grade
- Temperature grade
- (i) The data shown in the illustration is example data.
- i The classification is not legally stipulated for Canada, but it is generally stated.

## Tread wear grade

The treadwear grade is a comparative rating based on the wear rate of the tire when tested under controlled conditions on a specified government test course. For example, a tire graded 150 would wear one and one-half (1\1/2\) times as

well on the government course as a tire graded 100

The relative performance of tires depends upon the actual conditions of their use, however, and may depart significantly from the norm due to variations in driving habits, service practices and differences in road characteristics and climate.

## Traction grade

DANGER Risk of accident due to inadequate traction

The traction grade assigned to this tire is based on straight-ahead braking traction tests.

- Always adapt your driving style and drive at a speed to suit the prevailing traffic and weather conditions.
- **NOTE** Damage to the drivetrain from wheelspin
- Avoid wheelspin.

The traction grades, from highest to lowest, are AA, A, B, and C. Those grades represent the tire's ability to stop on wet pavement as measured under controlled conditions on specified government test surfaces of asphalt and concrete. A tire marked C may have poor traction performance.

## Temperature grade



WARNING Risk of accident from tire overheating and tire failure

Excessive speed, underinflation, or excessive loading, either separately or in combination, can cause excessive heat build-up and possible tire failure

- Observe the recommended tire pressure.
- Regularly check the pressure of all the tires.
- Adjust the tire pressure, if necessary.

The temperature grades are A (the highest), B, and C, representing the tire's resistance to the generation of heat and its ability to dissipate heat when tested under controlled conditions on a specified indoor laboratory test wheel. Sustained

high temperature can cause the material of the tire to degenerate and reduce tire life, and excessive temperature can lead to sudden tire failure. The grade C corresponds to a level of performance which all passenger car tires must meet under the Federal Motor Safety Standard No. 109. Grades B and A represent higher levels of performance on the laboratory test wheel than the minimum required by law.

## DOT. Tire Identification Number (TIN)

US tire regulations stipulate that every tire manufacturer or retreader must imprint a TIN in or on the side wall of each tire produced.



#### 388 Wheels and tires

i The data shown in the illustration is example data.

The TIN is a unique identification number to identify tires and comprises the following:

- DOT (Department of Transportation): tire symbol marks indicating that the tire complies with the requirements of the US Department of Transportation.
- Manufacturer identification code: manufacturer identification code ② contains details of the tire manufacturer. New tires have a code with two symbols. Retreaded tires have a code with four symbols. Further information on retreaded tires (→ page 393).
- Tire size: identifier (3) describes the tire size.
- Tire type code: tire type code an be used by the manufacturer as a code to describe specific characteristics of the tire.
- Manufacturing date: manufacturing date provides information about the age of a tire. The 1st and 2nd positions represent the calendar week and the 3rd and 4th positions state the year of manufacture (e.g. "3208" represents the 32nd week of 2008).

#### Information on the maximum tire load



(i) The data shown in the illustration is example data.

Maximum tire load ① is the maximum permissible weight for which the tire is approved.

Do not overload the tires by exceeding the specified load limit. The maximum permissible load can be found on the vehicle's Tire and Loading Information placard on the B-pillar on the driver's side ( $\rightarrow$  page 382).


## Specifications for maximum tire pressure



i The data shown in the illustration is example data.

Never exceed maximum tire pressure 0 specified for the tire. Always observe the recommended tire pressure for your vehicle when adjusting the tire pressure ( $\rightarrow$  page 378).

#### Information on tire characteristics



(i) The data shown in the illustration is example data.


This information describes the type of tire cord and the number of layers in side wall 1 and under tire tread 2.

## Tire size designation, load-bearing capacity, speed rating and load index

WARNING Risk of injury through exceeding the specified tire load-bearing capacity or the permissible speed rating

Exceeding the specified tire load rating or the permissible speed rating may lead to tire damage and to the tires bursting.

- Therefore, only use tire types and sizes approved for your vehicle model.
- Observe the tire load rating and speed rating required for your vehicle.



- First letter(s)
- Nominal tire width in millimeters
- Aspect ratio in %
- Tire code
- Rim diameter
- Load-bearing index
- Speed rating
- B Load index
- (i) The data shown in the illustration is example data.

Information about reading tire data can be obtained from any qualified specialist workshop.

#### 390 Wheels and tires

# First letter(s) ①:

- Without: passenger vehicle tires according to European manufacturing standards.
- "P": passenger vehicle tires according to US manufacturing standards.
- "LT": light truck tires according to US manufacturing standards.
- "T": compact emergency spare wheels with high tire pressure that are only designed for temporary use in an emergency.

# Aspect ratio 3:

Ratio between tire height and tire width in percent (tire height divided by tire width).

## Tire code (1) (tire type):

- "R" radial tire
- "D": bias ply tire
- . "B": bias belted tires
- "ZR": radial tire with a maximum speed above 149 mph (240 km/h) (optional)

# Rim diameter 6:

The diameter of the bead seat (not the diameter of the rim flange). The rim diameter is specified in inches (in).

# Load-bearing index 6:

Numerical code that specifies the maximum load-bearing capacity of a tire (e.g. "91" corresponds to 1,356 lbs (615 kg)).

The load-bearing capacity of the tire must be at least half the gross axle weight rating of your vehicle. Do not overload the tires by exceeding the specified load limit.

#### See also:

- Maximum permissible load on the Tire and Loading Information placard (→ page 382)
- Maximum tire load (→ page 388)
- Load index

# Speed rating 2:

Specifies the approved maximum speed of the tire.

(i) An electronic speed limiter prevents your vehicle from exceeding a speed of 130 mph (210 km/h).

Make sure that your tires have the required speed rating. You can obtain information on the required speed rating from an authorized Mercedes-Benz Center.

#### Summer tires

Index	Speed rating
Q	up to 100 mph (160 km/h)
R	up to 106 mph (170 km/h)
S	up to 112 mph (180 km/h)
T	up to 118 mph (190 km/h)
Н	up to 130 mph (210 km/h)
V	up to 149 mph (240 km/h)
W	up to 168 mph (270 km/h)
Υ	up to 186 mph (300 km/h)

Index	Speed rating
ZRY <sup>1</sup>	up to 186 mph (300 km/h)
ZR(Y) <sup>1</sup>	over 186 mph (300 km/h)
ZR <sup>1</sup>	over 149 mph (240 km/h)

- Specifying the speed rating as the "ZR" index in tire code (4) is optional for tires up to 186 mph (300 km/h).
- If your tire code (4) includes "ZR" and there is no speed rating 2. find out what the maximum speed is from the tire manufacturer.
- If load-bearing index 6 and speed rating 7 are in brackets, the maximum speed rating of vour tire is above 186 mph (300 km/h). To find out the maximum speed, ask the tire manufacturer.

## All-weather tires and winter tires

Index	Speed rating
Q M+S <sup>2</sup>	up to 100 mph (160 km/h)
T M+S <sup>2</sup>	up to 118 mph (190 km/h)
H M+S <sup>2</sup>	up to 130 mph (210 km/h)
V M+S <sup>2</sup>	up to 149 mph (240 km/h)

Winter tires bear the A snowflake symbol and fulfill the requirements of the Rubber Manufacturers Association (RMA) and the Rubber Association of Canada (RAC) regarding the tire traction on snow.

## Load index (3):

- No specification given: standard load (SL) tire
- "XL" or "Extra Load": extra load tire or reinforced tire
- · "Light Load": light load tire

• "C", "D", "E": a load range that depends on the maximum load that the tire can carry at a certain pressure

# Definition of terms for tires and loading

Tire structure and characteristics: describes the number of layers or the number of rubber-coated belts in the tire contact surface and the tire wall. These are made of steel, nylon, polyester and other materials.

Bar: metric unit for tire pressure. 14.5038 pounds per square inch (psi) and 100 kilopascal (kPa) is the equivalent of one bar.

DOT (Department of Transportation): DOT-marked tires fulfill the requirements of the U.S. Department of Transportation.

Average weight of the vehicle occupants: the number of vehicle occupants for which the vehicle is designed, multiplied by 150 lb (68 kg).

Uniform Tire Quality Grading Standards: a uniform standard to grade the quality of tires with regard

<sup>1 &</sup>quot;7R" stated in the tire code.

<sup>2</sup> Or "M+S & " for winter tires.

to tread quality, tire traction and temperature characteristics. The quality grading assessment is made by the manufacturer following specifications from the U.S. government. The quality grade of a tire is printed on the side wall of the tire.

Recommended tire pressure: the recommended tire pressure is the tire pressure specified for the tires mounted on the vehicle at the factory.

The tire and information placard contains the recommended tire pressure for cold tires, the maximum permissible load and the maximum permissible vehicle speed.

The tire pressure table contains the recommended tire pressure for cold tires under various operating conditions, i.e. loading and/or speed of the vehicle.

Increased vehicle weight due to optional equipment: the combined weight of all standard and optional equipment available for the vehicle, regardless of whether it is actually installed on the vehicle or not.

Rim: the part of the wheel on which the tire is installed.

**GAWR (Gross Axle Weight Rating):** the GAWR is the maximum gross axle weight rating. The actual load on an axle must never exceed the gross axle weight rating. The gross axle weight rating can be found on the vehicle identification plate on the B-pillar on the driver's side.

**Speed rating:** the speed rating is part of the tire identification. It specifies the speed range for which a tire is approved.

GVW (Gross Vehicle Weight): the gross vehicle weight comprises the weight of the vehicle including fuel, tools, the spare wheel, any accessories installed, occupants, luggage and the trailer noseweight, if applicable. The gross vehicle weight must not exceed the gross vehicle weight rating GVWR as specified on the vehicle identification plate on the B-pillar on the driver's side.

GVWR (Gross Vehicle Weight Rating): the GVWR is the maximum permitted gross weight of the fully laden vehicle (weight of the vehicle including all accessories, occupants, fuel, luggage and the trailer drawbar noseweight if applicable). The gross vehicle weight rating is specified on the vehicle identification plate on the B-pillar on the driver's side.

Maximum weight of the laden vehicle: the maximum weight is the sum of the curb weight of the vehicle, the weight of the accessories, the maximum load and the weight of optional equipment installed at the factory.

**Kilopascal (kPa):** metric unit for tire pressure. 6.9 kPa corresponds to 1 psi. Another unit for tire pressure is bar. 100 kilopascal (kPa) equals 1 bar.

**Load index:** in addition to the load-bearing index, the load index may also be printed on the side wall of the tire. This specifies the load-bearing capacity of the tire more precisely.

**Curb weight:** the weight of a vehicle with standard equipment including the maximum capacity of fuel, oil and coolant. It also includes the air conditioning system and optional equipment if these are installed on the vehicle, but does not include passengers or luggage.

**Maximum tire load:** the maximum tire load is the maximum permissible weight in kilograms or lbs for which a tire is approved.

**Maximum permissible tire pressure:** maximum permissible tire pressure for one tire.

Maximum load on one tire: maximum load on one tire. This is calculated by dividing the maximum axle load of one axle by two.

PSI (pounds per square inch): standard unit of measurement for tire pressure.

Aspect ratio: ratio between tire height and tire width in percent.

**Tire pressure:** the pressure inside the tire which applies an outward force to every square inch of the tire. The tire pressure is specified in pounds per square inch (psi), in kilopascals (kPa) or in bar. The tire pressure should only be corrected when the tires are cold

**Cold tire pressure:** the tires are cold when the vehicle has been parked for at least 3 hours without direct sunlight on the tires or the vehicle has been driven for less than 1 mile (1.6 km).

Tire contact surface: the part of the tire that comes into contact with the road.

Tire bead: the purpose of the tire bead is to ensure that the tire sits securely on the wheel rim. There are several wire cores in the tire bead to prevent the tire from changing length on the wheel rim.

Side wall: the part of the tire between the tread and the tire head

Weight of optional equipment: the combined weight of the optional equipment weighing more than the replaced standard parts and more than 5 lbs (2.3 kg). This optional equipment, such as high-performance brakes, level control system, a roof luggage rack or high-performance batteries, is not included in the curb weight and the weight of the accessories.

TIN (Tire Identification Number): a unique identification number which can be used by a tire manufacturer to identify tires, for example, in a product recall, and thus identify the purchasers. The TIN is made up of the manufacturer's identity code, tire size, tire type code and the manufacturing date.

Load-bearing index: the load-bearing index is a code that contains the maximum load-bearing capacity of a tire.

**Traction:** traction is the grip resulting from friction between the tires and the road surface.

Wear indicator: narrow bars (tread wear bars) that are distributed over the tire contact surface. If the tire tread is level with the bars, the wear limit of 1/16 in (1.6 mm) has been reached.

Distribution of vehicle occupants: distribution of vehicle occupants over designated seat positions in a vehicle

Maximum permissible payload weight: nominal load and luggage load plus 150 lb (68 kg) multiplied by the number of seats in the vehicle.

# Changing a wheel

Notes on selecting, installing and replacing tires



**NOTE** Mercedes-AMG vehicles



Observe the notes in the Supplement. You could otherwise fail to recognize dangers.



WARNING Risk of accident due to incorrect wheel and tire dimensions

If wheels and tires of the wrong size are installed, the service brakes or components in the

brake system and in the wheel suspension may be damaged.

Always replace wheels and tires with ones that fulfill the specifications of the original part.

For wheels, pay attention to the following:

- Designation
- Type

For tires, pay attention to the following:

- Designation
- Manufacturer
- Type

WARNING Risk of injury through exceeding the specified tire load-bearing capacity or the permissible speed rating

Exceeding the specified tire load rating or the permissible speed rating may lead to tire damage and to the tires bursting.

- Therefore, only use tire types and sizes approved for your vehicle model.
- Observe the tire load rating and speed rating required for your vehicle.
- I NOTE Vehicle and tire damage caused by non-approved tire types and sizes

For safety reasons, only use tires, wheels and accessories which have been specially approved by Mercedes-Benz for your vehicle.

These tires are specially adapted to the active safety systems, such as ABS, ESP® and 4MATIC, and marked as follows:

- MO = Mercedes-Benz Original
- MOE = Mercedes-Benz Original Extended (run-flat tires only for certain wheels)
- MO1 = Mercedes-Benz Original (only certain AMG tires)

Otherwise, certain properties, such as handling characteristics, vehicle noise emissions, consumption, etc. could be adversely affected. Furthermore, other tire sizes could result

in the tires rubbing against the body and axle components when loaded. This could result in damage to the tire or the vehicle.

Only use tires, wheels and accessories that have been checked and recommended by Mercedes-Benz.

NOTE Risk to driving safety from retreaded tires

Retreaded tires are neither tested nor recommended by Mercedes-Benz, since previous damage cannot always be detected on retreaded tires.

For this reason driving safety cannot be guaranteed.

- Do not use used tires if you have no information about their previous usage.
- NOTE Possible wheel and tire damage when driving over obstacles

Large wheels have a smaller section width. As the section width decreases, the risk of

wheels and tires being damaged when driving over obstacles increases

- Avoid obstacles or drive especially carefully.
- Reduce your speed when driving over curbs, speed bumps, manhole covers and potholes.
- Avoid particularly high curbs.
- **NOTE** Possible wheel and tire damage when parking on curbs or in potholes

Parking on curbs or in potholes can damage the wheels and tires.

- Only park on as level a surface as possible.
- Avoid curbs and potholes when parking.
- **NOTE** Damage to electronic component parts due to the use of tire-installing tools

Vehicles with tire pressure monitoring system: There are electronic component parts in the wheel.

If tire-installing tools are positioned in the area of the valve, the electronic components could be damaged.

- Tire-installing tools should not be applied in the area of the valve.
- Always have tires change at a qualified specialist workshop.
- **NOTE** Damage to summer tires at low ambient temperatures

At low ambient temperatures, tears could form when driving with summer tires, causing permanent damage to the tires.

► At temperatures below 45 °F (7 °C) use M+S tires.

Accessory parts which are not approved for your vehicle by Mercedes-Benz, or which are not used correctly, can impair the operating safety.

Before purchasing and using non-approved accessories, visit a qualified specialist workshop and enquire about:

Suitability

- Legal stipulations
- Factory recommendations
- WARNING Risk of accident with high performance tires

The special tire tread in combination with the optimized tire compound means that the risk of skidding and hydroplaning on wet roads is increased.

In addition, the tire grip is greatly reduced at a low outside temperature and tire running temperature.

- Switch on the ESP® and adapt your driving style accordingly.
- ▶ Use ♠ M+S tires at outside temperatures of less than 50 °F (10 °C).
- Only use the tires for their intended purpose.

#### 396 Wheels and tires

Observe the following when selecting, installing and replacing tires:

- Furthermore, the use of certain tire types in certain regions and areas of operation can be highly beneficial.
- Only use tires and wheels of the same type (summer tires, winter tires, MOExtended tires) and the same make.
- Only install wheels of the same size on one axle (left and right).
  - It is only permissible to install a different wheel size in the event of a flat tire in order to drive to the specialist workshop.
- Vehicles with a tire pressure monitoring system: all installed wheels must be equipped with functioning sensors for the tire pressure monitoring system.
- At temperatures below 45°F (7°C) use winter tires or all-season tire marked M+S for all wheels.
  - Winter tires provide the best possible grip in wintry road conditions.

- For M+S tires, only use tires with the same tread
- Observe the maximum permissible speed for the M+S tires installed.
  - If the tire's maximum speed is below that of the vehicle, this must be indicated by an appropriate label in the driver's field of vision.
- Break in new tires at moderate speeds for the first 60 miles (100 km).
- Replace the tires after six years at the latest, regardless of wear.
- When replacing with tires that do not feature run-flat characteristics: vehicles with MOExtended tires are not equipped with a TIREFIT kit at the factory. Equip the vehicle with a TIREFIT kit after replacing with tires that do not feature run-flat characteristics, e.g. winter tires.

For more information on wheels and tires, contact a qualified specialist workshop.

Be sure to also observe the following further related subjects:

Notes on tire pressure (→ page 376)

- Tire and Loading Information placard (→ page 382)
- Tire size designation, load-bearing capacity, speed rating and load index (→ page 389)
- Tire pressure table (→ page 378)
- Notes on the emergency spare wheel
   (→ page 404)

#### Notes on rotating wheels

A

**WARNING** Risk of injury through different wheel sizes

Rotating the front and rear wheels can severely impair the driving characteristics.

The wheel brakes or suspension components may also be damaged.

Rotate front and rear wheels only if the wheels and tires are of the same dimensions.

Observe the instructions and safety notes on "Changing a wheel" ( $\rightarrow$  page 393)

The wear patterns on the front and rear wheels differ.

- Front wheels wear more on the tire shoulder.
- · Rear wheels wear more in the center of the tire

Do not drive with tires that have too little tread depth. This significantly reduces traction on wet roads (hydroplaning).

On vehicles that have the same size front and rear wheels, rotate the wheels according to the intervals in the tire manufacturer's warranty book in your vehicle documents. If this is not available. rotate the tires every 3,000 to 6,000 miles (5,000 to 10,000 km), depending on the wear. Ensure that the direction of rotation is maintained.

# Notes on storing wheels

When storing wheels, observe the following notes:

- After removing wheels, store them in a cool, dry and preferably dark place.
- · Protect the tires from contact with oil, grease or fuel.

### Overview of the tire-change tool kit

Apart from some country-specific variants, vehicles are not equipped with a tire-change tool kit. For more information on which tools are required and approved to perform a wheel change on your vehicle, consult a qualified specialist workshop.

Required tire-changing tools may include, for example:

- lack
- Chock
- Lug wrench

Tire-change tool kit (1) is located under the cargo floor.

(i) Depending on the model, the tire change tool kit may be located in other positions under the cargo floor.



The tire-change tool kit includes the following:

- lack
- · Lug wrench
- · Wheel studs
- Extension attachment for wheel studs, if necessary (depending on vehicle version)
- · Folding chock
- Ratchet wrench

#### Preparing the vehicle for a wheel change

#### Requirements:

• The vehicle is not on a slope.

#### 398 Wheels and tires


- The vehicle is on solid, non-slippery and level ground.
- The required tire-change tool kit is available.
- i If your vehicle is not equipped with the tirechange tool kit, consult a qualified specialist workshop to find out about suitable tools.
- Apply the electric parking brake manually.
- Move the front wheels to the straight-ahead position.
- Shift the transmission to position P.
- Vehicles with level control system: Set the normal vehicle level (→ page 248).
- Switch off the vehicle.
- Make sure that the vehicle cannot be started.
- Place chocks or other suitable items under the front and rear of the wheel that is diagonally opposite the wheel you wish to change.
- ► Raise the vehicle (→ page 399).

#### Additionally, for Mercedes-Maybach vehicles:

Retract the running boards ( $\rightarrow$  page 80)

To remove stone chipping protective covers

2:



- Loosen expansion rivet 1 and pull it out.
- Fold down and remove stone chipping protective covers ②.

### Removing and installing the wheel trim/hub caps

#### Requirements

 The vehicle is prepared for a wheel change (→ page 397).


# Plastic hub cap

Turn the center cover of the hub cap counterclockwise and remove the hub cap.

#### To install:

- Make sure that the center cover of the hub cap is turned counter-clockwise.
- Position the hub cap and turn the center cover clockwise until the hub cap engages physically and audibly.

#### Aluminum hub cap



#### To remove:

- Position socket 2 from the tire-change tool kit on hub cap 1.
- Position wheel wrench (3) on socket (2).
- Using wheel wrench (3), turn hub cap (1) counter-clockwise and remove it.

#### To install:

- Follow the instructions above in reverse order.
- (i) Specified tightening torque: 18 lb-ft (25 Nm).


### Raising the vehicle when changing a wheel

#### Requirements:

- There are no persons in the vehicle.
- The vehicle has been prepared for a wheel change ( $\rightarrow$  page 397).

Important notes on using the jack:


- Use only a vehicle-specific jack that has been approved by Mercedes-Benz to raise the vehicle.
- . The jack is only designed for raising and holding the vehicle for a short time while a wheel is being changed and not for maintenance work under the vehicle.
- The jack must be placed on a firm, flat and non-slip surface. If necessary, use a large, flat, load-bearing, non-slip underlay.
- The foot of the jack must be positioned vertically under the jack support point.




Rules of conduct when the vehicle is raised:

- · Never place your hands or feet under the vehicle.
- Never lie under the vehicle.
- Do not start the vehicle and do not release the electric parking brake.
- Do not open or close any doors or the tailgate.

#### 400 Wheels and tires



Using the wheel wrench, loosen the wheel bolts on the wheel you wish to change by about one full turn. Do not unscrew the screws completely.



Position of the jack support points

**WARNING** Risk of injury from incorrect positioning of the jack

If you do not position the jack correctly at the appropriate jacking point of the vehicle, the jack could tip with the vehicle raised.

Only position the jack at the appropriate jacking point of the vehicle. The base of the jack must be positioned vertically under the jacking point of the vehicle. NOTE Damage to the vehicle due to the jack


If you do not position the jack at the jack support points provided for this purpose, you could damage your vehicle.

- Only position the jack at the jack support points provided for this purpose.
- ➤ Take the ratchet wrench out of the tire-change tool kit and place it on the hexagon nut of the jack so that the letters "AUF" are visible.

- Position support ② of jack ③ on jack support point ①.
- Turn ratchet wrench (a) clockwise until jack support (a) sits completely on jack support point (a) and the base of the jack lies evenly on the ground.

- Continue to turn ratchet wrench (3) until the tire is raised a maximum of 1.2 in (3 cm) off the ground.
- ▶ Loosen and remove the wheel ( $\rightarrow$  page 401).

#### Mercedes-Maybach vehicles:



# Requirements:

- The running boards are retracted (  $\rightarrow$  page 80)

- The stone chipping protective covers are removed (→ page 397)
- Position support ② of jack ④ on jack support point ①.
- Turn ratchet wrench clockwise until jack sits completely on jack support point and the base of the jack lies evenly on the ground.
- Continue to turn ratchet wrench (3) until the tire is raised a maximum of 1.2 in (3 cm) off the ground.
- ▶ Loosen and remove the wheel ( $\rightarrow$  page 401).

# Removing a wheel

#### Requirements

• The vehicle is raised ( $\rightarrow$  page 399).



Observe the notes in the Supplement.
 You could otherwise fail to recognize dangers.

#### 402 Wheels and tires

When changing a wheel, avoid applying any force to the brake discs, as this could impair the level of comfort when braking.

- ! NOTE Damage to threading from dirt on wheel bolts
- Do not place wheel bolts in sand or on a dirty surface.
- Completely unscrew the wheel bolts.
- Remove the wheel.

#### Installing a new wheel

#### Requirements

- The wheel that is to be replaced is removed (→ page 401).
- ! NOTE Mercedes-AMG vehicles
- Observe the notes in the Supplement. You could otherwise fail to recognize dangers.

WARNING Risk of accident from losing a wheel

Oiled, greased or damaged wheel bolt/wheel nut threads or wheel hub/wheel mounting bolt threads can cause the wheel bolts/wheel nuts to come loose.

- Never oil or grease the threads.
- In the event of damage to the threads, contact a qualified specialist workshop immediately.
- Have the damaged wheel bolts or damaged hub threads replaced.
- Do not continue driving.
- Observe the information on the choice of tires (→ page 393).

For tires with a specified direction of rotation, an arrow on the side wall of the tire indicates the correct direction of rotation. Observe the direction of rotation when installing.

Place the wheel to be installed on the wheel hub and push it on. WARNING Risk of injury from tightening wheel bolts and nuts

If you tighten the wheel bolts or wheel nuts when the vehicle is raised, the jack could tip.

- Only tighten wheel bolts or wheel nuts when the vehicle is on the ground.
- Observe the instructions and safety notes on "Changing a wheel" (→ page 393).
- For safety reasons, only use wheel bolts which have been approved by Mercedes-Benz and for the wheel in question.
- ! NOTE Damage to paintwork of the wheel rim when screwing in the first wheel bolt

If the wheel has too much play when screwing in the first wheel bolt, the wheel rim paint can be damaged.

Press the wheel firmly against the wheel hub when screwing in the first wheel bolt.

- Tighten the wheel bolts evenly in a diagonal pattern in the order indicated until they are finger-tight.
- If the collapsible spare wheel has been installed, inflate the collapsible spare wheel (→ page 407).
- $\triangleright$  Lower the vehicle ( $\rightarrow$  page 403).


#### Lowering the vehicle after a wheel change

#### Requirements:

 The new wheel has been mounted (→ page 402).

Observe the information on tire pressure  $(\rightarrow page 376)$ .

- Place the ratchet wrench onto the hexagon nut of the jack so that the lettering "AB" is visible.
- To lower the vehicle: turn the ratchet wrench of the jack counter-clockwise.



- Tighten the wheel bolts evenly in a diagonal pattern in the order indicated 10 to 60 with a maximum of 59 lb-ft (80 Nm).
- Then tighten the wheel bolts evenly in a diagonal pattern in the order indicated to to to the specified tightening torque of 111 lb-ft (150 Nm).
- **WARNING** Risk of accident due to incorrect tightening torque

The wheels could come loose if the wheel bolts or wheel nuts are not tightened to the prescribed torque.

- Ensure that the wheel bolts or wheel nuts are tightened to the prescribed tightening torque.
- If you are not sure, do not move the vehicle. Contact a qualified specialist workshop and have the tightening torque checked immediately.
- Check the tire pressure of the newly mounted wheel and adjust accordingly.
- i The following does not apply if the new wheel is an emergency spare wheel.
- Vehicles with a tire pressure monitoring system: restart the tire pressure monitoring system (→ page 381).

#### Emergency spare wheel

Notes on the emergency spare wheel

**WARNING** Risk of accident caused by incorrect wheel and tire dimensions

The wheel or tire sizes and the tire type of the emergency spare wheel or spare wheel and the wheel to be replaced may differ. The emergency spare wheel or spare wheel can significantly impair driving characteristics of the vehicle.

To prevent hazardous situations:

- Drive carefully.
- Never install more than one emergency spare wheel or spare wheel that differs in size.
- Only use an emergency spare wheel or spare wheel briefly.
- Do not deactivate ESP®.
- Have the emergency spare wheel or spare wheel of a different size replaced at the nearest qualified specialist work-

shop. The new wheel must have the correct dimensions.

- (i) The emergency spare wheel is fastened in the load compartment under the load compartment floor.
- (i) Not for Mercedes-Maybach vehicles.

Observe the following notes on installing an emergency spare wheel:

- The maximum permissible speed with an emergency spare wheel installed is 50 mph (80 km/h).
- Do not install the emergency spare wheel with snow chains.
- Replace the emergency spare wheel after six years at the latest, regardless of wear.
- Use the wheel bolts that are included with the emergency spare wheel.
- Check the tire pressure of the emergency spare wheel installed. Correct the pressure as necessary.
- (i) The specified tire pressure is stated on the label of the emergency spare wheel.

Vehicles with a tire pressure monitoring system: if an emergency spare wheel is installed, the tire pressure monitoring system cannot function reliably. For a few minutes after an emergency spare wheel is installed, the system may still display the tire pressure of the removed wheel. Only restart the system again when the emergency spare wheel has been replaced with a new wheel.


Be sure to also observe the following further related subjects:

- Notes on tire pressure (→ page 376)
- Tire and loading information placard (→ page 382)
- Tire pressure table (→ page 378)
- Notes on installing tires (→ page 393)
- Installing an emergency spare wheel (→ page 397)

- ! NOTE Overheating due to the tire inflation compressor running too long
- Do not run the tire inflation compressor for longer than ten minutes without interruption.

#### Requirements:

- The emergency spare wheel has been installed correctly. (→ page 397)
- (i) Comply with the manufacturer's safety notes on the sticker of the emergency spare wheel and on the tire inflation compressor.
- Remove the sticker with the label 50 mph (80 km/h) from the tire inflation compressor housing and affix it to the instrument cluster within the driver's field of vision.
- Remove the tire inflation compressor from the stowage space under the trunk floor.
   (→ page 356)



- Pull filler hose **()** and plug **(3)** out of the tire inflation compressor housing.
- Insert plug of filler hose in the socket on the tire inflation compressor and then turn it until plug engages.
- Unscrew the cap from the valve on the emergency spare wheel.
- Screw union nut ② of filler hose ① onto the valve.
- ► Make sure on and off switch ④ of the tire inflation compressor is set to 0.
- Insert plug (3) in a socket in your vehicle.
- 12 V socket: (→ page 143)

- Observe the notes on sockets: (→ page 143)
- Press the start/stop button once to switch on the power supply (→ page 175).
- Press On/Off switch (4) on the tire inflation compressor to I.
   The tire inflation compressor is switched on.
  - The tire irination compressor is switched on. The tire is inflated. The tire pressure appears on manometer (3).
- Pump the tire to the specified tire pressure.
- i The specified tire pressure is stated on the label of the emergency spare wheel.
- When the specified tire pressure has been reached, press on and off switch on the tire inflation compressor to 0.
  The tire inflation compressor is switched off.
- Press the start/stop button to switch off the power supply.
- If the tire pressure is higher than the specified pressure, press pressure release valve button
   until the correct tire pressure has been reached.

#### 406 Wheels and tires

- Unscrew union nut ② of filler hose ① from the valve.
- Screw the valve cap of the emergency spare wheel onto the valve again.
- Stow filler hose (1) and plug (3) in the lower section of the tire inflation compressor housing.
- Stow the tire inflation compressor in the vehicle.

#### Collapsible spare wheel

Notes on the collapsible spare wheel



**WARNING** Risk of accident caused by incorrect wheel and tire dimensions

The wheel or tire sizes and the tire type of the emergency spare wheel or spare wheel and the wheel to be replaced may differ. The emergency spare wheel or spare wheel can significantly impair driving characteristics of the vehicle.

To prevent hazardous situations:

- Drive carefully.
- Never install more than one emergency spare wheel or spare wheel that differs in size.
- Only use an emergency spare wheel or spare wheel briefly.
- Do not deactivate FSP<sup>®</sup>.
- Have the emergency spare wheel or spare wheel of a different size replaced at the nearest qualified specialist workshop. The new wheel must have the correct dimensions.

The collapsible spare wheel is an emergency spare wheel which is only suitable for use for a limited period of time and in a restricted manner in the event of a flat tire (e.g. until the nearest workshop).

The tire sidewalls are folded when in transport mode. Before use, the collapsible spare wheel has to be inflated with the accompanying compressor.

Check the tire pressure of the collapsible spare wheel once installed. Correct the pressure as necessary.

The maximum permissible speed with a collapsible spare wheel installed is 50 mph (80 km/h).

Do not install the collapsible spare wheel with snow chains.

Replace the collapsible spare wheel after six years at the latest, regardless of wear.

(i) Vehicles with a tire pressure monitoring system: if a collapsible spare wheel is installed the tire pressure monitoring system cannot function reliably. For a few minutes after an emergency spare wheel is installed, the system may still display the tire pressure of the removed wheel. Only restart the system again when the collapsible spare wheel has been replaced with a new wheel.

Be sure to also observe the following further related subjects:

- Notes on tire pressure (→ page 376)
- Tire pressure table (→ page 378)

# Removing the collapsible spare wheel

The collapsible spare wheel is located under the cargo compartment floor.

- Observe the information on mounting tires (→ page 393).
- Open the tailgate.
- Open the cargo compartment floor.
- Remove the collapsible spare wheel.

### Mercedes-Maybach vehicles

Without refrigerator box: The collapsible spare wheel is located in the collapsible spare wheel bag on the cargo compartment floor.

- Observe the information on mounting tires (→ page 393).
- Open the cargo compartment.
- Loosen the lashing straps.
- Unhook the retaining spring hooks of the lashing straps from the brackets.
- Remove the collapsible spare wheel bag together with the collapsible spare wheel.

Open the collapsible spare wheel bag and remove the collapsible spare wheel.

With refrigerator box:The collapsible spare wheel is located in the collapsible spare wheel bag inside the open cargo compartment floor.

- Observe the information on mounting tires (→ page 393).
- Open the cargo compartment.
- Loosen the lashing straps.
- Unhook the retaining spring hooks of the lashing straps from the brackets.
- Remove the collapsible spare wheel bag together with the collapsible spare wheel.
- Open the collapsible spare wheel bag and remove the collapsible spare wheel.

### Inflating the collapsible spare wheel

### Requirements:

Mount the collapsible spare wheel as described (→ page 402).

- Remove the tire inflation compressor from the storage space under the trunk floor (→ page 356).
- NOTE Damage to the collapsible spare wheel when lowering the vehicle

Lowering the vehicle without previously inflating the collapsible spare wheel can damage its rim.

- Inflate the collapsible spare wheel using the tire inflation compressor before lowering the vehicle.
- ! NOTE Overheating due to the tire inflation compressor running too long
- Do not run the tire inflation compressor for longer than ten minutes without interruption.

#### 408 Wheels and tires



- Pull connector (a) and the hose out of the housing.
- Unscrew the cap from the valve on the collapsible spare wheel.
- Screw union nut (1) of the hose onto the valve.
- Make sure on and off switch (3) of the tire inflation compressor is set to **0**.
- Insert connector 
   into the cigarette lighter socket or into a 12 V socket (→ page 143) in your vehicle.
- Switch on the power supply ( $\rightarrow$  page 175).

- Press on and off switch (3) on the tire inflation compressor to I.
   The tire inflation compressor is switched on.
   The tire is inflated. The tire pressure is shown on manometer (2).
- Pump the tire to the specified tire pressure.
- (i) The specified tire pressure is printed on the yellow label of the collapsible spare wheel.
- When the specified tire pressure has been reached, press on and off switch (3) on the tire inflation compressor to (0).
- If the tire pressure is higher than the specified pressure, press pressure release valve button ⑤ until the correct tire pressure has been reached.

#### Notes on technical data

- **NOTE** Mercedes-AMG vehicles
- Observe the notes in the Supplement. You could otherwise fail to recognize dangers.

The data stated only applies to vehicles with standard equipment. You can obtain further information from an authorized Mercedes-Benz Center.

#### Vehicle electronics

Two-way radios

Notes on installing two-way radios

WARNING Risk of accident due to improper work on two-way radios

If two-way radios are manipulated or retrofitted incorrectly, the electromagnetic radiation from the two-way radios can interfere with the vehicle electronics and jeopardize the operating safety of the vehicle.

You should have all work on electrical and electronic components carried out at a qualified specialist workshop.

WARNING Risk of accident due to improper operation of two-way radios

If you use two-way radios in the vehicle improperly, their electromagnetic radiation can disrupt the vehicle's electronics. This is the case in the following situations, in particular:

- The two-way radio is not connected to an exterior antenna.
- . The exterior antenna is installed incorrectly or is not a low-reflection antenna.


This could jeopardize the operating safety of the vehicle.

Have the low-reflection exterior antenna installed at a qualified specialist workshop.

- When operating two-way radios in the vehicle, always connect them to the lowreflection exterior antenna.
- **NOTE** Invalidation of the operating permit due to failure to comply with the instructions for installation and use

The operating permit may be invalidated if the instructions for installation and use of two-way radios are not observed.

- Only use approved frequency bands.
- Observe the maximum permissible output power in these frequency bands.
- Only use approved antenna positions.



- Front roof area
- Rear roof area
- Rear fenders

On vehicles with a panorama roof with power tilt/sliding panel, the installation of an antenna to the front or rear roof area is not permitted.

On the rear fenders, it is recommended that you install the antenna on the side of the vehicle closest to the center of the road.

Use Technical Specification ISO/TS 21609 (Road Vehicles – "EMC guidelines for installation of aftermarket radio frequency transmitting equipment") when retrofitting two-way radios. Comply with the legal requirements for detachable parts.

If your vehicle has a pre-installation for two-way radio equipment, use the power supply and antenna connectors provided in the pre-installation. Observe the manufacturer's supplements during installation.

## Two-way radio transmission output

The maximum transmission output (PEAK) at the base of the antenna must not exceed the values in the following table.

# Frequency band and maximum transmission output

out	
Frequency band	Maximum transmis- sion output
2-m- frequency band 144-174 MHz	50 W
Terrestrial Trunked Radio (TETRA) 380-460 MHz	10 W
Two-way radio 2G	2 W
Two-way radio 3G/4G/5G	0.5 W

The following can be used in the vehicle without restrictions:

- two-way radios with a maximum transmission output of 100 mW
- RF transmitters with transmitter frequencies in the 380-410 MHz frequency band and a maximum transmission output of 2 W (TETRA)

• mobile phones (2G/3G/4G/5G)

There are no restrictions regarding the position of the antenna on the outside of the vehicle for the following frequency bands:

- Terrestrial Trunked Radio (TETRA)
- 70-cm frequency band
- 2G/3G/4G/5G

# Radio regulations

# Regulatory radio identification and specific notes

Manufacturer information about radio-based vehicle components can be found using the key phrase "Regulatory radio information" in the Digital Operator's Manual in the vehicle, on the internet and in the app.


Further information and updates are available at the following web address:


https://
regulatoryradioinformation.corpinter.net/us



# Vehicle identification plate, VIN and engine number overview


#### Vehicle identification plate





Vehicle identification plate (USA only)

- Maximum permissible gross vehicle weight
- Maximum permissible front axle load
- Maximum permissible rear axle load
- Paint code
- VIN (vehicle identification number)




Vehicle identification plate (Canada only)

- Maximum permissible gross vehicle weight
- Maximum permissible front axle load
- Maximum permissible rear axle load
- Paint code
- VIN (vehicle identification number)

The maximum permissible gross vehicle weight is made up of the vehicle weight, all vehicle occupants, the fuel and the load. The maximum gross axle weight rating is the maximum weight that can be carried on one axle (front or rear axle).


Never exceed the maximum permissible gross vehicle weight or the maximum gross axle weight rating for the front or rear axle.

#### VIN in front of the front seat



VIN (vehicle identification number)

#### Additional plates



- Plate with information about emissions testing, including confirmation of emissions guidelines at the U.S. federal level as well as for California
- Engine number stamped into the crankcase
- VIN (vehicle identification number) as a label at the lower edge of the windshield

### Operating fluids

#### Notes on operating fluids

- NOTE Mercedes-AMG vehicles
- Observe the notes in the Supplement. You could otherwise fail to recognize dangers.
- WARNING Risk of injury due to harmful operating fluids

Operating fluids can be toxic.

- When using, storing and disposing of operating fluids, observe the imprints on the respective original containers.
- Always keep operating fluids in the sealed original container.
- Always keep children away from operating fluids.



**ENVIRONMENTAL NOTE** Pollution of the environment due to irresponsible disposal of operating fluids

Incorrect disposal of operating fluids can cause considerable damage to the environment.

Dispose of operating fluids in an environmentally responsible manner.

Operating fluids include the following:

- Fuels
- Lubricants
- Coolant
- Brake fluid
- Windshield washer fluid
- · Climate control system refrigerant

Only use products approved by Mercedes-Benz. Damage caused by the use of products that have not been approved is not covered by the Mercedes-Benz warranty or goodwill gestures.

The operating fluids approved by Mercedes-Benz can be identified by the following inscriptions on the container:

- MB-Freigabe (e.g. MB-Freigabe 229.51)
- MB-Approval (e.g. MB-Approval 229.51)

Further information on approved operating fluids:

- in the Mercedes-Benz Specifications for Operating Fluids by entering the designation
  - At https://operatingfluids.mercedesbenz.com
- · At a qualified specialist workshop

# WARNING Risk of fire or explosion from fuel

Fuels are highly flammable.

- Fire, open flames, smoking and creating sparks must be avoided.
- Before and during refueling, switch off the vehicle and, if installed, the stationary heater.

# **WARNING** Risk of injury from fuels

Fuels are poisonous and hazardous to your health.

- Do not swallow fuel or let it come into contact with skin, eyes or clothing.
- Do not inhale fuel vapor.
- Keep children away from fuel.
- Keep doors and windows closed during the refueling process.

If you or other people come into contact with fuel, observe the following:

- Immediately rinse fuel off your skin with soap and water.
- If fuel comes into contact with your eyes, immediately rinse them thoroughly with clean water. Seek medical attention immediately.
- If you swallow fuel, seek medical attention immediately. Do not induce vomiting.

Change immediately out of clothing that has come into contact with fuel.

Flexible-fuel vehicles can be refueled with the following fuel types:

- · premium-grade unleaded gasoline
- E85 fuel
- a mixture of E85 fuel and premium-grade unleaded gasoline

Flexible-fuel vehicles can be identified by the **Ethanol up to E85** sticker on the inside of the fuel filler flap.

Depending on the country, the fuels you can use in your vehicle may differ from the information in the Operator's Manual. The fuels that have been approved for your vehicle can be found on the instruction label on the inside of the fuel filler flap.

#### Fuel

# Notes on fuel grades for vehicles with a gasoline engine

Observe the notes on operating fluids ( $\rightarrow$  page 413).

NOTE Damage caused by the wrong fuel

Even small amounts of the wrong fuel could result in damage to the fuel system, the engine and the emission control system.

Only refuel with low-sulfur unleaded fuel.

This fuel may contain up to 10% ethanol by volume. Your vehicle is suitable for use with E10 fuel.

Never refuel with one of the following fuels:

- Diesel
- Gasoline with more than 10% ethanol by volume, e.g. E15, E85, E100
- Gasoline with more than 3% methanol by volume, e.g. M15, M30, M85, M100
- Gasoline with additives containing metal

If you have accidentally refueled with the wrong fuel:

- Do not switch on the ignition.
- Consult a qualified specialist workshop.

If the available fuel is not sufficiently low in sulfur, this can produce unpleasant odors.

Only refuel with fuel that has at least the octane number specified in the instruction label in the fuel filler flap ( $\rightarrow$  page 201). This may reduce engine output and increase fuel consumption.

If you want maximum engine output: only refuel with unleaded premium grade gasoline with an octane number of at least 91 AKI/95 RON.

As a temporary measure, if the recommended fuel is not available, you may also refuel with unleaded regular gasoline with at least 87 AKI/91 RON. This may reduce engine output and increase fuel consumption.

Never refuel using gasoline with an even lower RON.

NOTE Premature wear caused by unleaded regular gasoline

Unleaded regular gasoline can cause the engine to wear more quickly and impair longevity and performance.

If unleaded premium grade gasoline is unavailable and you have to refuel using unleaded regular gasoline:

- Only fill the fuel tank to half full with unleaded regular gasoline and refill as soon as possible with unleaded premium grade gasoline.
- Do not drive at the maximum speed.
- Avoid sudden acceleration and engine speeds over 3,000 rpm.

Further information on fuel is available at the following locations:

- At a gas station
- · At a qualified specialist workshop
- USA only: at http://www.mbusa.com

# Information on additives in gasoline (vehicles with gasoline engine)

Observe the notes on operating fluids ( $\rightarrow$  page 413).

! NOTE Damage from use of unsuitable additives

Even small amounts of the wrong additive may lead to malfunctions occurring.

Only add cleaning additives recommended by Mercedes-Benz to the fuel.

Mercedes-Benz recommends that you use brandname fuels with additives.

In some countries, the fuel available may not have sufficient additives. Deposits could build up in the fuel injection system as a result. In this case, in consultation with a qualified specialist workshop (e.g. an authorized Mercedes-Benz Service Center), mix the fuel with the cleaning additive recommended by Mercedes-Benz. Observe the notes and mixing ratios indicated on the tank.

#### ■ Tank content and fuel reserve

Total fuel tank capacity

Model	
All models	23.8 gal (90.0 liters)

# Fuel tank total capacity (Mercedes-Maybach)

#### Model

Wodel	
Mercedes-Maybach GLS 600 4MATIC	23.8 gal (90.0 liters)

#### Fuel tank reserve

Model	
All models	2.4 gal (9.0 liters)

# Fuel tank reserve (Mercedes-Maybach)

#### Model

Mercedes-Maybach	3.2 gal (12.0 liters)
GLS 600 4MATIC	

#### Engine oil

# Notes on engine oil

Observe the notes on operating fluids ( $\rightarrow$  page 413).



- ! NOTE Engine damage caused by an incorrect oil filter, incorrect oil or additives
- Do not use engine oils or oil filters other than those which meet the specifications necessary for the prescribed service intervals.

- Do not alter the engine oil or oil filter in order to achieve longer change intervals than prescribed.
- Do not use additives.
- Have the engine oil changed after the prescribed intervals.

Mercedes-Benz recommends having the oil changed at a qualified specialist workshop.

Only use engine oils approved for your vehicle by Mercedes-Benz.

# Engine oil quality and filling capacity

# Engine oil specifications

Model	MB-Freigabe or MB- Approval
GLS 450 4MATIC	229.51, 229.52, 229.61, 229.71 229.72*
GLS 580 4MATIC	229.52 229.61*

#### Engine oil specifications (Mercedes-Maybach)

Model	MB-Freigabe or MB- Approval
Mercedes-Maybach	229.5
GLS 600 4MATIC	229.51*

\* recommended for lowest possible fuel consumption (lowest SAE viscosity class in each case; observe possible restrictions of the approved SAE viscosity classes)

To achieve the lowest possible fuel consumption, it is recommended to use the engine oil specifications marked in the table for the lowest SAE viscosity class. Possible restrictions of the approved SAE viscosity classes must be observed.

**Mercedes-Maybach GLS 600 4MATIC:** only use SAE 0W-40 or SAE 5W-40 engine oils.

The following values refer to an oil change, including the oil filter.

Engine oil filling capacity

Model	Capacity
GLS 450 4MATIC	8.9 US qt (8.5 liters)
GLS 580 4MATIC	10.0 US qt (9.5 liters)

#### Engine oil capacity (Mercedes-Maybach)

Model	Capacity
Mercedes-Maybach GLS 600 4MATIC	10.0 US qt (9.5 liters)

#### Notes on brake fluid

Observe the notes on operating fluids ( $\rightarrow$  page 413).

**WARNING** Risk of an accident due to vapor pockets forming in the brake system

The brake fluid constantly absorbs moisture from the air. This lowers the boiling point of the brake fluid. If the boiling point is too low, vapor pockets may form in the brake system when the brakes are applied hard.

This causes the braking effect to be impaired.

Have the brake fluid renewed at the specified intervals.

Have the brake fluid regularly replaced at a qualified specialist workshop.

Only use a brake fluid approved by Mercedes-Benz according to MB-Freigabe or MB-Approval 331.0.

#### Coolant

#### Notes on coolant

Observe the notes on operating fluids  $(\rightarrow \text{page 413})$ .

**WARNING** - Risk of fire and injury from antifreeze

If antifreeze comes into contact with hot component parts in the engine compartment, it may ignite.

Allow the engine to cool down before adding antifreeze.

- Make sure that no antifreeze spills out next to the filler opening.
- Thoroughly clean off any antifreeze from component parts before starting the vehicle.
- NOTE Damage caused by incorrect coolant
- Only use coolant that has been premixed with the required antifreeze protection.

Information on coolant is available at the following locations:

- In the Mercedes-Benz Specification for Operating Fluids 320.1
  - At https://operatingfluids.mercedesbenz.com
- · At a qualified specialist workshop

NOTE Overheating at high outside temperatures

If an inappropriate coolant is used, the cooling system is not sufficiently protected against overheating and corrosion at high outside temperatures.

- Only use coolant approved for Mercedes-Benz.
- Observe the instructions in the Mercedes-Benz Specifications for Operating Fluids 320.1.

Have the coolant regularly replaced at a qualified specialist workshop.

Proportion of antifreeze concentrate in the cooling system:

- A minimum of 50% (antifreeze protection down to about -35°F (-37°C))
- A maximum of 55% (antifreeze protection down to -49°F (-45°C))

# Coolant filling capacity

### Engine coolant

Model	Capacity
GLS 450 4MATIC	18.0 US qt (17.0 liters)
GLS 580 4MATIC	16.6 US qt (15.7 liters)

# Engine coolant (Mercedes-Maybach)

Model	Capacity
Mercedes-Maybach	16.6 US qt
GLS 600 4MATIC	(15.7 liters)

#### Notes on windshield washer fluid

Observe the notes on operating fluids ( $\rightarrow$  page 413).

# **WARNING** - Risk of fire and injury from windshield washer concentrate

Windshield washer concentrate is highly flammable. It could ignite if it comes into contact with hot engine component parts or the exhaust system.

- Make sure that no windshield washer concentrate spills out next to the filler opening.
- I NOTE Damage to the exterior lighting due to unsuitable windshield washer fluid

Unsuitable windshield washer fluid may damage the plastic surface of the exterior lighting.

Only use windshield washer fluid which is also suitable for use on plastic surfaces, e.g. MB SummerFit or MB WinterFit.

- I NOTE Blocked spray nozzles caused by mixing windshield washer fluids
- Do not mix MB SummerFit and MB WinterFit with other windshield washer fluids.

Do not use distilled or de-ionised water. Otherwise, the fill level sensor may be triggered erroneously.

Recommended windshield washer fluid:

- Above freezing point: e.g. MB SummerFit
- · Below freezing point: e.g. MB WinterFit

For the correct mixing ratio, refer to the information on the antifreeze container.

Mix washing water with windshield washer fluid all year round.

### Refrigerant

# Notes on refrigerant

Observe the notes on operating fluids ( $\rightarrow$  page 413).

! NOTE Damage due to incorrect refrigerant

If a non-approved refrigerant is used, the climate control system may be damaged.

- ▶ USA: use only R-134a refrigerant.
- Canada: use only R-1234yf refrigerant.
- NOTE Damage to the climate control system due to incorrect refrigerant compressor oil
- Only use refrigerant compressor oil that has been approved by Mercedes-Benz.
- Do not mix the approved refrigerant compressor oil with a different refrigerant compressor oil.

Work on the climate control system may be carried out only at a qualified specialist workshop. All applicable regulations as well as SAE standard 1639 must be adhered to.

The information label for the climate control system regarding the refrigerant type and the refrigerant compressor oil (PAG oil) is located on the inside of the hood.



Information label (example - USA)

- Hazard and service warning symbols
- Refrigerant filling capacity
- 3 Applicable standards
- PAG oil part number
- GWP (global warming potential) of the refrigerant used
- 6 Refrigerant type



Information label (example - Canada)

- Hazard and service warning symbols
- Refrigerant filling capacity
- Applicable standards
- PAG oil part number
- GWP (global warming potential) of the refrigerant used
- Refrigerant type

Symbols ① indicate the following:

- Possible dangers
- Having maintenance work carried out at a qualified specialist workshop

# Filling capacity for refrigerant and PAG oil

Refrigerant filling capacity

Model	
All models	34.6 ± 0.4 oz (980 ± 10 g)

# Refrigerant filling capacity (Mercedes-Maybach)

Mercedes-Maybach	34.6 ± 0.4 oz
GLS 600 4MATIC	$(980 \pm 10 \text{ g})$

# Filling capacity for PAG oil

Model	
GLS 450 4MATIC	$5.6 \pm 0.4 \text{ oz}$ $(160 \pm 10 \text{ g})$
GLS 580 4MATIC	$5.6 \pm 0.4 \text{ oz}$ $(160 \pm 10 \text{ g})$

# Filling capacity for PAG oil (Mercedes-Maybach)


### Model

# Vehicle data

### Vehicle dimensions

The heights specified may vary as a result of the following factors:

- tires
- load
- condition of the suspension
- optional equipment



# Height when opened and headroom

Model	<ul><li>Height when opened*</li></ul>	Head- room*
Vehicles with AIR- MATIC	84.4 in (2144 mm) - 87.9 in (2234 mm)	75.9 in (1929 mm) - 79.4 in (2019 mm)
Vehicles with Offroad package	84.4 in (2144 mm) - 89.5 in (2274 mm)	75.9 in (1929 mm) - 81.0 in (2059 mm)

# Height when opened and headroom (Mercedes-Maybach)

Model	<ul><li>Height when opened*</li></ul>	Head- room*
Mercedes-Maybach GLS 600 4MATIC	85.0 in (2159 mm) - 87.9 in (2234 mm)	`- 79.4 in ´

<sup>\*</sup>When rear-end lowering is activated, the values will be lower accordingly.

# Vehicle dimensions

All models	
Vehicle length	205.0 in (5207 mm)
Vehicle length, AMG Styling	205.2 in (5213 mm)
Vehicle width including outside mirrors	84.9 in (2157 mm)

All models	
Maximum vehicle height (AIR-MATIC)	74.3 in (1888 mm)
Maximum vehicle height (Off-road package)	75.9 in (1928 mm)
Minimum vehicle height (highway driving level)	71.7 in (1823 mm)
Wheelbase	123.4 in (3135 mm)
Maximum ground clearance (AIRMATIC)	10.1 in (259 mm)
Maximum ground clearance (Offroad package)	11.3 in (289 mm)
Minimum ground clearance (AIRMATIC/Offroad package)	6.8 in (174 mm)
Turning radius	41.1 ft (12.52 m)

# Vehicle dimensions (Mercedes-Maybach)

Mercedes-Maybach GLS 600 4MATIC	
Vehicle length	204.9 in (5205 mm)
Vehicle width including outside mirrors	84.9 in (2157 mm)
Maximum vehicle height	74.3 in (1888 mm)
Minimum vehicle height (highway driving level)	72.3 in (1838 mm)
Wheelbase	123.4 in (3135 mm)
Maximum ground clearance	8.2 in (210 mm)
Minimum ground clearance	5.3 in (135 mm)
Turning radius	41.1 ft (12.52 m)

#### Weights and loads

Please note that for the specified vehicle data:

- Items of optional equipment increase the curb weight and reduce the payload.
- Vehicle-specific weight information can be found on the vehicle identification plate (→ page 411).

#### Roof load

All models	
Maximum roof load	220 lbs (100 kg)

### Running board

All models	
Maximum load	441 lbs (200 kg)

#### Off-road driving

#### Fording depth

! NOTE Damage caused by water when fording

In the following cases water can penetrate into the engine compartment and vehicle interior:


- The maximum permissible fording depth is exceeded when driving through standing water.
- When driving through the water a bow wave forms.
- Water accumulates when driving through running water.
- Do not exceed the maximum permissible fording depth and drive slowly through the water.

The specified value indicates the maximum permissible fording depth for:

- vehicles that are ready to drive
- slow driving through standing water

Driving through flowing water reduces the permissible fording depth due to the accumulation of water

Observe the notes on off-road driving and fording ( $\rightarrow$  page 183).



### Fording depth

Model	<ul><li>Fording depth</li></ul>
Vehicles with AIRMATIC	_
Raised level	19.7 in (50 cm)
Vehicles with Offroad package	


Model	<ul><li>Fording depth</li></ul>
Off-road level 1	19.7 in (50 cm)
Off-road level 2	19.7 in (50 cm)
Off-road level 3	23.6 in (60 cm)

# Fording depth (Mercedes-Maybach)

Mercedes-Maybach GLS 600 4MATIC	<ul><li>Fording depth</li></ul>
Raised level	19.7 in (50 cm)

Angle of approach/departure
The specified values are maximum values for vehicles that are ready to drive.

 $(\rightarrow$  page 183)Observe the notes on driving in mountainous terrain.



Angle of approach/departure (vehicles without AMG Styling)

All models	Front	Rear
Vehicles with AIR- MATIC*		
Normal level	23°	20°
Raised level	27°	24°
Vehicles with Off- road package		
Normal level	23°	20°

All models	Front	Rear
Off-road level 1	25°	22°
Off-road level 2	27°	24°
Off-road level 3	29°	26°

Angle of approach/departure (vehicles with AMG Styling)

All models	Front	Rear
Vehicles with AIR- MATIC		
Normal level	21° - 22°	20° - 21°
Raised level	25°	24°
Vehicles with Off- road package		
Normal level	21° - 22°	20° - 21°
Off-road level 1	23° - 24°	22° - 23°

# Angle of approach/departure (Mercedes-Maybach)

Mercedes-May- bach GLS 600 4MATIC	Front	Rear
Normal level	24°	21°
Raised level	27°	25°

<sup>\*</sup>Depending on the tire size

### Maximum gradient climbing ability

The vehicle's gradient climbing ability depends on the weight distribution in the vehicle, the terrain conditions and the road surface conditions.

The specified value applies when:

- · the vehicle is ready to drive
- the **LOW RANGE** off-road gear of the transfer case is engaged

• the road surface conditions and thus the traction are good

A gradient climbing ability of 100% corresponds to an incline of  $45^{\circ}$ .

 $(\rightarrow$  page 183)Observe the notes on driving in mountainous terrain.

#### Gradient climbing ability

Model	Maximum gradi- ent climbing abil- ity
Vehicles without Offroad package	80%
Vehicles with Offroad package When LOW RANGE off-road gear is engaged	100%

# Gradient climbing ability (Mercedes-Maybach)

Model	Maximum gradi- ent climbing abil- ity
Mercedes-Maybach GLS 600 4MATIC	80%

# Trailer hitch General notes on the trailer hitch

Modifications to the cooling system may be necessary, depending on the vehicle model. Retrofitting a trailer hitch is permissible only if a trailer load is specified in your vehicle documents.

Further information can be obtained at a qualified specialist workshop.

Observe the information and notes on the trailer hitch ( $\rightarrow$  page 279).

# Towing capacity

The tongue weight is not included in the towing capacity.

Missing values were not available at the time of going to press.

## Towing capacity, braked

Model	Towing capacity
All models	

# Towing capacity, braked (Mercedes-Maybach)

Model	Towing capacity
Mercedes-Maybach GLS 600 4MATIC	

# Maximum tongue weight and load capacity

NOTE Damage caused by the trailer coming loose

If the tongue weight used is too low, the trailer may come loose.

The tongue weight must not be below 110.2 lbs (50 kg).

Use a tongue weight that is as close as possible to the maximum permissible tongue weight.

I NOTE Damage caused by the bicycle rack coming loose

When using a bicycle rack, both the maximal tongue weight and the maximal load capacity should be observed.

Do not exceed the permissible load capacity.

Observe the additional notes on load capacity . Missing values were not available at the time of going to press.

## Tongue weight

Model	Maximum tongue weight
All models	

# Tongue weight (Mercedes-Maybach)

Model	Maximum tongue weight
Mercedes-Maybach GLS 600 4MATIC	

# Load capacity

Load Gapacity	
All models	Maximum load
When the bicycle rack is attached to the ball head	165.3 lbs (75 kg)
When the bicycle rack is attached to the ball head and additionally to the guide pin	220.5 lbs (100 kg)

# Load capacity (Mercedes-Maybach)

Mercedes-Maybach GLS 600 4MATIC	Maximum load
When the bicycle rack is attached to the ball head	165.3 lbs (75 kg)
When the bicycle rack is attached to the ball head and additionally to the guide pin	220.5 lbs (100 kg)

# Trailer operation axle load (Mercedes-Maybach)

Model	Axle load
Mercedes-Maybach GLS 600 4MATIC	

# Permissible rear axle load (trailer operation)

Missing values were not available at the time of going to press.

# Trailer operation axle load

Model	Axle load
All models	

#### Display messages

#### Introduction

# Information about display messages

Display messages appear on the instrument display.

Display messages with graphic symbols are simplified in the Operator's Manual and may differ from the symbols on the instrument display. The instrument display shows high-priority display messages in red. Certain display messages are accompanied by a warning tone.

Please act in accordance with the display messages and follow the additional notes in the Operator's Manual.

For some display messages, symbols will also be shown:

- (i) Further information
- × Hide display message

With the left-hand Touch Control, you can select the respective symbol by swiping to the left or right. Pressing (1) displays further information on the media display. Press the  $\boxed{\ \mathbf{x}\ }$  symbol to hide the display message.

Display messages to be acknowledged can be hidden by pressing the back button or with the left-hand Touch Control. The display messages will then be stored in the message memory.

Rectify the cause of a display message as quickly as possible.

High-priority display messages cannot be hidden. The instrument display will show these display messages permanently until the cause of the display message has been rectified.

# Calling up saved display messages

On-board computer:

→ Service → 1 Message

If there are no display messages, No Messages will appear on the instrument display.

- Scroll through the display messages by swiping upwards or downwards on the left-hand Touch Control.
- ► To exit the message memory: press the back button <a> button</a> <a> button</a

### Occupant safety

#### Display messages



SRS Malfunction Service Required



Front Left Malfunction Service Required (example)



Left Side Curtain Airbag Malfunction Service Required (example)

# Possible causes/consequences and ▶ Solutions

\* The restraint system is malfunctioning ( $\rightarrow$  page 42).



Components in the restraint system may be activated unintentionally or not deploy as planned in an accident.

- Have the restraint system checked and repaired immediately at a qualified specialist workshop.
- \* The restraint system is malfunctioning ( $\rightarrow$  page 42).

WARNING Risk of injury due to malfunctions in the restraint system

Components in the restraint system may be activated unintentionally or not deploy as planned in an accident.

- ► Have the restraint system checked and repaired immediately at a qualified specialist workshop.
- \* The restraint system is malfunctioning ( $\rightarrow$  page 42).

WARNING Risk of injury or fatal injury due to a malfunction in the window curtain airbag

The window curtain airbag might be triggered unintentionally or might not be triggered at all in the event of an accident.

Have the window curtain airbag checked and repaired immediately at a qualified specialist workshop.

Display messages	Possible causes/consequences and ▶ Solutions
Front Passenger Airbag Dis- abled See Operator's Man- ual	* The front passenger air bag has been disabled even though an adult or a person of adult build is on the front passenger seat. If additional forces are applied to the seat, the weight the system detects may be too low.
	<b>★</b> WARNING Risk of injury or fatal injury due to a disabled front passenger airbag
	If the front passenger airbag is disabled, the front passenger airbag will not be deployed in the event of an accident and cannot perform its intended protective function.
	A person in the front passenger seat could then, for example, come into contact with the vehicle's interior, especially if the person is sitting too close to the cockpit.
	Make sure, both before and during the journey, that the status of the front passenger airbag is correct.
	➤ Stop the vehicle immediately in accordance with the traffic conditions.
	▶ Make sure that no objects are trapped under the front passenger seat.
	Check the status of the automatic front passenger air bag shutoff (→ page 43).
	▶ If necessary, consult a qualified specialist workshop immediately.
Front Passenger Airbag Enabled See Operator's Manual	<ul> <li>* The front passenger air bag will be enabled while the vehicle is in motion in the following situations:</li> <li>even when a child, a small adult or an object weighing less than the system weight threshold is located on the front passenger seat</li> <li>even when the front passenger seat is not occupied</li> </ul>
	The system may detect objects or forces that are adding to the weight applied to the seat.

Display messages	Possible causes/consequences and ▶ Solutions
	<b>WARNING</b> Risk of injury or death when using a child restraint system while the front passenger airbag is enabled
	If you secure a child in a child restraint system on the front passenger seat and the front passenger airbag is enabled, the front passenger airbag can deploy in the event of an accident.
	The child could be struck by the airbag.
	Ensure, both before and during the journey, that the status of the front passenger airbag is correct.
	NEVER use a rearward facing child restraint on a seat protected by an ACTIVE AIRBAG in front of it, DEATH or SERIOUS INJURY to the CHILD can occur.
	Stop the vehicle immediately in accordance with the traffic conditions.
	Make sure that no objects are trapped under the front passenger seat.
	$\blacktriangleright$ Check the status of the automatic front passenger air bag shutoff ( $\rightarrow$ page 43).
	► If necessary, consult a qualified specialist workshop immediately.

### SmartKey

Display messages	Possible causes/consequences and ▶ Solutions
Obtain a New Key	* Have the key replaced.  Consult a qualified specialist workshop.
Replace Key Battery	* The key battery is discharged.  ▶ Replace the battery (→ page 74).
Key Not Detected (white display message)	<ul> <li>* The key is currently undetected.</li> <li>Change the location of the key in the vehicle.</li> <li>Try to start the vehicle.</li> <li>If the key is still not detected, place it in the slot for starting with the key (→ page 177).</li> <li>Start the vehicle.</li> </ul>

### Display messages Possible causes/consequences and ▶ Solutions \* The key can no longer be detected during a journey and may no longer be in the vehicle. If the key is no longer in the vehicle and you switch off the vehicle: • You can no longer start the vehicle. Key Not Detected (red dis-· You cannot centrally lock the vehicle. play message) Ensure that the key is in the vehicle. If the key is in the vehicle and is still not detected: Stop the vehicle immediately in accordance with the traffic conditions. Place the key in the slot for starting the engine with the key ( $\rightarrow$ page 177). The key battery is weak or discharged. $\triangleright$ Check the battery using the indicator lamp ( $\rightarrow$ page 72). Replace the key battery, if necessary ( $\rightarrow$ page 74). \* The vehicle is processing in order to teach in the new key. Wait until processing is complete. Key Being Initialized Please Wait

Display messages	Possible causes/consequences and ▶ Solutions
Don't Forget Your Key	* A warning tone will also sound. This message reminds you to take your key with you when you leave the vehicle.
Place the Key in the Marked Space See Opera- tor's Manual	<ul> <li>* Key detection is malfunctioning.</li> <li>Change the location of the key in the vehicle.</li> <li>Place the key in the slot for starting the engine with the key (→ page 177).</li> </ul>

### Lights

Display messages	Possible causes/consequences and ▶ Solutions
-\\\-	* The corresponding light source is malfunctioning.
, Y.	<ul><li>Drive on carefully.</li><li>Consult a qualified specialist workshop immediately.</li></ul>
Check Left Low Beam (example)	(i) LED light sources: the display message for the corresponding light appears only when all the light-emitting diodes in the light are faulty.

Display messages	Possible causes/consequences and ▶ Solutions
Malfunction See Operator's Manual	* The exterior lighting is malfunctioning.  Consult a qualified specialist workshop.
Automatic Headlamp Mode Inoperative	* The light sensor for automatic driving lights is malfunctioning.  Consult a qualified specialist workshop.
Active Headlamps Inoperative	* The active headlamps are malfunctioning.  Consult a qualified specialist workshop.
Switch On Headlamps	* You are driving without low-beam headlamps.  Turn the light switch to the D or AUTO position.

Display messages	Possible causes/consequences and ▶ Solutions
- <u>Ö</u> -	* You are leaving the vehicle and the lights are still switched on.  Turn the light switch to the AUTO position.
Switch Off Lights  Intell. Light System Inoperative	* The Intelligent Light System is malfunctioning. The lighting system continues to function properly without the functions of the Intelligent Light System.  Consult a qualified specialist workshop.
Adaptive Highbeam Assist Currently Unavailable See Operator's Manual	<ul> <li>* Adaptive Highbeam Assist is temporarily unavailable.</li> <li>The system limits have been reached (→ page 154).</li> <li>Once the cause of the problem is no longer present, the system will be available again. The Adaptive Highbeam Assist Now Available display message will appear.</li> <li>▶ Drive on.</li> <li>▶ Operate the high beam manually until Adaptive Highbeam Assist is available again.</li> </ul>
Adaptive Highbeam Assist Inoperative	* Adaptive Highbeam Assist is malfunctioning.  Drive on or

Display messages	Possible causes/consequences and ▶ Solutions
	<ul> <li>Stop the vehicle in accordance with the traffic conditions and restart the vehicle.</li> <li>If the display message does not disappear: consult a qualified specialist workshop.</li> <li>Until then, operate the high beam manually.</li> </ul>
Hazard Warning Flashers Malfunctioning	<ul><li>* The hazard warning lamp switch is malfunctioning.</li><li>Consult a qualified specialist workshop.</li></ul>

### Vehicle

Display messages	Possible causes/consequences and ▶ Solutions
Update Successfully Completed	* Installation of the software update has been successfully completed ( $\rightarrow$ page 300).
Update Failed Software Remains Unchanged	* An error occurred during installation of the software update ( $\rightarrow$ page 300). The previous software release remains in place.
Update Failed	* An error occurred during installation of the software update ( $\rightarrow$ page 300). Make a Mercedes me call via the overhead control panel ( $\rightarrow$ page 317).

Display messages	Possible causes/consequences and ▶ Solutions
Vehicle Ready to Drive Switch the Ignition Off Before Exiting	<ul> <li>You are leaving the vehicle in a ready-to-drive state.</li> <li>Get out of the vehicle, secure it against rolling away and take the key with you.</li> <li>If you do not leave the vehicle, switch off the electrical consumers, e.g. the seat heating. Otherwise, the 12 V battery may discharge and starting the engine may be possible only with the help of a second battery (jump start).</li> </ul>
Running Boards Not Retrac- ted Pay Attention to Excess Width of Vehicle	<ul> <li>* Mercedes-Maybach vehicles: the running boards are not retracted.</li> <li>• The running boards can be retracted via the multimedia system only when the vehicle is stationary (→ page 80).</li> <li>• The running boards and the side skirt must be free of dirt, ice and snow. Otherwise, they are unable to retract.</li> <li>▶ Clean the running boards (→ page 349).</li> <li>▶ Repeat the retraction of the running boards (→ page 79).</li> <li>If the running boards cannot be retracted again, consult a qualified specialist workshop.</li> <li>▶ If the running boards are not retracted, check the excess width of the vehicle.</li> </ul>
Running Board Not Extended	<ul> <li>* Mercedes-Maybach vehicles: the running boards are not extended.</li> <li>• The running boards extend only when the vehicle is stationary.</li> <li>• The running boards and the side skirt must be free of dirt, ice and snow. Otherwise, they are unable to extend.</li> <li>▶ Clean the running boards (→ page 349).</li> </ul>

Display messages	Possible causes/consequences and ▶ Solutions
	<ul> <li>Repeat the extension of the running boards (→ page 79).</li> <li>If the running boards fail to extend again, consult a qualified specialist workshop.</li> <li>If the running boards are not extended, be particularly careful when getting in or out.</li> </ul>
Head-up Display Currently Unavailable See Operator's Manual	<ul> <li>* The head-up display is temporarily unavailable. Possible causes are:</li> <li>malfunctions in the power supply</li> <li>signal interference</li> </ul>
	<ul><li>Stop in accordance with the traffic conditions and switch the vehicle off and on again.</li><li>If the display message still appears, consult a qualified specialist workshop.</li></ul>
Head-up Display Inoperative	<ul> <li>* The head-up display has an internal error.</li> <li>Consult a qualified specialist workshop.</li> </ul>
	* The power steering assistance is malfunctioning.
🐼	▲ WARNING Risk of an accident due to altered steering characteristics
Steering Malfunction Increased Physical Effort See Operator's Manual	If the power assistance of the steering fails partially or completely, you will need to use more force to steer.  If safe steering is possible, drive on carefully.  Visit or consult a qualified specialist workshop immediately.

Display messages	Possible causes/consequences and ▶ Solutions
	* The steering is malfunctioning. Steering capability is significantly impaired.
<b>S</b> :	▲ WARNING Risk of accident if steering capability is impaired
Steering Malfunction Stop Immediately See Opera- tor's Manual	If the steering does not function as intended, the vehicle's operating safety is jeopardized.  Pull over and stop the vehicle safely as soon as possible, paying attention to road and traffic conditions. Do not continue driving under any circumstances.  Consult a qualified specialist workshop.
	* At least one door is open.  Close all doors.
	* The hood is open.
(O-O)	▲ WARNING Risk of accident due to driving with the hood unlocked
	The hood may open and block your view.  Never release the hood when driving.  Before every trip, ensure that the hood is locked.
	<ul><li>Stop the vehicle immediately in accordance with the traffic conditions.</li><li>Close the hood.</li></ul>

Display messages	Possible causes/consequences and ▶ Solutions
LOW RANGE Malfunction To Park, Apply Brake	<ul> <li>* The transfer case is malfunctioning.</li> <li>Do not shift the transfer case!</li> <li>Use the electric parking brake to secure the vehicle against rolling away.</li> <li>Consult a qualified specialist workshop.</li> </ul>
LOW RANGE Shifting Canceled Please Reactivate	<ul> <li>* The transfer case did not perform the gear change.</li> <li>▶ Repeat the gear change.</li> <li>▶ Ensure that all shifting conditions are met (→ page 200).</li> </ul>
LOW RANGE Malfunction	<ul> <li>* The transfer case is malfunctioning.</li> <li>Do not shift the transfer case!</li> <li>Use the electric parking brake to secure the vehicle against rolling away.</li> <li>Consult a qualified specialist workshop.</li> </ul>
LOW RANGE Stop Apply Parking Brake	<ul> <li>* The transfer case is malfunctioning.</li> <li>Stop the vehicle in accordance with the traffic conditions.</li> <li>Apply the electric parking brake.</li> <li>Where necessary, also secure the vehicle against rolling away.</li> <li>Engage park position P.</li> </ul>
LOW RANGE Max. Speed 6 mph	* The maximum speed of 6 mph (10 km/h) for the gear change has been exceeded.

Display messages	Possible causes/consequences and ▶ Solutions
Cannot Fold Forward 2nd Seat Row, Left Adjust Front Seat	<ul> <li>* The left seat backrests on the second row of seats cannot be folded forward.</li> <li>▶ Adjust the corresponding front seat.</li> </ul>
Cannot Fold Forward 2nd Seat Row, Right Adjust Front Seat	* The right seat backrests on the second row of seats cannot be folded forward.  Adjust the corresponding front seat.
Check Washer Fluid	<ul> <li>* The washer fluid level in the washer fluid reservoir has dropped below the minimum.</li> <li>▶ Add washer fluid (→ page 343).</li> </ul>
Wiper Malfunctioning	* The windshield wiper is malfunctioning.  Restart the vehicle.

Display messages	Possible causes/consequences and ▶ Solutions
	If the display message still appears:
	Consult a qualified specialist workshop.

### Engine

Display messages	Possible causes/consequences and ▶ Solutions
To switch engine off, press and hold Start/Stop but- ton for at least 3 seconds or press 3 times.	<ul> <li>You have pressed the start/stop button while the vehicle is in motion.</li> <li>Information about switching off the vehicle while driving (→ page 176).</li> </ul>
Cannot Start Engine See Operator's Manual	<ul> <li>* The vehicle cannot be started.</li> <li>&gt; Switch the vehicle off and switch it back on</li> <li>If the display message still appears, consult a qualified specialist workshop.</li> </ul>
Check Coolant Level See Operator's Manual	* The coolant level is too low.  ■ NOTE Engine damage due to insufficient coolant  ■ Avoid long journeys with insufficient coolant.  ■ Add coolant (→ page 342).

Display messages	Possible causes/consequences and ▶ Solutions
	► Have the engine cooling system checked at a qualified specialist workshop.
<u></u>	* There is a malfunction in the engine cooling system.
	Avoiding high loads on the engine, drive to the nearest qualified specialist workshop. In doing so, ensure that the coolant temperature display remains below the red marking.
∩-	* The coolant is too hot.
	Stop immediately in accordance with the traffic conditions and switch off the vehicle.
Coolant Too Hot Stop Vehi-	WARNING Risk of burns when opening the hood
cle Turn Engine Off	If you open the hood in the event of an overheated engine or fire in the engine compartment, the following situations may occur:
	You may come into contact with hot gases.
	You may come into contact with other escaping hot operating fluids.
	▶ Before opening the hood, allow the engine to cool down.
	In the event of a fire in the engine compartment, keep the hood closed and call the fire service.
	Wait until the engine has cooled down.
	► Make sure that the air supply to the radiator is not obstructed.
	Avoiding high loads on the engine, drive to the nearest qualified specialist workshop. In doing so, ensure that the coolant temperature display remains below the red marking.

Display messages	Possible causes/consequences and ▶ Solutions
Fuel Level Low	* The fuel supply has dropped into the reserve range.  ▶ Refuel.
Gas Cap Loose	<ul> <li>* The fuel filler cap is not closed correctly or the fuel system is leaking.</li> <li>Close the fuel filler cap.</li> <li>If the fuel filler cap was already properly closed: consult a qualified specialist workshop.</li> </ul>

### Transmission

Display messages	Possible causes/consequences and ▶ Solutions
Only Shift to 'P' when Vehi- cle is Stationary	<ul> <li>* It is possible to select the park position P only if the vehicle is stationary.</li> <li>Depress the brake pedal to stop.</li> <li>Shift the transmission to park position P when the vehicle is stationary.</li> </ul>
Apply Brake to Shift from 'P'	<ul> <li>You have attempted to shift the transmission out of park position P and into another transmission position.</li> <li>Depress the brake pedal.</li> <li>Select transmission position D, R or neutral N.</li> </ul>

Display messages	Possible causes/consequences and ▶ Solutions
To Deselect P or N, Depress Brake and Start Engine	<ul> <li>* You have attempted to shift the transmission out of park position P or neutral N and into another transmission position.</li> <li>Depress the brake pedal.</li> <li>Start the vehicle.</li> <li>Change the transmission position.</li> </ul>
Apply Brake to Shift to D or R	<ul> <li>You have attempted to select transmission position D or R.</li> <li>Depress the brake pedal.</li> <li>Select transmission position D or R.</li> </ul>
Apply Brake to Shift to 'R'	<ul> <li>You have attempted to select transmission position R.</li> <li>Depress the brake pedal.</li> <li>Select transmission position R.</li> </ul>
Driver's Door Open & Transmission Not in P Risk of Vehicle Rolling Away	* The driver's door is not fully closed and transmission position D, R or neutral N is selected.  The vehicle may roll away.  Select park position P when switching off the vehicle.
N Permanently Active Risk of Rolling Away	<ul> <li>* While the vehicle is rolling or while you are driving, neutral N has been engaged.</li> <li>Depress the brake pedal to stop.</li> <li>Shift the transmission to park position P when the vehicle is stationary.</li> <li>To continue driving, select transmission position D or R.</li> </ul>

Display messages	Possible causes/consequences and ▶ Solutions
Service Required Do Not Shift Gears Visit Dealer	<ul> <li>* The transmission is malfunctioning. It is no longer possible to change the transmission position.</li> <li>If transmission position  is selected, consult a qualified specialist workshop and do not change the transmission position.</li> <li>For all other transmission positions, park the vehicle safely.</li> <li>Consult a qualified specialist workshop or breakdown service.</li> </ul>
Reversing Not Possible Service Required	<ul> <li>* The transmission is malfunctioning. It is not possible to select transmission position <b>R</b>.</li> <li>▶ Consult a qualified specialist workshop.</li> </ul>
Transmission Malfunction Stop	<ul> <li>* The transmission is malfunctioning. The transmission shifts to neutral N automatically.</li> <li>Stop the vehicle immediately in accordance with the traffic conditions.</li> <li>Depress the brake pedal.</li> <li>Engage park position P.</li> <li>Consult a qualified specialist workshop.</li> </ul>
Stop Vehicle Leave Engine Running Wait Transmission Cooling	<ul> <li>* The transmission is overheating. Pulling away may be temporarily impaired or not possible.</li> <li>Stop the vehicle immediately in accordance with the traffic conditions. Do not continue driving.</li> <li>Leave the engine running.</li> <li>Wait until the display message disappears before pulling away.</li> </ul>
Auxiliary Battery Malfunction (white display message)	* The auxiliary battery for the automatic transmission is no longer being charged.  Consult a qualified specialist workshop.

Display messages	Possible causes / consequences and ▶ Solutions
	<ul> <li>Until then, always select park position P manually before you switch off the vehicle.</li> <li>Before leaving the vehicle, apply the electric parking brake.</li> </ul>
Auxiliary Battery Malfunction (red display message)	<ul> <li>* Vehicles with automatic transmission: The auxiliary battery for the transmission is no longer being charged.</li> <li>Consult a qualified specialist workshop.</li> <li>Vehicles with automatic transmission: Until then, always select park position P before you switch off the vehicle.</li> <li>Before leaving the vehicle, apply the electric parking brake.</li> </ul>

### **Brakes**

### Display messages



(USA only)



(Canada only)

Parking Brake See Operator's Manual

### Possible causes/consequences and ▶ Solutions

\* The yellow indicator lamp is lit. The electric parking brake is malfunctioning.

### To apply:

- Switch the vehicle off and switch it back on.
- Apply the electric parking brake manually ( $\rightarrow$  page 209).

If it is not possible to apply the electric parking brake:

- Consult a qualified specialist workshop.
- Where necessary, also secure the parked vehicle against rolling away.
- \* The yellow (Park) indicator lamp and the red PARK (USA only) or (R) (Canada only) indicator lamp are lit. The electric parking brake is malfunctioning.

### To release:

- Switch the vehicle off and switch it back on.
- Release the electric parking brake manually ( $\rightarrow$  page 209).

or

Release the electric parking brake automatically (→ page 208).

If it is still not possible to release the electric parking brake:

▶ Do not continue driving. Consult a qualified specialist workshop.

Display messages	Possible causes/consequences and ▶ Solutions
	* The yellow (nicator lamp is lit and the red PARK (USA only) or (Canada only) indicator lamp is flashing. The electric parking brake is malfunctioning.
	The electric parking brake could not be applied or released.
	Switch the vehicle off and switch it back on.
	To apply:
	Release and then apply the electric parking brake manually ( $\rightarrow$ page 209).
	To release:
	Apply and then release the electric parking brake manually.
	If the electric parking brake cannot be applied or the red PARK (USA only) or (Canada only) indicator lamp continues to flash:
	Do not continue driving. Consult a qualified specialist workshop.
	▶ Where necessary, also secure the parked vehicle against rolling away.
	* The yellow (P) indicator lamp is lit and the red PARK (USA only) or (Canada only) indicator lamp flashes for approximately ten seconds after the electric parking brake has been applied or released. It then remains lit or goes out. The electric parking brake is malfunctioning.
	If the state of charge is too low:
	Charge the 12 V battery.

### Display messages Possible causes/consequences and > Solutions To apply: Switch off the vehicle. The electric parking brake will be applied automatically. If you do not want the electric parking brake to be applied, e.g. at an automatic car wash or when the vehicle is being towed, leave the vehicle switched on. This does not include having the vehicle towed with the rear axle raised. If the electric parking brake is not applied automatically: Switch the vehicle off and switch it back on. Release and then apply the electric parking brake manually ( $\rightarrow$ page 209). If it is still not possible to apply the electric parking brake: Consult a qualified specialist workshop. Where necessary, also secure the parked vehicle against rolling away. To release: If the conditions for automatic release are fulfilled and the electric parking brake is not released automatically, release the electric parking brake manually ( $\rightarrow$ page 209). If it is still not possible to release the electric parking brake: Do not continue driving. Consult a qualified specialist workshop.

# PARK (USA only) (Canada only) (Canada only) Please Release Parking Brake Possible causes/consequences and ▶ Solutions \* The red PARK indicator lamp (USA only) or pindicator lamp (Canada only) is flashing. The electric parking brake is applied while you are driving: • A condition for automatic release of the electric parking brake has not been fulfilled (→ page 208). • You are performing emergency braking using the electric parking brake. ▶ Release the electric parking brake manually.

### Display messages

### **PARK**

(USA only)



(Canada only)

Turn On the Ignition to Release the Parking Brake

### Possible causes/consequences and ▶ Solutions

- \* The red PARK (USA only) or (P) (Canada only) indicator lamp is lit. You have attempted to release the electric parking brake with the vehicle switched off.
  - Switch on the vehicle.

**BRAKE** 

(USA only)



(Canada only)

Check Brake Fluid Level

\* There is insufficient brake fluid in the brake fluid reservoir.

**A** WARNING Risk of an accident due to low brake fluid level

If the brake fluid level is too low, the braking effect and the braking characteristics may be impaired.

- > Pull over and stop the vehicle safely as soon as possible, paying attention to road and traffic conditions. Do not continue driving under any circumstances.
- Consult a qualified specialist workshop.
- Do not add brake fluid.

Display messages	Possible causes/consequences and ▶ Solutions
Check Brake Pads See Operator's Manual	<ul> <li>* The brakepads have reached the wear limit.</li> <li>Consult a qualified specialist workshop.</li> </ul>

### Driving and driving safety systems

### Display messages Possible causes/consequences and > Solutions \* ABS and ESP® are temporarily unavailable. Other driving systems and driving safety systems (e.g. BAS) may also be temporarily unavailable. The brake system will continue to operate normally. Braking distance may increase in an emergency braking situation. WARNING Risk of skidding if ABS and ESP® are malfunctioning The wheels may lock during braking and ESP® does not perform any vehicle stabilization. Currently Unavailable See The steerability and braking characteristics are heavily impaired and the braking distance may increase. In addi-Operator's Manual tion, other driving safety systems are switched off. ▶ Drive carefully on a suitable stretch of road, making slight steering movements at a speed above 19 mph (30 km/h).▶ If the display message does not disappear, consult a qualified specialist workshop immediately. Drive carefully.

### Display messages Inoperative See Operator's Manual

### Possible causes/consequences and ▶ Solutions

\* ABS and ESP® are malfunctioning.

Other driving systems and driving safety systems (e.g. BAS) may also be malfunctioning.

The brake system will continue to operate normally. Braking distance may increase in an emergency braking situation.

**WARNING** Risk of skidding if ABS and ESP® are malfunctioning

The wheels may block during braking and ESP® does not perform any vehicle stabilization.

The steerability and braking characteristics are heavily impaired and the braking distance may increase. In addition, other driving safety systems are switched off.

- Drive on carefully.
- Have ABS and ESP® checked immediately at a qualified specialist workshop.



Currently Unavailable See Operator's Manual

\* ESP® is temporarily unavailable.


Other driving systems and driving safety systems (e.g. BAS) may also be malfunctioning.

▲ WARNING Risk of skidding if ESP is malfunctioning®

If ESP® is malfunctioning, ESP® cannot carry out vehicle stabilization. In addition, other driving safety systems are switched off.

▶ Drive carefully on a suitable stretch of road, making slight steering movements at a speed above 19 mph (30 km/h).

Display messages	Possible causes/consequences and ▶ Solutions
	If the display message does not disappear, consult a qualified specialist workshop immediately. Drive carefully.
Inoperative See Operator's Manual	* ESP® is malfunctioning.  Other driving systems and driving safety systems (e.g. BAS) may also be malfunctioning.  The brake system will continue to operate normally. Braking distance may increase in an emergency braking situation.
	<b>▲ WARNING</b> Risk of skidding if ESP <sup>®</sup> is malfunctioning
	If ESP® is malfunctioning, ESP® cannot carry out vehicle stabilization. In addition, other driving safety systems are switched off.
	➤ Drive on carefully.
	Have ESP® checked at a qualified specialist workshop.



Display messages	Possible causes/consequences and ▶ Solutions
ATTENTION ASSIST: Take a Break!	<ul> <li>* ATTENTION ASSIST has detected fatigue or an increasing lack of concentration on the part of the driver (→ page 218).</li> <li>▶ If necessary, take a break.</li> </ul>
100	* Cruise control cannot be activated as not all activation conditions are fulfilled.
mph	ightharpoonup Observe the activation conditions for cruise control ( $ ightharpoonup$ page 221).
Cruise Control Inoperative	* Cruise control is malfunctioning.
	Consult a qualified specialist workshop.
Cruise Control Off	* Cruise control has been deactivated.
	If there is an additional warning tone, cruise control has been deactivated automatically ( $\rightarrow$ page 220).
Traffic Sign Assist Cur- rently Unavailable See Operator's Manual	* Traffic Sign Assist is temporarily unavailable.
	Once the cause of the problem is no longer present, the system will be available again.
	Continue driving in compliance with traffic regulations.
Traffic Sign Assist Inoperative	* Traffic Sign Assist is malfunctioning.
	Continue driving in compliance with traffic regulations.

Display messages	Possible causes/consequences and ▶ Solutions
	or
	Stop the vehicle in accordance with the traffic conditions and restart the vehicle.  If the display message does not disappear: consult a qualified specialist workshop.
	* AIRMATIC is functioning only to a limited extent. The vehicle's handling characteristics may be affected.
)))	I NOTE The tires on the front axle or the fenders could be damaged by large steering movements
Malfunction Drive at Max.	Avoid large steering movements while driving and listen for scraping sounds.
50 mph	If you hear scraping sounds, pull over and stop the vehicle in accordance with the traffic conditions, and set a higher vehicle level if possible.
	Drive in a manner appropriate for the current level, but do not exceed 50 mph (80 km/h).
	Consult a qualified specialist workshop.
Malfunction Drive at Max. 50 mph	* E-ACTIVE BODY CONTROL is malfunctioning. The vehicle's handling characteristics may be affected.
	! NOTE The tires on the front axle or the fenders could be damaged by large steering movements
	Avoid large steering movements while driving and listen for scraping sounds.
	If you hear scraping sounds, pull over and stop the vehicle in accordance with the traffic conditions, and set a higher vehicle level if possible.

Display messages	Possible causes/consequences and ▶ Solutions
	Consult a qualified specialist workshop.
	* The vehicle level will lower for the following reasons:
0	You have selected a different drive program.
	You have exceeded the speed limit.
Lowering	You have changed the vehicle level by pressing the button.
	<ul> <li>Operation with a trailer or bicycle rack: if an electrical connection has been correctly made, you have exceeded the speed limit.</li> </ul>
	<ul> <li>You have switched on the rear fog lamp in the off-road level +3.</li> </ul>
Vehicle Rising	* Your vehicle is adjusting to the level you have selected.
Vehicle Rising Please Wait	* The vehicle level is too low. The vehicle will be raised to the selected vehicle level.  Wait until the display message disappears before pulling away.

Display messages	Possible causes/consequences and ▶ Solutions
Compressor Is Cooling	* Due to frequent level changes within a short space of time, the compressor first needs to cool down in order to set the selected vehicle level.  When the compressor has cooled down, the vehicle will continue rising to the selected vehicle level.  Drive on in a manner appropriate for the current level. Make sure that there is sufficient ground clearance.
( <u>1</u>	* You are driving too fast for the selected vehicle level.
	Drive more slowly and then select the desired vehicle level again.
Drive More Slowly	You are driving too quickly with a trailer or the trailer hitch socket is being used, e.g. for a rear bicycle rack.  Read the notes on trailer operation.
E-ACTIVE BODY CONTROL Function Limited See Oper- ator's Manual	* At least one main function of the E-ACTIVE BODY CONTROL system is malfunctioning.  The system is outside the operating temperature range or the on-board electrical system voltage is too low.  Once the cause of the problem is no longer present, the system will be available again.
	NOTE The vehicle's suspension and damping behavior is restricted. The vehicle body may tilt heavily to the side during cornering.
	➤ Drive on carefully.
	Reduce speed considerably before taking a bend.
	Avoid sudden steering movements.

Display messages	Possible causes/consequences and ▶ Solutions
	<ul> <li>Drive on carefully.</li> <li>Reduce speed considerably before taking a curve.</li> <li>Avoid sudden steering movements.</li> </ul>
Selected Level Not Available When Rear Fog Lamp On	<ul><li>You cannot select off-road level +3.</li><li>Switch off the rear fog lamp.</li></ul>
Malfunction Drive at Max. 50 mph	* At least one main function of the E-ACTIVE BODY CONTROL system is malfunctioning.  The system is deactivated.  I NOTE The vehicle's suspension and damping behavior has changed significantly, the vehicle body may tilt heavily to the side during cornering.
	<ul> <li>Reduce vehicle speed. Drive on carefully.</li> <li>Reduce the vehicle speed considerably before taking a curve.</li> <li>Avoid sudden steering movements.</li> </ul>
	<ul> <li>Continue driving carefully and do not exceed 50 mph (80 km/h).</li> <li>If possible, stop in accordance with the traffic conditions and switch the vehicle off and on again.</li> <li>If the display message still appears, consult a qualified specialist workshop.</li> </ul>

## Display messages Possible causes/consequences and ▶ Solutions \* The Downhill Speed Regulation is not available in the currently selected drive program. Not in the Current Drive Program Possible causes/consequences and ▶ Solutions \* The Downhill Speed Regulation is not available in the currently selected drive program. Change the drive program.

### Driver assistance systems

Display messages	Possible causes/consequences and ▶ Solutions
mph	<ul> <li>* Active Distance Assist DISTRONIC cannot be activated as not all activation conditions are fulfilled.</li> <li>▶ Comply with the activation conditions of Active Distance Assist DISTRONIC (→ page 224).</li> </ul>
Suspended	* If you depress the accelerator pedal beyond the setting of Active Distance Assist DISTRONIC, the system will switch to passive mode (→ page 222).

Display messages	Possible causes/consequences and ▶ Solutions
Off	* Active Distance Assist DISTRONIC was deactivated. If a warning tone also sounds, Active Distance Assist DISTRONIC has deactivated automatically (→ page 224).
Active Distance Assist Cur-	* Active Distance Assist DISTRONIC is temporarily unavailable.
rently Unavailable See	The ambient conditions are outside the system limits ( $\rightarrow$ page 222).
Operator's Manual	As soon as the ambient conditions are within the system limits, the system will become available again.
	▶ Drive on carefully.
	or
	If the display message does not disappear, stop the vehicle in accordance with the traffic conditions and restart the vehicle.
Active Distance Assist Inoperative	* Active Distance Assist DISTRONIC is malfunctioning.
	Other driving systems and driving safety systems may also be malfunctioning.
	▶ Drive on carefully.
	or
	<ul><li>Stop the vehicle in accordance with the traffic conditions and restart the vehicle.</li><li>If the display message does not disappear: consult a qualified specialist workshop.</li></ul>

Display messages	Possible causes/consequences and ▶ Solutions
Active Distance Assist Now Available	<ul> <li>* Active Distance Assist DISTRONIC is operational again.</li> <li>▶ Switch on Active Distance Assist DISTRONIC (→ page 224).</li> </ul>
Active Brake Assist Functions Currently Limited See Operator's Manual	<ul> <li>* Vehicles with the Driving Assistance Package: Active Brake Assist with cross-traffic function, Evasive Steering Assist of PRE-SAFE® PLUS are temporarily unavailable or only partially available.</li> <li>Vehicles without the Driving Assistance Package: Active Brake Assist is temporarily unavailable.</li> <li>Drive on carefully.         <ul> <li>As soon as the ambient conditions are within the system limits, the system will become available again.</li> </ul> </li> <li>or</li> <li>If the display message does not disappear, stop the vehicle in accordance with the traffic conditions and restart the vehicle.</li> </ul>
Active Brake Assist Functions Limited See Operator's Manual	<ul> <li>* For vehicles with the Driving Assistance Package, the following functions may be temporarily unavailable or only partially available:</li> <li>Active Brake Assist with cross-traffic function</li> <li>Evasive Steering Assist</li> <li>PRE-SAFE® PLUS</li> <li>Vehicles without the Driving Assistance Package: Active Brake Assist is temporarily unavailable or only partially available.</li> <li>Drive on carefully.</li> </ul>

Display messages	Possible causes/consequences and ▶ Solutions
	<ul> <li>Stop the vehicle in accordance with the traffic conditions and restart the vehicle.</li> <li>If the display message does not disappear: consult a qualified specialist workshop.</li> </ul>
Active Steering Assist Currently Unavailable See Operator's Manual	<ul> <li>* Active Steering Assist is temporarily unavailable.</li> <li>The ambient conditions are outside the system limits (→ page 231).</li> <li>As soon as the ambient conditions are within the system limits, the system will become available again.</li> <li>▶ Drive on.</li> <li>▶ Check the tire pressure if necessary.</li> </ul>
Active Steering Assist Inoperative	<ul> <li>* Active Steering Assist is malfunctioning. Active Distance Assist DISTRONIC remains available.</li> <li>Drive on</li> <li>Stop the vehicle in accordance with the traffic conditions and restart the vehicle.</li> <li>If the display message does not disappear: consult a qualified specialist workshop.</li> </ul>
Active Steering Asst. Currently Unavailable Due to Multiple Emergency Stops	<ul> <li>* Active Steering Assist is temporarily unavailable due to several emergency stops having been performed.</li> <li>Take over the steering and stop in accordance with the traffic conditions.</li> <li>Switch the vehicle off and switch it back on.         Active Steering Assist is available once more.</li> </ul>
Beginning Emergency Stop	<ul> <li>* Your hands are not on the steering wheel. An emergency stop is being initiated (→ page 233).</li> <li>▶ Put your hands back on the steering wheel.</li> </ul>

Display messages	Possible causes/consequences and ▶ Solutions
	You can cancel the deceleration at any time by performing one of the following actions:  • Steering  • Braking or accelerating  • Possitivation Active Distance Acciet DISTRONIC
	Deactivating Active Distance Assist DISTRONIC      A 1:    Our in A 1:    Ou
	* Active Steering Assist has reached the system limits (→ page 231).  You have not steered independently for a considerable period of time.
	► Take over the steering and drive on in accordance with the traffic conditions.
Active Stop & Go Assist Currently Unavailable See	* Active Stop-and-Go Assist is temporarily unavailable. Active Distance Assist DISTRONIC and Active Steering Assist are still available.
Operator's Manual	The ambient conditions are outside the system limits ( $\rightarrow$ page 228).
	As soon as the ambient conditions are within the system limits, the system will become available again.  Drive on
Active Stop & Go Assist Inoperative See Operator's Manual	* Active Stop-and-Go Assist is malfunctioning.
	Active Stop-and-Go Assist has been deactivated. Active Distance Assist DISTRONIC and Active Steering Assist are still available.
	➤ Drive on
	or
	Stop the vehicle in accordance with the traffic conditions and restart the vehicle.

Display messages	Possible causes/consequences and ▶ Solutions
	If the display message does not disappear: consult a qualified specialist workshop.
Blind Spot Assist Currently Unavailable See Operator's Manual	<ul> <li>* Blind Spot Assist is temporarily unavailable. The system limits have been reached (→ page 242). Once the cause of the problem is no longer present, the system will be available again. Drive on. or If the display message does not disappear, stop the vehicle in accordance with the traffic conditions and restart the vehicle. </li> </ul>
Blind Spot Assist Inoperative	<ul> <li>Blind Spot Assist is malfunctioning.</li> <li>Drive on</li> <li>Stop the vehicle in accordance with the traffic conditions and restart the vehicle.</li> <li>If the display message does not disappear: consult a qualified specialist workshop.</li> </ul>
Blind Spot Assist Not Avail- able When Towing a Trailer See Operator's Manual	* When you establish the electrical connection to the trailer, Blind Spot Assist will be unavailable.  Press the left-hand Touch Control and acknowledge the display message.
Active Blind Spot Assist Currently Unavailable See Operator's Manual	* Active Blind Spot Assist is temporarily unavailable.  The system limits have been reached (→ page 242).

Display messages	Possible causes/consequences and ▶ Solutions
	Once the cause of the problem is no longer present, the system will be available again.  Drive on.  or  If the display message does not disappear, stop the vehicle in accordance with the traffic conditions and restart the vehicle.
Active Blind Spot Assist Inoperative	<ul> <li>* Active Blind Spot Assist is malfunctioning.</li> <li>Drive on</li> <li>or</li> <li>Stop the vehicle in accordance with the traffic conditions and restart the vehicle.</li> <li>If the display message does not disappear: consult a qualified specialist workshop.</li> </ul>
Active Blind Spot Asst. Not Available When Towing a Trailer See Operator's Man- ual	* When you establish the electrical connection to the trailer, Active Blind Spot Assist will be unavailable.  Press the left-hand Touch Control and acknowledge the display message.
Active Lane Keeping Assist Currently Unavailable See Operator's Manual	<ul> <li>* Active Lane Keeping Assist is temporarily unavailable.</li> <li>The ambient conditions are outside the system limits (→ page 244).</li> <li>As soon as the ambient conditions are within the system limits, the system will become available again.</li> <li>▶ Drive on.</li> </ul>

Display messages	Possible causes/consequences and ▶ Solutions
Active Lane Keeping Assist Inoperative	* Active Lane Keeping Assist is malfunctioning.
	▶ Drive on
	or
	Stop the vehicle in accordance with the traffic conditions and restart the vehicle.  If the display message does not disappear: consult a qualified specialist workshop.
	* Front and corner radar sensors (hereafter "sensors") are malfunctioning. Possible causes are:
▎░█░▕	The sensors are dirty
	Heavy rain or snow
	Extended country driving without other traffic, e.g. in the desert
	Driving systems and driving safety systems may be malfunctioning or temporarily unavailable. The brake system, steer ing and drive system will continue to function normally.
	➤ Drive on carefully.
	Once the causes of the problem are no longer present, the driving systems and driving safety systems will be available again and the corresponding symbols will be switched off.
	If the display message does not disappear:
Temporarily Unavailable	Stop the vehicle in accordance with the traffic conditions.
Sensors are Dirty	Clean all sensor covers from outside (→ page 211).
	Restart the vehicle.

#### Display messages



#### Temporarily Unavailable Camera View Restricted

#### Possible causes/consequences and ▶ Solutions

- \* The view of the multifunction camera is restricted. Possible causes are:
  - Dirt on the windshield in the field of vision of the multifunction camera
  - · Heavy rain, snow or fog
  - Mist on the inside of the windshield: in certain weather conditions, mist can form on the inside of the windshield during cold times of year in particular.
  - (i) This mist on the windshield will be removed automatically within a short time with the aid of a heater. The restriction is temporary.

Driving systems and driving safety systems may be malfunctioning or temporarily unavailable. The brake system, steering and drive system will continue to function normally.

Drive on carefully.

Once the causes of the problem are no longer present, the driving systems and driving safety systems will be available again and the corresponding symbols will be switched off.

If the display message does not disappear:

- Stop the vehicle in accordance with the traffic conditions.
- ightharpoonup Clean the windshield, especially in the position of the multifunction camera (ightharpoonup page 211).
- Restart the vehicle.

Display messages	Possible causes/consequences and ▶ Solutions
PRE-SAFE Inoperative See Operator's Manual	<ul> <li>* The PRE-SAFE® functions are malfunctioning.</li> <li>Lonsult a qualified specialist workshop.</li> </ul>
PRE-SAFE Impulse Side Inoperative See Operator's Manual	* The PRE-SAFE® Impulse Side system is malfunctioning or inoperative after having already been triggered.  Consult a qualified specialist workshop.

# Parking assistance systems

Display messages	Possible causes ∕ consequences and ▶ Solutions
Parking Assist and	* Vehicles with Active Parking Assist: Active Parking Assist and Parking Assist PARKTRONIC are malfunctioning.
PARKTRONIC Inoperative See Operator's Manual	Vehicles without Active Parking Assist: Parking Assist PARKTRONIC is malfunctioning.
	Stop the vehicle in accordance with the traffic conditions and restart the vehicle.
	If the display message still appears, consult a qualified specialist workshop.

#### Mercedes-Benz emergency call system

Display messages	Possible causes/consequences and ▶ Solutions
Inoperative	* The Mercedes-Benz emergency call system is malfunctioning. The Mercedes me connect system is also malfunctioning.  Consult a qualified specialist workshop.
Device Detected at Diagnostics Connection See Operator's Manual	<ul> <li>* The vehicle functions for malfunction detection are restricted.</li> <li>At least one of the main functions of the Mercedes me connect system is malfunctioning.</li> <li>Doserve the notes on the diagnostics connection (→ page 28).</li> <li>Consult a qualified specialist workshop.</li> </ul>

#### **Battery**

# Possible causes/consequences and ➤ Solutions \* The vehicle is off and the state of charge of the 12 V battery is too low. Switch off electrical consumers that are not required. Drive for 30-60 mins. or Charge the 12 V battery when stationary (→ page 365).

Display messages	Possible causes/consequences and ▶ Solutions
	* If the message appears while the vehicle is switched on, this indicates an on-board electrical system malfunction.  Consult a qualified specialist workshop.
رجع	* The 12 V battery is not being charged.
- +	I NOTE Possible engine damage if you continue driving
See Operator's Manual	<ul><li>Do not continue driving under any circumstances.</li><li>Consult a qualified specialist workshop.</li></ul>
	<ul><li>Stop immediately in accordance with the traffic conditions and switch off the vehicle.</li><li>Consult a qualified specialist workshop.</li></ul>
رجع	* The 12 V battery is no longer being charged and the condition of charge is too low.
- +	I NOTE Possible engine damage if you continue driving
Stop Vehicle See Operator's Manual	<ul><li>Do not continue driving under any circumstances.</li><li>Consult a qualified specialist workshop.</li></ul>
	Stop the vehicle immediately in accordance with the traffic conditions. Do not continue driving under any circumstances.
	> Switch off the vehicle.
	Consult a qualified specialist workshop.

Display messages	Possible causes/consequences and ▶ Solutions
Stop Vahiala Lagya Engine	* The state of charge of the 12 V battery is too low.  Stop the vehicle immediately in accordance with the traffic conditions. Do not continue driving under any circumstances.
Stop Vehicle Leave Engine Running	<ul> <li>Leave the engine running.</li> <li>If the display message disappears: drive on.</li> <li>If the display message does not disappear: consult a qualified specialist workshop.</li> </ul>
Battery Overheated Stop, Everyone Get Out Out- doors if Possible	* The 48 V battery is overheating. There is a risk of fire.  Stop the vehicle immediately in accordance with the traffic conditions.  If possible, stop the vehicle in the open air and ensure that all vehicle occupants get out.  Supporting vehicle functions may activate automatically, e.g. air-recirculation mode as part of climate control.  Do not continue driving.  If smoke is present, leave the danger zone and call the fire service immediately.  Consult a qualified specialist workshop even if there are no external signs of a fire.
48 V Battery See Operator's Manual	* The 48 V on-board electrical system has function restrictions.  Comfort functions, such as the climate control system, may be restricted.  It is possible to continue driving.  If the display message remains active continuously, consult a qualified specialist workshop immediately.

Display messages	Possible causes/consequences and ▶ Solutions
<del></del>	* The 48 V battery is discharged. You have switched on the vehicle while the 12 V battery was being charged with a suitable charger or while another vehicle was providing starting assistance.
Please Wait Charging 48 V Battery	The discharged 48 V battery is charged automatically via the voltage converter. After a few minutes, the Engine Can Now Be Started display message will be shown on the instrument display.
	Start the vehicle.
	Drive the vehicle for a while to charge the 12 V battery and the 48 V battery after disconnecting the charger from the vehicle.
	If the Engine Can Now Be Started display message does not appear after a few minutes:  Try to start the vehicle.
	If the vehicle does not start, consult a qualified specialist workshop.
Cannot Start Engine See Operator's Manual	* The state of charge of the 48 V battery is too low. You can no longer start the vehicle.
	Switch off electrical consumers that are not required.
	Connect a suitable charger approved for Mercedes-Benz with sufficient charge output to the jump-start connection point of the 12 V battery (→ page 365).
	The 48 V battery is charged via the voltage converter in the vehicle.
Engine Can Now Be Started	* The 48 V battery has been charged automatically via the voltage converter.
	➤ Start the vehicle and drive for a while to charge the 12 V battery and the 48 V battery.

# Tire pressure monitor

Display messages	Possible causes/consequences and ▶ Solutions				
Tire Press. Monitor Cur- rently Unavailable	* There is interference from a powerful radio signal source. As a result, no signals from the tire pressure sensor are being received. The tire pressure monitoring system is temporarily unavailable.  The tire pressure monitoring system will restart automatically as soon as the cause has been rectified.  Drive on.				
Tire Press. Monitor Inoperative	* The tire pressure monitoring system is malfunctioning.				
uve	▲ WARNING There is a risk of an accident if the tire pressure monitoring system is malfunctioning				
	The tire pressure monitoring system cannot issue a warning if there is pressure loss in one or more of the tires.  Tires with insufficient tire pressure may impair the driving characteristics as well as steering and braking.  Have the tire pressure monitoring system checked at a qualified specialist workshop.				
Tire Pressure Monitor Inoperative No Wheel Sensors	* The wheels installed do not have suitable tire pressure sensors. The tire pressure monitoring system is deactivated.  Install wheels with suitable tire pressure sensors.				
Wheel Sensor(s) Missing	<ul> <li>* There is no signal from the tire pressure sensor in at least one wheel. No pressure value is displayed for the affected tire.</li> <li>Have the faulty tire pressure sensor replaced at a qualified specialist workshop.</li> </ul>				


# Display messages Possible causes/consequences and ▶ Solutions \* The tire pressure in one or more tires has dropped significantly. The wheel position is displayed. A warning tone will also sound. **WARNING** Risk of an accident due to insufficient tire pressure **Check Tires** . The tires can burst. • The tires can wear excessively and/or unevenly. • The driving characteristics as well as the steering and braking may be greatly impaired. You could then lose control of the vehicle Observe the recommended tire pressures. Adjust the tire pressure if necessary. Stop the vehicle in accordance with the traffic conditions. $\triangleright$ Check the tire pressure ( $\rightarrow$ page 376) and the tires. \* The tire pressure is too low in at least one of the tires, or the difference in tire pressure between the individual wheels is too great. Check the tire pressure and add air, if necessary. Please Correct Tire Pres-▶ When the tire pressure is correct, restart the tire pressure monitor ( $\rightarrow$ page 381).

sure

# Possible causes/consequences and ▶ Solutions Display messages \* The pressure in one or more tires has dropped suddenly. The wheel position is displayed. **WARNING** Risk of an accident from driving with a flat tire Warning Tire Malfunction • The tires can overheat and be damaged. • The driving characteristics as well as the steering and braking characteristics may be greatly impaired. You could then lose control of the vehicle Do not drive with a flat tire. Do not exceed the maximum permissible driving distance in emergency mode and the maximum permissible speed with a flat MOExtended tire. Observe the notes on flat tires. Notes on flat tires ( $\rightarrow$ page 354). Stop the vehicle in accordance with the traffic conditions. Check the tires. \* At least one tire is overheating. The affected tires are displayed in red. At temperatures close to the limit value, the tires are displayed in yellow. WARNING Risk of an accident from driving with overheated tires Tires Overheated Overheated tires can burst.

Display messages	Possible causes/consequences and ▶ Solutions
	Reduce speed so that the tires cool down.
Decrease Speed	* At least one tire is overheating. The affected tires are displayed in red. At temperatures close to the limit value, the tires are displayed in yellow.
	▲ WARNING Risk of an accident from driving with overheated tires
	Overheated tires can burst.
	Reduce speed so that the tires cool down.

#### Engine oil



# Display messages Possible causes/consequences and ▶ Solutions \* The engine oil level is too high. **NOTE** Engine damage caused by driving with excess engine oil Engine Oil Reduce Oil Level Avoid long journeys with excess engine oil. Consult a qualified specialist workshop immediately and have the engine oil level reduced. \* The engine oil level is too low. NOTE Engine damage caused by driving with insufficient engine oil Engine Oil Level Low Stop Avoid long journeys with insufficient engine oil. Vehicle Turn Engine Off Stop the vehicle immediately in accordance with the traffic conditions. Do not continue driving under any circumstances. Switch off the vehicle. Add 1.1 US gt (1 I) of engine oil ( $\rightarrow$ page 341). Check the engine oil level. Notes on engine oil ( $\rightarrow$ page 416).

# Possible causes/consequences and ▶ Solutions Display messages \* The oil pressure is too low. **NOTE** Engine damage caused by driving with insufficient oil pressure **Engine Oil Pressure Stop** Avoid driving with insufficient oil pressure. Switch Off Engine Stop the vehicle immediately in accordance with the traffic conditions. Do not continue driving under any circumstances Switch off the vehicle. Consult a qualified specialist workshop. \* The electrical connection to the oil level sensor has been interrupted or the oil level sensor is faulty. Consult a qualified specialist workshop. Engine Oil Level Cannot Be Measured

# Warning and indicator lamps

#### Overview of indicator and warning lamps

Some systems will perform a self-test when the vehicle is switched on. Some indicator and warning lamps may briefly light up or flash. This behav-

ior is non-critical. These indicator and warning lamps indicate a malfunction only if they light up or flash after the vehicle has been started or during a journey.

#### Instrument display



#### Indicator and warning lamps

Occupant safety

Restraint system ( $\rightarrow$  page 487)

 $\nearrow$  Seat belt ( $\rightarrow$  page 487)

Vehicle

 $\Theta$ ! Power steering ( $\rightarrow$  page 488)

Engine

 $\blacksquare$  Coolant temperature ( $\rightarrow$  page 489)

Engine diagnosis ( $\rightarrow$  page 489)

Electrical malfunction (→ page 489)

Reserve fuel with fuel filler flap location indicator (→ page 489)

Braking

Electric parking brake (yellow)(→ page 493)

USA: electric parking brake (red) (→ page 493)

Canada: electric parking brake (red)(→ page 493)

RBS USA: Recuperative Brake System (→ page 493)

(D) Canada: brakes (yellow)(→ page 493)

BRAKE USA: brakes (red) (→ page 493)

 $\bigcirc$  Canada: brakes (red) ( $\rightarrow$  page 493)

Driving and driving safety systems

 $\bigcirc$  ABS ( $\rightarrow$  page 496)

 $\blacksquare$  ESP<sup>®</sup> ( $\rightarrow$  page 496)

ESP<sup>®</sup> OFF ( $\rightarrow$  page 496)

 $\triangle$  Distance warning ( $\rightarrow$  page 496)

★! Active Brake Assist (→ page 496)

off | Active Brake Assist (→ page 496)

AIRMATIC / E-ACTIVE BODY CONTROL
 (→ page 496)

Tire pressure monitoring system

∴ Tire pressure monitoring system(→ page 500)

Exterior lighting

Standing lights (→ page 151)

Low beam ( $\rightarrow$  page 151)

High beam (→ page 152)

Turn signal lights (→ page 152)

0 Rear fog light (→ page 151)

Symbols on the media display

Drive Away Assist ( $\rightarrow$  page 275)

 $\triangle$  Cross Traffic Alert ( $\rightarrow$  page 276)

#### Occupant safety

#### Warning/indicator lamp



Restraint system warning lamp

#### Possible causes/consequences and ▶ Solutions

\* The restraint system red warning lamp is lit while the vehicle is on. The restraint system is malfunctioning ( $\rightarrow$  page 42).

#### WARNING Risk of injury due to malfunctions in the restraint system

Components in the restraint system may be activated unintentionally or not deploy as planned in an accident.

- Have the restraint system checked and repaired immediately at a qualified specialist workshop.
- Drive on carefully.
- Note the messages on the instrument display.
- Consult a qualified specialist workshop immediately.
- \* The red seat belt warning lamp flashes and an intermittent warning tone sounds. The driver or front passenger has not fastened his/her seat belt while the vehicle is in motion.
- $\triangleright$  Fasten your seat belt ( $\rightarrow$  page 41).

There are objects on the front passenger seat.

Remove the objects from the front passenger seat.



Seat belt warning lamp flashes

#### Warning/indicator lamp



Seat belt warning lamp lights up

#### Possible causes/consequences and ▶ Solutions

\* The red seat belt warning lamp lights up for six seconds once the vehicle has started.

In addition, an intermittent warning tone may sound.

The red seat belt warning lamp reminds the driver and front passenger to fasten their seat belts.

► Fasten your seat belt (→ page 41).

If you have placed objects on the front passenger seat, the red seat belt warning lamp may remain lit.

#### Vehicle

#### Warning/indicator lamp



Power steering warning lamp (red)

#### Possible causes/consequences and ▶ Solutions

\* The red power steering warning lamp is lit while the vehicle is running. The power assistance or the steering itself is malfunctioning.

▲ WARNING Risk of accident if steering capability is impaired

If the steering does not function as intended, the vehicle's operating safety is jeopardized.

- Pull over and stop the vehicle safely as soon as possible, paying attention to road and traffic conditions. Do not continue driving under any circumstances.
- Consult a qualified specialist workshop.
- Note the messages on the instrument display.

#### Engine

#### Warning/indicator lamp



Coolant warning lamp (red)

#### Possible causes/consequences and ▶ Solutions

- \* The red coolant warning lamp is lit while the engine is running.
- Possible causes are:
- The temperature sensor is malfunctioning
- The coolant level is too low
- The air supply to the radiator is obstructed
- · The radiator fan is faulty
- The engine coolant pump is faulty

If there is an additional warning tone, the coolant temperature has exceeded the maximum permissible temperature.

# WARNING Risk of burns when opening the hood

If you open the hood in the event of an overheated engine or fire in the engine compartment, the following situations may occur:

- · You may come into contact with hot gases.
- You may come into contact with other escaping hot operating fluids.
- Before opening the hood, allow the engine to cool down.
- In the event of a fire in the engine compartment, keep the hood closed and call the fire service.
- Stop immediately in accordance with the traffic conditions and switch off the vehicle. Do not continue driving.

Warning/indicator lamp	Possible causes/consequences and ➤ Solutions					
	Note the messages on the instrument display.					
	If the coolant temperature display is at the lower end of the temperature scale:					
	Consult a qualified specialist workshop.					
	If the coolant temperature display is at the upper end of the temperature scale:					
	Exit the vehicle and keep a safe distance from it until the engine has cooled down.					
	► Check the coolant level ( $\rightarrow$ page 342).					
	Make sure that the air supply to the radiator is not obstructed.					
	Avoiding high loads on the engine, drive to the nearest qualified specialist workshop. In doing so, ensure that the coolant temperature display remains below the red area.					
ſŒ.	* The yellow coolant warning lamp is lit while the engine is running.					
Coolant warning lamp (yellow)	Possible causes are:					
	The temperature sensor is malfunctioning					
	The charge air, transmission oil or battery cooling is faulty					
	The radiator shutters are blocked or defective					
	Avoiding high loads on the engine, drive to the nearest qualified specialist workshop.					

Warning/indicator lamp	Possible causes/consequences and ▶ Solutions
HP	* The yellow Check Engine warning lamp is lit while the engine is running.  A malfunction has occurred in the engine, the exhaust system or the fuel system.
المــــــــــــــــــــــــــــــــــــ	The emissions limit value may have been exceeded and the engine may be running in emergency operation mode.
Check Engine warning lamp	In some states, legal requirements stipulate that you must immediately consult a qualified specialist workshop as soon as the yellow Check Engine warning lamp lights up.
	► Have the vehicle checked as soon as possible at a qualified specialist workshop.
<del>-</del> +	* The red electrical malfunction warning lamp is lit. There is a malfunction in the electrics.
Electrical malfunction warning lamp	Note the messages on the instrument display.
	* The yellow fuel reserve warning lamp lights up while you are driving.  There has been pressure loss in the fuel system. The fuel filler cap is not closed correctly or the fuel system is leaking.
	Close the fuel filler cap.
Fuel reserve warning lamp flashes	If the fuel filler cap has already been closed correctly:
	Consult a qualified specialist workshop.

# Warning/indicator lamp



Fuel reserve warning lamp lights up

### Possible causes/consequences and ▶ Solutions

- \* The yellow fuel reserve warning lamp lights up while the engine is running. The fuel supply has dropped into the reserve range.
  - Refuel.

#### **Brakes**

#### Warning/indicator lamp



Electric parking brake indicator lamp (red) (USA only)



Electric parking brake indicator lamp (red) (Canada only)



Electric parking brake indicator lamp (yellow)

#### Possible causes/consequences and ▶ Solutions

- \* The red electric parking brake indicator lamp flashes or is lit.
- The yellow electric parking brake indicator lamp is also lit in the event of a malfunction.
- Note the messages on the instrument display.

#### Warning/indicator lamp

RBS

RBS warning lamp (USA only)



Brakes warning lamp (yellow) (Canada only)

#### Possible causes/consequences and ▶ Solutions

\*The yellow  $\begin{tabular}{l}$  warning lamp (USA only) or the yellow  $\begin{tabular}{l}$  brake warning lamp (Canada only) is lit while the vehicle is running.

WARNING Risk of an accident due to a brake system malfunction

If the brake system is malfunctioning, braking characteristics may be impaired.

- Drive on carefully.
- ► Have the brake system checked immediately at a qualified specialist workshop.
- Adjust your speed and drive on carefully, leaving a suitable distance to the vehicle in front.
- If the instrument display shows a display message, observe it.
- Consult a qualified specialist workshop.

# Warning/indicator lamp



Brakes warning lamp (USA only)



Brakes warning lamp (Canada only)

#### Possible causes / consequences and ▶ Solutions

- \* The red brake warning lamp is lit while the vehicle is running.
- Possible causes are:
- The brake force boosting is malfunctioning and the braking characteristics may be affected.
- There is insufficient brake fluid in the brake fluid reservoir.
- Note the messages on the instrument display.
- **WARNING** Risk of accident and injury if brake force boosting is malfunctioning

If brake force boosting is malfunctioning, increased brake pedal force may be necessary for braking. The braking characteristics may be impaired. The braking distance can increase in emergency braking situations.

- Stop in a safe location immediately. Do not continue driving.
- Consult a qualified specialist workshop.
- WARNING Risk of an accident due to low brake fluid level

If the brake fluid level is too low, the braking effect and the braking characteristics may be impaired.

- > Pull over and stop the vehicle safely as soon as possible, paying attention to road and traffic conditions. Do not continue driving under any circumstances.
- Consult a qualified specialist workshop.
- Do not add brake fluid.

#### Driving and driving safety systems

#### Warning/indicator lamp




ABS warning lamp

#### Possible causes/consequences and ▶ Solutions

\* The yellow ABS warning lamp is lit while the vehicle is running. ABS is malfunctioning.

If an additional warning tone sounds,  $\ensuremath{\mathsf{EBD}}$  is malfunctioning.

Note the messages on the instrument display.



Other driving systems and driving safety systems may also be malfunctioning.

The wheels may lock during braking.

The steerability and braking characteristics are heavily impaired and the braking distance may increase. In addition, other driving safety systems are switched off.

- Drive on carefully.
- Have the brake system checked immediately at a qualified specialist workshop.



ESP® warning lamp flashes

- \* The yellow ESP® warning lamp flashes while the vehicle is in motion. One or more wheels have reached their grip limit (→ page 214).
- Adapt your driving style to suit the road and weather conditions.

# Warning/indicator lamp ESP® warning lamp lights up

#### Possible causes/consequences and ▶ Solutions

\* The yellow ESP® warning lamp is lit while the vehicle is running. ESP® is malfunctioning.

Other driving systems and driving safety systems (e.g. BAS) may also be malfunctioning.

Note the messages on the instrument display.

# WARNING Risk of skidding if ESP® is malfunctioning

If ESP® is malfunctioning, ESP® cannot carry out vehicle stabilization. In addition, other driving safety systems are switched off.

- Drive on carefully.
- ► Have ESP<sup>®</sup> checked at a qualified specialist workshop.



ESP® OFF warning lamp

\* The yellow ESP® OFF warning lamp is lit while the vehicle is running. ESP® is deactivated.


Other driving systems and driving safety systems may also be inoperative.

## WARNING Risk of skidding when driving with ESP® deactivated

ESP® does not act to stabilize the vehicle. The availability of further driving safety systems is also limited.

- Drive on carefully.
- ► Deactivate ESP® only for as long as the situation requires.

Warning/indicator lamp	Possible causes/consequences and ▶ Solutions
	If ESP® cannot be activated, ESP® is malfunctioning.  Have ESP® checked immediately at a qualified specialist workshop.
	ightharpoonup Observe the notes on deactivating ESP <sup>®</sup> ( $ ightharpoonup$ page 214).
Distance warning lamp	<ul> <li>* The red distance warning lamp lights up while the vehicle is in motion. The distance to the vehicle in front is too small for the speed selected.</li> <li>If there is an additional warning tone, you are approaching an obstacle at too high a speed.</li> <li>▶ Be prepared to brake immediately.</li> <li>▶ Increase the distance.</li> <li>Function of Active Brake Assist (→ page 235).</li> </ul>
Active Brake Assist warning lamp	<ul> <li>* The Active Brake Assist warning lamp is on. Due to dirty sensors or a malfunction, the system is not available or the range of functions is restricted.</li> <li>▶ Note the messages on the instrument display.</li> </ul>



#### Tire pressure monitor

#### Warning/indicator lamp



Tire pressure monitoring system warning lamp flashes

(!)

Tire pressure monitoring system warning lamp lights up

#### Possible causes/consequences and ▶ Solutions

\*The yellow tire pressure monitor warning lamp (pressure loss/malfunction) flashes for approximately one minute and then remains lit.

The tire pressure monitoring system is malfunctioning.

WARNING There is a risk of an accident if the tire pressure monitoring system is malfunctioning

The tire pressure monitoring system cannot issue a warning if there is pressure loss in one or more of the tires.

Tires with insufficient tire pressure may impair the driving characteristics as well as steering and braking.

- ▶ Have the tire pressure monitoring system checked at a qualified specialist workshop.
- \* The yellow tire pressure monitoring system warning lamp (pressure loss/malfunction) is lit.

  The tire pressure monitoring system has detected tire pressure loss in at least one of the tires.

#### **WARNING** Risk of an accident due to insufficient tire pressure

- · The tires can burst.
- The tires can wear excessively and/or unevenly.
- The driving characteristics as well as the steering and braking may be greatly impaired.

You could then lose control of the vehicle.

- Observe the recommended tire pressures.
- Adjust the tire pressure if necessary.

Warning/indicator lamp	Possible causes/consequences and ▶ Solutions
	> Stop the vehicle in accordance with the traffic conditions.
	Check the tire pressure and the tires.

# 502 Index

1, 2, 3 (SmartKey) battery	Active Brake Assist Function	<ul><li>242</li><li>243</li><li>235</li></ul>	Towing a trailer	154 274 271
360° Camera Function	Active Distance Assist DISTRONIC  Activating/deactivating  Active Emergency Stop Assist  Active Lane Change Assist		Active Service System PLUS	336
A/C function activating/deactivating (MBUX)	Calling up a speed	224 222 224 227	Activating/deactivating	233 234
ABS       213         Acceleration       Kickdown       198         Optimized acceleration       179	Active Emergency Stop Assist	233	Active Stop-and-Go Assist Function  Active Traffic Jam Assist Activating/deactivating	229
Accident, emergency call	Function  Active Lane Keeping Assist  Activating/deactivating	<ul><li>234</li><li>246</li><li>244</li></ul>	Adaptive cruise control	155

Leg rest	106	Air suspension	247	Apps, Mercedes me Mercedes me calls	317
Additives	447	Air vents	1.70	Mercedes me connect	
Engine oil		Adjusting	172		
Fuel		Glove box		Assistance system	ZIZ
After-sales service	336	Air/water duct	344	ASSYST PLUS	
Air bag		Airflow		Battery disconnection periods	
Cushion bag	. 54	Setting	167	Service interval display	
Front air bag	. 54	AIRMATIC		Service requirements	336
Inflating	. 49	Lowering/raising the rear end of the		ATA	
Overview		vehicle	251	Deactivating the alarm	
PASSENGER AIR BAG indicator lamp		Setting entering/exiting level	251	Function	
Warning lamp	. 42	Setting the vehicle level	248	Interior protection	
Air conditioning menu		Vehicle levels	247	Interior protection function	
Air distribution	169	Alarm system	. 96	Tow-away alarm function	
Calling up	168	All-wheel drive		Tow-away protection	. 97
Climate control				ATTENTION ASSIST	
lonization	171	Alternative route	308	Function	
Rear passenger compartment climate	4.60	Ambient lighting	157	Setting	220
control	169	Animals	. 50	Attention assistant	218
Air distribution		Anti-lock braking system		Authorized Mercedes-Benz Service Center	. 29
Adjusting				Authorized workshop	
Setting	167	Anti-theft alarm system	. 96		
Air inlet	344	Anti-theft protection		Automatic car wash	
Air pressure	376	Immobilizer	. 95	Automatic car wash mode	346

Automatic climate control	152	Steering wheel paddle shifters	194 194 194	Battery (48 V) Notes  Battery (starter battery) charging, Remote Online  Belt	
Automatic engine start/stop	186	Axle load		Fastening	41
Automatic front passenger air bag shutoff Function Information (child restraint system on		Towing a trailer	427	Notes on wearing correctly Releasing To adjust the height	41 54
the front passenger seat) PASSENGER AIR BAG indicator lamp	43	Back seat		Bicycle rack Load capacity	426
Automatic measures after an accident	48	Ball neck	107	Blind Spot Assist	
Automatic mirror folding function	165	Installing	280	Activating/deactivating	
Automatic seat adjustment	114	BAS		Function	242
520. 022201.0101	194	Basic information		Bluetooth® Connecting a mobile phone	316
DYNAMIC SELECT switch Engages neutral	190 190 195	ChargingNotes	365 360	Brake Assist Active Brake Assist Brake Assist System	
000	196 195	Notes (starting assistance and charging)	363	Brake Assist System	213
0 0 0	193	Replacing		Brake disks	
Manual gear shifting		Starting assistance	365	Brake fluid	417
Selecting park position	196			Brake force distribution	217

Active Brake AssistBAS (Brake Assist System) Driving tips	213 235	Breakdown (Roadside Assistance) Buttons	369 25 286	Car wash Automatic car wash Power washer Washing by hand  Car-to-X-Communication Display on map	34 34
EBD (Electronic Brakeforce Distribution)  Electric parking brake  Handbrake  HOLD function  Limited braking effect (salt-treated roads)  New/replaced brake pads/brake discs  Notes on breaking in a new vehicle  Parking brake  Post-collision brake  Braking assistance  Brake Assist System	207 207 217 180 178 178 207 . 48	Calling the customer center for Mercedes-Benz	317 316 317 263 349 211	Care Air/water duct Automatic car wash Camera Car parts Decorative foil Display Exterior lighting Head-up display Headliner Paint Plastic trim Power washer	34 34 34 35 34 35 34 35
Breakdown Changing a wheel Flat tire Overview of aids Tow-starting Towing methods	397 354 18 371	Rear view camera	261 255 266	Real wood/trim elements	34 35 35 34

Caring for plastic trim  Caring for rims  Central locking system Button SmartKey  Change of address  Change of ownership  Changing a wheel Preparation Raising the vehicle  Charging 12 V battery	349 136 135 136 140 138 350 349 76 73 25 25 397 399 365	Checking the coolant level  Child safety lock Rear door Side windows (rear passenger compartment)  Child seat Adjusting the vehicle seat Basic instructions Front passenger seat Installing ISOFIX Rearward-facing Risks/dangers Securing on the rear seat with the seat belt Securing to the front passenger seat with the seat belt The most important information in brief Top Tether  Children Avoiding dangers in the vehicle Basic instructions Special seat belt retractor  Chock	. 69 71 62 56 59 . 64 . 61 . 57 69 . 55 . 67 . 57 . 63 . 397	Cleaning  Air/water duct	344 349 348 347 346 350 350 350 350 168 168 168
	145	Chock			170 172

Air vents (rear passenger compart-		Setting the air distribution	167	Windshield wipers	158
,	173	Setting the airflow	167	Commuter route	308
	169	Setting the vehicle interior tempera-	167	Components relevant to radio regulation	
Automatically controlling (rear operating unit)	169	tureSwitching air-recirculation mode	107	Declaration of conformity	. 28
<del>_</del>	168	on/off	170	Convenience closing	89
Control panel for 3-zone automatic		Switching the rear window heater		Convenience opening	
	167	on/off	167	coolant	
Control panel for dual-zone automatic climate control	167	Synchronization function		Notes	418
Defrosting the windshield 1		Ventilating with convenience opening		Coolant (engine)	
	170	Coat hook	139	Capacity	419
Filling capacity for refrigerant and	1	COC papers, CERTIFICATE OF CONFORM- ITY	409	Copyright	
PAG oil4	421		409	License	. 37
8	171 <b>(</b> 174	<b>Cockpit</b> Dashboard	6	Copyrights	
Inserting/removing the flacon (fra-		Coffee cup symbol		Trademarks	. 37
	171		210	Correct use	. 30
Ionization 1	1/1	Collapsible spare wheel Inflating	407	Cover	. 90
	167	Notes		Cross traffic (warning)	276
Rear operating unit Rear passenger compartment operat-	16	Removing		Cross Traffic Alert, Cross traffic warning	276
ing unit 1	168	Collision detection (parked vehicle)		Crosswind Assist	215
Refrigerant4	419	Setting	209	Cruise control	
Residual heat		Combination switch		Activating/deactivating	221
Setting (MBUX multimedia system) 1	168	Lights	152		

Calling up a speed.       221         Function.       220         Requirements:       221         Setting a speed.       221         Storing a speed.       221         Cushion air bag (reclining rear seat)       49         Cushion bag, Reclining rear passenger       54         Cushionbag       54         Information.       54         Customer Assistance Center (CAC).       31         Customer Relations Department.       31         D       Damage         Limited protection.       50	DashcamSelecting a USB device	Deployed components Limited protection
Damping system ADS PLUS         247           AIRMATIC	Declaration of conformity Components relevant to radio regulation 28  Decorative foil	Manual gearshifting

Display message Calling up in the on-board computer Notes		Cannot Fold Row, Left Adjust Fro
Display messages		Row, Right Adjust F
<b>三</b> 致 mph	466	
(S) mph	460	BRAKE Check Brake
2nd Seat Row, Center Not		Check Coola
Locked	443	ator's Manual
िन। 12 V Battery See Operator's		Check Engine
Manual	476	quart)
48 V Battery See Operator's	., 0	Check Left L
Manual	478	Check Tires
		Check Washe
Active Headlamps Inoperative	435	Compressor
ATTENTION ASSIST Inoperative	459	Coolant Too I
ATTENTION ASSIST: Take a		
Break!	460	Turn Engine Off
Automatic Headlamp Mode		Currently Un
Inoperative	435	Operator's Manual.
Battery Overheated Stop,		<b>?</b> Currently Un
Everyone Get Out Outdoors if Possible	178	Operator's Manual
Everyone det out outdoors il Possible	4/0	Decrease Sp

7	Cannot Fold Forward 2nd Seat	
Row, I	Left Adjust Front Seat	444
7	Cannot Fold Forward 2nd Seat	
Row, I	Right Adjust Front Seat	444
BRAKE	Check Brake Fluid Level	455
	Check Coolant Level See Oper-	
ator's	Manual	445
متح	Check Engine Oil Level (Add 1	
quart)		483
-Ö-	Check Left Low Beam (example)	434
8	Check Tires	481
<b>(4)</b>	Check Washer Fluid	444
<b>6</b> ♣0	Compressor Is Cooling	463
	Coolant Too Hot Stop Vehicle	
Turn E	ngine Off	446
(ABS)	Currently Unavailable See	
Opera	itor's Manual	456
2 2	Currently Unavailable See	
Opera	itor's Manual	457
8	Decrease Speed	483

(P)	Don't Forget Your Key	434
<b>6</b> ♣0	Drive More Slowly	463
احته	Engine Oil Level Cannot Be	
Measi	ured	485
احته	Engine Oil Level Low Stop Vehi-	
cle Tu	rn Engine Off	484
احته	Engine Oil Pressure Stop	
Switcl	n Off Engine	485
الحية	Engine Oil Reduce Oil Level	484
<b>%</b>	Front Left Malfunction Service	
Requi	red (example)	429
	red (example) Fuel Level Low	429 447
	Fuel Level Low	447
	Fuel Level Low	447
Manu	Fuel Level Low	447 447
Manu	Fuel Level Low	447 447
Manus	Fuel Level Low	447 447 457
Manua Manua Manua EBD	Fuel Level Low	447 447 457

Inoperative	465
Intell. Light System Inoperative	436
Key Being Initialized Please Wait	433
Key Not Detected (red display	
message)	433
Key Not Detected (white dis-	
play message)	432
Left Side Curtain Airbag Mal-	
function Service Required (example)	429
Lowering	462
Malfunction Drive at Max. 50	
mph	, 464
Malfunction See Operator's	
Manual	435
§ Malfunction Stop	465
Max. Speed 25 mph	465
Not in the Current Drive Pro-	
gram	466
Obtain a New Key	432
PS Off	467

HOLD	Off	459
PARK	Parking Brake See Operator's	
/lanu	al	451
8	Please Correct Tire Pressure	481
PARK	Please Release Parking Brake	454
	Please Wait Charging 48 V Bat-	
ery		479
	Replace Key Battery	432
	Running Board Not Extended	438
<del>- +</del>	See Operator's Manual	477
<b>%</b>	SRS Malfunction Service	
Requi	red	429
<b>⊕</b> !	Steering Malfunction Increased	
hysio	cal Effort See Operator's Manual	439
<b>⊕</b> !	Steering Malfunction Stop	
mme	diately See Operator's Manual	440
<del>- +</del>	Stop Vehicle Leave Engine Run-	
ing		478
<del>- +</del>	Stop Vehicle See Operator's	
/lanu	al	477

<b>=</b> (3)	Suspended	466
Ŏ.	Switch Off Lights	436
-Ö:	Switch On Headlamps	435
<b>≅</b> †	Temporarily Unavailable Cam-	
era Vi	ew Restricted	474
<b>1</b>	Temporarily Unavailable Sen-	
sors a	re Dirty	473
8	Tires Overheated	482
PARK	Turn On the Ignition to Release	
the Pa	arking Brake	455
$\triangle$	Vehicle Ready to Drive Switch	
the Ig	nition Off Before Exiting	438
<b>⊙</b>	Vehicle Rising Please Wait	462
<b>⊙</b> ••••	Vehicle Rising	462
7	Warning Tire Malfunction	482
7	Wheel Sensor(s) Missing	480
Active	Blind Spot Assist Currently	
Unava	ilable See Operator's Manual	471
Active	Blind Spot Assist Inoperative	472

Active Blind Spot Asst. Not Available		Active Stop & Go Assist Currently		Cannot Start Engine See Operator's	
When Towing a Trailer See Operator's		Unavailable See Operator's Manual	470	Manual 445,	479
Manual	472	Active Stop & Go Assist Inoperative		Check Brake Pads See Operator's	
Active Brake Assist Functions Cur-		See Operator's Manual	470	Manual	456
rently Limited See Operator's Manual	468	Adaptive Highbeam Assist Currently		Cruise Control Inoperative	460
Active Brake Assist Functions Limited		Unavailable See Operator's Manual	436	Cruise Control Off	460
See Operator's Manual	468	Adaptive Highbeam Assist Inoperative	436	Device Detected at Diagnostics Con-	
Active Distance Assist Currently		Apply Brake to Shift from 'P'	447	nection See Operator's Manual	476
Unavailable See Operator's Manual	467	Apply Brake to Shift to 'R'	448	Driver's Door Open & Transmission	
Active Distance Assist Inoperative	467	Apply Brake to Shift to D or R	448	Not in P Risk of Vehicle Rolling Away	448
Active Distance Assist Now Available	468	Auxiliary Battery Malfunction (red dis-		Engine Can Now Be Started	479
Active Lane Keeping Assist Currently		play message)	450	Front Passenger Airbag Disabled See	
Unavailable See Operator's Manual	472	Auxiliary Battery Malfunction (white		Operator's Manual	430
Active Lane Keeping Assist Inoperative	473	display message)	449	Front Passenger Airbag Enabled See	
Active Steering Assist Currently		Beginning Emergency Stop		Operator's Manual	430
Unavailable See Operator's Manual	469	Blind Spot Assist Currently Unavaila-		Gearbox Protection Limit 18 mph Dis-	
Active Steering Assist Inoperative	469	ble See Operator's Manual	471	able LOW RANGE	443
Active Steering Asst. Currently		Blind Spot Assist Inoperative	471	Hazard Warning Flashers Malfunction-	
Unavailable Due to Multiple Emer-		Blind Spot Assist Not Available When		ing	437
gency Stops	469	Towing a Trailer See Operator's Manual	471		

448
445
460
460
449
437
437
437
444
308
222
235
222
4: 4: 4: 4: 4: 4: 2:

Child safety lock (rear door)	. 78 . 76 . 78 . 76 . 16 . 14 . 387 . 229 . 180 . 142 . 275 . 196 . 192	Seat heating  Driving off-road  Driving safety system  ABS (Anti-lock Braking System) Active Brake Assist ATTENTION ASSIST BAS (Brake Assist System) Blind Spot Assist/Active Blind Spot Assist Cameras Cruise control EBD (Electronic Brakeforce Distribution) ESP® (Electronic Stability Program) Hill Start Assist HOLD function Off-road ABS Overview Radar and ultrasonic sensors STEER CONTROL Traffic Sign Assist Trailer Maneuvering Assist Your responsibility	183 213 235 218 213 242 211 220 217 214 218 217 213 212 211 217 240 277 211	Driving tips  Drinking and driving	180 178 183 179 218 230 229 229 229 193 193 193 193 193
Adjusting electrically		Your responsibility  Driving system		Function	190

E	Electric parking brake	007	Emergency call system	0.05
E-ACTIVE BODY CONTROL  Electrohydraulic suspension	56 Releasing automatically	209 209 208 371	Mercedes me connect	78 86
Suspension	52 Electrohydraulic suspension	252	Emergency release Tailgate	
E10	20 First-aid kit (soft sided)	354 18 353	Emergency spare wheel Inflating Emergency stop assistant Emergency Tensioning Devices Inflating	405 233
ECO Assist 48 V on-board electrical system	88 Active Brake Assist	213 209	Engine Emergency operation mode Emergency start Engine number Jump-starting	177 371 411
ECO start/stop function         1           Automatic engine start	86 Manual 86	325 326	Parking (start/stop button)  Engine data  Displaying  DYNAMIC SELECT	203

Engine number Engine oil, Oil Additives Capacity	416	Exterior lighting Care  Exterior mirrors Parking position		Foil covering On camera/sensors Radar and ultrasonic sensors Folding table, Table	211
Checking the oil level using the on- board computer	417 417	Factory settings MBUX reset function	304	Fragrance system Adjusting Inserting/removing the flacon Perfume vial	171
Refilling  Environmentally friendly driving  ESC, Electronic Stability Control  ESP®	22	First aid First-aid kit (soft sided)  First-aid kit (soft sided)		Free driving mode Starting Free software	
Activating/deactivating	216 215 214	Fitting accessories Limited protection  Flacon Flat tire	171	Frequencies Two-way radio  Front air bag Inflating	49
Trailer stabilization  Event Data Recorder  Exit warning	36	Changing a wheel	355 354	Front headlamps  Front passenger air bag  Disabling/enabling  Front passenger air bag shutoff,	
Exiting a parking space Active Parking Assist Drive Away Assist PARKTRONIC	275	Flat towing Pulling/towing  Floor mats  Fog lamp		PASSENGER AIR BAG OFF Information (child restraint system on the front passenger seat)	60

Front passenger seat  Adjusting electrically	02	Cockpit Engine compartment Front passenger footwell Fuse assignment diagram Notes	372 373 371	H Handbrake	
Fuel         Additives	16 15	G Garage door opener	007	HANDS-FREE ACCESS	375 84
Gasoline	15 01	Clearing the memory Opening/closing a door Problem	207	Handset Stowage compartment	
Reserve	15 16	Garage door openers Programming buttons Synchronizing the rolling code		Hazard warnings Car-to-X-Communication	310
Fuel reserve	16	GasolineGearshift		Adjusting (rear passenger compart- ment)1	
Function in the event of an accident	49	DIRECT SELECT lever	196	Adjusting manually (front)	
Function seat (rear passenger compartment)	16	Glide mode	198	EASY ADJUST luxury head restraint (front)	111
<u> </u>					

Removing/installing (rear passenger compartment)	112	HIGH RANGE Shifting	200	Individual drive program Configuring	192
<b>Head-up display</b> , Display in the windshield Adjusting brightness (on-board com-		Hill descent control		Inside rearview mirrorInstalling	164
puter) Adjusting display elements (on-board computer)		HOLD function Function	217	Snow chains	
CareFunction	. 350 . 288	Switching on/off  Home screen		Instrument cluster Function/notes	285
Memory function Setting the position (on-board computer) Switching on/off	. 289	Media display  Hood  Opening/closing	338	Instrument display Function/notes Head-up display Head-up display menu	288
Headlamp flashing	152			Instrument cluster	10
Heating Activating/deactivating		Identification plate Engine Refrigerant		Overview of displays	288
Center console Panel heating	. 168 . 118	VehicleImmobilizer	411	Intelligent Light System Active headlamps Adaptive Highbeam Assist	
Seat  Help call  Mercedes-Benz emergency call system.		Incorrect behavior by vehicle occupants Limited protection	. 50	Interior lighting Adjusting Ambient lighting	
High beam		PASSENGER AIR BAG	. 43	MBUX reading light Switch-off delay time	297

Interior protection	Kickdown 19	8 <b>Light switch</b>
Internet Mercedes me connect	Knee air bag	4 <b>Lighting</b> Interior lighting
Setting up a Wi-Fi hotspot	L	Lights
Web browser	Lane change assist 23	
lonization	Lane Keeping Assist 24	4 lighting 156
ISOFIX child seat anchor	Lane recognition	Active neadlamps 154
Installing 64	Active Lane Change Assist	Adaptive Highbeam Assist
	Lane recognition (automatic)	4 Automatic driving lights 152 Combination switch 152
J	Active Lane Keeping Assist	
Jack	. 3	150
Storage location	Lane scan	Interior lighting
Jump-start connection	Language	Reading Jamn 156
	Notes	O Reading light 207
K	Setting	Rear fog light
Key	Leg rest	Responsibility for lighting systems 151
Problem	Attaching/removing the additional	Switch-off delay time
Replacement key 75	cushion10	
KEYLESS-GO	Level control	lamps
Deactivating	AIRMATIC	,
Locking/unlocking the vehicle	E-ACTIVE BODY CONTROL 25	Zimitou Warranty
Problem 77	License plate (front)	7 Live Traffic Information 310
Unlocking setting	License plate assembly (front)	7

Load capacity Bicycle rack Load index		Loud sound  PRE-SAFE® Sound  LOW RANGE	46	Maintenance Management Notes Transferred data	33
Tires  Load protection net	389	Shifting Low-beam headlamps	200	Malfunction Restraint system	4
Attaching	137	Activating/deactivating		Malfunction message Instrument display	
	389		<ul><li>251</li><li>251</li></ul>	Maneuvering assistance	
Loading, Stowage compartments Bag hook	139		413	Activating/deactivating  Maneuvering assistant	
Cargo tie-down rings	139	Luggage rack	126	Drive Away Assist	27
Definitions Roof luggage rack		Lumbar support	104	Activating/deactivating  Map	19
Loading guidelines		M		Displaying online map contents	
Loading information table		MAGIC VISION CONTROL Windshield wiper	161	Displaying weather information	30
Locking/unlocking Automatic locking (MMS)	. 78	Maintaining safe distance Active Distance Assist DISTRONIC	224	Selecting the map orientation	30
Doors (from the inside) Emergency key	76		350 350	Switching freeway information on/off  Map functions	
KEYLESS-GO	. 76	Maintaining the steering wheel  Maintenance	330	Massage program	11
		Vehicle	25	Massage programs	11

Maximum full-stop braking	388 384 383	System settings Touchscreen  MBUX reading light  MBUX search light  Mechanical key Inserting/removing	293 297 297	Overview  Mercedes me App Activating on-demand features  Mercedes me Apps  Mercedes me calls Arranging a service appointment	24 322
MBUX Interior Assistant Overview	297 297 230 210 192	Media Overview of functions/symbols  Media display Operating  Media mode Connecting Bluetooth® audio equipment  Medical aids  Memory function Head-up display	293 329 . 31	Calling the Mercedes-Benz customer center after automatic accident/breakdown detection	317 317 319 321 320
Media	328 322 304 291 291 228	Outside mirrors	122 122 ent) 125 123	Mercedes-AMG vehicles, Notes  Mercedes-Benz emergency call system Automatic emergency call Data transfer Information	175 325 326 324

Mercedes-Benz GenuineParts 22	N	Information on the correct seat position 40
Message memory 428	Navigation	Pets in the vehicle
Mirrors	Activating	PRE-SAFE®
Mirror folding function 165	Destination entry	<b>Off-road ABS</b>
Outside mirrors	Displaying/hiding the menu	Off-road Assist
Rearview mirror 164	Live Traffic Information 310	Setting
Mobile phone	Map	Off-road driving
Notes on wireless charging	Notes	Offroad Score
Wireless charging (rear passenger		Displaying 193
compartment) 16, 148	Neutral	On-board computer, Operating system
Model type 411	Non-operational time	Displaying the service due date
Modification	Activating/deactivating standby mode 210	Instrument display
Limited protection 50	Notes on breaking in a new vehicle 178	Menu overview
MOExtended tires, Run-flat tires		Operating
Multifunction camera	0	On-board diagnostics interface
ROAD SURFACE SCAN	Objects in the vehicle interior	On-board electronics
Multifunction steering wheel	Limited protection 50	Two-way radios
Overview of buttons	Occupant safety	On-demand feature
Multimedia system	Air bag	Online services
Extending/retracting the running	Child seat	Open Source Software
boards 80	Information on the child restraint sys-	Opening angle
	tem	Limiting (tailgate)85

Opening the tailgate using your foot HANDS-FREE ACCESS	Setting Warning lamp		FunctionSide impact protection	
Opening/closing a door 207	Overhead control panel	. 12	Parking assistance systems	074
Opening/closing a garage door 207	Overview of air bags	54	Active Parking Assist	
Operating fluids Additives	P		Drive Away AssistPARKTRONIC	266
Brake fluid	Paddle shifters		Parking brake	207
coolant418	Steering wheel paddle shifters	196	Parking for an extended period	210
Engine oil	Paint code	411	Parking lamps	151
Fuel (gasoline)	Panel heating	118	Parking lights	151
Refrigerant (air conditioning system) 419 Windshield washer fluid	Panic alarm, Alarm Activating/deactivating	73	Parking option Selecting	310
Operating safety 48 V on-board electrical system	Park position DIRECT SELECT lever	194	Parking position Exterior mirrors	164
Operator's manual	Parking		Storing the position of the front-	
Operator's Manual digital	Active Parking Assist PARKTRONIC		passenger outside mirror using reverse gear	165
Outside mirrors  Automatic anti-glare mode	Parking Assist Active Parking Assist PARKTRONIC		Parking service Selecting parking options  Parking space	
Assist	Parking Assist PARKTRONIC Activating/deactivatingAdjusting warning tones		Finding PARKTRONIC	

PASSENGER AIR BAG Status display, front passenger air bag 43	Inflating	R Radar and ultrasonic sensors
Payload384Calculation example	Backing up measures	Radio Overview of functions/symbols
Permitted towing methods Overview	Profile, User profiles	Radio regulations Regulatory radio identification
Personalization	Creating a new profile	Rain closing function Sliding sunroof
Post-collision brake 48 Power closing function Door. 78	Programs	Rain sensor Sliding sunroof
Power supply Start/stop button	Protection of the environment Driving style	Reading lamp Interior lighting
Power washer	Hill Start Assist	Rear fog light
Function	QR code rescue card	control
PRE-SAFE® Impulse Side Function	Qualified specialist workshop	Reclining rear seat

Rear view camera 360° Camera Function Opening the camera cover  Rear window	261	Replacement key	Reversing camera         349           Care
Replacing wiper blade  Rear window heater  Rear window wiper  Activating/deactivating  Rearview mirror	<ul><li>167</li><li>158</li></ul>	Resetting MBUX reset function	Roll away protection.       217         Roller sunblind       95         Electric.       90         Rollover crash.       30         Roof load.       423
Automatic anti-glare mode	61 353 419	Basic information	Roof load display Information
Refueling Fuel	201 201 177 177	Limited protection	Route         308           Alternative route         308           Calculating         308           Commuter route         308           Navigation         306           Selecting options         308           Route guidance with augmented reality           Activating         308

Displaying road names/house numbers	308	Adjusting the front passenger seat from the rear passenger compartment	103	Workout programs	1
Route-based speed adaptation Function	228 355 349 . 80	Automatic adjustment	114 99	Seat belt Automatic tightening Warning lamp Seat belt adjustment Activating/deactivating Function Seat belt warning	4 4 4
\$		(third row of seats)Folding the backrest on the third row	107	Seat belts	
Safety system	334 334	of seats forwards	134 105 104 115 107 122 118	Activating/deactivating seat belt adjustment	35 4 4 5
Adjusting electricallyAdjusting electrically (rear passenger compartment)			104 105 116 14	Activating/deactivating	10

Seats, Through-loading feature		Shunting support	276	SmartKey	
Folding the backrest forwards (rear		Side impact air bag		Acoustic locking verification signal	73
passenger compartment)	131			Battery	74
Selecting a gear	196	Side impact protection	209	Deactivating a function	
Selector lever		Side windows		Function	
	171	Child safety lock (rear passenger	71	Key ring attachment	74
Self-test		compartment)		Mechanical key	/4
Automatic front passenger air bag shu		Closing with SmartKey		Panic alarm	
toff		Convenience closing	89	Power consumption	
Restraint system	42	Convenience opening	. 88	Unlocking setting	73
Sensors		Electric roller sunblind		Smartphone Integration, iPhone®	
Cleaning	349	Opening with the SmartKey		Android Auto	323
Service		Opening/closing		Apple CarPlay®	
Service center		Problem	89		376
		Size designation			3/0
Service interval display	336	Tires	389	Socket	
Shifting		Skid chains	376	12 V	143
Automatic transmission	196		0,0	Socket (115 V), 115 V socket	
Gearshift recommendation		Sliding sunroof, Panorama roof with		Rear passenger compartment	144
	196	power tilt/sliding panel	0.0	Sound	
Steering wheel paddle shifters	196	Automatic functions		Menu	225
Shortening the braking distance		Closing with SmartKey		PRE-SAFE® Sound	
	212	Opening with the SmartKey	88		
Brake Assist System		Opening/closing	90	Wheels/tires	
Shunting assistant	277	Problem Rain closing function		Sound settings	335

			Index	527
Spare parts	Starter battery		Buttons Driver's air bag Manually adjusting	. 54 119
Specialist workshop	Starting Remote Online Start/stop button	178 176	Steering wheel adjustments Steering wheel heater Steering wheel heater Steering wheel paddle shifters	119 120
Speed adaptation, Route-based	Starting the engine Emergency operation mode Remote Online	1 <i>77</i> 1 <i>7</i> 8	StepStop and go  ECO start/stop functionStopping	. 79
Speed rating Tires	Starting-off aid Drive Away AssistHill Start Assist	218	Parking the vehicle	
Sport Utility Vehicle	Status display Front passenger air bag Steer Assist	43	Stowage compartment Folding table Handset (rear passenger compartment) Rear seat backrest	131
Start/stop button Parking the vehicle	STEER CONTROL	217 217	Stowage spaces Armrest Center console (front) Door Glove box	129 129 129

Substances hazardous to health	299	Synchronization function Activating/deactivating (control panel)  System settings Language setting	303	Roof load Tongue weight Towing capacity  Telediagnosis	426 425
Surround lightingSurround sound system		MBUX reset function		Diagnostic data  Telediagnostics  Transferred data	
Suspension Adjusting the vehicle level (E-ACTIVE BODY CONTROL)		Tailgate, Trunk lid Closing Emergency key Emergency release HANDS-FREE ACCESS. Limiting the opening angle Opening Opening dimensions  Tank content Fuel Reserve.  Tank filler cap / flap Technical data	. 86 . 85 . 84 . 85 . 80 . 421 . 416 . 416	Telephone, Smartphone Bluetooth®	148 316 325 316 313 147 316 316 315
Exterior	157	Axle load (trailer operation)	409	<b>Telephony operating modes</b> Bluetooth <sup>®</sup> telephony	316

Temperature		Maximum tire pressure	388	Tire-change tool kit	397
Setting the vehicle interior temperature	167	Size designationSpeed rating	389 389	TIREFIT kit, Tire inflation compressor	254
Temperature grade		Temperature grade	386	Storage location	330
Themes		Tire Quality Grading Traction grade	386 386	Breakdown	
Fastening	299	Tread wear grade	386	Characteristics	
Third row of seats, Through-loading feature		Tire pressure	000	Checking the tire pressure manually	
Folding back the backrest on the third	105	Checking Checking manually	380 379	Definitions DOT, Tire Identification Number (TIN)	391 387
row of seatsFolding the backrest on the third row	135	Maximum		Installing	402
of seats forwards	134	Notes Tire pressure table		Labeling Load index	386
Getting in/out		TIREFIT kit	356	Load-bearing capacity	389
TIN (Tire Identification Number)		Tire pressure monitor		Maximum pressure	388
Tire and Loading Information placard	382	Function	379	Maximum tire load	
Tire characteristics	389	Tire pressure monitoring system		MOExtended	
Tire information table	382	Restarting	381	Notes on installing	
Tire labeling		Tire pressure table	378	Notes on installing Removing	
Characteristics		Tire Quality Grading	386	Removing/installing hub cap	
DOT, Tire Identification Number (TIN)	387 389	Tire sealant	356	Replacing	
Load index Load-bearing capacity		Tire tread	375	Rotating Selecting	
Maximum tire load	388	Tire-change tool	397	Size designation	

	376	Tow-away protection	. 97	Trailer hitch	
1 0	389	Tow-starting	371		280
0	397	Towing		Axle load	
1 0	386		266	Care	
	382	Towing methods	300	Coupling up/uncoupling a trailer	281
Tire pressure table	378	Towing a trailer		General notes	425
	386	Active Lane Keeping Assist	244	Tongue weight	426
	356	Notes	279	Towing capacity	
Traction grade	386	Towing eye		Trailer Maneuvering Assist	277
Tread wear grade	386	installing/removing	370	Trailer Maneuvering Assist	
	375	Storage location			277
Toll system		_		Using	
Debiting toll fees	306	Towing methods	240	_	270
Windshield	166	Both axles on the ground		Trailer operation	0.40
		Overview		Active Blind Spot Assist	
Tongue weight	426	Traction grade	386	Attaching the ball neck	
Top Tether	67	Traffic information	310	Coupling up/uncoupling a trailer	281
Touch Control		Traffic Jam Assistant		Trailer stabilization	215
MBUX	293			Transfer case	
On-board computer		Traffic light warning/display	240	HIGH RANGE	199
		Traffic Sign Assist		LOW RANGE	199
Touchpad	000	Function	240		
Operating	293	Setting		0	
Touchscreen	293	Trailer drawbar, Pulling/towing	283	Transmission position display	194
Tow bar system		mailer arawbar, railing/towing	200	Transmission positions	
Towing away	283			DIRECT SELECT lever	194
0 )					

Transporting Vehicle	333 152 152 410 409	Diagnostics connection	36 36 8 21 42 19 42 42 42
U		Medical aids	42 42
Unfastening Unlocking setting USB port Rear passenger compartment Stowage compartments (front)	73 145	Parking for an extended period. 210 Problem notification. 31 Pulling. 283 QR code rescue card. 33 Raising. 399 Set collision detection. 200 Vehicle length. 4 Vehicle width. 4 Wheelbase. 4 Vehicle dimensions. 4 Vehicle emergency start. 5	42 42 42 42 37
V Vehicle, Switching on the ignition 48 V on-board electrical system		Standby mode function	41 41

Fuel reserve warning lamp flashes  Fuel reserve warning lamp lights up  Power steering warning lamp (red)  RBS RBS warning lamp (USA only)  Restraint system warning lamp  Seat belt warning lamp flashes  Seat belt warning lamp lights up  Suspension warning lamp (red)  Suspension warning lamp (yel-	492 488 494 487 487	Washing by hand  Water tank  Wear  Limited protection  Weather information  Web browser  Weight information  Wheel change  Installing a new wheel  Lowering the vehicle	419 347 344 50 310 322 411 402 403	Load-bearing capacity  Maximum tire load  MoExtended  Noise  Notes on installing  Removing  Replacing  Rotating  Selecting  Size designation  Snow chains	38 38 38 35 37 39 40 39 39 39 39 37
	499 499	Installing a new wheel Lowering the vehicle Removing a wheel		Size designation Snow chains Speed rating	38 37
(1) Tire pressure monitoring system warning lamp flashes	500	Wheel rotation	398 396 354	Tire and Loading Information placard Tire characteristics	38
tem warning lamp lights up		Care	349 375 379 391 387	0	38 35

0	386 375 301	Windshield wipers  Activating/deactivating  Replacing the windshield wiper blades  Replacing the wiper blades	159
Window curtain air bagWindows		Winter operation Snow chains	376
CareOpening/closingRemoving mist	87	Wiper blades Care	349 159
Defrosting	167 166	TROLWipers	161 158
Replacing the wiper blades Replacing the wiper blades with MAGIC VISION CONTROL	161	Wireless charging Mobile phone Mobile phone (rear passenger compartment)	148
Toll system		Overview	147 115
Windshield washer system Windshield wiper Replacing the wiper blades with MAGIC VISION CONTROL	343	Workshop	



